



Python - List Comprehension

[< Previous](#)[Next >](#)

List Comprehension

List comprehension offers a shorter syntax when you want to create a new list based on the values of an existing list.

Example:

Based on a list of fruits, you want a new list, containing only the fruits with the letter "a" in the name.

Without list comprehension you will have to write a **for** statement with a conditional test inside:

Example

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
newlist = []

for x in fruits:
    if "a" in x:
        newlist.append(x)

print(newlist)
```

Try it Yourself »

With list comprehension you can do all that with only one line of code:

Example

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]  
  
newlist = [x for x in fruits if "a" in x]  
  
print(newlist)
```

[Try it Yourself »](#)

The Syntax

```
newlist = [expression for item in iterable if condition == True]
```

The return value is a new list, leaving the old list unchanged.

Condition

The *condition* is like a filter that only accepts the items that valuate to **True** .

Example

Only accept items that are not "apple":

```
newlist = [x for x in fruits if x != "apple"]
```

[Try it Yourself »](#)

The condition `if x != "apple"` will return **True** for all elements other than "apple", making the new list contain all fruits except "apple".

The *condition* is optional and can be omitted:

Example

With no `if` statement:

```
newlist = [x for x in fruits]
```

[Try it Yourself »](#)

Iterable

The *iterable* can be any iterable object, like a list, tuple, set etc.

Example

You can use the `range()` function to create an iterable:

```
newlist = [x for x in range(10)]
```

[Try it Yourself »](#)

Same example, but with a condition:

Example

Accept only numbers lower than 5:

```
newlist = [x for x in range(10) if x < 5]
```

[Try it Yourself »](#)

Expression

The *expression* is the current item in the iteration, but it is also the outcome, which you can manipulate before it ends up like a list item in the new list:

Example

Set the values in the new list to upper case:

```
newlist = [x.upper() for x in fruits]
```

[Try it Yourself »](#)

You can set the outcome to whatever you like:

Example

Set all values in the new list to 'hello':

```
newlist = ['hello' for x in fruits]
```

[Try it Yourself »](#)

The *expression* can also contain conditions, not like a filter, but as a way to manipulate the outcome:

Example

Return "orange" instead of "banana":

```
newlist = [x if x != "banana" else "orange" for x in fruits]
```

[Try it Yourself »](#)

The *expression* in the example above says:


"Return the item if it is not banana, if it is banana return orange".

[< Previous](#)[Next >](#)



NEW

We just launched
W3Schools videos



[Explore now](#)

COLOR PICKER



Get certified
by completing
a Python
course today!



Get started

CODE GAME



Play Game



Report Error

Spaces

Pro

Get Certified

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial

[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

W3Schools is Powered by W3.CSS.

