

1. What is CSS? Explain the full form of CSS.

CSS - Cascading Style Sheet.

Cascading is stylesheet language used to design and format HTML page. It controls the appearance of the webpage such as color, fonts, spacing etc.

2. What is Cascading in CSS? Give real-time example.

Cascading means when multiple CSS rules apply to the same element, the browser decides which rule to use based on priority.

example

```
P {  
  Color: blue  
}
```

Output: red

```
P {  
  Color: red  
}
```

The second rule comes later, it overrides the first one.

③ difference bt Cascading & Specificity?

Cascading which rule wins based on order & importance.

If Specificity is equal decide which Selector is Stronger

$Id > Class > Element$.

④ What are the three types of CSS? which one is recommended in real-time project & why?

There are three type of CSS.

- (i) inline
- (ii) internal
- (iii) external

External CSS is recommended in real-time project because in external CSS we have separate file rather than the inline & internal CSS,

Internal CSS is also best for project but it not work it out because if we use the internal CSS it took so much line of code on the same page it look clumsy to see the code, CSS work on it own, so we can use the external CSS.

5) CSS Selector

1. Universal Selector (*)

The universal Selector Select every HTML element on the webpage

```
* {
```

```
  Property: value
```

```
}
```

2. Element Selector.

The element Selector Select all HTML Element with same tag name.

```
tagname {
```

```
  Property: value
```

```
}
```

3. Class Selector (.)

The Class Selector Element with same class name. The class can be use multiple time.

```
.classname {
```

```
  Property: value
```

```
}
```

4. ID Selector (#)

The ID Selector Select one unique element

An ID should not be repeated

```
#idName {
```

```
  Property: value
```

```
}
```


5) Group Selector (,)

The Group Selector applies the same CSS to multiple selectors. Instead of writing CSS repeatedly, separate selector using commas.

Selector1, Selector2 {

Property: value

}

6) Descendant Selector (space)

The Descendant Selector matches all matching element inside a parent, no matter how deeply they are nested.

Parent child {

Property: value

}

7) Child Selector (>)

The child Selector selects only the direct children of a parent element.

It does not select grandchildren or deeper nested element.

Parent > child {

Property: value

}

6) What is the difference bt Class Selector and ID Selector?

A class Selector is used to apply the same style to multiple HTML element

An ID Selector is used to style one unique HTML element.

7) What is the difference bt Descendant Selector & Child Selector?

A Descendant Selector select all matching element inside a parent element regardless of how deeply they are nested

A Child Selector select only the direct children of parent element

8) Explain the CSS Box model. Name its four parts.

The CSS Box model is a concept that describes how every HTML element is displayed as a rectangular box on a webpage

HTML element consist of four parts.

Content

Padding

Border

margin.

9) what is difference bt padding & margin?

padding is the space inside an element between the content & the border.

margin is the space outside an element between the border & neighbouring element.

10) what is box-sizing: border-box? why is it recommended?

The box-sizing property determine how the browser calculate the total width & height of an HTML element

make width & height calculation easier,
keep layout predicatable, help avoid layout
& overflow issues ^{etc.} That's why it is recommended.

11) explain the difference bt the following display properties.

block

inline

inline-block

display: block

A block element start on a new line & takes up the full available width of its parent container by default.

display : inline

An inline element takes only as much width as its content & does not start on a new line.

display : inline-block.

An inline block element stay on the same line like an inline element, but also allow width & height like a block element.

12 Can we apply width & height to.

div

span

button

div is block level element. So we can ~~not~~ apply width & height.

span is inline level element So we cannot apply width & height.

button. is act as a inline-block element So width & height Can we change.

13. difference bt `display:none` & `visibility:hidden`

`display:none`;

The property completely remove an element from the webpage.

The element is not visible

It does not occupy any space

Other element move into its place.

`visibility:hidden`.

The property hidden an element but keeps its space in the layout

The element is not visible.

It still occupies its original space

Other element do not move.

14 Explain Flexbox what are Flex container, Flex item, main axis, cross axis.

Flexbox is CSS layout model used to arrange align & distribute element efficiently in a row (or) column.

Flex container

The parent element with `display:flex` is called flex container

Flex item.

The direct children inside the flex container is called flex item.

main axis

The main axis is the direction in which flex items are placed

Cross Axis

A cross axis is perpendicular to main axis.

15. How do you perfectly center div using Flexbox? write CSS code & explain each property.

```
<div class="container">
```

```
<div class="box"> Hello </div>
```

```
</div>
```

• Container

display: flex;

justify-content: center;

align-items: center;

display: flex;

Convert parent element to one flex container

justify-content: center;

Center the child horizontally along the main axis

Align - items : Center ;

Center the child vertically along
the cross axis