

Citizen science for traffic monitoring: Investigating the potentials
for complementing traffic counters with crowdsourced data
Descriptions of the best regression models

Miha Janež¹, Špela Verovšek², Tadeja Zupančič², Miha Moškon^{1,*}

¹Faculty of Computer and Information Science, University of Ljubljana

²Faculty of Architecture, University of Ljubljana

* corresponding author; e-mail: miha.moskon@fri.uni-lj.si

This document is supplementing the paper *Citizen science for traffic monitoring: Investigating the potentials for complementing traffic counters with crowdsourced data* with a more detailed description of the best performing models together with their parameters. In each of the observed road segments either kernel ridge regression (krr) or gradient boosting regression (gbr) yields the best results. All the models were implemented using the `scikit-learn` Python library [1]. The details of the implementations of the kernel ridge regression together with the description of its parameters are available here. The details of the implementations of the gradient boosting regression together with the description of its parameters are available here.

Dunajska (from centre)

Summary

- Model: krr
- Features: basic, 0656-1, 0655-2

Model parameters

- $\alpha = 0.001$
- $\text{coef0} = 1$
- $\text{degree} = 3$
- $\gamma = 0.001$
- $\text{kernel} = \text{chi2}$

Dunajska (to centre)

Summary

- Model: krr
- Features: basic, 0656-2, 0655-1

Model parameters

- $\alpha = 0.001$
- $\text{coef0} = 1$
- $\text{degree} = 3$
- $\gamma = 0.001$
- $\text{kernel} = \text{chi2}$

Ižanska (from centre)

Summary

- Model: krr
- Features: basic, 0820-1, 1506-1

Model parameters

- $\alpha = 0.0001$
- $\text{coef0} = 1$
- $\text{degree} = 3$
- $\gamma = 0.001$
- $\text{kernel} = \text{chi2}$

Ižanska (to centre)

Summary

- Model: krr
- Features: basic, 0820-2, 1506-2

Model parameters

- $\alpha = 1\text{e-}05$
- $\text{coef0} = 1$
- $\text{degree} = 3$
- $\gamma = 0.001$
- $\text{kernel} = \text{chi2}$

Slovenska (from centre)

Summary

- Model: krr
- Features: basic, 0619-1

Model parameters

- $\alpha = 1.0$
- $\text{coef0} = 1$
- $\text{degree} = 3$
- $\gamma = 0.1$
- $\text{kernel} = \text{chi2}$

Slovenska (to centre)

Summary

- Model: krr
- Features: basic, 0619-2

Model parameters

- $\alpha = 0.0001$
- $\text{coef0} = 1$
- $\text{degree} = 3$
- $\gamma = 0.01$
- $\text{kernel} = \text{chi2}$

Škofije (towards Koper)

Summary

- Model: gbr
- Features: basic, 1092-1

Model parameters

- $\alpha = 0.9$
- $\text{ccp_alpha} = 0.0$
- $\text{criterion} = \text{friedman_mse}$
- $\text{learning_rate} = 0.1$
- $\text{loss} = \text{squared_error}$
- $\text{max_depth} = 3$
- $\text{min_impurity_decrease} = 0.0$
- $\text{min_samples_leaf} = 1$
- $\text{min_samples_split} = 2$
- $\text{min_weight_fraction_leaf} = 0.0$
- $\text{n_estimators} = 100$

- subsample = 1.0
- tol = 0.0001
- validation_fraction = 0.1
- verbose = 0
- warm_start = False

Škofije (towards Trieste)

Summary

- Model: krr
- Features: basic, 1092-2

Model parameters

- alpha = 0.0001
- coef0 = 1
- degree = 3
- gamma = 0.01
- kernel = chi2

References

- [1] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay, “Scikit-learn: Machine learning in Python,” *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.