EXPERIMENT NO. 5

AIM

To familiarize with set operations


Questions

- 1. List all the customers who are depositors but not borrowers.
- 2. List all the customers who are both depositors and borrowers
- 3. List all the depositors having deposit in all the branches where Sunil is having Account
- 4. List all the customers living in city NAGPUR and having branch city BOMBAY or DELHI
- 5. List all the depositors living in city NAGPUR
- 6. List all the depositors living in the city NAGPUR and having branch in city BOMBAY
- 7. List the branch cities of Anil and Sunil
- 8. List the customers having deposit greater than 1000 and loan less than 10000.
- 9. List the cities of depositors having branch VRCE.
- 10. List the depositors having amount less than 1000 and living in the same city as Anil
- 11. List all the cities where branches of Anil and Sunil are locate
- 12. List the amount for the depositors living in the city where Anil is living

OUTPUT

1. mysql> SELECT CNAME FROM DEPOSIT WHERE CNAME NOT IN (SELECT CNAME FROM BORROW);


Empty set (0.00 sec)



2. mysql> SELECT CNAME FROM DEPOSIT UNION (SELECT CNAME FROM BORROW);

2. mysqr blller ervrivi.
CNAME
ANIL
SUNIL
MEHUL
MADHURI
PRAMOD
SANDIP
SHIVANI
KRANTI
NAREN


9 rows in set (0.01 sec)



3. mysql> SELECT D1.CNAME FROM DEPOSIT D1 WHERE D1.BNAME IN (SELECT D2.BNAME FROM DEPOSIT D2 WHERE D2.CNAME = 'SUNIL');

CNAME	
SUNIL	


1 row in set (0.00 sec)



4. mysql> SELECT C1.CNAME FROM CUSTOMER C1,DEPOSIT D1, BRANCH B1 WHERE C1.CITY = 'NAGPUR' AND C1.CNAME = D1.CNAME AND D1.BNAME = B1.BNAME AND B1.CITY IN ('BOMBAY','DELHI');

CNAME	
MADHURI	


1 row in set (0.01 sec)



5. mysql> SELECT Distinct(CUSTOMER.CNAME) from CUSTOMER, DEPOSIT WHERE City='NAGPUR';

CNAME	
PRAMOD	
MADHURI	

2 rows in set (0.00 sec)



6. mysql> SELECT C1.CNAME FROM CUSTOMER C1,DEPOSIT D1, BRANCH B1 WHERE C1.CITY = 'NAGPUR' AND C1.CNAME = D1.CNAME AND D1.BNAME = B1.BNAME AND B1.CITY IN ('BOMBAY');


Empty set (0.00 sec)

Result Grid	Filter Rows:	
CNAME		

7. mysql> SELECT B1.CITY FROM DEPOSIT D1, BRANCH B1 WHERE D1.BNAME = B1.BNAME AND D1.CNAME IN ('SUNIL', 'ANIL');

CITY
NAGPUR
NAGPUR


2 rows in set (0.00 sec)



8. mysql> SELECT DISTINCT D1.CNAME FROM deposit D1, borrow B1 WHERE D1.AMOUNT>1000 AND B1.AMOUNT<10000;

CNAME
SUNIL
MEHUL
MADHURI
PRAMOD
SANDIP
KRANTI
NAREN


7 rows in set (0.00 sec)



9. mysql> SELECT B1.CITY FROM deposit D1, branch B1 WHERE D1.BNAME=B1.BNAME AND B1.BNAME='VRCE';




1 row in set (0.00 sec)



10. mysql> SELECT D1.CNAME FROM DEPOSIT D1,CUSTOMER C1 , CUSTOMER C2 WHERE C1.CITY = C2.CITY AND C2.CNAME = 'ANIL' AND C1.CNAME = D1.CNAME AND D1.AMOUNT < 1000;


Empty set, 10 warnings (0.00 sec)



11. mysql> SELECT B1.CITY FROM BRANCH B1 WHERE B1.BNAME IN (SELECT D1.BNAME FROM DEPOSIT D1 WHERE D1.CNAME IN ('ANIL', 'SUNIL'));

CITY
NAGPUR
NAGPUR

2 rows in set (0.00 sec)



12. mysql> SELECT DISTINCT(D1.CNAME),D1.AMOUNT ,C1.CITY FROM deposit D1, CUSTOMER C1, BRANCH B1 WHERE D1.CNAME=C1.CNAME AND C1.CITY IN(SELECT C2.CITY FROM customer C2 WHERE C2.CNAME='ANIL');

CNAME	AMOUNT	CITY
ANIL	1000.00	CULCUTTA

1 row in set (0.00 sec)

