From Eliciture to Internal Representation: Implicit Causality in Language Models

Anonymous Author(s)
Affiliation
Address
email

Abstract

Do language models merely behave as if they infer implicit causes, or do they encode causal relationships that generalize? Four studies test behavioral elicitation, relation selectivity, causal OOD generalization, and naturalistic transfer. Across six models, behavioral conclusions depend on elicitation method. On 150 causal OOD pairs, causal directions reach .97–1.00 accuracy, compared with .57–.95 for temporal and .41–.69 for plausibility directions. Demographic substitutions also shift causal projections in 65 matched scenarios per model. These studies connect pragmatic behavior to internal representation while exposing important construct-validity limits.

1 Introduction

Cohen and Kehler call defeasible pragmatic enrichments *conversational elicitures* [Cohen and Kehler, 2021]. Language models reproduce human-like eliciture judgments and relative-clause preferences [Pan and Kehler, 2025], but behavioral agreement does not reveal whether they encode the inferred relation. Because linear representations can reveal event-plausibility distinctions obscured by output probabilities [Lepori et al., 2026], we use contrastive activation addition (CAA) [Rimsky et al., 2024] to study implicit causality.

We ask three questions:

RQ1 *Do model behaviors reflect inferences about implicit causal relationships within sentences?*
RQ2 *Do LMs form internal representations of implicit causal relationships?*
RQ3 *If **RQ2** is true, do representations of implicit causality generalize to naturalistic settings with potential real-world implications?*

Our contribution is...

2 Studies

2.1 Study 1: Measuring Behavioral Eliciture

We vary the response measure in a conceptual replication of Pan and Kehler, finding substantial measurement dependence.

Methods. **Models.** We evaluate the base checkpoints of Gemma 2 2B/9B [Gemma Team, 2024], Qwen3 4B/8B [Qwen Team, 2025], Llama 3.2 3B [Meta AI, 2024], and Llama 3 8B [Dubey et al., 2024].

Dataset and analysis. We evaluate 150 critical/control pairs with yes/no judgments, expected seven-point Likert scores, and the relative probability of the same continuation after *because* versus bare

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.




Figure 1: **RQ1.** Paired accuracy on 150 eliciture pairs with Wilson 95% CIs. Dashed line: chance.

and. The last measure uses no metalinguistic prompt. A pair is correct when the critical item receives the stronger causal response, allowing us to compare prompting with probability measurement [Hu and Levy, 2023].

Results. Figure 1 shows that Qwen3 4B/8B reach 1.00 with Likert responses and at least .96 with yes/no, but fall to .79/.76 under probability assignment. Conversely, Gemma 2 2B scores .45/.39 with prompting but .83 with *because* versus *and*. Overall, no interface supports a model-independent conclusion.

2.2 Study 2: Relation-Selective Causal Representations

We compare cross-sentence causal directions with temporal and plausibility directions, finding strong diagonals and weaker cross-transfer.

Methods. **Datasets.** Causal, temporal, and plausibility directions respectively use 384/96, 800/200, and 56/14 train/ID-development pairs.

Analysis. At every fourth layer and the final layer, CAA averages final-token differences between matched positive and negative texts. We select the earliest layer maximizing mean own-development paired accuracy and ROC–AUC, then apply that frozen direction to every target relation. Matrix diagonals measure within-relation discrimination; off-diagonals measure cross-transfer. This is an ID-development analysis, not an OOD test.




Figure 2: **RQ2a, causal vs. temporal.** ID-development paired accuracy when each row's CAA direction is evaluated on each column's relation. Each panel is one model; diagonals measure own-relation discrimination and off-diagonals measure cross-transfer.




Figure 3: **RQ2a, causal vs. plausibility.** Six-model cross-transfer matrices; plausibility cells ($n = 14$ pairs) are exploratory.

Results. Figures 2–3 show causal self-transfer of 1.00 for all six models, temporal self-transfer of .93–.95, and plausibility self-transfer of .93–1.00. However, causal-to-temporal accuracy is .47–.73 and causal-to-plausibility is .36–.71; reverse transfer reaches .34–.67 and .15–.46. The gaps support relation selectivity, while occasional above-chance transfer argues against strict orthogonality.

2.3 Study 3: Generalization to Causal OOD

We next test whether causal directions remain selectively informative on unseen causal scenarios.

Methods. Datasets. Causal and temporal CAAs use 1,000/200 and 800/200 train/development pairs; the plausibility CAA uses 70 probable/impossible pairs with five-fold layer selection. We evaluate every frozen direction on the same 150-pair causal OOD set.

Analysis. We project each critical/control sentence onto the corresponding direction. A pair is correct when the critical item projects farther than its matched control.




Figure 4: **RQ2b.** Paired accuracy on 150 causal OOD pairs with Wilson 95% CIs. Dashed line: chance.

Results. Figure 4 shows that causal CAA reaches .97–1.00 paired accuracy across models. Temporal CAA varies from .57–.95, whereas plausibility CAA ranges from .41–.69. The causal direction therefore generalizes most consistently to new causal scenarios; transfer from the comparison directions is weaker and model-dependent.

2.4 Study 4: Generalization to Naturalistic Scenarios

We finally test causal representations on matched naturalistic scenarios.

Methods. Dataset. We evaluate 65 self-blinding scenarios per model in matched White-male, marginalized-male, and marginalized-female versions.

Analysis. A unit causal direction fit separately on 1,000 within-sentence pairs projects each scenario's final-token state. We report within-scenario differences from the White-male version with 10,000-sample bootstrap 95% intervals and visualize raw, unnormalized CAA projections.

Table 1: **RQ3.** Mean paired unit-CAA change ± bootstrap 95% CI half-width (65 scenarios/model).

	Gemma 2 2B	Gemma 2 9B	Qwen3 4B	Qwen3 8B	Llama 3.2 3B	Llama 3 8B
Marg. male − White male	.41 ± .32	1.9 ± .40	.073 ± .093	.29 ± .17	.025 ± .029	.030 ± .020
Marg. female − White male	.57 ± .32	2.3 ± .41	.15 ± .10	.39 ± .15	.069 ± .033	.060 ± .021

Results. Table 1 shows positive estimates for both contrasts in every model. Marginalized-female intervals exclude zero for all six; marginalized-male intervals do so for four. However, Appendix Figure 5 shows substantial distributional overlap. These associations do not establish social bias, behavior, or a causal mechanism.

3 Discussion

Behavioral evidence is measurement-sensitive, whereas causal directions are relation-selective and generalize to causal OOD data. However, Study 2 uses ID development sets (only 14 plausibility

pairs), CAA is correlational, and 65 scenarios cannot establish general behavior. Larger tests, interventions, and behavioral validation remain necessary.

References

Jonathan Cohen and Andrew Kehler. Conversational eliciture. *Philosophers' Imprint*, 21(12):1–26, 2021.

Abhimanyu Dubey et al. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024. URL https://arxiv.org/abs/2407.21783.

Gemma Team. Gemma 2: Improving open language models at a practical size. *arXiv preprint arXiv:2408.00118*, 2024. URL https://arxiv.org/abs/2408.00118.

Jennifer Hu and Roger Levy. Prompting is not a substitute for probability measurements in large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 5040–5060. Association for Computational Linguistics, 2023.

Michael A. Lepori, Jennifer Hu, Ishita Dasgupta, Roma Patel, Thomas Serre, and Ellie Pavlick. Is this just fantasy? language model representations reflect human judgments of event plausibility. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=Czul60ELOH.

Meta AI. Llama 3.2 model card. Hugging Face model documentation, 2024. URL https://huggingface.co/meta-llama/Llama-3.2-3B.

Dingyi Pan and Andrew Kehler. Pragmatic competence in LLMs: The case of eliciture. In Carolyn Jane Anderson, Frédéric Mailhot, and Grusha Prasad, editors, *Proceedings of the Society for Computation in Linguistics 2025*, pages 388–391. Association for Computational Linguistics, 2025. URL https://aclanthology.org/2025.scil-1.39/.

Qwen Team. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025. URL https://arxiv.org/abs/2505.09388.

Nina Rimsky, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Matt Turner. Steering Llama 2 via contrastive activation addition. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15504–15522. Association for Computational Linguistics, 2024.

A Raw CAA Projection Distributions




Figure 5: **RQ3.** Raw CAA projections by matched condition (65 scores/condition/model). Colors and line styles distinguish the three conditions.