

## Importing the libraries

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

## Importing the dataset

```
df =
pd.read_csv('https://github.com/YBI-Foundation/Dataset/raw/main/Custom
er%20Purchase.csv')
```

## Get Information of Dataframe

```
df.head()
```

	Customer ID	Age	Gender	Education	Review	Purchased
0	1021	30	Female	School	Average	No
1	1022	68	Female	UG	Poor	No
2	1023	70	Female	PG	Good	No
3	1024	72	Female	PG	Good	No
4	1025	16	Female	UG	Average	No

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 50 entries, 0 to 49
Data columns (total 6 columns):
#   Column          Non-Null Count  Dtype
---  -
0   Customer ID     50 non-null    int64
1   Age             50 non-null    int64
2   Gender          50 non-null    object
3   Education       50 non-null    object
4   Review          50 non-null    object
5   Purchased       50 non-null    object
dtypes: int64(2), object(4)
memory usage: 2.5+ KB
```

```
df.isnull().sum()
```

```
Customer ID    0
Age            0
Gender          0
Education       0
Review         0
Purchased      0
dtype: int64
```

```
df.columns
```

```
Index(['Customer ID', 'Age', 'Gender', 'Education', 'Review',  
      'Purchased'], dtype='object')
```

## Setting X and y

```
X= df[['Age', 'Gender', 'Education', 'Review']]
```

```
y=df['Purchased']
```

```
X[:]
```

	Age	Gender	Education	Review
0	30	Female	School	Average
1	68	Female	UG	Poor
2	70	Female	PG	Good
3	72	Female	PG	Good
4	16	Female	UG	Average
5	31	Female	School	Average
6	18	Male	School	Good
7	60	Female	School	Poor
8	65	Female	UG	Average
9	74	Male	UG	Good
10	98	Female	UG	Good
11	74	Male	UG	Good
12	51	Male	School	Poor
13	57	Female	School	Average
14	15	Male	PG	Poor
15	75	Male	UG	Poor
16	59	Male	UG	Poor
17	22	Female	UG	Poor
18	19	Male	School	Good
19	97	Male	PG	Poor
20	57	Female	School	Average
21	32	Male	PG	Average
22	18	Female	PG	Poor
23	96	Female	School	Good
24	16	Female	PG	Average
25	57	Female	School	Good
26	53	Female	PG	Poor
27	69	Female	PG	Poor
28	48	Male	School	Poor
29	83	Female	UG	Average
30	73	Male	UG	Average
31	22	Female	School	Poor
32	92	Male	UG	Average
33	89	Female	PG	Good
34	86	Male	School	Average
35	74	Male	School	Poor
36	34	Female	UG	Good

37	94	Male	PG	Average
38	45	Female	School	Good
39	76	Male	PG	Poor
40	39	Male	School	Good
41	23	Male	PG	Good
42	30	Female	PG	Good
43	27	Male	PG	Poor
44	77	Female	UG	Average
45	61	Male	PG	Poor
46	64	Female	PG	Poor
47	38	Female	PG	Good
48	39	Female	UG	Good
49	25	Female	UG	Good

## Ordinal Encoder for rank categorical data

```
from sklearn.preprocessing import OrdinalEncoder
oe=OrdinalEncoder()
X[['Gender', 'Education', 'Review']] = oe.fit_transform(X[['Gender',
'Education', 'Review']])
#X[:,1:] = oe.fit_transform(X[:,1:])
X
```

```
/usr/local/lib/python3.7/dist-packages/pandas/core/frame.py:3678:
SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame.
Try using .loc[row_indexer,col_indexer] = value instead
```

See the caveats in the documentation:

[https://pandas.pydata.org/pandas-docs/stable/user\\_guide/indexing.html#returning-a-view-versus-a-copy](https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy)

```
self[col] = igetitem(value, i)
```

	Age	Gender	Education	Review
0	30	0.0	1.0	0.0
1	68	0.0	2.0	2.0
2	70	0.0	0.0	1.0
3	72	0.0	0.0	1.0
4	16	0.0	2.0	0.0
5	31	0.0	1.0	0.0
6	18	1.0	1.0	1.0
7	60	0.0	1.0	2.0
8	65	0.0	2.0	0.0
9	74	1.0	2.0	1.0
10	98	0.0	2.0	1.0
11	74	1.0	2.0	1.0
12	51	1.0	1.0	2.0
13	57	0.0	1.0	0.0
14	15	1.0	0.0	2.0
15	75	1.0	2.0	2.0

16	59	1.0	2.0	2.0
17	22	0.0	2.0	2.0
18	19	1.0	1.0	1.0
19	97	1.0	0.0	2.0
20	57	0.0	1.0	0.0
21	32	1.0	0.0	0.0
22	18	0.0	0.0	2.0
23	96	0.0	1.0	1.0
24	16	0.0	0.0	0.0
25	57	0.0	1.0	1.0
26	53	0.0	0.0	2.0
27	69	0.0	0.0	2.0
28	48	1.0	1.0	2.0
29	83	0.0	2.0	0.0
30	73	1.0	2.0	0.0
31	22	0.0	1.0	2.0
32	92	1.0	2.0	0.0
33	89	0.0	0.0	1.0
34	86	1.0	1.0	0.0
35	74	1.0	1.0	2.0
36	34	0.0	2.0	1.0
37	94	1.0	0.0	0.0
38	45	0.0	1.0	1.0
39	76	1.0	0.0	2.0
40	39	1.0	1.0	1.0
41	23	1.0	0.0	1.0
42	30	0.0	0.0	1.0
43	27	1.0	0.0	2.0
44	77	0.0	2.0	0.0
45	61	1.0	0.0	2.0
46	64	0.0	0.0	2.0
47	38	0.0	0.0	1.0
48	39	0.0	2.0	1.0
49	25	0.0	2.0	1.0

## Display Encoded Categories

```
oe.categories_
```

```
[array(['Female', 'Male'], dtype=object),
 array(['PG', 'School', 'UG'], dtype=object),
 array(['Average', 'Good', 'Poor'], dtype=object)]
```

## Reverse Encode Integer array to Categorical Features

```
oe.inverse_transform([[0,0,0]])
```

```
array([[15, 'Female', 'PG', 'Average']], dtype=object)
```

```
oe.inverse_transform([[1,1,1]])
```

```
array([[ 'Male', 'School', 'Good']], dtype=object)
```

```
oe.inverse_transform([[1,2,2]])
```

```
array([[ 'Male', 'UG', 'Poor']], dtype=object)
```

## Encoding Categorical features as an integer array of your choice

```
X=df[['Gender', 'Education', 'Review']]
```

```
oe=OrdinalEncoder(categories=[['Male','Female'], ['School','UG','PG'],  
                               ['Poor','Average','Good']])
```

```
X=oe.fit_transform(X)
```

```
oe.categories_
```

```
[array(['Male', 'Female'], dtype=object),  
 array(['School', 'UG', 'PG'], dtype=object),  
 array(['Poor', 'Average', 'Good'], dtype=object)]
```