

# 11.1\_Matplotlib

October 30, 2023

## 1 Introduction to Python for Open Source Geocomputation



- Instructor: Dr. Wei Kang

Content:

- What is Matplotlib?
- Options with Matplotlib
  - Different plot types
  - Styling
  - multiple plots
- Saving a plotted figure

## 2 What is Matplotlib?

- One of the most popular packages for quickly creating figures in python
- Many packages are built on top of and extending Matplotlib
  - Examples
    - \* pandas: Tabular data analysis and manipulation tool providing a `.plot()` API for Matplotlib plotting.
    - \* animatplot: Interactive animated plots.
    - \* seaborn: High-level interface for drawing attractive statistical graphics.
    - \* GeoPandas: Pandas extended to support geographical data, algorithms, and visualization
  - See a fuller list [here](#)

## 2.1 Installation of Matplotlib

From a terminal:

```
pip install matplotlib
```

or

```
conda install matplotlib
```

matplotlib is included in conda installation, so our working environment should already have matplotlib installed.

## 2.2 Support Many Different Types of Plots

- Basic plots: lines, scatter plot, bar plot
- image plots
- statistical plots: histogram, boxplot, pie
- 3D plots

```
[1]: from IPython.display import IFrame
      IFrame(src="https://matplotlib.org/stable/plot_types/index.html", width=1000, height=550)
```

```
[1]: <IPython.lib.display.IFrame at 0x7f7f50c2aca0>
```

## 2.3 Creating a simple figure in Matplotlib

Two interfaces for plotting with Matplotlib

- implicit interface:
  - procedural approach
  - inspired by and modeled on MATLAB
  - uses an global state-based interface which is encapsulated in the `pyplot` module to plot to the “current Axes”
  - use functions
  - See the [pyplot tutorials](#) for a more in-depth look at the pyplot interface.
- explicit interface:
  - object-oriented (OO) interface
  - directly utilize instances of `axes.Axes` to build up the visualization in an instance of `figure.Figure`
  - use methods associated with instances of classes `axes.Axes` and `figure.Figure`

```
[2]: import matplotlib.pyplot as plt #import the pyplot module from matplotlib
```

```
Intel MKL WARNING: Support of Intel(R) Streaming SIMD Extensions 4.2 (Intel(R) SSE4.2) enabled only processors has been deprecated. Intel oneAPI Math Kernel Library 2025.0 will require Intel(R) Advanced Vector Extensions (Intel(R) AVX) instructions.
```

```
Intel MKL WARNING: Support of Intel(R) Streaming SIMD Extensions 4.2 (Intel(R) SSE4.2) enabled only processors has been deprecated. Intel oneAPI Math Kernel
```

Library 2025.0 will require Intel(R) Advanced Vector Extensions (Intel(R) AVX) instructions.

```
[3]: dir(plt)
```

```
[3]: ['Annotation',  
      'Arrow',  
      'Artist',  
      'AutoLocator',  
      'Axes',  
      'Button',  
      'Circle',  
      'Enum',  
      'ExitStack',  
      'Figure',  
      'FigureBase',  
      'FigureCanvasBase',  
      'FigureManagerBase',  
      'FixedFormatter',  
      'FixedLocator',  
      'FormatStrFormatter',  
      'Formatter',  
      'FuncFormatter',  
      'GridSpec',  
      'IndexLocator',  
      'Line2D',  
      'LinearLocator',  
      'Locator',  
      'LogFormatter',  
      'LogFormatterExponent',  
      'LogFormatterMathtext',  
      'LogLocator',  
      'MaxNLocator',  
      'MouseButton',  
      'MultipleLocator',  
      'Normalize',  
      'NullFormatter',  
      'NullLocator',  
      'Number',  
      'PolarAxes',  
      'Polygon',  
      'Rectangle',  
      'ScalarFormatter',  
      'Slider',  
      'Subplot',  
      'SubplotSpec',  
      'Text',
```

```
'TickHelper',
'Widget',
'_REPL_DISPLAYHOOK',
'_ReplDisplayHook',
'__builtins__',
'__cached__',
'__doc__',
'__file__',
'__loader__',
'__name__',
'__package__',
'__spec__',
'_api',
'_auto_draw_if_interactive',
'_backend_mod',
'_copy_docstring_and_deprecators',
'_docstring',
'_draw_all_if_interactive',
'_get_backend_mod',
'_get_pyplot_commands',
'_get_required_interactive_framework',
'_interactive_bk',
'_log',
'_pylab_helpers',
'_warn_if_gui_out_of_main_thread',
'acorr',
'angle_spectrum',
'annotate',
'arrow',
'autoscale',
'autumn',
'axes',
'axhline',
'axhspan',
'axis',
'axline',
'axvline',
'axvspan',
'bar',
'bar_label',
'barbs',
'barh',
'bone',
'box',
'boxplot',
'broken_barh',
'cbook',
```

'cla',  
'clabel',  
'clf',  
'clim',  
'close',  
'cm',  
'cohere',  
'color\_sequences',  
'colorbar',  
'colormaps',  
'connect',  
'contour',  
'contourf',  
'cool',  
'copper',  
'csd',  
'cyclcr',  
'delaxes',  
'disconnect',  
'draw',  
'draw\_all',  
'draw\_if\_interactive',  
'errorbar',  
'eventplot',  
'figaspect',  
'figimage',  
'figlegend',  
'fignum\_exists',  
'figtext',  
'figure',  
'fill',  
'fill\_between',  
'fill\_betweenx',  
'findobj',  
'flag',  
'functools',  
'gca',  
'gcf',  
'gci',  
'get',  
'get\_backend',  
'get\_cmap',  
'get\_current\_fig\_manager',  
'get\_figlabels',  
'get\_fignums',  
'get\_plot\_commands',  
'get\_scale\_names',

```
'getp',
'ginput',
'gray',
'grid',
'hexbin',
'hist',
'hist2d',
'hlines',
'hot',
'hsv',
'importlib',
'imread',
'imsave',
'imshow',
'inferno',
'inspect',
'install_repl_displayhook',
'interactive',
'ioff',
'ion',
'isinteractive',
'jet',
'legend',
'locator_params',
'logging',
'loglog',
'magma',
'magnitude_spectrum',
'margins',
'matplotlib',
'matshow',
'minorticks_off',
'minorticks_on',
'mlab',
'new_figure_manager',
'nipy_spectral',
'np',
'pause',
'pcolor',
'pcolormesh',
'phase_spectrum',
'pie',
'pink',
'plasma',
'plot',
'plot_date',
'polar',
```

'prism',  
'psd',  
'quiver',  
'quiverkey',  
'rc',  
'rcParams',  
'rcParamsDefault',  
'rcParamsOrig',  
'rc\_context',  
'rcdefaults',  
'rcsetup',  
're',  
'register\_cmap',  
'rgrids',  
'savefig',  
'sca',  
'scatter',  
'sci',  
'semilogx',  
'semilogy',  
'set\_cmap',  
'set\_loglevel',  
'setp',  
'show',  
'specgram',  
'spring',  
'spy',  
'stackplot',  
'stairs',  
'stem',  
'step',  
'streamplot',  
'style',  
'subplot',  
'subplot2grid',  
'subplot\_mosaic',  
'subplot\_tool',  
'subplots',  
'subplots\_adjust',  
'summer',  
'suptitle',  
'switch\_backend',  
'sys',  
'table',  
'text',  
'thetagrids',  
'threading',

```
'tick_params',
'ticklabel_format',
'tight_layout',
'time',
'title',
'tricontour',
'tricontourf',
'tripcolor',
'triplot',
'twinx',
'twiny',
'uninstall_repl_displayhook',
'violinplot',
'viridis',
'vlines',
'waitforbuttonpress',
'winter',
'xcorr',
'xkcd',
'xlabel',
'xlim',
'xscale',
'xticks',
'ylabel',
'ylim',
'yscale',
'yticks']
```

```
[4]: import numpy as np
```

```
[5]: x = np.arange(10)
     y = x * 2
```

```
[6]: x
```

```
[6]: array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

```
[7]: y
```

```
[7]: array([ 0,  2,  4,  6,  8, 10, 12, 14, 16, 18])
```


**Explicit interface** This interface works by

- instantiating an instance of a Figure class (fig below)
- using a method subplots method (or similar) on that object to create one or more Axes objects (ax below)
- then calling drawing methods on the Axes (plot in this example)



```
[8]: fig, ax = plt.subplots() # Create a figure containing a single axes.  
ax.plot(x, y) # Plot some data on the axes.
```

```
[8]: [<matplotlib.lines.Line2D at 0x7f7f491fd940>]
```




### implicit interface

- shadows most of the Axes plotting methods to give the equivalent of the above
- the creation of the Figure and Axes is done for the user

```
[9]: plt.plot(x,y)
```

```
[9]: [<matplotlib.lines.Line2D at 0x7f7f786d7fd0>]
```




## 2.4 Anatomy of a Matplotlib Figure

### 2.4.1 Figure and Axes

- Axes:
  - represent an individual plot
  - different from “axis”, which refers to the x/y axis of a plot
- Figure: the final image that may contain 1 or more Axes
- Syntax for creating Figure and Axes
  - `fig = plt.figure()` # an empty figure with no Axes
  - `fig, ax = plt.subplots()` # a figure with a single Axes
  - `fig, axs = plt.subplots(2, 2)` # a figure with a 2x2 grid of Axes


```
[10]: fig, ax = plt.subplots() # Create a figure containing a single axes.  
      ax.plot(x, y) # Plot some data on the axes.
```

```
[10]: [<matplotlib.lines.Line2D at 0x7f7f28019ee0>]
```



```
[11]: fig, ax = plt.subplots() # Create a figure containing a single axes.  
      ax.plot(x, y) # Plot some data on the axes.  
      ax.set_xlabel("X")  
      ax.set_ylabel("Y = X*2")
```


```
[11]: Text(0, 0.5, 'Y = X*2')
```



What if we want to add another line to the current plot?

```
[12]: fig, ax = plt.subplots() # Create a figure containing a single axes.  
      ax.plot(x, y) # Plot some data on the axes.  
  
      y2 = x ** 2  
      ax.plot(x, y2) # Plot some data on the axes.  
  
      ax.set_xlabel("X")  
      ax.set_ylabel("Y")
```


```
[12]: Text(0, 0.5, 'Y')
```



add legend to different different lines

```
[13]: fig, ax = plt.subplots() # Create a figure containing a single axes.  
x = np.arange(10)  
y = x * 2  
ax.plot(x, y, label='linear')  
  
y2 = x ** 2  
ax.plot(x, y2, label='quadratic') # Plot some data on the axes.  
  
ax.set_xlabel("X")  
ax.set_ylabel("Y")  
ax.legend()
```

```
[13]: <matplotlib.legend.Legend at 0x7f7f58ccc400>
```



add a third line


```
[14]: fig, ax = plt.subplots() # Create a figure containing a single axes.
x = np.arange(10)
y = x * 2
ax.plot(x, y, label='linear')

y2 = x ** 2
ax.plot(x, y2, label='quadratic') # Plot some data on the axes.

y3 = x ** 3
ax.plot(x, y3, label='cubic')

ax.set_xlabel("X")
ax.set_ylabel("Y")
ax.legend()
```

```
[14]: <matplotlib.legend.Legend at 0x7f7f58efc130>
```




### 2.4.2 Styling Artists

Axes's plotting methods have styling options for:

- color
- linewidth
- [linestyle](#)

```
[15]: fig, ax = plt.subplots()  
      ax.plot(x, y, color='blue', linewidth=3, linestyle='--')
```


```
[15]: [<matplotlib.lines.Line2D at 0x7f7f49678160>]
```



```
[16]: fig, ax = plt.subplots()
      ax.plot(x, y, color='blue', linewidth=6, linestyle=':')
```

```
[16]: [<matplotlib.lines.Line2D at 0x7f7f7889e5b0>]
```





### 2.4.3 Group exercise

Edit the following python program to change the style (color, linewidth, linestyle) of the three plotted lines

```
fig, ax = plt.subplots()
x = np.arange(10)
y = x * 2
ax.plot(x, y, label='linear')

y2 = x ** 2
ax.plot(x, y2, label='quadratic')

y3 = x ** 3
ax.plot(x, y3, label='cubic')

ax.set_xlabel("X")
ax.set_ylabel("Y")
ax.legend()
```

when you are done, raise your hand!


```
[17]: fig, ax = plt.subplots()
x = np.arange(10)
y = x * 2
ax.plot(x, y, label='linear', color="green", linewidth = 8, linestyle = "dotted")

y2 = x ** 2
ax.plot(x, y2, label='quadratic', linewidth = 8)

y3 = x ** 3
ax.plot(x, y3, label='cubic', linestyle = "dotted")

ax.set_xlabel("X")
ax.set_ylabel("Y")
ax.legend()
```

[17]: <matplotlib.legend.Legend at 0x7f7f788b2d60>



```
[18]: fig, ax = plt.subplots()
x = np.arange(10)
y = x * 2
```

```

ax.plot(x, y, label='linear', color='blue', linewidth=2, linestyle=':')


y2 = x ** 2
ax.plot(x, y2, label='quadratic',color='orange', linewidth=2, linestyle='-')

y3 = x ** 3
ax.plot(x, y3, label='cubic',color='red', linewidth=2, linestyle=(0, (1,10)))

ax.set_xlabel("X")
ax.set_ylabel("Y")
ax.legend()

```

[18]: <matplotlib.legend.Legend at 0x7f7f684114f0>



## 2.5 multiple plots (Axes) in one figure

When to use multiple plots instead of one

- the two plots are on different scales
  - linear: range [0,9]
  - cubic: range [0, 800]

How?

- Create a figure containing two axes.


```
fig, axes = plt.subplots(1,2)
```

- Create a figure containing four axes.


```
fig, axes = plt.subplots(2,2) (2 rows and 2 columns)
```

```
fig, axes = plt.subplots(1,4) (1 row and 4 columns)
```


```
[19]: fig, axes = plt.subplots()
```



```
[20]: fig, axes = plt.subplots(1,2) # Create a figure containing two axes.
```




```
[21]: fig, axes = plt.subplots(2,1)
```



```
[22]: fig, axes = plt.subplots(1,2)  # Create a figure containing two axes.  
      ax1 = axes[0]  
      ax1.plot(x,y)
```


```
[22]: [<matplotlib.lines.Line2D at 0x7f7f499b60a0>]
```



```
[23]: fig, axes = plt.subplots(1,2) # Create a figure containing two axes.
      ax1 = axes[0]
      ax1.plot(x,y)

      ax2 = axes[1]
      ax2.plot(x,x**2)
```


```
[23]: [<matplotlib.lines.Line2D at 0x7f7f58ed51c0>]
```



```
[24]: fig, axes = plt.subplots(1,2,figsize=(8,3)) # Create a figure containing two
      ↪ axes.
      ax1 = axes[0]
      ax1.plot(x,y)

      ax2 = axes[1]
      ax2.plot(x,x**2)
```

[24]: [<matplotlib.lines.Line2D at 0x7f7f519c0070>]






```
[25]: fig, axes = plt.subplots(1,2,figsize=(8,3)) # Create a figure containing two
      ↪axes.
      ax1 = axes[0]
      ax1.plot(x,y)
      ax1.set_xlabel("X")
      ax1.set_ylabel("Y")
      ax1.set_title("Linear function")

      ax2 = axes[1]
      ax2.plot(x,x**3)
      ax2.set_xlabel("X")
      ax2.set_ylabel("Y")
      ax2.set_title("Cubic function")
```

```
[25]: Text(0.5, 1.0, 'Cubic function')
```




```
[26]: fig, axes = plt.subplots(2,2,figsize=(8,8)) # Create a figure containing two
      ↪axes.
      ax1 = axes[0,0]
      ax1.plot(x,y)
      ax1.set_xlabel("X")
      ax1.set_ylabel("Y")
      ax1.set_title("Linear function")

      ax2 = axes[0,1]
      ax2.plot(x,x**2)
      ax2.set_xlabel("X")
```

```
ax2.set_ylabel("Y")
ax2.set_title("Cubic function")
```

```
[26]: Text(0.5, 1.0, 'Cubic function')
```



```
[27]: x = np.arange(10)


fig, axes = plt.subplots(2,2 ,figsize=(10,9)) # Create a figure containing four
↪ axes.
ax1 = axes[0,0]
ax1.plot(x,x)
ax1.set_xlabel("X")
ax1.set_ylabel("Y")
ax1.set_title("Linear function")
```

```
ax2 = axes[0,1]
ax2.plot(x,x**2)
ax2.set_xlabel("X")
ax2.set_ylabel("Y")
ax2.set_title("Quadratic function")

ax3 = axes[1,0]
ax3.plot(x,x**3)
ax3.set_xlabel("X")
ax3.set_ylabel("Y")
ax3.set_title("Cubic function")

ax4 = axes[1,1]
ax4.plot(x,x**4)
ax4.set_xlabel("X")
ax4.set_ylabel("Y")
ax4.set_title("Polynomial function")
```

```
[27]: Text(0.5, 1.0, 'Polynomial function')
```




## 2.6 Scatter plot

`axes.scatter()`

- marker size `s=None`
- marker colors `c=None`
- marker style `marker=None`


```
[28]: fig, ax = plt.subplots()
      ax.scatter(x,y)
```

```
[28]: <matplotlib.collections.PathCollection at 0x7f7f59046b50>
```




```
[29]: fig, ax = plt.subplots()  
      ax.scatter(x,y, s=1)
```

```
[29]: <matplotlib.collections.PathCollection at 0x7f7f59046850>
```




```
[30]: fig, ax = plt.subplots()
      ax.scatter(x,y, s=np.arange(10))
```

```
[30]: <matplotlib.collections.PathCollection at 0x7f7f590b0fd0>
```



```
[31]: fig, ax = plt.subplots()
      ax.scatter(x,y, s=np.arange(10),c="red")
```


```
[31]: <matplotlib.collections.PathCollection at 0x7f7f18057910>
```



```
[32]: fig, ax = plt.subplots()
      ax.scatter(x,y, s=np.arange(10),c=np.arange(10))
```


```
[32]: <matplotlib.collections.PathCollection at 0x7f7f59213b50>
```





```
[33]: fig, ax = plt.subplots()
      ax.scatter(x,y, s=np.arange(10),c=np.arange(10), marker="v")
```

```
[33]: <matplotlib.collections.PathCollection at 0x7f7f49a7d040>
```




```
[34]: import numpy as np
import matplotlib.pyplot as plt

# Fixing random state for reproducibility
np.random.seed(0)

N = 50
x = np.random.rand(N)
y = np.random.rand(N)
colors = np.random.rand(N)
area = (30 * np.random.rand(N))**2 # 0 to 15 point radii
fig, ax = plt.subplots()
ax.scatter(x, y, s=area, c=colors, alpha=0.5)
```

```
[34]: <matplotlib.collections.PathCollection at 0x7f7f51b33280>
```




## 2.7 bar plot for categorical variables

`axes.bar()`: a vertical bar plot.

`axes.barh()`: a horizontal bar plot.


```
[35]: names = ['group_a', 'group_b', 'group_c']
      values = [1, 5, 10]
      fig, ax = plt.subplots()
      ax.bar(names, values)
```

```
[35]: <BarContainer object of 3 artists>
```




```
[36]: names = ['group_a', 'group_b', 'group_c']  
      values = [1, 5, 10]  
      fig, ax = plt.subplots()  
      ax.barh(names, values)
```

```
[36]: <BarContainer object of 3 artists>
```



```
[37]: names = ['group_a', 'group_b', 'group_c']
      values = [1, 5, 10]
      fig, axes = plt.subplots(1,3, figsize=(10,2))
      axes[0].bar(names, values)
      axes[1].plot(names, values)
      axes[2].scatter(names, values)
```

[37]: <matplotlib.collections.PathCollection at 0x7f7f49ab53d0>



## 2.8 Distributions and Densities

```
[38]: import numpy as np
```


```
x = np.random.normal(1,1,100)
```

```
[39]: x
```

```
[39]: array([ 2.12663592e+00, -7.99315084e-02, -1.47468652e-01,  5.62179955e-01,
          5.01967549e-01,  2.92953205e+00,  1.94942081e+00,  1.08755124e+00,
         -2.25435519e-01,  1.84436298e+00, -2.15347390e-04, -5.44771097e-01,
          2.18802979e+00,  1.31694261e+00,  1.92085882e+00,  1.31872765e+00,
          1.85683061e+00,  3.48974407e-01, -3.42428418e-02,  1.68159452e+00,
          1.96590336e-01,  3.10450222e-01,  5.44467496e-01,  1.01747916e+00,
          6.46006089e-01, -3.74951293e-01,  3.56381597e-01, -1.22340315e+00,
          1.62523145e+00, -6.02057656e-01, -1.04383339e-01,  1.05216508e+00,
          2.60437004e-01,  2.54301460e+00, -2.92856910e-01,  1.26705087e+00,
          9.60717182e-01, -1.68093498e-01,  1.52327666e+00,  8.28453669e-01,
          1.77179055e+00,  1.82350415e+00,  3.16323595e+00,  2.33652795e+00,
          6.30818162e-01,  7.60620822e-01,  2.09965960e+00,  1.65526373e+00,
          1.64013153e+00, -6.16956044e-01,  9.75673876e-01,  2.61969091e-01,
          1.27992460e+00,  9.01849610e-01,  1.91017891e+00,  1.31721822e+00,
          1.78632796e+00,  5.33580903e-01,  5.55537441e-02,  5.89950307e-01,
          9.82979586e-01,  1.37915174e+00,  3.25930895e+00,  9.57742848e-01,
          4.40549995e-02,  6.54018224e-01,  5.36404025e-01,  1.48148147e+00,
         -5.40797014e-01,  1.06326199e+00,  1.15650654e+00,  1.23218104e+00,
          4.02683931e-01,  7.62078270e-01, -4.24060909e-01,  5.06680117e-01,
          4.57138524e-01,  1.41605005e+00, -1.56182432e-01,  1.78119810e+00,
          2.49448454e+00, -1.06998503e+00,  1.42625873e+00,  1.67690804e+00,
          3.62562974e-01,  6.02728186e-01,  8.67119422e-01,  7.02209121e-01,
          6.90987031e-01, -6.76003806e-01,  2.15233156e+00,  2.07961859e+00,
          1.86635741e-01, -4.66424328e-01,  1.52106488e+00,  4.24212030e-01,
          1.14195316e+00,  6.80671583e-01,  1.69153875e+00,  1.69474914e+00])
```


```
[40]: fig, ax = plt.subplots()
      ax.plot(x)
```

```
[40]: [<matplotlib.lines.Line2D at 0x7f7f59a61910>]
```



```
[41]: fig, ax = plt.subplots()
      ax.plot(np.arange(100),x)
```


```
[41]: [<matplotlib.lines.Line2D at 0x7f7f49ddb640>]
```



```
[42]: fig, ax = plt.subplots()
      ax.scatter(np.arange(100),x)
```


```
[42]: <matplotlib.collections.PathCollection at 0x7f7f5956a8e0>
```






```
[43]: fig, ax = plt.subplots()
      ax.hist(x)
```

```
[43]: (array([ 2.,  8., 11., 17., 18., 14., 17.,  8.,  2.,  3.]),
      array([-1.22340315, -0.77513194, -0.32686073,  0.12141048,  0.56968169,
              1.0179529 ,  1.46622411,  1.91449532,  2.36276653,  2.81103774,
              3.25930895]),
      <BarContainer object of 10 artists>)
```




```
[44]: fig, ax = plt.subplots()
      ax.hist(x, density=True)
```

```
[44]: (array([0.04461585, 0.17846339, 0.24538716, 0.3792347 , 0.40154263,
              0.31231093, 0.3792347 , 0.17846339, 0.04461585, 0.06692377]),
      array([-1.22340315, -0.77513194, -0.32686073,  0.12141048,  0.56968169,
              1.0179529 ,  1.46622411,  1.91449532,  2.36276653,  2.81103774,
              3.25930895]),
      <BarContainer object of 10 artists>)
```



```
[45]: ax.hist?
```

```
[46]: fig, ax = plt.subplots()
ax.hist(x, density=True)
ax.set_xlabel('x')
ax.set_ylabel('Probability')
ax.set_title('Histogram')
ax.text(-1, .4, r'$\mu=1, \sigma=1$')
ax.grid(True)
```



## 2.9 Image plotting


`ax.imshow`

```
[47]: image = np.eye(100)
      image
```

```
[47]: array([[1., 0., 0., ..., 0., 0., 0.],
            [0., 1., 0., ..., 0., 0., 0.],
            [0., 0., 1., ..., 0., 0., 0.],
            ...,
            [0., 0., 0., ..., 1., 0., 0.],
            [0., 0., 0., ..., 0., 1., 0.],
            [0., 0., 0., ..., 0., 0., 1.]])
```

```
[48]: fig, ax = plt.subplots()
      ax.imshow(image)
```


```
[48]: <matplotlib.image.AxesImage at 0x7f7f59b034f0>
```



```
[49]: dim = 50
x_coords, y_coords = np.meshgrid(range(dim), range(dim), indexing='ij')
beta_low = np.zeros((dim,dim))
for i in range(x_coords.shape[0]):
    for j in range(x_coords.shape[1]):
        x = x_coords[i,j]
        y = y_coords[i,j]
        beta_low[i,j] = 1 + 1/24*(i+j)
```

```
[50]: fig, ax = plt.subplots()
ax.imshow(beta_low,cmap="jet")
```

```
[50]: <matplotlib.image.AxesImage at 0x7f7f59b856a0>
```




## 2.10 Saving a figure

`plt.savefig()`

Save the current figure.

```
[51]: fig, ax = plt.subplots()
      ax.imshow(beta_low, cmap='jet')
      plt.savefig("image.png")
```



```
[52]: x = np.arange(10)

fig, axes = plt.subplots(2,2,figsize=(10,9)) # Create a figure containing four
↪axes.
ax1 = axes[0,0]
ax1.plot(x,x)
ax1.set_xlabel("X")
ax1.set_ylabel("Y")
ax1.set_title("Linear function")

ax2 = axes[0,1]
ax2.plot(x,x**2)
ax2.set_xlabel("X")
ax2.set_ylabel("Y")
ax2.set_title("Quadratic function")


ax3 = axes[1,0]
ax3.plot(x,x**3)
ax3.set_xlabel("X")
ax3.set_ylabel("Y")
ax3.set_title("Cubic function")
```

```

ax4 = axes[1,1]
ax4.plot(x,x**4)
ax4.set_xlabel("X")
ax4.set_ylabel("Y")
ax4.set_title("Polynomial function")

plt.savefig("functions_4.png",dpi=500)

```



There is a lot more to matplotlib. One can visit the [gallery](#) and pull examples in to get a sense of what is possible, and how to adapt examples for your own purposes.