

Python from Scratch

Python Dictionaries

Lesson 13

- **Python Dictionaries**
 - Dictionary
 - Dictionary Items
 - Ordered or Unordered?
 - Changeable
 - Duplicates Not Allowed
 - Dictionary Length
 - Dictionary Items - Data Types
 - type()
 - The dict() Constructor
 - Python Collections (Arrays)
- **Access Items**
 - Accessing Items
 - Get Keys
 - Get Values
 - Get Items
 - Check if Key Exists
- **Change Items**
 - Change Values
 - Update Dictionary
- **Add Items**
 - Adding Items
 - Update Dictionary
- **Remove Items**
- **Loop Dictionaries**
- **Copy Dictionaries**
- **Nested Dictionaries**
- **Python - Dictionaries Methods**
- **Python - Dictionaries Exercises**

Python Dictionaries

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}
```

Dictionary

Dictionaries are used to store data values in key:value pairs.

A dictionary is a collection which is ordered*, changeable and do not allow duplicates.

As of Python version 3.7, dictionaries are *ordered*. In Python 3.6 and earlier, dictionaries are *unordered*.

Dictionaries are written with curly brackets, and have keys and values:

Example

Create and print a dictionary:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
print(thisdict)
```

Dictionary Items

Dictionary items are ordered, changeable, and does not allow duplicates.

Dictionary items are presented in key:value pairs, and can be referred to by using the key name.

Example

Print the "brand" value of the dictionary:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
print(thisdict["brand"])
```

Ordered or Unordered?

As of Python version 3.7, dictionaries are *ordered*. In Python 3.6 and earlier, dictionaries are *unordered*.

When we say that dictionaries are ordered, it means that the items have a defined order, and that order will not change.

Unordered means that the items does not have a defined order, you cannot refer to an item by using an index.

Changeable

Dictionaries are changeable, meaning that we can change, add or remove items after the dictionary has been created.

Duplicates Not Allowed

Dictionaries cannot have two items with the same key:

Example

Duplicate values will overwrite existing values:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964,  
    "year": 2020  
}  
print(thisdict)
```

Python - Access Dictionary Items

Accessing Items

You can access the items of a dictionary by referring to its key name, inside square brackets:



Example

Get the value of the "model" key:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
x = thisdict["model"]
```

There is also a method called `get()` that will give you the same result:



Example

Get the value of the "model" key:

```
x = thisdict.get("model")
```

Get Keys

The `keys()` method will return a list of all the keys in the dictionary.



Example

Get a list of the keys:

```
x = thisdict.keys()
```

The list of the keys is a *view* of the dictionary, meaning that any changes done to the dictionary will be reflected in the keys list.

Example

Add a new item to the original dictionary, and see that the keys list gets updated as well:

```
car = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}
```



```
x = car.keys()
```

```
print(x) #before the change
```

```
car["color"] = "white"
```

```
print(x) #after the change
```

Get Values

The `values()` method will return a list of all the values in the dictionary.



Example

Get a list of the values:

```
x = thisdict.values()
```

The list of the values is a *view* of the dictionary, meaning that any changes done to the dictionary will be reflected in the values list.

Example

Make a change in the original dictionary, and see that the values list gets updated as well:

```
car = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}
```



```
x = car.values()
```

```
print(x) #before the change
```

```
car["year"] = 2020
```

```
print(x) #after the change
```

Example

Add a new item to the original dictionary, and see that the values list gets updated as well:

```
car = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}
```

```
x = car.values()
```

```
print(x) #before the change
```

```
car["color"] = "red"
```

```
print(x) #after the change
```


Get Items

The `items()` method will return each item in a dictionary, as tuples in a list.

Example



Get a list of the key:value pairs

```
x = thisdict.items()
```

The returned list is a *view* of the items of the dictionary, meaning that any changes done to the dictionary will be reflected in the items list.

Example

Make a change in the original dictionary, and see that the items list gets updated as well:

```
car = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}
```



```
x = car.items()
```

```
print(x) #before the change
```

```
car["year"] = 2020
```

```
print(x) #after the change
```

Example

Add a new item to the original dictionary, and see that the items list gets updated as well:

```
car = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
  
x = car.items()  
  
print(x) #before the change  
  
car["color"] = "red"  
  
print(x) #after the change
```

Check if Key Exists

To determine if a specified key is present in a dictionary use the `in` keyword:

Example

Check if "model" is present in the dictionary:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
if "model" in thisdict:  
    print("Yes, 'model' is one of the keys in the  
    thisdict dictionary")
```

Python - Change Dictionary Items

Change Values

You can change the value of a specific item by referring to its key name:

Example



Change the "year" to 2018:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict["year"] = 2018
```

Update Dictionary

The `update()` method will update the dictionary with the items from the given argument.

The argument must be a dictionary, or an iterable object with key:value pairs.

Example

Update the "year" of the car by using the `update()` method:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict.update({"year": 2020})
```



Python - Add Dictionary Items

Adding Items

Adding an item to the dictionary is done by using a new index key and assigning a value to it:



Example

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict["color"] = "red"  
print(thisdict)
```

Update Dictionary

The `update()` method will update the dictionary with the items from a given argument. If the item does not exist, the item will be added.

The argument must be a dictionary, or an iterable object with key:value pairs.

Example



Add a color item to the dictionary by using the `update()` method:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict.update({"color": "red"})
```



Python - Remove Dictionary Items

Removing Items

There are several methods to remove items from a dictionary:

Example

The `pop()` method removes the item with the specified key name:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict.pop("model")  
print(thisdict)
```



Example

The `popitem()` method removes the last inserted item (in versions before 3.7, a random item is removed instead):

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict.popitem()  
print(thisdict)
```



Example

The **del** keyword removes the item with the specified key name:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
del thisdict["model"]  
print(thisdict)
```



Example

The **del** keyword can also delete the dictionary completely:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
del thisdict  
print(thisdict) #this will cause an error because  
"thisdict" no longer exists.
```

Example



The **clear()** method empties the dictionary:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict.clear()  
print(thisdict)
```

Python - Loop Dictionaries

Loop Through a Dictionary



You can loop through a dictionary by using a **for** loop.

When looping through a dictionary, the return value are the *keys* of the dictionary, but there are methods to return the *values* as well.

Example

Print all key names in the dictionary, one by one:

```
for x in thisdict:  
    print(x)
```

Example



Print all *values* in the dictionary, one by one:

```
for x in thisdict:  
    print(thisdict[x])
```

Example



You can also use the **values()** method to return values of a dictionary:

```
for x in thisdict.values():  
    print(x)
```

Example



You can use the **keys()** method to return the keys of a dictionary:

```
for x in thisdict.keys():  
    print(x)
```

Example



Loop through both *keys* and *values*, by using the **items()** method:

```
for x, y in thisdict.items():  
    print(x, y)
```



Python - Copy Dictionaries

Copy a Dictionary

You cannot copy a dictionary simply by typing `dict2 = dict1`, because: `dict2` will only be a *reference* to `dict1`, and changes made in `dict1` will automatically also be made in `dict2`.

There are ways to make a copy, one way is to use the built-in Dictionary method `copy()`.

Example



Make a copy of a dictionary with the `copy()` method:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
mydict = thisdict.copy()  
print(mydict)
```



Another way to make a copy is to use the built-in function `dict()`.

Example

Make a copy of a dictionary with the `dict()` function:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
mydict = dict(thisdict)  
print(mydict)
```



Python - Nested Dictionaries

Nested Dictionaries

A dictionary can contain dictionaries, this is called nested dictionaries.

Example



Create a dictionary that contain three dictionaries:

```
myfamily = {  
    "child1" : {  
        "name" : "Emil",  
        "year" : 2004  
    },  
    "child2" : {  
        "name" : "Tobias",  
        "year" : 2007  
    },  
    "child3" : {  
        "name" : "Linus",  
        "year" : 2011  
    }  
}
```

Or, if you want to add three dictionaries into a new dictionary:

Example

Create three dictionaries, then create one dictionary that will contain the other three dictionaries:

```
child1 = {  
    "name" : "Emil",  
    "year" : 2004  
}  
child2 = {  
    "name" : "Tobias",  
    "year" : 2007  
}  
child3 = {  
    "name" : "Linus",  
    "year" : 2011  
}  
  
myfamily = {  
    "child1" : child1,  
    "child2" : child2,  
    "child3" : child3  
}
```



Python Dictionary Methods

Dictionary Methods

Python has a set of built-in methods that you can use on dictionaries.

Method	Description
<u>clear()</u>	Removes all the elements from the dictionary
<u>copy()</u>	Returns a copy of the dictionary
<u>fromkeys()</u>	Returns a dictionary with the specified keys and value
<u>get()</u>	Returns the value of the specified key
<u>items()</u>	Returns a list containing a tuple for each key value pair
<u>keys()</u>	Returns a list containing the dictionary's keys
<u>pop()</u>	Removes the element with the specified key
<u>popitem()</u>	Removes the last inserted key-value pair
<u>setdefault()</u>	Returns the value of the specified key. If the key does not exist: insert the key, with the specified value
<u>update()</u>	Updates the dictionary with the specified key-value pairs
<u>values()</u>	Returns a list of all the values in the dictionary

Python Dictionary Exercises

Test Yourself With Exercises

Now you have learned a lot about dictionaries, and how to use them in Python.

Are you ready for a test?

Try to insert the missing part to make the code work as expected:

Exercise:

Use the `get` method to print the value of the "model" key of the `car` dictionary.

```
car = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
print()
```