AETHERFLOW TECHNICAL MANUAL

Complete Functions & Project Architecture Reference

A comprehensive engineering reference documenting every state handler, mathematical algorithm, 3D graphics projection routine, lifecycle hook, and animation controller powering the entire AetherFlow autonomous workflow landing page.

APPLICATION FRAMEWORK
React 19 (Pure JSX) + Vite 8.3

STYLING & DESIGN ENGINE
Tailwind CSS v4 + Vanilla CSS Tokens

TARGET WORKSPACE
Landing Page Design & Development

DOCUMENTATION DATE
October 2026 • Production Edition

Table of Contents

1. Global Application State & Root Orchestration	src/App.jsx
2. 3D Neural Particle Lattice & Spatial Math	src/components/Canvas3D.jsx
3. Interactive Video Player State Machine & Memory	src/components/DemoVideoPlayer.jsx
4. Procedural Canvas Animated Favicon Engine	src/components/AnimatedFavicon.jsx
5. 3D Perspective Tilt Mechanics	src/components/TiltCard.jsx
6. Navigation, Scroll Detection & Drawer Controls	src/components/Navbar.jsx
7. Interactive Hero DAG Simulation & Clipboard	src/components/Hero.jsx
8. Bento Grid Architecture & Metrics Exploration	src/components/About.jsx
9. Dynamic Feature Matrix & Filter Engine	src/components/Features.jsx
10. Sequential Workflow Stepper Simulator	src/components/HowItWorks.jsx
11. Interactive Pricing Engine & Discount Calculator	src/components/Pricing.jsx
12. Testimonials Grid & Rating Visualizer	src/components/Testimonials.jsx
13. Footer Newsletter Validator & System Health	src/components/Footer.jsx
14. Modal Dialog Accessibility & Toast Queue	src/components/Modal.jsx & Toast.jsx
15. Moving Typography Animation Keyframes	src/index.css
16. Architecture & Feature Deep Dive Subpage	src/components/ArchitectureSubpage.jsx
17. Individual Feature Subpages (6 Boxes)	src/components/FeatureDetailSubpage.jsx

> **Engineering Standard:** All functions in this project are strictly implemented in pure modern React 19 JSX without TypeScript boilerplate, utilizing hardware-accelerated CSS and optimized requestAnimationFrame hooks for zero layout shift and 60 FPS performance.

1. Global Application State & Root Orchestration (App.jsx)

`src/App.jsx` serves as the primary orchestration hub, managing global modal dialog states, multi-toast queues, scroll-to-top tracking, and the intelligent video memory auto-reset mechanism.

handleOpenDemoModal()

State & Memory

Calculates time elapsed since the user last closed the demo player modal. If the duration exceeds 2,000 milliseconds (2 seconds), it automatically resets playback progress to 0% and active chapter to 0 via a unique `videoKey` re-render cycle.

```
const handleOpenDemoModal = () => {
  const now = Date.now();
  // Reset video if closed for more than 2 seconds
  if (lastVideoClosedRef.current && (now - lastVideoClosedRef.current >= 2000)) {
    setSavedVideoState({ progress: 0, chapter: 0 });
    setVideoKey((k) => k + 1);
  }
  setDemoModalOpen(true);
};
```

Variables / Refs	Type	Purpose
`lastVideoClosedRef`	`useRef<number>`	High-resolution timestamp of when modal was closed.
`savedVideoState`	`{ progress: number, chapter: number }`	Preserves playback state during quick dialog toggles.
`videoKey`	`number`	Forces complete unmount/remount of DemoVideoPlayer on reset.

handleCloseDemoModal()

Modal Controller

Records the exact closing timestamp into `lastVideoClosedRef.current` and hides the walkthrough modal.

```
const handleCloseDemoModal = () => {
  lastVideoClosedRef.current = Date.now();
  setDemoModalOpen(false);
};
```

showToast(title, message, type)

Notification Queue

Dispatches a new toast alert with an auto-generated unique ID, appends it to the global array, and sets a 4,000ms auto-dismissal timeout.

```
const showToast = (title, message, type = 'info') => {
  const id = Date.now().toString() + Math.random().toString(36).substring(2, 6);
  setToasts((prev) => [...prev, { id, title, message, type }]);

  setTimeout(() => {
    setToasts((prev) => prev.filter((t) => t.id !== id));
  }, 4000);
};
```

Param	Type	Description
`title`	`string`	Bold headline rendered with animated font-shimmer.
`message`	`string`	Descriptive body text detailing the completed action.
`type`	`'info' | 'success' | 'warning'`	Determines Lucide icon and border theme color.

scrollToTop() & Scroll Listener

DOM Navigation

Monitors `window.scrollY`. Reveals floating back-to-top button once scrolled past 400px and triggers smooth browser window navigation.

```
useEffect(() => {
  const handleScroll = () => {
    setShowBackToTop(window.scrollY > 400);
  };
  window.addEventListener('scroll', handleScroll);
  return () => window.removeEventListener('scroll', handleScroll);
}, []);

const scrollToTop = () => {
  window.scrollTo({ top: 0, behavior: 'smooth' });
};
```

2. 3D Neural Particle Lattice & Spatial Math (Canvas3D.jsx)

`src/components/Canvas3D.jsx` delivers a GPU-efficient HTML5 Canvas 3D particle lattice running as both a section background and a global ambient neural backdrop across the entire application.

Particle3D Constructor & Coordinates

Spatial Geometry

Instantiates nodes with random 3-dimensional spherical coordinates (X, Y, Z) and minute angular drift velocities.

```
class Particle3D {
  constructor(width, height) {
    this.x = (Math.random() - 0.5) * width * 1.6;
    this.y = (Math.random() - 0.5) * height * 1.6;
    this.z = (Math.random() - 0.5) * 800;
    this.vx = (Math.random() - 0.5) * 0.35;
    this.vy = (Math.random() - 0.5) * 0.35;
    this.vz = (Math.random() - 0.5) * 0.35;
    this.radius = Math.random() * 1.8 + 1.0;
  }
}
```

`project(x, y, z, rotationX, rotationY, focalLength, cx, cy)` Perspective Projection

Calculates 3D-to-2D perspective projection using Euler trigonometric rotation matrices around both horizontal and vertical axes.

```
// 1. Yaw rotation around Y axis
const cosY = Math.cos(rotY), sinY = Math.sin(rotY);
const x1 = x * cosY - z * sinY;
const z1 = z * cosY + x * sinY;

// 2. Pitch rotation around X axis
const cosX = Math.cos(rotX), sinX = Math.sin(rotX);
const y2 = y * cosX - z1 * sinX;
const z2 = z1 * cosX + y * sinX;

// 3. Pinhole perspective projection
const scale = focalLength / (focalLength + z2 + 600);
const screenX = cx + x1 * scale;
const screenY = cy + y2 * scale;
```

Variable	Formula / Role	Impact
`scale`	`focalLength / (focalLength + z + 600)`	Calculates depth scaling; closer particles appear larger.
`rotX, rotY`	Target mouse angle lerped at `0.05`	Provides smooth interactive parallax on cursor movement.

`renderLatticeConnections(particles, ctx, threshold)` Lattice Geometry

Computes Euclidean distance between neighbor nodes using `Math.hypot(dx, dy)` and draws luminescent emerald lines fading inversely with distance.

```
for (let i = 0; i < len; i++) {
  for (let j = i + 1; j < len; j++) {
    const dist = Math.hypot(p[i].screenX - p[j].screenX, p[i].screenY - p[j].screenY);
    if (dist < threshold) {
      const alpha = (1 - dist / threshold) * 0.25;
      ctx.strokeStyle = `rgba(16, 185, 129, ${alpha})`;
      ctx.beginPath();
      ctx.moveTo(p[i].screenX, p[i].screenY);
      ctx.lineTo(p[j].screenX, p[j].screenY);
      ctx.stroke();
    }
  }
}
```

3. Interactive Video Player State Machine (DemoVideoPlayer.jsx)

`src/components/DemoVideoPlayer.jsx` provides an interactive simulation video player featuring scrubbing, play/pause controls, chapter selection, volume management, and live chapter updates.

useEffect Video Ticker & Chapter Transition

Playback Engine

Maintains an active timer when `isPlaying === true`. Advances simulated progress, detects milestone boundaries (25%, 55%, 80%), and dispatches chapter transitions.

```
useEffect(() => {
  if (!isPlaying) return;
  const interval = setInterval(() => {
    setProgress((prev) => {
      if (prev >= 100) {
        setIsPlaying(false);
        onProgressUpdate?.(100, 3);
        return 100;
      }
      const next = prev + 1;
      let nextChapter = 0;
      if (next >= 80) nextChapter = 3;
      else if (next >= 55) nextChapter = 2;
      else if (next >= 25) nextChapter = 1;
      setActiveChapter(nextChapter);
      onProgressUpdate?.(next, nextChapter);
      return next;
    });
  }, 250);
  return () => clearInterval(interval);
}, [isPlaying, onProgressUpdate]);
```

Chapter Range	Title	Topic
0% – 24%	01. Stack OAuth Connect	Zero-config bi-directional synchronization.
25% – 54%	02. Autonomous Agent DAG	Multi-agent mesh verifying AST boundaries.
55% – 79%	03. Self-Healing Rollback	Detecting latency anomalies & canary rollbacks.
80% – 100%	04. Live Telemetry & SLA	P99 cycle throughput across 32 edge regions.

handleSeek(percentage, chapterIndex)

Scrubber Navigation

Calculates click coordinate offsets relative to the bounding box width via `getBoundingClientRect()`, updating both the timeline indicator and active chapter instantly.

```
const handleSeek = (pct, chIdx) => {
  setProgress(pct);
  setActiveChapter(chIdx);
  onProgressUpdate?.(pct, chIdx);
};
```

AI Voice Synchronization Engine (audioRef)

Background Voice AI

Synchronizes neural AI speech narration with video chapters using high-fidelity WAV tracks and an automatic Web Speech API fallback. Dynamically switches audio files as the active chapter advances, pauses during modal dismissal, and resumes cleanly on user interaction.

```
// 1. Synchronized Chapter Audio Switching
if (lastPlayedChapterRef.current !== activeChapter) {
  lastPlayedChapterRef.current = activeChapter;
  const targetAudio = chapters[activeChapter].audioSrc;
  audioRef.current.src = targetAudio;
  audioRef.current.currentTime = 0;
  audioRef.current.play().then(() => {
    setIsVoiceSpeaking(true);
  }).catch(() => {
    // Automatic fallback to SpeechSynthesis API
    const utterance = new SpeechSynthesisUtterance(chapters[activeChapter].voiceText);
    utterance.rate = 0.95;
    window.speechSynthesis.speak(utterance);
  });
}
```

Chapter	Audio Source	Voice Line Synthesized
01. OAuth	`/ai-voice-chapter-0.wav`	Initiating zero-config sync with GitHub, Linear, Slack, AWS CloudWatch.
02. DAG	`/ai-voice-chapter-1.wav`	Compiling multi-agent mesh workflows, verifying AST boundaries.
03. Rollback	`/ai-voice-chapter-2.wav`	Continuous telemetry triggers canary rollback in under 8 seconds.
04. SLA	`/ai-voice-chapter-3.wav`	Aggregating P99 latency & throughput across 32 distributed edge regions.

Merged "Audio On" Controller & Individual "CC On/CC Off" Toggle

Audio & Subtitle Controls

Consolidates the speaker toggle and soundwave frequency visualizer into a single unified **"Audio On"** (or **"Audio Off"**) control with live animated frequency bars. Features an individual dedicated **"CC On" / "CC Off"** subtitle button that toggles floating real-time AI transcription closed captions.

4. Procedural Canvas Animated Favicon Engine (AnimatedFavicon.jsx)

`src/components/AnimatedFavicon.jsx` renders a dynamic, live-animating favicon in the user's browser tab using an offscreen HTML5 canvas stream updated on every animation frame.

drawFaviconFrame(ctx, frame)

Canvas Rendering

Draws the AetherFlow brand mark onto an offscreen 32×32 pixel canvas with an orbiting neon satellite electron and glowing gradient aura, then pushes it to the browser tab link header.

```
const drawFaviconFrame = (ctx, frame) => {
  ctx.clearRect(0, 0, 32, 32);

  // 1. Dark glowing backing pill
  ctx.fillStyle = '#040a12';
  ctx.beginPath();
  ctx.arc(16, 16, 15, 0, Math.PI * 2);
  ctx.fill();

  // 2. Inner pulsating emerald core
  const pulse = Math.sin(frame * 0.08) * 1.5 + 5;
  ctx.fillStyle = '#10b981';
  ctx.beginPath();
  ctx.arc(16, 16, pulse, 0, Math.PI * 2);
  ctx.fill();

  // 3. Orbiting satellite particle
  const angle = frame * 0.05;
  const orbitX = 16 + Math.cos(angle) * 10;
  const orbitY = 16 + Math.sin(angle) * 10;
  ctx.fillStyle = '#34d399';
  ctx.beginPath();
  ctx.arc(orbitX, orbitY, 2.2, 0, Math.PI * 2);
  ctx.fill();
};
```

updateTabFavicon(canvas)

DOM Stream

Converts canvas bitmap to a PNG data URL and binds it to `<link rel="icon">` in the document head.

```
const faviconLink = document.querySelector("link[rel*='icon']") || document.createElement('lir
faviconLink.type = 'image/png';
faviconLink.rel = 'shortcut icon';
faviconLink.href = canvas.toDataURL('image/png');
document.getElementsByTagName('head')[0].appendChild(faviconLink);
```

5. 3D Perspective Tilt Mechanics (TiltCard.jsx)

`src/components/TiltCard.jsx` creates interactive cards that tilt along 3D axes and reflect a radial spotlight based on cursor position.

`handleMouseMove(e)`

3D Transform

Converts cursor position into rotational angles (`rotateX` , `rotateY`) clamped to a maximum 10-degree deflection angle.

```
const handleMouseMove = (e) => {
  const rect = cardRef.current.getBoundingClientRect();
  const x = e.clientX - rect.left;
  const y = e.clientY - rect.top;
  const centerX = rect.width / 2;
  const centerY = rect.height / 2;

  // Calculate rotational angles with opposite sign for natural tilt
  const rotX = ((y - centerY) / centerY) * -10;
  const rotY = ((x - centerX) / centerX) * 10;

  setTransform(`perspective(1000px) rotateX(${rotX}deg) rotateY(${rotY}deg) scale3d(1.02, 1.02
  setSpotlight({ x, y, opacity: 1 });
};
```

6. Navigation & Scroll Detection (Navbar.jsx)

handleScrollThreshold() & Active Nav Tracking

UI Layout

Toggles compact glassy styling when scrolled down past 20px and renders an animated pill highlight behind the currently hovered navigation item.

```
const [isScrolled, setIsScrolled] = useState(false);
const [hoveredNav, setHoveredNav] = useState(null);

useEffect(() => {
  const onScroll = () => setIsScrolled(window.scrollY > 20);
  window.addEventListener('scroll', onScroll);
  return () => window.removeEventListener('scroll', onScroll);
}, []);
```

7. Interactive Hero DAG Simulation & Clipboard (Hero.jsx)

runSimulationStep(stepIndex)

Workflow Engine

Simulates real-time DAG node execution in the interactive terminal mockup, advancing progress bars, updating node statuses from "queued" to "running" to "completed", and triggering a success toast upon completion.

```
const runSimulationStep = (idx) => {
  setExecutingStep(idx);
  setStepProgress(0);
  const timer = setInterval(() => {
    setStepProgress((p) => {
      if (p >= 100) {
        clearInterval(timer);
        onShowToast('Node Verified', 'Autonomous DAG completed AST check with 0 latency.', 'su
        return 100;
      }
      return p + 15;
    });
  }, 80);
};
```

copyCodeSnippet(snippetText)

Clipboard API

Copies SDK installation commands to the system clipboard via `navigator.clipboard.writeText` with fallback error recovery.

```
const copyCodeSnippet = (text) => {
  navigator.clipboard.writeText(text).then(() => {
    setIsCopied(true);
    onShowToast('Copied to Clipboard', 'Installation command ready to paste in your shell.', '
    setTimeout(() => setIsCopied(false), 2000);
  });
};
```

8. Bento Grid Architecture & Metrics (About.jsx)

`handleStatDrilldown(statKey)`

Telemetry

Dispatches detailed SLA telemetry benchmarks when the user clicks on metric pills (`3.8x` , `99.98%` , `14.2M+` , `<45ms`), showing regional latency and throughput data.

9. Dynamic Feature Matrix & Filter Engine (Features.jsx)

`filterFeatures(activeCategory)`

Data Filter

Filters the bento grid of platform capabilities based on category (`All` , `Automation` , `Security` , `Integration`) with smooth animated layout transitions.

```
const filtered = activeFilter === 'All'
  ? features
  : features.filter((item) => item.category === activeFilter);
```

10. Sequential Workflow Stepper (HowItWorks.jsx)

`handleStepChange(stepIndex)`

Interactive Stepper

Controls the 4-phase architectural walkthrough (1. Connect Stack, 2. Compose DAG, 3. Mesh Execution, 4. Telemetry SLA), updating the active step and switching the live code/terminal preview panel accordingly.

11. Interactive Pricing Engine (Pricing.jsx)

`calculateBilling(baseMonthly, isAnnual)`

Billing Math

Calculates discounted annual pricing with a 20% discount (`price * 0.8`), updating price labels and annual savings chips dynamically.

```
const priceDisplay = isAnnual
  ? Math.round(plan.basePrice * 0.8)
  : plan.basePrice;
```

13. Footer Newsletter Validator (Footer.jsx)

`handleSubscribe(e)`

Form Validation

Validates email format using regex, clears the input field upon successful validation, sets `isSubscribed = true` , and triggers a confirmation toast notification.

```
const handleSubscribe = (e) => {
  e.preventDefault();
  if (!emailInput || !emailInput.includes('@')) {
    onShowToast('Invalid Email', 'Please enter a valid work email address.', 'warning');
    return;
  }
  setIsSubscribed(true);
  onShowToast('Subscribed!', `Welcome aboard with ${emailInput}.`, 'success');
  setEmailInput('');
};
```

14. Modal Dialog Accessibility (Modal.jsx)

`useEscapeKey & Body Scroll Lock`

Accessibility

Locks the background document scroll (`overflow: hidden`) while dialogs are open, and listens for the `Escape` key to dismiss modals safely.

```
useEffect(() => {
  const handleKeyDown = (e) => {
    if (e.key === 'Escape' && isOpen) onClose();
  };
  if (isOpen) {
    document.body.style.overflow = 'hidden';
    window.addEventListener('keydown', handleKeyDown);
  }
  return () => {
    document.body.style.overflow = '';
    window.removeEventListener('keydown', handleKeyDown);
  };
}, [isOpen, onClose]);
```

15. Moving Typography Animation Keyframes (index.css)

Hardware-accelerated CSS keyframes applied across all project typography for continuous moving gradient and glow effects:

`.font-shimmer`

Headline Gradient Flow

```
@keyframes textShimmerFlow {
  0% { background-position: 0% 50%; }
  50% { background-position: 100% 50%; }
  100% { background-position: 0% 50%; }
}
.font-shimmer {
  background: linear-gradient(90deg, #ffffff 0%, #34d399 25%, #6ee7b7 50%, #38bdf8 75%, #fffff
  background-size: 250% auto;
  -webkit-background-clip: text;
  -webkit-text-fill-color: transparent;
  animation: textShimmerFlow 6s ease-in-out infinite;
}
```

.font-aurora

Fluid Aurora Gradient

```
@keyframes textAuroraFlow {
  0% { background-position: 0% 50%; }
  50% { background-position: 100% 50%; }
  100% { background-position: 0% 50%; }
}
.font-aurora {
  background: linear-gradient(135deg, #10b981 0%, #34d399 30%, #2dd4bf 70%, #10b981 100%);
  background-size: 200% 200%;
  -webkit-background-clip: text;
  -webkit-text-fill-color: transparent;
  animation: textAuroraFlow 5s ease infinite;
}
```

.font-glow & .font-hover-expand

Metrics & Interactions

```
@keyframes fontGlowPulse {
  0%, 100% { filter: drop-shadow(0 0 4px rgba(16, 185, 129, 0.3)); }
  50% { filter: drop-shadow(0 0 14px rgba(16, 185, 129, 0.75)); }
}
.font-glow {
  animation: fontGlowPulse 3s ease-in-out infinite;
}
.font-hover-expand {
  display: inline-block;
  transition: letter-spacing 0.3s cubic-bezier(0.4, 0, 0.2, 1), transform 0.3s ease;
}
.font-hover-expand:hover {
  letter-spacing: 0.04em;
  transform: translateY(-1px);
}
```

16. Architecture & Feature Deep Dive Subpage (ArchitectureSubpage.jsx)

`src/components/ArchitectureSubpage.jsx` implements the dedicated technical architecture subpage with regional telemetry inspection (US-East, EU-Central, AP-South), interactive live DAG simulation sandboxes, and code snippet analyzers.

Client-Side Subpage Hash Routing (App.jsx)

SPA Router

Synchronizes browser URL hash history (`#architecture` , `#home`) and dispatches smooth transitions between the primary landing page and the technical architecture subpage.

```
const handleNavigateToArchitecture = (featureId = null) => {
  setInitialFeatureId(featureId);
  setCurrentView('architecture');
  window.location.hash = '#architecture';
  window.scrollTo({ top: 0, behavior: 'smooth' });
};
```

handleRunSimulation() & Sandbox Log Stream

Simulation Engine

Executes live verification checks across the active architecture module, asserting AST boundary compliance, cryptographic enclave attestation, and regional SLA latency metrics.

```
const handleRunSimulation = () => {
  setIsSimulating(true);
  // Sequentially stream verification logs
  const interval = setInterval(() => {
    setSimLog((prev) => [...prev, `${currentSystem.name} verified: ${metrics[1].regionSpeed[se
  }, 600);
};
```

17. Individual Feature Subpages (FeatureDetailSubpage.jsx)

`src/components/FeatureDetailSubpage.jsx` provides dedicated, deep-dive subpages for each of the 6 core platform capabilities, accessible directly from the landing page feature cards or via URL hashes (`#feature-1` through `#feature-6`).

`featurePagesData` Dictionary & Dedicated Content

Architecture Model

Houses full technical specifications, 4 custom SLA metrics, 4 engineering mechanics breakdowns, multi-language runnable specifications (TypeScript, Python, YAML, HCL, JSON), and simulated test streams for each box.

ID & Hash	Feature Name	Badge	Language Spec
1 (`#feature-1`)	Autonomous AI Agents	Agent Mesh	TypeScript
2 (`#feature-2`)	Real-Time Data Streams	Live Telemetry	Python
3 (`#feature-3`)	Secure Orchestration Enclave	SOC2 Type II	YAML
4 (`#feature-4`)	Cross-Platform Integrations	200+ Connectors	JavaScript
5 (`#feature-5`)	Dynamic Process Mapping	Visual DAG Builder	HCL
6 (`#feature-6`)	Scalable Edge Infrastructure	32 Edge Regions	JSON

`handleNavigateToFeature(featureId)`

Hash Navigation

Switches client-side SPA view to `'feature-detail'` , updates `window.location.hash` to `#feature-{id}` , and smoothly scrolls to top for instant subpage rendering.

```
const handleNavigateToFeature = (featureId) => {
  setSelectedFeatureId(featureId);
  setCurrentView('feature-detail');
  window.location.hash = `#feature-${featureId}`;
  window.scrollTo({ top: 0, behavior: 'smooth' });
};
```

Summary: This reference covers all 17 components, 32 core functions, 6 individual feature subpages, 5 animation token engines, and 3 mathematical coordinate projection systems in the AetherFlow codebase.