

# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_Week 12\_Java\_Lambda Expressions\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

###### Problem Statement

Sophia, a data analyst, is studying experimental results collected from various lab sensors. Each sensor provides a list of numeric readings, and Sophia wants to calculate the average of these readings to analyze consistency.

She decides to use lambda expressions and the Function functional interface to compute the average of all the recorded values efficiently.

###### Your Task

Write a Java program that:

Reads the total number of measurements. Reads all the measurement values as doubles. Uses a `Function<double[], Double>` lambda expression

to calculate the average value. Displays the final average, formatted to two decimal places.

### ***Input Format***

The first line of input consists of an integer N, representing the number of measurements.

The second line contains N space-separated double values.

### ***Output Format***

Print the average of the entered values, rounded to two decimal places.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 6

2.2 1.2 5.4 4.6 2.9 55.7

Output: 12.00

### ***Answer***

// You are using Java

import java.util.\*;

import java.util.function.Function;

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        double[] readings = new double[n];  
        for (int i = 0; i < n; i++) {  
            readings[i] = sc.nextDouble();  
        }  
    }  
}
```

```
Function<double[], Double> averageCalculator = arr -> {  
    double sum = 0;  
    for (double val : arr) {  
        sum += val;  
    }  
}
```

```

        return sum / arr.length;
    };

    double average = averageCalculator.apply(readings);
    System.out.printf("%.2f%n", average);
}
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Riya is developing a college admission system that assigns unique roll numbers to each newly admitted student.

Each roll number should follow this fixed format:

<DEPT>-<YEAR>-<4-digit-sequence>

where:

<DEPT> is the department code (in uppercase, e.g., CSE, ECE, MECH). <YEAR> is the admission year (e.g., 2025). <4-digit-sequence> starts from a given number and increases sequentially for each student. Write a Java program using a Supplier<String> lambda to generate and print the roll numbers for n students.

### **Input Format**

First line: integer n — number of roll numbers to generate

Second line: string DEPT — department code (uppercase letters only)

Third line: integer YEAR — admission year

Fourth line: integer start — starting sequence number ( $0 \leq \text{start} \leq 9999$ )

### **Output Format**

Print n roll numbers, one per line, in the required format

Sequence must be zero-padded to 4 digits

If sequence exceeds 9999, wrap around to 0000

### Sample Test Case

Input: 5

CSE

2025

98

Output: CSE-2025-0098

CSE-2025-0099

CSE-2025-0100

CSE-2025-0101

CSE-2025-0102

### Answer

// You are using Java

```
import java.util.Scanner;
```

```
import java.util.function.Supplier;
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
        Scanner sc = new Scanner(System.in);
```

```
        int n = Integer.parseInt(sc.nextLine());
```

```
        String dept = sc.nextLine();
```

```
        int year = Integer.parseInt(sc.nextLine());
```

```
        int start = Integer.parseInt(sc.nextLine());
```

```
        Supplier<String> rollSupplier = new Supplier<>() {
```

```
            int seq = start;
```

```
            public String get() {
```

```
                String roll = String.format("%s-%d-%04d", dept, year, seq);
```

```
                seq = (seq + 1) % 10000;
```

```
                return roll;
```

```
            }
```

```
        };
```

```
        for (int i = 0; i < n; i++) {
```

```
            System.out.println(rollSupplier.get());
```

```
        }
```

```
    }
```

```
}
```

Status : Correct

Marks : 10/10

### 3. Problem Statement

Nethra is a researcher working on a project that involves analyzing experimental data. As part of her analysis, she needs to determine whether a given word is a palindrome or not.

Create a Java program that allows Nethra to input a word, and then check and display whether the entered word is a palindrome. Use lambda expressions to perform the palindrome check.

#### ***Input Format***

The first line of input consists of a word.

#### ***Output Format***

The output prints whether the given word is a palindrome or not in the following format:

"<input> is palindrome" or "<input> is not palindrome".

Refer to the sample output for formatting specifications.

#### ***Sample Test Case***

Input: malayalam

Output: malayalam is palindrome

#### ***Answer***

// You are using Java

```
import java.util.Scanner;
```

```
import java.util.function.Predicate;
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        String word = sc.nextLine();
```

```
        Predicate<String> isPalindrome = s -> s.equals(new  
        StringBuilder(s).reverse().toString());
```

```
        if (isPalindrome.test(word)) {  
            System.out.println(word + " is palindrome");  
        } else {  
            System.out.println(word + " is not palindrome");  
        }  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

A company named TechNova is collecting feedback from its customers. Each customer gives a feedback score (an integer between 1 and 10) along with their name.

The company wants to:

Display each customer's name along with their feedback in a formatted way using a lambda expression and a Consumer functional interface. After displaying all feedbacks, calculate and display the average feedback score. You need to implement this functionality using Java lambda expressions and streams, emphasizing the Consumer interface for displaying formatted output.

##### **Input Format**

The first line of input contains an integer  $n$ , representing the number of customers.

The next  $n$  lines each contain a String (customer name) followed by an int (feedback score).

##### **Output Format**

- Each line prints a customer's name and feedback in the format:
- Customer: <name>, Feedback Score: <score>

- After all customers are displayed, print the average feedback as:
- Average Feedback: <average\_value>

(Average should be displayed up to two decimal places.)

### **Sample Test Case**

Input: 3

Ravi 7

Ananya 9

Kiran 8

Output: Customer: Ravi, Feedback Score: 7

Customer: Ananya, Feedback Score: 9

Customer: Kiran, Feedback Score: 8

Average Feedback: 8.00

### **Answer**

// You are using Java

import java.util.\*;

import java.util.function.Consumer;

class Customer {

String name;

int score;

Customer(String name, int score) {

this.name = name;

this.score = score;

}

}

public class Main {

public static void main(String[] args) {

Scanner sc = new Scanner(System.in);

int n = Integer.parseInt(sc.nextLine());

List<Customer> customers = new ArrayList<>();

for (int i = 0; i < n; i++) {

String[] input = sc.nextLine().split(" ");

String name = input[0];

```
int score = Integer.parseInt(input[1]);
customers.add(new Customer(name, score));
}

Consumer<Customer> display = c ->
    System.out.println("Customer: " + c.name + ", Feedback Score: " +
c.score);

double total = 0;
for (Customer c : customers) {
    display.accept(c);
    total += c.score;
}

double average = total / n;
System.out.printf("Average Feedback: %.2f%n", average);
}
}
```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_Week 12\_Java\_Lamba Expressions\_MCQ

Attempt : 1  
Total Mark : 10  
Marks Obtained : 9

#### Section 1 : MCQ

1. What is the syntax for a basic lambda expression in Java?

**Answer**

(parameters) -> expression

**Status : Wrong**

**Marks : 0/1**

2. What is a lambda expression in Java?

**Answer**

A way to define anonymous methods

**Status : Correct**

**Marks : 1/1**

3. Can a lambda expression have more than one parameter?

**Answer**

Yes, it can have multiple parameters

**Status : Correct**

**Marks : 1/1**

4. Which functional interface is commonly used with lambda expressions in Java?

**Answer**

Runnable

**Status : Correct**

**Marks : 1/1**

5. Can a lambda expression in Java have a body with multiple statements?

**Answer**

Yes, if the statements are enclosed in curly braces

**Status : Correct**

**Marks : 1/1**

6. Which functional interface in Java takes two arguments and returns a result?

**Answer**

BiFunction

**Status : Correct**

**Marks : 1/1**

7. Which of the following is a valid lambda expression in Java?

**Answer**

All of the mentioned options

**Status : Correct**

**Marks : 1/1**

8. Can a lambda expression in Java have a body with multiple statements?

**Answer**

Yes, if the statements are enclosed in curly braces

**Status :** Correct

**Marks :** 1/1

9. Which of the following interfaces is NOT a functional interface in Java?

**Answer**

Iterable

**Status :** Correct

**Marks :** 1/1

10. What is the return type of a lambda expression in Java?

**Answer**

The return type is inferred from the context

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_Week 12\_Java\_Lamba Expressions\_PAH

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : COD

##### 1. Problem Statement

Aditya is developing a reading app that recommends books to users based on a predefined list.

Each time a user opens the app, it should supply the next book title in the list, one at a time, using a lambda expression and the Supplier functional interface.

When all books have been recommended, the list should start again from the beginning.

##### ***Input Format***

The first line contains an integer  $n$  — the total number of available book titles.

The next n lines each contain a book title (a string).

The next line contains an integer m – the number of times users open the app (i.e., the number of recommendations to be made).

### ***Output Format***

Print the supplied book title for each recommendation, one per line.

If  $m > n$ , repeat the list from the start.

### ***Sample Test Case***

Input: 3

The Alchemist

Atomic Habits

Ikigai

5

Output: The Alchemist

Atomic Habits

Ikigai

The Alchemist

Atomic Habits

### ***Answer***

// You are using Java

import java.util.\*;

import java.util.function.Supplier;

```
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());
        List<String> books = new ArrayList<>();
        for (int i = 0; i < n; i++) {
            books.add(sc.nextLine());
        }
        int m = Integer.parseInt(sc.nextLine());

        Iterator<String> iterator = new Iterator<>() {
            int index = 0;
            public boolean hasNext() { return true; }
            public String next() {
                String book = books.get(index);
```

```

        index = (index + 1) % books.size();
        return book;
    }
};

Supplier<String> bookSupplier = iterator::next;

for (int i = 0; i < m; i++) {
    System.out.println(bookSupplier.get());
}
}
}

```

**Status :** Correct

**Marks : 10/10**

## 2. Problem Statement

Sneha is developing a feature for an e-commerce application that helps display product details after applying a seasonal discount.

She decides to use lambda expressions with the Consumer functional interface to print each product's name, original price, and discounted price neatly.

The program should:

Accept a list of product names and their prices. Apply a 15% discount on all products. Use a Consumer lambda expression to display the details in a formatted manner.

### ***Input Format***

The first line of input consists of an integer  $n$ , representing the number of products.

The next  $n$  lines each contain a String (product name) and a double (price) separated by a space.

### ***Output Format***

For each product, print the details in the format:

Product: <name>, Original Price: <price>, Discounted Price: <discounted price>

If there are no products, print:

No products available

### **Sample Test Case**

Input: 1

Phone 60000

Output: Product: Phone, Original Price: 60000.0, Discounted Price: 51000.0

### **Answer**

// You are using Java

import java.util.\*;

import java.util.function.Consumer;

```
class Product {  
    String name;  
    double price;
```

```
    Product(String name, double price) {  
        this.name = name;  
        this.price = price;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int n = Integer.parseInt(sc.nextLine());
```

```
        if (n == 0) {  
            System.out.println("No products available");  
            return;  
        }
```

```
        List<Product> products = new ArrayList<>();  
        for (int i = 0; i < n; i++) {  
            String[] input = sc.nextLine().split(" ");  
            String name = input[0];  
            double price = Double.parseDouble(input[1]);  
            products.add(new Product(name, price));
```

```

    }
    Consumer<Product> display = p -> {
        double discounted = p.price * 0.85;
        System.out.printf("Product: %s, Original Price: %.1f, Discounted Price: %.1f\n", p.name, p.price, discounted);
    };

    for (Product p : products) {
        display.accept(p);
    }
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Rishi is working as an HR analyst in a software company. He wants to filter a list of employees based on their salary using modern Java techniques. He has a list of employee names and salaries and wants to use lambda expressions to filter those who earn more than a specific threshold.

Implement a program using lambda expressions and functional interfaces to print the names of employees whose salary is greater than or equal to 50,000.

#### **Input Format**

The first line of input consists of an integer  $n$ , representing the number of employees.

The next  $n$  lines. Each line contains a String (employee name) and an int (salary).

#### **Output Format**

The output prints the names of employees whose salary is greater than or equal to 50000, each on a new line.

If no employee found with salary greater than 50000, print: No employee found with salary  $\geq 50000$



Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 4  
Amit 45000  
Sneha 50000  
Ravi 60000  
Priya 30000  
Output: Sneha  
Ravi

### **Answer**

```
// You are using Java
import java.util.*;
import java.util.function.Predicate;
```

```
class Employee {
    String name;
    int salary;
```

```
    Employee(String name, int salary) {
        this.name = name;
        this.salary = salary;
    }
}
```

```
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());

        List<Employee> employees = new ArrayList<>();
        for (int i = 0; i < n; i++) {
            String[] input = sc.nextLine().split(" ");
            String name = input[0];
            int salary = Integer.parseInt(input[1]);
            employees.add(new Employee(name, salary));
        }
    }
}
```

```

Predicate<Employee> highEarner = e -> e.salary >= 50000;
boolean found = false;

for (Employee e : employees) {
    if (highEarner.test(e)) {
        System.out.println(e.name);
        found = true;
    }
}

if (!found) {
    System.out.println("No employee found with salary >= 50000");
}
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Emily, an analyst at a data processing firm, is tasked with cleaning up datasets to remove duplicate values from lists of integers.

Create a Java program that allows Emily to input a series of integers, with the program then utilizing a lambda expression to efficiently remove any duplicates.

##### **Input Format**

The first line of input consists of an integer N, representing the size of the array.

The second line consists of N space-separated integers, each denoting an array element.

##### **Output Format**

The output prints the array elements after removing the duplicates inside the square bracket separated by a comma and space.

Refer to the sample output for formatting specifications.

### Sample Test Case

Input: 15

1 2 3 4 3 2 1 2 3 4 4 5 5 6

Output: [1, 2, 3, 4, 5, 6]

### Answer

// You are using Java

import java.util.\*;

import java.util.function.Function;

import java.util.stream.Collectors;

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        List<Integer> input = new ArrayList<>();  
        for (int i = 0; i < n; i++) {  
            input.add(sc.nextInt());  
        }  
    }  
}
```

```
Function<List<Integer>, List<Integer>> removeDuplicates = list ->  
    list.stream().distinct().collect(Collectors.toList());
```

```
List<Integer> result = removeDuplicates.apply(input);  
System.out.println(result);
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 12\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Sabrina is working on a project that involves analyzing a set of numbers. In her exploration, she encounters scenarios where extracting even numbers and finding their sum is essential.

Create a program that calculates the sum of even numbers from a given array of integers using a lambda expression.

##### ***Input Format***

The first line of input consists of an integer N, representing the size of the array.

The second line consists of N space-separated integers, representing the elements of the array.

##### ***Output Format***

The output prints the sum of the even integers from the array.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3

29 37 45

Output: 0

### **Answer**

// You are using Java

```
import java.util.*;
```

```
import java.util.stream.*;
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);
```

```
  
        int n = sc.nextInt();  
        int[] arr = new int[n];
```

```
  
        for(int i = 0; i < n; i++) {  
            arr[i] = sc.nextInt();  
        }
```

```
  
        int sum = Arrays.stream(arr)  
            .filter(x -> x % 2 == 0)  
            .sum();
```

```
  
        System.out.println(sum);  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 12\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Alex is learning about Java's functional interfaces and lambda expressions.

He wants to write a simple program that prints the square of each number in an array using a predefined functional interface.

Help Alex complete this task using the Consumer functional interface.

##### ***Input Format***

- The first line contains an integer N, the number of elements in the array.
- The second line contains N space-separated integers.

##### ***Output Format***

- Print the squares of all elements in the array, separated by a space.

Refer to the sample output for formatting specifications.

**Sample Test Case**

Input: 4

1 2 3 4

Output: 1 4 9 16

**Answer**

// You are using Java

import java.util.\*;

import java.util.function.Consumer;

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);
```

```
        int n = sc.nextInt();
```

```
        int[] arr = new int[n];
```

```
        for(int i = 0; i < n; i++) {
```

```
            arr[i] = sc.nextInt();
```

```
        }
```

```
        Consumer<Integer> squarePrinter = x -> System.out.print((x * x) + " ");
```

```
        for(int num : arr) {
```

```
            squarePrinter.accept(num);
```

```
        }
```

```
    }
```

```
}
```

**Status : Correct**

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 12\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 0

#### Section 1 : Coding

##### 1. Problem Statement

In the mystical realm of programming, there exists a magical incantation to reveal hidden words.

Elara, the skilled enchantress, wishes to summon a word using her spell and then reverse its characters to uncover its enchanted reflection.

Write a program that uses the predefined functional interface `Supplier<String>` and a lambda expression to:

Supply (generate) a string, and

Display its reversed form.

***Input Format***



No input is required from the user.

The string must be supplied internally using a Supplier<String>.

**Output Format**

Print the reversed version of the supplied string.

Refer to the sample output for formatting specifications.

**Sample Test Case**

Input: Wizard!!

Output: !!draziW

**Answer**

```
import java.util.function.Supplier;

public class Main {
    public static void main(String[] args) {
        Supplier<String> spell = () -> "Enchanted"; // Change this to match the
        expected test case

        String original = spell.get();
        String reversed = new StringBuilder(original).reverse().toString();
        System.out.println(reversed);
    }
}
```

**Status : Wrong**

**Marks : 0/10**