

# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 10\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : COD

##### 1. Problem Statement

A linguist named Meera is classifying a list of words based on their first character. She wants to store words grouped by their starting letter using a TreeMap so that the groups appear in sorted order of characters (i.e., 'a' to 'z'). For each letter, all words starting with that letter should be stored in the order they appear.

Implement the logic inside a class named WordClassifier using the TreeMap<Character, List<String>> collection.

##### ***Input Format***

The first line of the input contains an integer n, representing the number of words.

The next n lines each contain a word.

### **Output Format**

The first line of the output prints: "Grouped Words by Starting Letter:"

The next lines print each character key and its list of words in the format:

"letter: word1 word2 word3..."

..."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

dog

deer

cat

cow

camel

Output: Grouped Words by Starting Letter:

c: cat cow camel

d: dog deer

### **Answer**

```
import java.util.*;
```

```
// You are using Java
```

```
class WordClassifier {
```

```
    public void classifyWords(List<String> words) {
```

```
        TreeMap<Character, List<String>> map = new TreeMap<>();
```

```
        for (String word : words) {
```

```
            char firstChar = word.charAt(0);
```

```
            if (!map.containsKey(firstChar)) {
```

```
                map.put(firstChar, new ArrayList<>());
```

```
            }
```

```
            map.get(firstChar).add(word);
```

```
        }
```

```

        System.out.println("Grouped Words by Starting Letter:");
        for (Map.Entry<Character, List<String>> entry : map.entrySet()) {
            System.out.print(entry.getKey() + ": ");
            for (String word : entry.getValue()) {
                System.out.print(word + " ");
            }
            System.out.println();
        }
    }
}

```

//Type your code here

```

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());

        List<String> words = new ArrayList<>();
        for (int i = 0; i < n; i++) {
            words.add(sc.nextLine());
        }

        WordClassifier classifier = new WordClassifier();
        classifier.classifyWords(words);
    }
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

A college professor wants to keep track of students who attend classes. Each student has a unique roll number and their attendance count increases every time they attend a class. The system should allow adding a student, marking their attendance, and displaying all students with their total attendance.

Your task is to implement a Java program using TreeSet to maintain students in sorted order of roll numbers and track their attendance count.

Operations:

A roll\_no name Add a student with roll number and name (if not already added). M roll\_no Mark attendance for the student with the given roll number (increase their count by 1). D Display all students in ascending order of roll number along with their attendance count.

***Input Format***

The first line contains an integer N - the number of students.

The next N lines contain one of the following commands:

A roll\_no name

M roll\_no

D

- A (Add) Adds a new student with a unique roll number and name.
- M (Mark) Increases attendance count for the given roll number.
- D (Display) Prints all students in ascending order of roll number.

***Output Format***

For D, output prints each student's roll number, name, and attendance count in ascending order of roll number.

Refer to the sample output for formatting specifications.

***Sample Test Case***

Input: 5

A 101 Alice

A 102 Bob

M 101

M 101

D

Output: 101 Alice 2

102 Bob 0

***Answer***

```
// You are using Java
import java.util.Scanner;
import java.util.TreeSet;
```

```
class Student implements Comparable<Student> {
    int rollNo;
    String name;
    int attendance;

    public Student(int rollNo, String name) {
        this.rollNo = rollNo;
        this.name = name;
        this.attendance = 0;
    }

    public int compareTo(Student other) {
        return Integer.compare(this.rollNo, other.rollNo);
    }

    public boolean equals(Object obj) {
        if (obj instanceof Student) {
            return this.rollNo == ((Student) obj).rollNo;
        }
        return false;
    }

    public int hashCode() {
        return Integer.hashCode(rollNo);
    }

    public String toString() {
        return rollNo + " " + name + " " + attendance;
    }
}
```

```
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int N = Integer.parseInt(sc.nextLine());

        TreeSet<Student> students = new TreeSet<>();
```

```

for (int i = 0; i < N; i++) {
    String line = sc.nextLine();
    String[] parts = line.split(" ");

    if (parts[0].equals("A")) {
        int rollNo = Integer.parseInt(parts[1]);
        String name = parts[2];
        Student newStudent = new Student(rollNo, name);
        students.add(newStudent);
    } else if (parts[0].equals("M")) {
        int rollNo = Integer.parseInt(parts[1]);
        for (Student s : students) {
            if (s.rollNo == rollNo) {
                s.attendance++;
                break;
            }
        }
    } else if (parts[0].equals("D")) {
        for (Student s : students) {
            System.out.println(s);
        }
    }
}
}
}
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Bob wants to develop a score-tracking application for a gaming tournament. Each player's score is stored in a HashMap with the player's name as the key and the score as the value.

Write a program to assist Bob that takes user input to enter player scores, calculates the maximum score from the HashMap, and prints the player with the highest score.

#### **Input Format**

The input consists of strings representing player details in the format "playerName:score".

The input is terminated by entering "done".

### **Output Format**

The output displays a string, representing the player's name who scored the maximum.

If the value is not numeric, print "Invalid input".

If any special characters other than ':' are given, print "Invalid format".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Alice:15

Bob:56

done

Output: Bob

### **Answer**

```
import java.util.*;
```

```
// You are using Java
```

```
class ScoreTracker {
```

```
    HashMap<String, Integer> scoreMap = new HashMap<>();
```

```
    public boolean processInput(String input) {
```

```
        if (!input.contains(":") || input.contains(" ") || input.matches(".*[a-zA-Z0-9:].*")) {
```

```
            System.out.println("Invalid format");
```

```
            return false;
```

```
        }
```

```
        String[] parts = input.split(":");
```

```
        if (parts.length != 2) {
```

```
            System.out.println("Invalid format");
```

```
            return false;
```

```
        }
```

```

String name = parts[0];
String scoreStr = parts[1];

try {
    int score = Integer.parseInt(scoreStr);
    scoreMap.put(name, score);
} catch (NumberFormatException e) {
    System.out.println("Invalid input");
    return false;
}

```

```

return true;
}

```

```

public String findTopPlayer() {
    String topPlayer = "";
    int maxScore = -1;

    for (String player : scoreMap.keySet()) {
        int score = scoreMap.get(player);
        if (score > maxScore) {
            maxScore = score;
            topPlayer = player;
        }
    }
}

```

```

return topPlayer;
}
}

```

//type your code here

```

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        ScoreTracker tracker = new ScoreTracker();
        boolean validInput = true;

        while (true) {
            String input = scanner.nextLine();

            if (input.toLowerCase().equals("done")) {
                break;
            }
        }
    }
}

```



```

    }

    if (!tracker.processInput(input)) {
        validInput = false;
        break;
    }
}

if (validInput && !tracker.scoreMap.isEmpty()) {
    System.out.println(tracker.findTopPlayer());
}

scanner.close();
}
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

David is managing an employee database where each employee has a unique ID, name, and department. He wants to ensure that duplicate employee IDs are not added to the system. Implement a Java program that allows adding employees to the system, displaying all employees, and checking if an employee exists based on the given ID.

Implement a class `EmployeeDatabase` that contains a `HashSet` to store employee records. The `Employee` class should be a user-defined object containing employee details. The main class should handle user operations and interact with the `EmployeeDatabase` class.

##### **Input Format**

The first line contains an integer `n` representing the number of employees to be added.

The next `n` lines follow, each containing:

1. An integer `employee_id`
2. A string `name`
3. A string `department`

The next line contains an integer  $m$  representing the number of queries.

The next  $m$  lines follow, each containing an employee ID to check for existence.

### ***Output Format***

The output prints a list of all employees added in the format:

"ID: <employee\_id>, Name: <name>, Department: <department>"

For each query, output "Employee exists" if the ID is found, otherwise "Employee not found".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 3

101 John IT

102 Alice HR

103 Bob Finance

2

101

104

Output: ID: 101, Name: John, Department: IT

ID: 102, Name: Alice, Department: HR

ID: 103, Name: Bob, Department: Finance

Employee exists

Employee not found

### ***Answer***

```
import java.util.*;
```

```
// You are using Java
```

```
class Employee {
```

```
    int id;
```

```
    String name;
```

```
    String department;
```

```
    public Employee(int id, String name, String department) {
```

```

        this.id = id;
        this.name = name;
        this.department = department;
    }

    @Override
    public boolean equals(Object obj) {
        if (obj instanceof Employee) {
            Employee other = (Employee) obj;
            return this.id == other.id;
        }
        return false;
    }

    @Override
    public int hashCode() {
        return Integer.hashCode(id);
    }

    @Override
    public String toString() {
        return "ID: " + id + ", Name: " + name + ", Department: " + department;
    }
}

```

```

class EmployeeDatabase {
    HashSet<Employee> employees = new HashSet<>();

    public void addEmployee(int id, String name, String department) {
        Employee newEmp = new Employee(id, name, department);
        employees.add(newEmp);
    }

    public void displayEmployees() {
        for (Employee emp : employees) {
            System.out.println(emp);
        }
    }

    public boolean checkEmployee(int id) {
        for (Employee emp : employees) {
            if (emp.id == id) {

```

```

        return true;
    }
    }
    return false;
}
}

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        EmployeeDatabase db = new EmployeeDatabase();
        int n = sc.nextInt();
        for (int i = 0; i < n; i++) {
            int id = sc.nextInt();
            String name = sc.next();
            String department = sc.next();
            db.addEmployee(id, name, department);
        }
        db.displayEmployees();
        int m = sc.nextInt();
        for (int i = 0; i < m; i++) {
            int id = sc.nextInt();
            if (db.checkEmployee(id))
                System.out.println("Employee exists");
            else
                System.out.println("Employee not found");
        }
        sc.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 10\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 15

#### Section 1 : MCQ

1. Which method retrieves the lowest key in a TreeMap?

**Answer**

firstKey()

**Status : Correct**

**Marks : 1/1**

2. What will happen if you add elements in descending order in a TreeSet?

**Answer**

They are sorted in ascending order

**Status : Correct**

**Marks : 1/1**

3. Which statement is true about HashSet and TreeSet?

**Answer**

TreeSet provides sorted elements

**Status : Correct**

**Marks : 1/1**

4. Which of the following is true about TreeMap?

**Answer**

It maintains natural ordering

**Status : Correct**

**Marks : 1/1**

5. What happens if two keys have the same hash code in a HashMap?

**Answer**

A linked list is used to store values with the same hash

**Status : Correct**

**Marks : 1/1**

6. What is the time complexity of retrieving an element from a HashSet?

**Answer**

$O(1)$

**Status : Correct**

**Marks : 1/1**

7. Which of the following is true about HashMap?

**Answer**

It is not synchronized

**Status : Correct**

**Marks : 1/1**

8. How does HashSet check for duplicate elements?

**Answer**

Using equals() and hashCode()

**Status :** Correct

**Marks :** 1/1

9. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        HashMap<String, Integer> map = new HashMap<>();
        map.put("A", 1);
        map.put("B", 2);
        map.put("C", 3);
        System.out.println(map.containsKey("B"));
    }
}
```

**Answer**

true

**Status :** Correct

**Marks :** 1/1

10. Which of the following allows null keys in Java?

**Answer**

HashMap

**Status :** Correct

**Marks :** 1/1

11. Which method removes all elements from a Set?

**Answer**

clear()

**Status :** Correct

**Marks :** 1/1

12. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        HashMap<String, String> map = new HashMap<>();
        map.put("A", "Apple");
        map.put("B", "Banana");
        map.put("C", "Cherry");
        map.replace("B", "Blueberry");
        System.out.println(map);
    }
}
```

**Answer**

{A=Apple, B=Blueberry, C=Cherry}

**Status :** Correct

**Marks :** 1/1

13. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        HashMap<String, Integer> map = new HashMap<>();
        map.put("X", 10);
        map.put("Y", 20);
        map.put("Z", 30);
        map.remove("Y");
        System.out.println(map);
    }
}
```

**Answer**

{X=10, Z=30}

**Status :** Correct

**Marks :** 1/1

14. What happens when you add duplicate elements to a HashSet?



**Answer**

The duplicate is ignored

**Status :** Correct

**Marks :** 1/1

15. What will happen if you add a null element to a TreeSet?

**Answer**

An exception occurs

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 10\_PAH

Attempt : 1  
Total Mark : 30  
Marks Obtained : 25

#### Section 1 : Coding

##### 1. Problem Statement

Sarah is working on a spam detection system that analyzes incoming messages for unique patterns. Spammers often use repetitive character sequences, making it important to identify the first non-repeating character in a message.

Given a string, Sarah needs to determine the first character that appears only once. If all characters repeat, the system should return -1.

She decides to use a HashMap to efficiently track character frequencies and find the solution.

##### ***Input Format***

The first line contains an integer N representing , the length of the string.

The second line contains a string of N lowercase English letters (a-z).

### **Output Format**

The output prints a character representing the first non-repeating character. If none exist, print -1.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 10  
abacabadac

Output: d

### **Answer**

```
// You are using Java
import java.util.HashMap;
import java.util.Scanner;
```

```
public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int n = Integer.parseInt(scanner.nextLine());
        String input = scanner.nextLine();

        HashMap<Character, Integer> freqMap = new HashMap<>();

        for (int i = 0; i < n; i++) {
            char ch = input.charAt(i);
            if (freqMap.containsKey(ch)) {
                freqMap.put(ch, freqMap.get(ch) + 1);
            } else {
                freqMap.put(ch, 1);
            }
        }

        boolean found = false;
        for (int i = 0; i < n; i++) {
            char ch = input.charAt(i);
```

```

        if (freqMap.get(ch) == 1) {
            System.out.println(ch);
            found = true;
            break;
        }
    }

    if (!found) {
        System.out.println("-1");
    }
}
}

```

**Status :** Partially correct

**Marks :** 5/10

## 2. Problem Statement

Riya is building a calendar event scheduler where each event is stored in chronological order using a TreeMap. The key represents the event time in 24-hour format (HH:MM), and the value is the event description.

She wants the system to:

Automatically sort events by time. Avoid duplicate time entries — if a duplicate time is entered, ignore the new entry. Print all scheduled events in order.

Implement this logic using a class named EventManager.

### **Input Format**

The first line of the input contains an integer  $n$ , representing the number of events.

The next  $n$  lines each contain a string in the format: "HH:MM Description"

(Example: 09:00 TeamMeeting).

### **Output Format**

The first line of the output prints "Scheduled Events:"

The next k lines print each event in the format: "HH:MM - Description"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

09:00 TeamMeeting

13:30 LunchBreak

11:00 ProjectUpdate

09:00 Standup

15:00 ClientCall

Output: Scheduled Events:

09:00 - TeamMeeting

11:00 - ProjectUpdate

13:30 - LunchBreak

15:00 - ClientCall

### **Answer**

// You are using Java

```
import java.util.Scanner;
```

```
import java.util.TreeMap;
```

```
class EventManager {
```

```
    public static void main(String[] args) {
```

```
        Scanner scanner = new Scanner(System.in);
```

```
        int n = Integer.parseInt(scanner.nextLine());
```

```
        TreeMap<String, String> events = new TreeMap<>();
```

```
        for (int i = 0; i < n; i++) {
```

```
            String line = scanner.nextLine();
```

```
            String[] parts = line.split(" ");
```

```
            String time = parts[0];
```

```
            String description = parts[1];
```

```
            if (!events.containsKey(time)) {
```

```
                events.put(time, description);
```

```
            }
```

```
        }
```

```
        System.out.println("Scheduled Events:");
        for (String time : events.keySet()) {
            System.out.println(time + " - " + events.get(time));
        }
    }
}
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

A university maintains a list of student records and wants to store them in a sorted manner based on their GPA. If two students have the same GPA, they should be further sorted by their name in lexicographical order. Implement a program that uses a TreeSet to store student records and ensures unique student IDs.

#### **Input Format**

The first line contains an integer N - the number of students.

The next N lines contain details of each student in the format: "StudentID Name GPA"

- StudentID (Integer) - A unique identifier.
- Name (String) - The student's name (can contain spaces).
- GPA (Double) - The Grade Point Average.

#### **Output Format**

The output prints the list of students in ascending order of GPA.

If two students have the same GPA, sort them by name.

Print details in the format: "StudentID Name GPA" in the output, GPA is rounded to two decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

101 John 8.5

102 Alice 9.1

103 Bob 8.5

104 Zoe 7.3

105 Charlie 9.1

Output: 104 Zoe 7.30

103 Bob 8.50

101 John 8.50

102 Alice 9.10

105 Charlie 9.10

### **Answer**

// You are using Java

```
import java.util.Scanner;
```

```
import java.util.TreeSet;
```

```
class Student implements Comparable<Student> {
```

```
    int id;
```

```
    String name;
```

```
    double gpa;
```

```
    public Student(int id, String name, double gpa) {
```

```
        this.id = id;
```

```
        this.name = name;
```

```
        this.gpa = gpa;
```

```
    }
```

```
    public int compareTo(Student other) {
```

```
        if (this.gpa != other.gpa) {
```

```
            return Double.compare(this.gpa, other.gpa);
```

```
        } else {
```

```
            return this.name.compareTo(other.name);
```

```
        }
```

```
    }
```

```
    public String toString() {
```

```
        return id + " " + name + " " + String.format("%.2f", gpa);
```

```
    }
```

```
}
```

```

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int n = Integer.parseInt(scanner.nextLine());

        TreeSet<Student> students = new TreeSet<>();

        for (int i = 0; i < n; i++) {
            String line = scanner.nextLine();
            String[] parts = line.trim().split(" ");
            int id = Integer.parseInt(parts[0]);
            double gpa = Double.parseDouble(parts[parts.length - 1]);
            StringBuilder nameBuilder = new StringBuilder();
            for (int j = 1; j < parts.length - 1; j++) {
                nameBuilder.append(parts[j]);
                if (j < parts.length - 2) {
                    nameBuilder.append(" ");
                }
            }
            String name = nameBuilder.toString();
            students.add(new Student(id, name, gpa));
        }

        for (Student s : students) {
            System.out.println(s);
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 10\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : COD

##### 1. Problem Statement

A city traffic management system needs to track vehicles entering a toll booth. Each vehicle is uniquely identified by its registration number. The system should allow adding vehicles to a record, ensuring that no duplicate registration numbers exist. The vehicles should be stored in a HashSet, which does not guarantee any specific order.

Your task is to implement a program using a HashSet that allows adding vehicle details and displaying the records.

##### ***Input Format***

The first line of input contains an integer N - the number of vehicles.

The next N lines contain details of each vehicle in the format: "RegNumber

OwnerName VehicleType"

1. RegNumber (String) - A unique registration number (Alphanumeric).
2. OwnerName (String) - The name of the vehicle owner.
3. VehicleType (String, Car, Bike, or Truck) - The type of vehicle.

If a vehicle with the same registration number is already present, ignore the duplicate entry.

### **Output Format**

The output prints the unique vehicle records in any order (since HashSet does not maintain order).

Output format: "RegNumber OwnerName VehicleType"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

KA01AB1234 John Car

MH02CD5678 Alice Bike

DL03EF9012 Bob Truck

TN04GH3456 Mike Car

KA01AB1234 John Car

Output: TN04GH3456 Mike Car

KA01AB1234 John Car

MH02CD5678 Alice Bike

DL03EF9012 Bob Truck

### **Answer**

```
// You are using Java
import java.util.HashSet;
import java.util.Scanner;
```

```
class Vehicle {
    String regNumber;
    String ownerName;
    String vehicleType;
```

```
public Vehicle(String regNumber, String ownerName, String vehicleType) {
    this.regNumber = regNumber;
    this.ownerName = ownerName;
    this.vehicleType = vehicleType;
}
```

```
@Override
public boolean equals(Object obj) {
    if (obj instanceof Vehicle) {
        Vehicle other = (Vehicle) obj;
        return this.regNumber.equals(other.regNumber);
    }
    return false;
}
```

```
@Override
public int hashCode() {
    return regNumber.hashCode();
}
```

```
@Override
public String toString() {
    return regNumber + " " + ownerName + " " + vehicleType;
}
}
```

```
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());
```

```
        HashSet<Vehicle> vehicles = new HashSet<>();
```

```
        for (int i = 0; i < n; i++) {
            String[] parts = sc.nextLine().split(" ");
            String reg = parts[0];
            String owner = parts[1];
            String type = parts[2];
```

```
            vehicles.add(new Vehicle(reg, owner, type));
        }
```

```
    for (Vehicle v : vehicles) {  
        System.out.println(v);  
    }  
}  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 10\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : COD

##### 1. Problem Statement

John is organizing a fruit festival, and the quantities of various fruits are stored in a HashMap where fruit names are keys and quantities are values.

Help him develop a program to find the total quantity of fruits for the festival by summing up the values in the HashMap.

##### ***Input Format***

The input consists of fruit quantities in the format 'fruitName:quantity', where fruitName is the name of the fruit(a string), and quantity is a double value representing the quantity.

The input is terminated by entering "done".

##### ***Output Format***

The output prints a double value, representing the sum of values in the HashMap, rounded off to two decimal places.

If the value is not numeric, print "Invalid input".

If any special characters other than ':' are entered, print "Invalid format".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Banana:15.2

Orange:56.3

Mango:47.3

done

Output: 118.80

### **Answer**

// You are using Java

import java.util.HashMap;

import java.util.Scanner;

```
public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        HashMap<String, Double> fruitMap = new HashMap<>();

        while (true) {
            String line = scanner.nextLine();
            if (line.equalsIgnoreCase("done")) {
                break;
            }

            if (!line.contains(":") || line.matches(".*[^a-zA-Z0-9:~].*")) {
                System.out.println("Invalid format");
                return;
            }

            String[] parts = line.split(":");
            if (parts.length != 2) {
```

```
        System.out.println("Invalid format");
        return;
    }

    String fruit = parts[0];
    String quantityStr = parts[1];

    try {
        double quantity = Double.parseDouble(quantityStr);
        fruitMap.put(fruit, quantity);
    } catch (NumberFormatException e) {
        System.out.println("Invalid input");
        return;
    }
}

double total = 0.0;
for (double qty : fruitMap.values()) {
    total += qty;
}

System.out.printf("%.2f\n", total);
}
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Sushanth Reddy P V  
Email: 241901115@rajalakshmi.edu.in  
Roll no: 241901115  
Phone: 9840125574  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 10\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : COD

##### 1. Problem Statement

Priya is analyzing encrypted messages in a research project. She wants to analyze the frequency of each character in a given paragraph. The characters should be stored in a TreeMap so that the output is sorted in ascending order of characters automatically.

You are required to build a Java program that:

Uses a `TreeMap<Character, Integer>` to count how many times each character appears in the message. Ignores spaces and considers only alphabets (case-sensitive). Outputs the frequencies of characters in sorted order.

You must use a TreeMap in the class named MessageAnalyzer.

***Input Format***



The first line of input contains an integer n, the number of lines in the message.

The next n lines each contain a string (the encrypted message line).

### **Output Format**

The first line of output prints: "Character Frequency:"

Then print each character and its frequency in the format: "<character>: <count>"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 2  
Hello World  
Java

Output: Character Frequency:

H: 1

J: 1

W: 1

a: 2

d: 1

e: 1

l: 3

o: 2

r: 1

v: 1

### **Answer**

```
// You are using Java
import java.util.Scanner;
import java.util.TreeMap;
```

```
class MessageAnalyzer {
    public void analyzeMessage(int n, Scanner sc) {
        TreeMap<Character, Integer> freqMap = new TreeMap<>();
        for (int i = 0; i < n; i++) {
            String line = sc.nextLine();
            for (int j = 0; j < line.length(); j++) {
```

```

        char ch = line.charAt(j);
        if (Character.isLetter(ch)) {
            freqMap.put(ch, freqMap.getOrDefault(ch, 0) + 1);
        }
    }
}

System.out.println("Character Frequency:");
for (Character ch : freqMap.keySet()) {
    System.out.println(ch + ": " + freqMap.get(ch));
}
}
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());
        MessageAnalyzer analyzer = new MessageAnalyzer();
        analyzer.analyzeMessage(n, sc);
    }
}

```

**Status :** Correct

**Marks :** 10/10