

Status Finished

Started Monday, 23 December 2024, 5:33 PM

Completed Tuesday, 12 November 2024, 8:59 AM

Duration 41 days 8 hours

Question 1

Correct

Marked out of
3.00

[Flag question](#)

Write a program that prints a simple chessboard.

Input format:

The first line contains the number of inputs T.

The lines after that contain a different values for size of the chessboard

Output format:

Print a chessboard of dimensions size * size. Print a Print W for white spaces and B for black spaces.

Input:

2

3

5

Output:

```

1  #include<stdio.h>
2  int main(){
3      int T,d,i=0,i1,i2,o;
4      char c;
5      scanf("%d",&T);
6      while(i<T)
7      {
8          scanf("%d",&d);
9          i1=0;
10         while(i1<d)
11         {
12             o=1;
13             i2=0;
14             if(i1%2==0)
15             {
16                 o=0;
17             }
18             while(i2<d)
19             {
20                 c='B';
21                 if(i2%2==o)
22                 {
23                     c='W';
24                 }
25                 printf("%c",c);
26                 i2++;
27             }
28             i1+=1;
29             printf("\n");
30         }
31     }
32 }
33

```

```

24
25         }
26         printf("%c",c);
27         i2++;
28
29     }
30     i1+=1;
31     printf("\n");
32
33
34     }
35     i=i+1;
36 }
37 return 0;
38 }

```

	Input	Expected	Got	
✓	2	WBW	WBW	✓
	3	BWB	BWB	
	5	WBW	WBW	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	

Passed all tests! ✓

Question **2**

Correct

Marked out of
5.00

🚩 Flag question

Let's print a chessboard!

Write a program that takes input:

The first line contains T, the number of test cases

Each test case contains an integer N and also the starting character of the chessboard

Output Format

Print the chessboard as per the given examples

Sample Input / Output

Input:

2

2 W

3 B

```

2  int main(){
3      int T,d,i,i1,i2,o,z;
4      char c,s;
5      scanf("%d",&T);
6      for(i=0;i<T;i++)
7      {
8          scanf("%d %c",&d,&s);
9          for(i1=0;i1<d;i1++)
10         {
11             z=(s=='W')?0:1;
12             o=(i1%2==z)?0:1;
13             for(i2=0;i2<d;i2++)
14             {
15                 c=(i2%2==o)?'W':'B';
16                 printf("%c",c);
17             }
18             printf("\n");
19         }
20     }
21     }
22     return 0;
23 }
24

```

	Input	Expected	Got	
✓	2	WB	WB	✓
	2 W	BW	BW	
	3 B	BWB	BWB	
		WBW	WBW	

Question 3

Correct

Marked out of
7.00

[Flag question](#)

Decode the logic and print the Pattern that corresponds to given input.

If $N = 3$

then pattern will be :

10203010011012

**4050809

****607

If $N = 4$, then pattern will be:

1020304017018019020

**50607014015016

***809012013

*****10011

Constraints

$2 \leq N \leq 100$

```

1 #include<stdio.h>
2 int main()
3 {
4     int n,v,p3,c,in,i1,i2,i,t,ti;
5     scanf("%d",&t);
6     for(ti=0;ti<t;ti++)
7     {
8         v=0;
9         scanf("%d",&n);
10        printf("Case #%d\n",ti+1);
11        for(i=0;i<n;i++){
12            c=0;
13            if(i>0){
14                for(i1=0;i1<i;i1++) printf("***");
15
16                }
17            for(i1=i;i1<n;i1++){
18                if(i>0) c++;
19                printf("%d0",++v);
20            }
21            if(i==0){
22                p3=v+(v*(v-1))+1;
23                in=p3;
24
25            }
26            in=in-c;
27            p3=in;
28            for(i2=1;i2<n;i2++){
29                printf("%d",p3++);
30                if(i2!=n-1) printf("0");
31
32            }
33            printf("\n");
34

```

```

31
32     }
33     printf("\n");
34
35
36
37     }
38 }
39 return 0;
40 }

```

	Input	Expected	Got	
✓	3	Case #1	Case #1	✓
	3	10203010011012	10203010011012	
	4	**4050809	**4050809	
	5	****607	****607	
		Case #2	Case #2	
		1020304017018019020	1020304017018019020	
		**50607014015016	**50607014015016	
		****809012013	****809012013	
		*****10011	*****10011	
		Case #3	Case #3	
		102030405026027028029030	102030405026027028029030	
		**6070809022023024025	**6070809022023024025	
		****10011012019020021	****10011012019020021	
		*****13014017018	*****13014017018	
		*****15016	*****15016	

Question 1

Correct

Marked out of
3.00

[Flag question](#)

The k -digit number N is an Armstrong number if and only if the k -th power of each digit sums to N .

Given a positive integer N , return true if and only if it is an Armstrong number.

Example 1:

Input:

153

Output:

true

Explanation:

153 is a 3-digit number, and $153 = 1^3 + 5^3 + 3^3$.

Example 2:

1 <= N <= 10^8

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<math.h>
3 int main(){
4     int n;
5     scanf("%d",&n);
6     int x=0,n2=n;
7     while(n2!=0)
8     {
9         x++;
10        n2=n2/10;
11    }
12    int sum=0;
13    int n3=n,n4;
14    while(n3!=0)
15    {
16        n4=n3%10;
17        sum = sum+pow(n4,x);
18        n3=n3/10;
19    }
20    if(n==sum)
21    {
22        printf("true");
23    }
24    else
25    {
26        printf("false");
27    }
```

```

12     int sum=0;
13     int n3=n,n4;
14     while(n3!=0)
15     {
16         n4=n3%10;
17         sum = sum+pow(n4,x);
18         n3=n3/10;
19     }
20     if(n==sum)
21     {
22         printf("true");
23     }
24     else
25     {
26         printf("false");
27     }
28     return 0;
29
30 }

```

	Input	Expected	Got	
✓	153	true	true	✓
✓	123	false	false	✓

Passed all tests! ✓

Question 2

Correct

Marked out of
5.00

Flag question

Take a number, reverse it and add it to the original number until the obtained number is a palindrome. Constraints $1 \leq \text{num} \leq 999999999$

Sample Input 1 32 Sample Output 1 55 Sample Input 2 789 Sample Output 2 66066

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c=0,i=0;
5     scanf("%d",&b);
6     do{
7         c=b;a=0;
8         while(b!=0)
9         {
10             a=a*10+b%10;
11             b/=10;
12         }
13         b=a+c;
14         i++;
15     }
16     while(a!=c || i--1);
17     printf("%d",a);
18     return 0;
19 }
```

	Input	Expected	Got	
✓	32	55	55	✓
✓	789	66066	66066	✓

Question 3

Correct

Marked out of
7.00

 Flag question

A number is considered lucky if it contains either 3 or 4 or 3 and 4 both in it. Write a program to print the nth lucky number. Example, 1st lucky number is 3, and 2nd lucky number is 4 and 3rd lucky number is 33 and 4th lucky number is 34 and so on. Note that 13, 40 etc., are not lucky as they have other numbers in it.

The program should accept a number 'n' as input and display the nth lucky number as output.

Sample Input 1:

3

Sample Output 1:

33

Explanation:

Here the lucky numbers are 3, 4, 33, 34, and the 3rd lucky number is 33.

Sample Input 2:

```

1 #include<stdio.h>
2 int con(int a){
3     int c=a;
4     while(c!=0){
5         int d=c%10;
6         if(d!=3 && d!=4) return 0;
7         c/=10;
8     }
9     return 1;
10 }
11 int main(){
12     int a,b=0;
13     scanf("%d",&a);
14     while(a!=0){
15         b++;
16         if(con(b)){
17             a--;
18         }
19     }
20 }
21 printf("%d",b);
22 return 0;
23 }

```

	Input	Expected	Got	
✓	34	33344	33344	✓

Passed all tests! ✓