```
Question 1
Correct
Marked out of
3.00
P Flag question
```

Many people think about their height in feet and inches, even in some countries that primarily use the metric system.

Write a program that reads a number of feet from the user, followed by a number of inches. Once these values are read, your program should compute and display the equivalent number of centimeters.

Hint:

One foot is 12 inches.

One inch is 2.54 centimeters.

Input Format

First line, read the number of feet.

Second line, read the number of inches.

Output Format

In one line print the height in centimeters.

Note: All of the values should be displayed using two decimal places.

Sample Input 1

ompie mput

Sample Output 1

167.64

56

Answer: (penalty regime: 0 %)

```
#include(stdio.h>
 3 - int main(){
        int feet, inch;
 4
 5
        float cm;
        scanf("%d %d",&feet,&inch);
 6
        cm=((feet*12)+inch)*2.54;
 7
 8
        printf("%.2f",cm);
 9
        return 0;
10
11
12
```

	Input	Expected	Got	
4	5	167.64	167.64	~

Question 2	Create a program that reads two integers, a and b, from the user. Your program should compute and display: • The sum of		
Correct	a and b • The difference when b is subtracted from a • The product of a and b • The quotient when a is divided by b • The		
Marked out of	remainder when a is divided by b		
5.00	Input Format		
Flag question	First line, read the first number.		
	Second line, read the second number.		
	Output Format		
	First line, print the sum of a and b		
	Second line, print the difference when b is subtracted from a		
	Third line, print the product of a and b		
	Fourth line, print the quotient when a is divided by b		
	Fifth line, print the remainder when a is divided by b		
	Sample		
	Input 1 100 6		
	Sample Output		
	106 94 600 16 4		

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
 2 - int main(){
 3
        int a,b;
        scanf("%d %d",&a,&b);
 4
        printf("%d\n",a+b);
 5
 6
        printf("%d\n",a-b);
        printf("%d\n",a"b);
 7
        printf("%d\n",a/b);
 8
        printf("%d\n",a%b);
9
18
11
        return θ;
12
13
14
15
16
    }
```

	Input	Expected	Got	
~	100	106	106	1
	6	94	94	
		600	600	
		16	16	
		4	4	

Question 3	A bakery sells loaves of bread for \$3.49 each. Day old bread is discounted by 60 percent. Write a program that begins to
Correct	reading the number of loaves of day old bread being purchased from the user. Then your program should display the
Marked out of 7.00	regular price for the bread, the discount because it is a day old, and the total price. Each of these amounts should be displayed on its own line with an appropriate label. All of the values should be displayed using two decimal places.
P Flag question	Input Format
	Read the number of day old loaves.
	Output Format
	First line, print Regular price: price
	Second line, print Discount: discount
	Third line, print Total: total
	Note: All of the values should be displayed using two decimal places.
	Sample Input 1
	10
	Sample Output 1
	Regular price: 34.90
	Discount: 20.94
	Total: 13.96
	Answer: (penalty regime: 0 %)

```
2 . int main(){
3
        int n;
4
        float reg, dis, tot;
5
        scanf("%d",&n);
6
        reg-n*3.49;
7
        dis-(reg*60)/100;
8
        tot=reg-dis;
9
        printf("Regular price: %.2f\nDiscount: %.2f\nTotal: %.2f", reg, dis, tot);
10
        return 0;
11
12
13
```

	Input	Expected	Got	
~	10	Regular price: 34.90 Discount: 20.94 Total: 13.96	Regular price: 34.90 Discount: 20.94 Total: 13.96	~

Passed all tests! <

Question 1	Goki recently had a breakup, so he wants to have some more friends in his life. Goki has N people who he can be friends
Correct	with, so he decides to choose among them according to their skills set Yi(1<=i<=n). He wants atleast X skills in his friends.
Marked out of 3.00	Help Goki find his friends.
	INPUT
P Flag question	First line contains a single integer X - denoting the minimum skill required to be Goki's friend. Next line contains one integer Y - denoting the skill of the person
	OUTPUT
	Print if he can be friend with Goki. 'YES' (without quotes) if he can be friends with Goki else 'NO' (without quotes).
	CONSTRAINTS
	1<=N<=1000000
	1 < = X,Y <= 1000000
	SAMPLE INPUT 1
	100 110
	SAMPLE OUTPUT 1
	YES
	SAMPLE INPUT 2
	100 90
	SAMPLE OUTPUT 2
	NO

```
#include<stdio.h>
    int main()
 3 .
        int x,y;
        scanf("%d %d",&x,&y);
 5
        If(y>=x)
 6
 7 .
            printf("YES");
 8
 9
10
        else
11
12 -
            printf("NO");
13
14
15
16
        return 0;
17
18
19
```

	Input	Expected	Got	
~	100	YES	YES	~
~	166 98	NO	NO	~

Question 2
Correct

Marked out of

F Flag question

Before the outbreak of corona virus to the world, a meeting happened in a room in Wuhan. A person who attended that meeting had COVID-19 and no one in the room knew about it! So everyone started shaking hands with everyone else in the room as a gesture of respect and after meeting unfortunately everyone got infected! Given the fact that any two persons shake hand exactly once, Can you tell the total count of handshakes happened in that meeting? Say no to shakehands. Regularly wash your hands. Stay Safe.

Input Format

Read an integer N, the total number of people attended that meeting.

Output Format

Print the number of handshakes.

Constraints

0 < N < 106

SAMPLE INPUT 1

1

SAMPLE OUTPUT

0

SAMPLE INPUT 2

2

SAMPLE OUTPUT 2

9

Explanation Case 1: The lonely board member shakes no hands, hence 0. Case 2: There are 2 board members, 1 handshake takes place.

```
1 #includecstdio.h>
2 int main()
3 - {
4     int N;
5     scanf("%d",&N);
6     int x-(N'(N-1))/2;
7
8     printf("%d",x);
9
10     return 0;
11
12 }
```

	Input	Expected	Got	
~	1	а	9	~
~	2	1	1	~

Passed all tests! <

Question **3**Correct
Marked out of

7.00

P Flag question

In our school days, all of us have enjoyed the Games period. Raghav loves to play cricket and is Captain of his team. He always wanted to win all cricket matches. But only one last Games period is left in school now. After that he will pass out from school. So, this match is very important to him. He does not want to lose it. So he has done a lot of planning to make sure his teams wins. He is worried about only one opponent - Jatin, who is very good batsman. Raghav has figured out 3 types of bowling techniques, that could be most beneficial for dismissing Jatin. He has given points to each of the 3 techniques. You need to tell him which is the maximum point value, so that Raghav can select best technique. 3 numbers are given in input. Output the maximum of these numbers.

Input:

Three space separated integers.

Output:

Maximum integer value

SAMPLE INPUT

861

SAMPLE OUTPUT

8

Explanation Out of given numbers, 8 is maximum.

Answer: (penalty regime: 0 %)

```
#include(stdio.h>
    int main()
 3 . {
        int a,b,c;
 4
         scanf("%d %d %d", &a, &b, &c);
 5
         if(a>b && a>c)
 6
 7 -
         -
             printf("%d",a);
 Н
 Q
10
         else if(b>a && b>c)
11
12 .
             printf("%d",b);
13
14
15
         else
16
17 .
             printf("%d",c);
18
19
28
21
         return 0;
22
23
```

	Input	Expected	Got	
~	81 26 15	51	81	~