

Web Programming

Lab - 10

Java Script

Name: Sushen Grover

Reg No: 23BCE1728

Slot: L11+L12+L31+L32

Class No: CH2024250502774

Course Code: BCSE203E

Faculty: Dr. L.M. Jenila Livingston

Question 1:

1. Assume that you are appointed as Data Analytics Engineer for a hospital. Ages for 8 patients are given below.

P-Id	Name	Age
1	Alen	39
2	Deena	47
3	Diana	21
4	Jack	54
5	Jain	23
6	Kelvin	61
7	Louis	69
8	Rex	49

Write a JavaScript program using appropriate functions to

- (i) sort the data in descending order according to the patient's age and display the same
- (ii) check whether a particular P-Id is presented in the list
- (iii) filter the patients by age range.

Code:

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>23BCE1728</title>
  <style>
    table{
      border-collapse: collapse;
      border: 2px solid black;
      box-sizing: border-box;
    }
    td,th{
      text-align: left;
      width: 150px;
    }
    #sort-button{
      width: 150px;
    }
    input{
      width: 100px;
    }
    #pid-found-status{
      width: 400px;
      height: 50px;
      margin: 20px 0px 0px 0px;
    }
    .range-value{
      border: 2px solid black;
      border-radius: 5px;
      width: 40px;
      height: 20px;
      display: inline-block;
    }
    .range-container{
      width: 300px;
      display: flex;
      justify-content: space-evenly;
      align-items: center;
    }
  </style>
</head>
```

```

<body>
  <h2>Exercise 10.1</h2>
  <table border="1" id="table1">
    <tr class="table-header-row">
      <th>P-Id</th>
      <th>Name</th>
      <th>Age</th>
    </tr>
    <tr class="table-row">
      <td>1</td>
      <td>Alen</td>
      <td>39</td>
    </tr>
    <tr class="table-row">
      <td>2</td>
      <td>Deena</td>
      <td>47</td>
    </tr>
    <tr class="table-row">
      <td>3</td>
      <td>Diana</td>
      <td>21</td>
    </tr>
    <tr class="table-row">
      <td>4</td>
      <td>Jack</td>
      <td>54</td>
    </tr>
    <tr class="table-row">
      <td>5</td>
      <td>Jain</td>
      <td>23</td>
    </tr>
    <tr class="table-row">
      <td>6</td>
      <td>Kelvin</td>
      <td>61</td>
    </tr>
    <tr class="table-row">
      <td>7</td>
      <td>Luis</td>
      <td>69</td>
    </tr>
    <tr class="table-row">
      <td>8</td>
      <td>Rex</td>
      <td>49</td>
    </tr>
  </table>
  <button class="sort-button">Sort</button>
  <br>
  <br>
  <div style="border: 2px solid black;width: 450px;padding: 5px;">
    <label for="">Enter PID to find: </label>
    <input type="text" id="pid-input">
    <br>
    <button id="pid-submit">Submit</button>
    <br>
    <div id="pid-found-status">
      <table id="pid-found-status-table"></table>
    </div>
  </div>
  <br>
  <div style="border: 2px solid black;width: 450px;padding: 5px;height: 500px;">
    <h3>Age Range Filter</h3>
    <div class="range-container">
      <label for="">Min Range</label>
      <input type="range" class="range-input" value="20" min="20" max="70">
      <p class="range-value"></p>
    </div>
    <div class="range-container">
      <label for="">Max Range</label>
      <input type="range" class="range-input" value="70" min="20" max="70">
    </div>
  </div>

```

```

        <p class="range-value"></p>
    </div>
    <table border="1" id="table2">
    </table>
</div>
<script src="script1.js"></script>
</body>
</html>

```

JS

```

function sortAge(event){
    event.preventDefault();
    flag=0;
    let table=document.querySelector('#table1');
    let rows=document.querySelectorAll('.table-row');
    let arr=Array.from(rows);
    arr.sort((a,b)=>{
        let age1=parseInt(a.cells[2].textContent);
        let age2=parseInt(b.cells[2].textContent);
        return age1-age2;
    });
    arr.forEach(row=>table.appendChild(row));
}
function findPID(event){
    event.preventDefault();
    let pid=parseInt(document.querySelector("#pid-input").value);
    let table=document.querySelector('table');
    let rows=document.querySelectorAll('.table-row');
    let arr=Array.from(rows);
    let ans=-1;
    let i;
    for(i=0;i<arr.length;i++){
        if(arr[i].cells[0].textContent==pid){
            ans=i;
            break;
        }
    }
    if(ans===-1){
        let element=document.createElement('tr');
        element.innerHTML='<td colspan="3" style="width:450px;text-align:center;">No Patient Found</td>';
        document.querySelector("#pid-found-status-table").innerHTML=element.outerHTML;
    }
    else{
        document.querySelector("#pid-found-status-table").innerHTML=rows[i].outerHTML;
    }
}
document.querySelector(".sort-button").addEventListener('click',sortAge);
document.querySelector("#pid-submit").addEventListener('click',findPID);

const rangeInputs=document.querySelectorAll(".range-input");
const rangeValues=document.querySelectorAll(".range-value");
max=50;
min=20;
function updateRangeValue(index){
    let num=rangeInputs[index].value;
    rangeValues[index].innerHTML=num;
    if(index==0){min=parseInt(num);}
    else{max=parseInt(num);}
    let rows=document.querySelectorAll('.table-row');
    let arr=Array.from(rows);
    let table2=document.querySelector('#table2');
    min=parseInt(min);
    max=parseInt(max);
    table2.innerHTML="";
    for(let i=0;i<arr.length;i++){
        let num=parseInt(arr[i].cells[2].textContent);
        if(num<=max&&num>=min){
            let element=document.createElement('tr');
            element.innerHTML=rows[i].innerHTML;
            table2.append(element);
        }
    }
}

```

```
rangeInputs.forEach((i,index)=>{
  updateRangeValue(index);
  i.addEventListener('input',()=>updateRangeValue(index));
})
```

Output:

23BCE1728

127.0.0.1:5500/ex1.html

Exercise 10.1

P-Id	Name	Age
1	Alen	39
2	Deena	47
3	Diana	21
4	Jack	54
5	Jain	23
6	Kelvin	61
7	Luis	69
8	Rex	49

Sort

Enter PID to find:

Submit

23BCE1728

127.0.0.1:5500/ex1.html

Exercise 10.1

P-Id	Name	Age
3	Diana	21
5	Jain	23
1	Alen	39
2	Deena	47
8	Rex	49
4	Jack	54
6	Kelvin	61
7	Luis	69

Sort

Enter PID to find:

Submit

23BCE1728

127.0.0.1:5500/ex1.html

1	Alen	39
2	Deena	47
8	Rex	49
4	Jack	54
6	Kelvin	61
7	Luis	69

Sort

Enter PID to find: 5

Submit

5Jain23


Age Range Filter

Min Range

20

Max Range

70



Question 2:

2. Write a JavaScript program that performs the following actions using **different DOM selection methods**:

(a) Using `getElementById`:

Select the `<h1>` element and change its text to "Updated Title".

(b) Using `getElementsByName`:

Select the input field with the `name="username"` and set its value to "John Doe".

Select all radio buttons with the name `gender` and print the value of the selected radio button.

(c) **Using `getElementsByTagName`:**

Count and print the total number of `<p>` elements on the page.

Select all `` elements inside the `` and print their text content to the console.

(d) **Using `getElementsByClassName`:**

Change the background color of all elements with the class `input-field` to lightblue.

(e) **Using `querySelector`:**

Select the first `<p>` element with the class `info` and update its text to "This is the first info paragraph".

Select the first radio button with the name `gender` and check it programmatically.

(f) **Using `querySelectorAll`:**

Select all `<p>` elements with the class `info`, loop through them, and print their text content.

Select all checkboxes with the class `hobby`, loop through them, set them as checked and print the checked values.

Code:

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>23BCE1728</title>
</head>
<body>
  <h2>Exercise 10.2</h2>
  <h1 id="title">Original Title</h1>

  <input type="text" name="username">
  <br>
  <input type="radio" name="gender" value="Male"> Male
  <input type="radio" name="gender" value="Female"> Female
  <br>

  <p>This is paragraph 1.</p>
  <p>This is paragraph 2.</p>
  <ul>
    <li>Item 1</li>
    <li>Item 2</li>
  </ul>
```

```
<input type="text" class="input-field">
<input type="text" class="input-field">

<p class="info">Info paragraph 1</p>
<p class="info">Info paragraph 2</p>
```

```
<input type="checkbox" class="hobby" value="Reading"> Reading
<input type="checkbox" class="hobby" value="Gaming"> Gaming
<input type="checkbox" class="hobby" value="Coding"> Coding

<script src="script2.js"></script>
</body>
</html>
```

JS

```
document.getElementById("title").textContent = "Updated Title";
```

```
document.getElementsByName("username")[0].value = "John Doe";
```

```
const genderRadios = document.getElementsByName("gender");
```

```
for (let radio of genderRadios) {  
  if (radio.checked) {  
    console.log("Selected Gender:", radio.value);  
  }  
}
```

```
const paragraphs = document.getElementsByTagName("p");  
console.log("Total <p> elements:", paragraphs.length);
```

```
const listItems = document.getElementsByTagName("li");  
for (let li of listItems) {  
  console.log("List Item:", li.textContent);  
}
```

```
const inputFields = document.getElementsByClassName("input-field");  
for (let field of inputFields) {  
  field.style.backgroundColor = "lightblue";  
}
```

```
const firstInfoParagraph = document.querySelector(".info");  
if (firstInfoParagraph) {  
  firstInfoParagraph.textContent = "This is the first info paragraph";  
}
```

```
const firstGenderRadio = document.querySelector('input[name="gender"]');  
if (firstGenderRadio) {  
  firstGenderRadio.checked = true;  
}
```

```
const infoParagraphs = document.querySelectorAll(".info");  
infoParagraphs.forEach(p => console.log("Info Paragraph:", p.textContent));
```

```
const hobbyCheckboxes = document.querySelectorAll(".hobby");  
hobbyCheckboxes.forEach(checkbox => {  
  checkbox.checked = true;  
  console.log("Checked Hobby:", checkbox.value);  
});
```

Output:

23BCE1728

127.0.0.1:5500/ex2.html

Exercise 10.2

Updated Title

☒ Male ☐ Female

This is paragraph 1.

This is paragraph 2.

- Item 1
- Item 2

This is the first info paragraph

Info paragraph 2

☒ Reading ☒ Gaming ☒ Coding

Design an order form as below and implement a JavaScript program to pass the entries to another page and display the receipt.



The image shows a 'Grocery Order Form' with a light green background. It has a title 'Grocery Order Form' at the top. Below the title are three input fields for 'Customer Name', 'Phone Number', and 'Email'. The 'Customer Name' and 'Phone Number' fields are split into two parts each. Below these fields is a section titled 'Products'. This section contains three items: 'Apple' with a price of '\$ 10' and a unit of 'kg', 'Banana' with a price of '\$ 5' and a unit of 'kg', and 'Avocado' with a price of '\$ 7' and a unit of 'kg'. Each item has a small circular image of the fruit and a checkbox. At the bottom of the form is a brown 'SUBMIT' button.

Code:

HTML

ex31.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>23BCE1728</title>
  <link rel="stylesheet" href="style3.css">
</head>
<body>
  <h2>Exercise 10.3</h2>
  <div class="wrapper">
    <h3 class="heading">Grocery Order Form</h3>
    <div class="info-input-div">
      Customer Name
      <br>
      <input type="text" class="customer-name">
    </div>
    <div class="info-input-div">
      Phone Number
      <br>
      <input type="text" class="phone-number">
    </div>
    <div class="info-input-div">
      Email
      <br>
      <input type="text" class="email">
    </div>
    <hr>
    <h4>Products</h4>
    <form action="" name="f1">
      <ul>
        <li>
          
          <input type="checkbox" name="fruit" id="">
          <div class="fruit-name">Apple</div>
        </li>
      </ul>
    </form>
  </div>
</body>
</html>
```

```

        <div class="fruit-price">&dollar;10</div>
        <input type="text" class="fruit-qty">
        <div class="kg">kg</div>
    </li>
    <li>
        
        <input type="checkbox" name="fruit" id="">
        <div class="fruit-name">Banana</div>
        <div class="fruit-price">&dollar;5</div>
        <input type="text" class="fruit-qty">
        <div class="kg">kg</div>
    </li>
    <li>
        
        <input type="checkbox" name="fruit" id="">
        <div class="fruit-name">Avocado</div>
        <div class="fruit-price">&dollar;7</div>
        <input type="text" class="fruit-qty">
        <div class="kg">kg</div>
    </li>
</ul>
<button id="submit-button">Submit</button>
</form>
</div>
<script src="script3.js"></script>
</body>
</html>

```

receipt.html

```

<!DOCTYPE html>
<html lang="en">

<head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>Receipt</title>
    <link rel="stylesheet" href="style3.css" />
</head>

```

```

<body>
    <h2>Order Receipt</h2>
    <div id="receipt"></div>
    <script>
        document.addEventListener("DOMContentLoaded", function () {
            let name = localStorage.getItem("customerName");
            let phone = localStorage.getItem("customerPhone");
            let email = localStorage.getItem("customerEmail");
            let products = JSON.parse(localStorage.getItem("orderedProducts"));
            let totalCost = localStorage.getItem("totalCost");
            let receiptHTML = `<p><strong>Name:</strong> ${name}</p><p><strong>Phone:</strong>
${phone}</p><p><strong>Email:</strong> ${email}</p><h3>Products Ordered:</h3><ul>`;
            products.forEach((product) => {receiptHTML += `<li>${product.name} - ${product.quantity} kg @
${product.price} per kg</li>`;});
            receiptHTML += `</ul><p><strong>Total Cost:</strong> ${totalCost}</p>`;
            document.getElementById("receipt").innerHTML = receiptHTML;
        });
    </script>
</body>

```

```

</html>

```

style3.css

```

*{
    margin: 0px;
    padding: 0px;
}
body{
    display: flex;
    flex-direction: column;
    align-items: center;
}
.wrapper{

```

```

background-color: #9fac91;
border: 2px solid black;
width: 50vw;
height: 77vh;
margin: 10px;
padding: 10px;
display: flex;
flex-direction: column;
justify-content: space-around;
align-content: space-around;
}
.heading{
text-align: center;
padding: 0px;
margin: 0px;
}
.fruit-image{
width: 40px;
height: 40px;
border-radius: 50%;
}
li{
margin: 5px 0px 5px 0px;
display: flex;
flex-direction: row;
justify-content: space-around;
}
hr{
margin: 5px 0px 0px 0px;
background-color: black;
height: 1px;
border: none;
border-radius: 10px;
}
input{
height: 25px;
border: none;
border-radius: 10px;
}
.fruit-name{
/* border: 2px solid black; */
width: 100px;
}
.fruit-qty{
width: 50px;
}
.info-input-div{
padding: 5px 0px 0px 0px;
}
ul{
padding: 0px;
width: 50vw;
}
#submit-button{
width: 100px;
border: none;
border-radius: 10px;
background-color: rgb(166, 108, 0);
color: white;
font-weight: bold;
height: 25px;
}
form[name="f1"]{
display: flex;
flex-direction: column;
justify-content: center;
align-items: center;
}

```

JS

script3.js

```
document.addEventListener("DOMContentLoaded", function() {
```

```

const form = document.forms["f1"];
const submitButton = document.getElementById("submit-button");

submitButton.addEventListener("click", function(event) {
    event.preventDefault();

    let name = document.querySelector(".customer-name").value.trim();
    let phone = document.querySelector(".phone-number").value.trim();
    let email = document.querySelector(".email").value.trim();

    if (!name || !phone || !email) {
        alert("Please fill in all customer details.");
        return;
    }

    let products = [];
    let totalCost = 0;

    const items = [
        { name: "Apple", price: 10 },
        { name: "Banana", price: 5 },
        { name: "Avocado", price: 7 }
    ];

    const checkboxes = document.querySelectorAll("input[name='fruit']");
    const quantities = document.querySelectorAll(".fruit-qty");

    checkboxes.forEach((checkbox, index) => {
        if (checkbox.checked) {
            let quantity = parseFloat(quantities[index].value);
            if (!isNaN(quantity) && quantity > 0) {
                products.push({ name: items[index].name, quantity, price: items[index].price });
                totalCost += items[index].price * quantity;
            }
        }
    });


    if (products.length === 0) {
        alert("Please select at least one product and enter a valid quantity.");
        return;
    }

    localStorage.setItem("customerName", name);
    localStorage.setItem("customerPhone", phone);
    localStorage.setItem("customerEmail", email);
    localStorage.setItem("orderedProducts", JSON.stringify(products));
    localStorage.setItem("totalCost", totalCost);

    window.location.href = "receipt.html";
});
});

```

Output:



Exercise 10.3

Grocery Order Form

Customer Name
Sushen Grover

Phone Number
07009367016

Email
groversushen@gmail.com

Products

	<input checked="" type="checkbox"/> Apple	\$10	<input type="text" value="3"/>	kg
	<input type="checkbox"/> Banana	\$5	<input type="text" value=""/>	kg
	<input checked="" type="checkbox"/> Avocado	\$7	<input type="text" value="5"/>	kg

Submit

