

Distributed Operating Systems, Project 4 Part I: Twitter Simulator
Date: December 2, 2017

Group Members:

1. Sanket Achari, UFID: 71096329, sanketachari@ufl.edu
2. Sushmit Dharurkar, UFID: 14969578, sushmitdharurkar@ufl.edu

Instructions to RUN:

1. Make sure epmd daemon is running. Run `epmd -daemon`
2. Run following commands from the directory which has `mix.exs`
`mix escript.build`
`./project2 numNodes`
3. `numNodes` has to be between 10 to 10000

Working:

1. Simulation of Twitter Engine.
2. Tweet, Retweet, Subscribe to tweets, hashtag, mention, live connection
3. Query hashtags, mentions

Largest Simulation:

10,000 active users each tweeting at least 1 tweet

Time Required: 3min 15.730s

100 active users each tweeting at least 1 tweet:

Time Required: 0.467s

Sample Outputs:

Example 1: Considering 100 live users

Sankets-MacBook-Pro:project4 sanket\$./project4 100

Number of users present: 100

Total tweets till now: 100

Total tweets with hashtag #DOS : 15

Tweets (Showing Max 10):

```
["Another tweet, study #DOS and do #projects @user86 @user97",  
"Another tweet, study #DOS and do #projects @user30 @user14",  
"Another tweet, study #DOS and do #projects @user95 @user28",  
"Another tweet, study #DOS and do #projects @user22 @user63",  
"Another tweet, study #DOS and do #projects @user7 @user54",  
"Another tweet, study #DOS and do #projects @user80 @user44",  
"Another tweet, study #DOS and do #projects @user78 @user89",  
"Another tweet, study #DOS and do #projects @user50 @user70",  
"Another tweet, study #DOS and do #projects @user15 @user62",  
"Another tweet, study #DOS and do #projects @user9 @user33"]
```

Total tweets with mention @user1: 1

Tweets (Showing Max 10):

```
["This is #mytweet some tweet #sometweet @user1 @user21"]
```

Printing user1 details:

```
%{"followers" => [#PID<0.125.0>, #PID<0.175.0>, #PID<0.164.0>, #PID<0.124.0>,
  #PID<0.167.0>, #PID<0.107.0>, #PID<0.156.0>, #PID<0.133.0>, #PID<0.137.0>],
"notifications" => %{"#PID<0.82.0>" => ["Another tweet, study #DOS and do #projects @user31
@user59"],
  #PID<0.94.0> => ["Some random tweet #randomtweet #newtweet @user55 @user51"],
  #PID<0.117.0> => ["Some random tweet #randomtweet #newtweet @user92 @user94"],
  #PID<0.125.0> => ["This is #mytweet some tweet #sometweet @user86 @user21"],
  #PID<0.157.0> => ["Another tweet, study #DOS and do #projects @user13 @user35"],
  #PID<0.165.0> => ["Another tweet, study #DOS and do #projects @user77 @user79"],
  #PID<0.175.0> => ["This is #mytweet some tweet #sometweet @user79 @user26"]},
"retweets" => ["This is #mytweet some tweet #sometweet @user65 @user52"],
"subscribed" => [], "tweets" => [], "username" => "user1"}
```

Implementation Details:

1. We have used Gen Server for twitter engine. This server is the single process which will keep the track of each & every user, tweet, subscription, retweet, follower, hashtag and mention.
2. This gen server acts as a backend for the twitter simulation.
Gen server's state is as following

State of Engine:

```
%{ "users" => %{pid1 => true/false, pid2 => true/false,...},
  "usernames" => %{"username1" => pid1, "username2" => pid2,...}
  "tweets" => %{"tweetId1" => {tweet1, pid1}, "tweetId2" => {tweet2, pid2}....}
  "user_details" => %{ pid =>
    %{ "username" => "Unique name"
      "tweets" => [],
      "retweets" => [],
      "followers" => [],
      "notifications" => %{source_pid => [tweet1, ...]},
      "subscribed" => [tweetId1, tweetId2, ....]
    }
  }
  "hashtags" => %{ "hashtag1" => %{pid => [tweet1, tweet2, ...]}, ...}
  "mentions" => %{ "mention1" => %{"username1" => [tweet1, tweet2, ...]}, ...}
}
```

3. Initially we create total number of users which is taken from the command line argument. After this we add followers for each user randomly.
4. We have considered all the live connection in the simulation. That is no
5. Also, each user can subscribe to a random tweet. And this subscription is also random based on *Enum.random([true, false])*
6. Then each user can send tweet and retweet randomly. We have taken 3 sample tweets as follows:

```
tweet1 = "Some random tweet #randomtweet #newtweet @randomuser1 @randomuser2"
```

```
tweet2 = "This is #mytweet some tweet #sometweet @randomuser1 @randomuser2  
tweet3 = "Another tweet, study #DOS and do #projects @randomuser1 @randomuser2"
```

Note that, we have total 6 hashtags:

#randomtweet, #newtweet, #mytweet, #sometweet, #DOS, #projects

And 2 mentions:

@randomuser1, @randomuser2

These mentions are usernames of 2 users which are selected randomly.

In this simulation, we have considered above 3 tweets with hashtags and mentions. Out of these 3 tweets 1 tweet will be selected randomly and that tweet is broadcasted to the followers. Retweet is also based on the same logic.