

Microsoft Windows [Version 10.0.26200.8457]

(c) Microsoft Corporation. All rights reserved.

C:\Users\Sushmitha>ping google.com

Pinging google.com [2404:6800:4007:834::200e] with 32 bytes of data:

Reply from 2404:6800:4007:834::200e: time=54ms

Reply from 2404:6800:4007:834::200e: time=24ms

Reply from 2404:6800:4007:834::200e: time=29ms

Reply from 2404:6800:4007:834::200e: time=43ms

Ping statistics for 2404:6800:4007:834::200e:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 24ms, Maximum = 54ms, Average = 37ms

C:\Users\Sushmitha>ipconfig

Windows IP Configuration

Wireless LAN adapter Wi-Fi 2:

Media State : Media disconnected

Connection-specific DNS Suffix . :

Wireless LAN adapter Wi-Fi 4:

Media State : Media disconnected

Connection-specific DNS Suffix . :

Wireless LAN adapter Wi-Fi:

Connection-specific DNS Suffix . :

IPv6 Address. : 2401:4900:7b74:cf2f:19d8:8ad7:8125:ded3

Temporary IPv6 Address. : 2401:4900:7b74:cf2f:a9bb:41cb:eac1:9191

Link-local IPv6 Address : fe80::8103:ddef:625a:16f0%14

IPv4 Address. : 10.24.244.102

Subnet Mask : 255.255.255.0

Default Gateway : fe80::e085:7cff:fe08:5ed1%14

10.24.244.230

Ethernet adapter Bluetooth Network Connection:

Media State : Media disconnected

Connection-specific DNS Suffix . :

C:\Users\Sushmitha>tracert google.com

Tracing route to google.com [2404:6800:4007:834::200e]

over a maximum of 30 hops:

```
 1  20 ms  2 ms  3 ms 2401:4900:7b74:cf2f::f1
 2  *    *    *   Request timed out.
 3  93 ms  19 ms 119 ms 2401:4900:0:fd5::1
 4  38 ms 138 ms 123 ms 2401:4900:0:6fb::2
 5  38 ms 136 ms 140 ms 2401:4900:0:6f5::1
 6  *    *    *   Request timed out.
 7 131 ms 100 ms 100 ms 2404:a800:3a00:1::7d9
 8 100 ms *    57 ms 2404:a800::92
 9  86 ms 123 ms 78 ms 2404:6800:8202:400::1
10 435 ms 227 ms 283 ms 2404:6800:8202:400::1
```

11 85 ms 102 ms 101 ms 2001:4860:0:1::1c74
12 66 ms 145 ms 103 ms 2001:4860:0:1::5651
13 129 ms 115 ms 269 ms pnmaaa-av-in-x0e.1e100.net [2404:6800:4007:834::200e]

Trace complete.

C:\Users\Sushmitha>nslookup

Default Server: UnKnown

Address: 10.24.244.230

> nslookup www.amazon.com

Server: cf.47cf2c8c9-frontier.amazon.com

Addresses: 2600:9000:2241:ea00:7:49a5:5fd6:da1

2600:9000:2241:2600:7:49a5:5fd6:da1

2600:9000:2241:c800:7:49a5:5fd6:da1

2600:9000:2241:ee00:7:49a5:5fd6:da1

2600:9000:2241:c00:7:49a5:5fd6:da1

2600:9000:2241:fa00:7:49a5:5fd6:da1

2600:9000:2241:4000:7:49a5:5fd6:da1

2600:9000:2241:ae00:7:49a5:5fd6:da1

18.67.150.142

Aliases: www.amazon.com

tp.47cf2c8c9-frontier.amazon.com

DNS request timed out.

timeout was 2 seconds.

DNS request timed out.

timeout was 2 seconds.

*** Request to www.amazon.com timed-out

> exit

```
C:\Users\Sushmitha>arp -a
```

```
Interface: 10.24.244.102 --- 0xe
```

Internet Address	Physical Address	Type
10.24.244.92	94-e7-0b-bc-e2-38	dynamic
10.24.244.230	e2-85-7c-08-5e-d1	dynamic
10.24.244.255	ff-ff-ff-ff-ff-ff	static
224.0.0.22	01-00-5e-00-00-16	static
224.0.0.251	01-00-5e-00-00-fb	static
224.0.0.252	01-00-5e-00-00-fc	static
239.255.102.18	01-00-5e-7f-66-12	static
239.255.255.250	01-00-5e-7f-ff-fa	static
255.255.255.255	ff-ff-ff-ff-ff-ff	static

```
C:\Users\Sushmitha>systeminfo
```

Host Name: SUSHMITHA

OS Name: Microsoft Windows 11 Home Single Language

OS Version: 10.0.26200 N/A Build 26200

OS Manufacturer: Microsoft Corporation

OS Configuration: Standalone Workstation

OS Build Type: Multiprocessor Free

Registered Owner: Sushmitha

Registered Organization: HP

Product ID: 00342-42727-75788-AAOEM

Original Install Date: 06-08-2025, 20:13:29

System Boot Time: 27-05-2026, 19:49:11

System Manufacturer: HP

System Model: HP Laptop 15-fd0xxx

System Type: x64-based PC

Processor(s): 1 Processor(s) Installed.

[01]: Intel64 Family 6 Model 186 Stepping 3 GenuineIntel ~1300 Mhz

BIOS Version: AMI F.12, 20-08-2024

Windows Directory: C:\windows

System Directory: C:\windows\system32

Boot Device: \Device\HarddiskVolume1

System Locale: en-us;English (United States)

Input Locale: 00004009

Time Zone: (UTC+05:30) Chennai, Kolkata, Mumbai, New Delhi

Total Physical Memory: 16,028 MB

Available Physical Memory: 7,392 MB

Virtual Memory: Max Size: 17,052 MB

Virtual Memory: Available: 7,747 MB

Virtual Memory: In Use: 9,305 MB

Page File Location(s): C:\pagefile.sys

Domain: WORKGROUP

Logon Server: \\SUSHMITHA

Hotfix(s): 4 Hotfix(s) Installed.

[01]: KB5092427

[02]: KB5054156

[03]: KB5089549

[04]: KB5092762

Network Card(s): 1 NIC(s) Installed.

[01]: Bluetooth Device (Personal Area Network)

Connection Name: Bluetooth Network Connection

Status: Media disconnected

Virtualization-based security: Status: Running

Required Security Properties:

Base Virtualization Support

Available Security Properties:

Base Virtualization Support

Secure Boot

DMA Protection

UEFI Code Readonly

SMM Security Mitigations 1.0

Mode Based Execution Control

APIC Virtualization

Services Configured:

Hypervisor enforced Code Integrity

Services Running:

Hypervisor enforced Code Integrity

App Control for Business policy: Enforced

App Control for Business user mode policy: Off

Security Features Enabled:

Hyper-V Requirements: A hypervisor has been detected. Features required for Hyper-V will not be displayed.

C:\Users\Sushmitha>nbstat

Displays protocol statistics and current TCP/IP connections using NBT (NetBIOS over TCP/IP).

NBTSTAT [[-a RemoteName] [-A IP address] [-c] [-n]
[-r] [-R] [-RR] [-s] [-S] [interval]]

-a (adapter status) Lists the remote machine's name table given its name

-A (Adapter status) Lists the remote machine's name table given its
IP address.

-c (cache) Lists NBT's cache of remote [machine] names and their IP addresses

-n (names) Lists local NetBIOS names.

-r (resolved) Lists names resolved by broadcast and via WINS

-R (Reload) Purges and reloads the remote cache name table

-S (Sessions) Lists sessions table with the destination IP addresses

-s (sessions) Lists sessions table converting destination IP addresses to computer NETBIOS names.

-RR (ReleaseRefresh) Sends Name Release packets to WINS and then, starts Refresh

RemoteName Remote host machine name.

IP address Dotted decimal representation of the IP address.

interval Redisplays selected statistics, pausing interval seconds between each display. Press Ctrl+C to stop redisplaying statistics.

```
C:\Users\Sushmitha>pathping google.com
```

```
Tracing route to google.com [2404:6800:4007:834::200e]
```

```
over a maximum of 30 hops:
```

```
0 SUSHMITHA [2401:4900:7b74:cf2f:a9bb:41cb:eac1:9191]
```

```
1 2401:4900:7b74:cf2f::f1
```

```
2 * * *
```

```
Computing statistics for 25 seconds...
```

```
Source to Here This Node/Link
```

```
Hop RTT Lost/Sent = Pct Lost/Sent = Pct Address
```

```
0 SUSHMITHA [2401:4900:7b74:cf2f:a9bb:41cb:eac1:9191]
```

```
2/ 100 = 2% |
```

```
1 62ms 2/ 100 = 2% 0/ 100 = 0% 2401:4900:7b74:cf2f::f1
```

```
Trace complete.
```

```
C:\Users\Sushmitha>hostname
```

```
SUSHMITHA
```

```
C:\Users\Sushmitha>route
```

Manipulates network routing tables.

ROUTE [-f] [-p] [-4|-6] command [destination]

[MASK netmask] [gateway] [METRIC metric] [IF interface]

- f Clears the routing tables of all gateway entries. If this is used in conjunction with one of the commands, the tables are cleared prior to running the command.
- p When used with the ADD command, makes a route persistent across boots of the system. By default, routes are not preserved when the system is restarted. Ignored for all other commands, which always affect the appropriate persistent routes.
- 4 Force using IPv4.
- 6 Force using IPv6.

command One of these:

PRINT Prints a route

ADD Adds a route

DELETE Deletes a route

CHANGE Modifies an existing route

destination Specifies the host.

MASK Specifies that the next parameter is the 'netmask' value.

netmask Specifies a subnet mask value for this route entry.

If not specified, it defaults to 255.255.255.255.

gateway Specifies gateway.

interface the interface number for the specified route.

METRIC specifies the metric, ie. cost for the destination.

All symbolic names used for destination are looked up in the network database file NETWORKS. The symbolic names for gateway are looked up in the host name database file HOSTS.

If the command is PRINT or DELETE. Destination or gateway can be a wildcard, (wildcard is specified as a star '*'), or the gateway argument may be omitted.

If Dest contains a * or ?, it is treated as a shell pattern, and only matching destination routes are printed. The '*' matches any string, and '?' matches any one char. Examples: 157.*.1, 157.*, 127.*, *224*.

Pattern match is only allowed in PRINT command.

Diagnostic Notes:

Invalid MASK generates an error, that is when (DEST & MASK) != DEST.

Example> route ADD 157.0.0.0 MASK 155.0.0.0 157.55.80.1 IF 1

The route addition failed: The specified mask parameter is invalid. (Destination & Mask) != Destination.

Examples:

> route PRINT

> route PRINT -4

> route PRINT -6

> route PRINT 157* Only prints those matching 157*

> route ADD 157.0.0.0 MASK 255.0.0.0 157.55.80.1 METRIC 3 IF 2

destination^ ^mask ^gateway metric^ ^
Interface^

If IF is not given, it tries to find the best interface for a given gateway.

```
> route ADD 3ffe::/32 3ffe::1
```

```
> route CHANGE 157.0.0.0 MASK 255.0.0.0 157.55.80.5 METRIC 2 IF 2
```

CHANGE is used to modify gateway and/or metric only.

```
> route DELETE 157.0.0.0
```

```
> route DELETE 3ffe::/32
```

```
C:\Users\Sushmitha>
```