Diagnosing Human-to-Robot Transfer Failures with a Transfer Gap Budget in Simulation

Anonymous Author(s)
Affiliation
Address
email

Abstract: A failed rollout does not show which stage of human-to-robot transfer failed. We introduce the *Transfer Gap Budget*, which replaces one pipeline component at a time with a declared oracle and measures the paired change in task success. A joint oracle measures non-additivity. In an injected-error study with 500 fresh seeds per arm, perception has the largest budget on both the UR5e and UR10e. A look-again correction, selected on development seeds, raises success by 26.8 and 25.8 pp, respectively, the largest observed gains among four corrections. In exploratory runs, perception keeps the largest budget under halved or doubled errors and layout changes, but not when perception error is small or the depth camera well calibrated; the budget then selects a different correction that beats always applying look-again by 12 and 44 pp (95% intervals above 7 pp). On six demonstrations, diagnosis and a revised retreat raise paired success from 0–31/60 to 28–60/60 on unused seeds. Simulated depth perception meets pre-declared criteria on three manipulators. A G1 humanoid study finds 11/40 versus 31/40 placements for the same closed-loop controller across two runtime setups, with the cause unresolved. All robot evaluations are in simulation.

Keywords: human-to-robot transfer, failure diagnosis, oracle substitution

1 Introduction

Human-to-robot transfer requires motion estimation, retargeting, calibration, and executable timing. Aggregate success does not say which component to revisit, particularly with diverse human data [1]. We ask how much success correcting one pipeline component could recover. The *Transfer Gap Budget* measures each component's net oracle gain; gains can overlap. The largest development-set gain selects a correction for fresh evaluation. We test it on two arms, with real-video and depth-camera inputs, and report humanoid runtime sensitivity.

2 Related Work

Human-to-robot transfer. H2RBench reports transfer gains by execution stage on a Franka arm [2]; we intervene on pipeline components. Human-as-Humanoid and HumanEgo learn from human video [3, 4]; hand-pose quality and motion mismatch affect cotraining [5, 6]. **Diagnosis and correction.** AHA, RoboFAC, and Guardian diagnose manipulation failures [7, 8, 9]. RHO and GaP search policy code and skill graphs [10, 11]. We use oracle gains to select from a fixed correction menu.

3 Method: the Transfer Gap Budget

Paired interventions. Let $\mathcal{K}$ contain perception, retargeting, tool-frame calibration, and execution timing. In the controlled-error study, *full* includes all four perturbations; $oracle_k$ removes only perturbation k, and *oracle-all* removes all four. Their ideal outputs are exact object pose, unperturbed

Submitted to the 10th Conference on Robot Learning (CoRL 2026). Do not distribute.




Figure 1: **Controlled-error study: 500 fresh seeds per arm.** (a) Paired success gains from single and joint oracles. (b) Gains from the four corrections; look-again was selected on development seeds. Bars: paired bootstrap 95% intervals.

IK, zero tool offset, and nominal timing. Each random stream is keyed by seed and component, preserving initial scenes and unreplaced error draws across conditions. For binary success $s_c(i)$ on seed i in condition c,

$$B_k = \frac{1}{n}\sum_{i=1}^{n}\big(s_{\text{oracle}_k}(i) - s_{\text{full}}(i)\big), \qquad \Delta_{\text{int}} = \sum_{k\in\mathcal{K}} B_k - B_{\text{all}}. \tag{1}$$

Here B_{all} uses the joint oracle in the same paired difference. Budgets are signed net gains: an oracle can both rescue and lose trials. The residual shows whether summed single-stage gains exceed (> 0) or fall below (< 0) the joint gain; it does not allocate failures to interactions.

Correction selection. The menu pairs perception with look-again, retargeting with an IK re-solve, calibration with a modelled touch probe, and timing with a speed cap. We select $k^\star = \arg\max_k B_k$ on development seeds, breaking ties in pipeline order. Look-again and probing reduce assumed residual errors; their manoeuvres are not simulated.

Statistics. Paired percentile bootstrap intervals (95%; 5000 resamples in Section 5.1, 2000 elsewhere) resample seeds, preserving all condition scores of each seed. Demo intervals are descriptive: seeds 1000–1059 informed the revision, and demonstrations and stacks are not resampled.

4 Experimental Setup

Task. MuJoCo simulates a fixed-base UR5e or UR10e with a Robotiq 2F-85 from MuJoCo Menagerie [12], a 4 cm block with ±3 cm position jitter, and a 14 cm tray. A scripted IK controller uses simulated contact in a UR5e-tuned layout. Success requires a lift of at least 5 cm, release within 3 cm of the goal, and speed below 0.02 m/s for 0.5 s after release.

A: controlled errors. The injected magnitudes are assumptions. Both arms receive the same seed-dependent draws: Gaussian xy perception error ($\sigma = 1.5$ cm), joint offsets ($\sigma = 0.5°$ per joint), a uniformly directed tool-frame offset with magnitude $\mathcal{U}(0, 3)$ cm, and a timing speed-up of $\mathcal{U}(1.0, 4.5)$ relative to robot pace. The corrections reduce perception noise to 0.4 cm, joint-offset noise to $0.05°$, or calibration noise to 2 mm per axis, or cap speed-up at $3\times$. Development seeds 0–59 select look-again on both arms. After freezing the protocol and four hypotheses, we evaluate ten conditions on 500 fresh seeds (3000–3499) per arm: *full*, four single oracles, the joint oracle, and four corrections applied to *full*.

E: sensitivity. On further fresh seeds (200 per arm unless stated) we repeat A's conditions with errors scaled by 0.5 (500 seeds) and 2, a 3 or 5 cm block, ±5 cm jitter, the tray or block moved 8–10 cm, perception error scaled 0.1–2, cut to 25% alone or with calibration error doubled (500 seeds), and set to the depth estimator's measured error. Correction constants are unchanged.

B: real-video motion. Five pick-and-place cycles from two people in two freely licensed videos, plus one from a third person's 50 s recording, supply motion and timing. GEM-X [13] estimates hand trajectories; grasp and release frames are annotated manually. Reach and retreat are anchored to the simulated grasp and release points, and the carry path is rotated and scaled to connect them; the scene is not reconstructed. Perception and calibration errors remain injected; no object detector is used, and retargeting is excluded from the real-video oracle analysis. Each demo–arm pair uses 60 seeds from the revision period (1000–1059) and 60 unused seeds (5000–5059). We report leg-wise path RMSE against the retargeted reference.

C: depth perception. A geometric estimator fits the table plane, clusters points above it, and selects a cube and tray; its position, yaw, and size drive the controller. We test 5, 6, and 7 cm cubes on the two arms and a third manipulator (UR10e with a Robotiq 2F-140), with 40 seeds per size: 120 episodes per condition. **D: humanoid.** A Unitree G1 with Dex3 hands uses SONIC whole-body control [14]. We score grasp (5 cm lift with contact) and placement within 5 cm of the goal; we do not estimate stage budgets here.

5 Results

5.1 Controlled errors on two arms

Uncorrected success is 232/500 on the UR5e and 240/500 on the UR10e. Removing all errors recovers 53.6 and 52.0 pp. Perception has the largest budget: 30.0 [25.8, 34.4] pp on the UR5e and 29.4 [25.0, 33.8] pp on the UR10e. Calibration follows (17.0 and 12.0 pp), then timing (11.2 and 8.0 pp) and retargeting (8.8 and 6.4 pp); all single-stage intervals exclude zero (Fig. 1a).

The interaction residual is 13.4 [6.2, 20.8] pp on the UR5e and 3.8 [-2.6, 10.4] pp on the UR10e.

Look-again, selected on development trials, raises success from 232 to 366/500 (UR5e) and 240 to 369/500 (UR10e); the paired gains are 26.8 [22.6, 31.2] pp and 25.8 [21.6, 30.2] pp, respectively, the largest observed. Probing gives 17.6 and 13.4 pp; IK re-solving and the speed cap 6–8 pp (Fig. 1b).

5.2 Sensitivity to assumptions, layout and the budget rule

Perception has the largest budget at nominal and doubled errors, with 3 or 5 cm blocks, $\pm$5 cm jitter (ten cells), and moved tray or block (six cells). At $0.5\times$ errors (484 and 485 of 500 uncorrected) it still leads, by 0.8 pp [0.2, 1.6] over calibration on both arms. Varying only perception error (Fig. 2), perception leads from the assumed 1.5 cm upward; at $0.75\times$ and below calibration and timing take over.




Figure 2: Budgets against injected perception error (200 seeds per point); dotted: assumed 1.5 cm.

The depth estimator's block-position error is 0.34 mm RMS per axis with exact camera calibration, and 7.1 and 14.2 mm with $0.5°$/5 mm and $1°$/10 mm calibration error. Injecting these values, the perception budget is -1.0 and 2.0 pp at 0.34 mm and 10.0 and 9.5 pp at 7.1 mm (timing leads), and 28.5 and 31.0 pp at 14.2 mm (perception leads), near the assumed 15 mm. This ties one magnitude to a calibration scenario; the other three remain assumed.

With 500 seeds per arm, the largest budget on the first 100 selects a correction evaluated on the other 400. With perception error cut to 25%, the rule picks timing and gains 14.0 and 13.0 pp, against 2.2 and 1.0 pp for look-again: a difference of +11.8 [7.5, 16.0] and +12.0 [7.8, 16.2] pp. Calibration was best in hindsight (15.2 and 14.5 pp), so the rule is 1.2 and 1.5 pp short (intervals include zero). With calibration error also doubled, it picks calibration, gains 43.8 and 44.5 pp against about zero for look-again (difference +43.8 [39.0, 48.5] and +44.0 [39.0, 49.0] pp), and matches the best correction. Where perception dominates, it picks look-again and ties with that fixed choice.

Table 1: Successes of 60 paired seeds, uncorrected → revised stack; left seeds were reused in development, right seeds not. P1–P3: demonstrators.

	Seeds 1000–1059		Unused seeds	
Demonstration	UR5e	UR10e	UR5e	UR10e
P1 notebook	0→ 57	0→ 60	0→ 60	0→ 60
P1 markers	0→ 51	0→ 25	0→ 49	0→ 28
P1 orange marker	0→ 46	0→ 58	0→ 51	0→ 59
P1 notepad	0→ 58	0→ 58	0→ 60	0→ 60
P2 box (own stack)	11→ 60	4→ 55	23→ 60	9→ 49
P2 box (P1 stack)	11→ 60	4→ 50	23→ 60	9→ 52
P3 recording (P1 stack)	35→ 59	30→ 56	31→ 57	21→ 53

5.3 Real-video demonstrations

The notebook demo fails uncorrected on both arms at about $6\times$ robot pace. Sequential diagnosis selects a $3\times$ speed cap, look-again, calibration probing, then a tighter $2\times$ cap; with the revised retreat the stack reaches 57/60 and 60/60 (Table 1), and RMSE to the retargeted reference falls from 13.9 to 4.9 cm (UR5e) and 9.1 to 2.9 cm (UR10e).

The original stack scored 0/60 on all 3 additional P1 cycles, whose copied retreat paths intersect the tray, and cut P2 success on the UR5e from 11/60 to 0/60. We therefore added a 5 cm lift before retreating along the human path (selected on development seeds 0–19; path-RMSE cost 2.7–4.1 cm). The revised P1 stack transfers to P2 and P3 without retuning; P1 markers remain difficult on the UR10e (25/60). Seeds 1000–1059 informed the revision, so those columns are exploratory. On seeds 5000–5059, which no development step used, every cell improves: the revised stack reaches 28–60/60 against 31 or fewer uncorrected, all paired intervals exclude zero, and P1 markers on the UR10e reaches 28/60.

5.4 Depth perception and humanoid runtime sensitivity

All 30/30 pre-declared acceptance cells reach the 90% point-estimate threshold (113–120 of 120 episodes), covering yaw, distractors, depth noise, occlusion with a retry, and combined stressors on three manipulators. Report-only stress tests expose limits: 2°/20 mm calibration error gives 25/120 on the UR5e, and occlusion without retry 0–16/120. For the notebook path at robot pace, depth versus ground-truth success is 109 versus 108/120 (UR5e), 112 versus 111/120 (UR10e), and 120 versus 118/120 (third arm): 0.8–1.7 pp higher, with path RMSE within 0.01 cm. All three meet the point-estimate margins of 10 pp success loss and 0.5 cm added RMSE (no inferential non-inferiority test); combined stress gives 88/120, 88/120, 91/120.

G1 humanoid. With IK-planned targets, the same frozen closed-loop controller places 11/40 objects in a volume-based installation and 31/40 in a packaged container (same GPU, seeds 1200–1239; discordant placements 20 to 0, exact McNemar $p = 1.9 \times 10^{-6}$). Code and environment checks did not identify the cause; a four-seed MuJoCo 3.15.0 rebuild (0/4 lifts versus 4/4 on 3.14.0) also changed `filelock`.

6 Limitations and Conclusion

The study uses one simulated task, scripted controllers, a UR5e-tuned layout, and assumed error and correction magnitudes; only the perception magnitude is tied to a measurement, and layout runs move the tray and block, not the table or task. Six demonstrations from three people and unreconstructed scenes limit generalisation; look-again and probing cost no simulated time. Perception has the largest budget under the declared model and its correction the largest observed gain; when perception error is small, both move to other stages. This supports diagnosis in simulation; real-robot performance remains untested. An AI assistant helped draft parts of the manuscript and code; values were checked against saved results.

References

[1] Scaling H2R. CoRL 2026 Workshop "Scaling H2R" (Human-to-Robot). https://scaling-h2r-corl.github.io/, 2026. Call for papers, accessed Sept. 2026.

[2] C. Xiao, H. Zhan, S. Krishna, P. Meng, M. Z. Irshad, S. Zakharov, and D. Held. H2RBench: A real-to-sim benchmark for evaluating human-to-robot transfer. *arXiv preprint arXiv:2609.24778*, 2026. CoRL 2026.

[3] X. Lin, R. Yang, S. Lian, Z. Shen, B. Yu, C. Wu, H. Liu, Y. Zhang, H. Li, Q. Su, H. Liu, X. He, Y. Shi, C. Huang, Z. Zhang, B. Cheng, and K. Chen. Human-as-Humanoid: Enabling zero-shot humanoid learning from ego-exo human videos with human-aligned embodiments. *arXiv preprint arXiv:2606.32009*, 2026.

[4] Z. Wang, B. He, K. Yu, S. Lee, R. Gao, F. Huang, and Y. Aloimonos. HumanEgo: Zero-shot robot learning from minutes of human egocentric videos. *arXiv preprint arXiv:2605.24934*, 2026.

[5] R. Li, A. Prakash, A. Wen, S. Gupta, Y. Du, and P. Agrawal. What matters when cotraining robot manipulation policies on everyday human videos? *arXiv preprint arXiv:2606.06627*, 2026.

[6] Y. Domae, K. Shirai, H. Oh, R. Nakajo, T. Motoda, K. Makihara, M. Murooka, T. Yagi, Y. Bando, and R. Hanai. The embodiment gap in robot foundation models. *Transactions on Machine Learning Research*, 2026. arXiv:2608.18433.

[7] J. Duan, W. Pumacay, N. Kumar, Y. R. Wang, S. Tian, W. Yuan, R. Krishna, D. Fox, A. Mandlekar, and Y. Guo. AHA: A vision-language-model for detecting and reasoning over failures in robotic manipulation. *arXiv preprint arXiv:2410.00371*, 2024.

[8] Z. Ye, W. Lu, M. Ye, T. Lin, S. Yang, J. Yan, and B. Zhao. RoboFAC: A comprehensive framework for robotic failure analysis and correction. *arXiv preprint arXiv:2505.12224*, 2025.

[9] P. Pacaud, R. Garcia, S. Chen, and C. Schmid. Guardian: Detecting robotic planning and execution errors with vision-language models. *arXiv preprint arXiv:2512.01946*, 2025.

[10] K. Elmaaroufi, J. Svegliato, S. Kalade, G. Schelle, S. A. Seshia, and M. Zaharia. RHO: Your coding agent is secretly a roboticist. *arXiv preprint arXiv:2606.16458*, 2026.

[11] K. Chen, S. Xie, L. Fu, J. Yu, W. Pacini, S. Bajamahal, H. Kim, J. Drake, D. Kim, H. Xue, J. Francis, C. Juette, P. Schaldenbrand, M. Y. Seker, R. Wickramarachchi, U. Yoo, G. Wang, A. Murali, B. Sundaralingam, S. S. Sastry, S. Huang, Y. Zhu, L. Fan, and K. Goldberg. GaP: A graph-as-policy multi-agent self-learning harness for variational automation tasks. *arXiv preprint arXiv:2607.05369*, 2026.

[12] MuJoCo Menagerie. MuJoCo Menagerie. https://github.com/google-deepmind/mujoco_menagerie, 2026. Software repository.

[13] GEM-X. GEM-X: Monocular whole-body 3d human pose estimation. https://github.com/NVlabs/GEM-X, 2026. Software repository.

[14] Z. Luo, Y. Yuan, T. Wang, C. Li, F. Castañeda, S. Chen, Z.-A. Cao, J. Li, D. Minor, Q. Ben, J. Park, D. Sami, Z. Wang, X. Da, R. Ding, C. Hogg, L. Song, E. Lim, E. Jeong, T. He, H. Xue, W. Xiao, S. Yuen, J. Kautz, Y. Chang, U. Iqbal, L. Fan, and Y. Zhu. SONIC: Supersizing motion tracking for natural humanoid whole-body control. *Science Robotics*, 11(117):eaed4592, 2026. arXiv:2511.07820.