UNIVERSITY

OF

CALCUTTA

Roll No :- 3012-51-0084

Reg. No :- 012-1121-2659-16

Subject   :- Shell Script

Paper   :- VIII

Index of the Shell Assignment

Index of the Shell Assignment

Assignment No :- 1

Program Statement:-

Write a shell script / program to print a reverse number of a given number.

Program Algorithm:-

Description:

This is a program to reverse a number. We take a number a reverse it by using 'rev' command, and display it.

Steps:

Step 1 print "Enter a number"
             input n

Step 2 n=`echo $n|rev`
             [rev is a command that returns reverse of the hole inputted string.]

Step 3 print "Number in reverse order =" n

Step 4 Exit from the program.

Shell Script:-

Write a shell script / program to print a reverse number of a given number.

```
echo -n "Enter a Number ="
read n
n=`echo "$n"|rev`
echo "Number in reverse order =$n"
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 4.sh
Enter a Number =14
Number in reverse order =41
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 4.sh
Enter a Number =483
Number in reverse order =384
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 4.sh
Enter a Number =64064
Number in reverse order =46046

Assignment No :- 2

Program Statement:-

Write a shell script / program to determine whether the number is prime or not.

Program Algorithm:-

Description:

This is a program to check a number that is prime or not. Here we take a number and if it is a prime number then display prime otherwise not prime.

Steps:

Step 1 print "Enter a Number ="
input n
flag ← 0
i ← 2

Step 2 Loop continues when i less than or equal to n/2 true
If n mod I equal to 0 then
flag ← 1
goto **Step 3**
[End of if]
i ← i+1
[End of Loop]

Step 3 If n not equal to 1 AND flag equal to 0 then
print "n is a Prime Number."
else
print "n is Not a Prime Number."
[End of if]

Step 4 Exit from the program.

Shell Script:-

Write a shell script / program to determine whether the number is prime or not.

```
echo -n "Enter a Number ="
read n
flag=0
for ((i=2;i<=n/2;i++))
do
        if [ $((n%i)) -eq 0 ]
```

```
        then
                flag=1
                break
        fi
done
if [ $flag -eq 0 -a $n -ne 1 ]
then
        echo "$n is a Prime Number."
else
        echo "$n is Not a Prime Number."
fi
```

Output:-

```
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 5.sh
Enter a Number =23
23 is a Prime Number.
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 5.sh
Enter a Number =18
18 is Not a Prime Number.
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 5.sh
Enter a Number =103
103 is a Prime Number.
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 5.sh
Enter a Number =97
97 is a Prime Number.
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 5.sh
Enter a Number =91
91 is Not a Prime Number.
```

Assignment No :- 3

Program Statement:-

Write a shell script / program to determine whether a particular user logged into the system or not.

Program Algorithm:-

Description:

This is a program to check that a user is logged in or not. Here we take a user name and if it is already logged in then prints it's name otherwise we wait for that user when he/She login and then display the waiting time we were waited for that user.

Steps:

Step 1 print "Enter the User Name ="
        input u
        t ← 0
        f ← 0

Step 2 Loop starts
                ch ← `who| grep  -i $u`
                [here who command finds the all user that currently logged in and grep -i finds that string
                is present into that fie or not and if not exist then returns it otherwise return
                nothing.]
Step 2.1   If ch not equal to nothing then
                        If f equal to 0 then
                                print u "is already logged in."
                        else
                                print u "is logged in after " t "minutes."
                        [End of if]
                        exit from the program.
Step 2.2   else
                        wait for 60 seconds
                        t ← t+1
                        f ← 1
                [End of if]
        [End of Loop]

Step 3 Exit from the program.

Shell Script:-

\# Write a shell script / program to determine whether a particular user logged into the system or not.

```
echo -n "Enter the User Name ="
read u
t=0
f=0
while true
do
        ch=`who|grep -i $u`
        if [ "$ch" != ""  ]
        then
                if [ $f -eq 0 ]
                then
                        echo "$u is already logged in."
                else
                        echo "$u is logged in after $t minutes."
                fi
                exit
        else
                sleep 60
                t=$(($t+1))
                f=1
        fi
done
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 6.sh
Enter the User Name =susovan
susovan is already logged in.

Assignment No :- 4

Program Statement:-

Write a shell script /program that reads an integer and test whether it is divisible by 11 using divisibility rule.

Program Algorithm:-

Description:

This is a program to check that a number is divisible or not. Here we take a integer number and check it by 11's divisibility rule that is divisible or not, if yes then print divisible otherwise print not divisible.

Steps:

Step 1 print "Enter a Number ="
input n
i ← 1
s ← 0

Step 2 Loop starts
ch=`echo "$n"|cut -c $i`
[cut -c cut a character of the string from which location that passes into it and returns that character.]
Step 2.1 If ch equal to nothing then
goto the **Step 3**
[end of if]
Step 2.2 If I mod 2 equal to 1 then
s ← s+ch
else
s ← s-ch
[end of if]
i ← i+1
[end of Loop]

Step 3 If s mod 11 equal to 0 then
print n "is Divisible by 11."
else
print n "is Not Divisible by 11."
[end of If]

Step 4 Exit from the program.

Shell Script:-

Write a shell script /program that reads an integer and test whether it is divisible by 11 using divisibility rule.

```
echo -n "Enter a Number ="
read n
i=1
s=0
while true
do
        ch=`echo "$n"|cut -c $i`
        if [ "$ch" = "" ]
        then
                break
        fi
        if [ $(($i%2)) -eq 1 ]
        then
                s=$(($s+$ch))
        else
                s=$(($s-$ch))
        fi
        i=$(($i+1))
done
if [ $(($s%11)) -eq 0 ]
then
        echo "$n is Divisible by 11."
else
        echo "$n is Not Divisible by 11."
fi
```

Output:-

```
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 7.sh
Enter a Number =146
146 is Not Divisible by 11.
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 7.sh
Enter a Number =121
121 is Divisible by 11.
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 7.sh
Enter a Number =712457
712457 is Not Divisible by 11.
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 7.sh
Enter a Number =278828
278828 is Divisible by 11.
```

Assignment No :- 5.i

Program Statement:-

Write a shell / program to print a pattern.
```
 *
 * *
 * * *
 * * * *
 …
```

Program Algorithm:-

Description:

This is a program to print a pattern. Here we take the lines numbers as input and prints the corresponding pattern.

Steps:

Step 1 print "Enter the Line Number ="
input n
i ← 0

Step 2 Loop continue when i less than n true
j ← 0
Step 2.1   Loop continue when j less than or equal to i true
print "*"
j ← j+1
[end of Loop]
print a new line.
i ← i+1
[End of Loop]

Step 3 Exit from the program.

Shell Script:-

```
# Write a shell / program to print the following pattern
# *
# * *
# * * *
# * * * *
#  ...
```

```
echo -n "Enter the Line Number ="
read n
for ((i=0;i<n;i++))
do
        for ((j=0;j<=i;j++))
        do
                echo -n "* "
        done
        echo
done
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 8a.sh
Enter the Line Number =6
*
* *
* * *
* * * *
* * * * *
* * * * * *

Assignment No :- 5.ii

Program Statement:-

Write a shell / program to print a pattern.

```
      *
    * * *
  * * * * *
* * * * * * *

 .........
```

Program Algorithm:-

Description:

This is a program to print a pattern. Here we take the lines numbers as input and prints the corresponding pattern.

Steps:

Step 1 print "Enter the Line Number ="
        input n
        i ← 0

Step 2 Loop continue when i less than n true
                j ← n-1
Step 2.1   Loop continue when j greater than to i true
                        print blank space
                        j ← j-1
                [end of Loop]
Step 2.2   j ← 0
                Loop continue when j is less than to i*2+1 true
                        print "*"
                        j ← j+1
                [end of Loop]
                print a new line.
                i ← i+1
        [End of Loop]

Step 3 Exit from the program.

Shell Script:-

```
# Write a shell / program to print the following pattern
#         *
#       * * *
#     * * * * *
#   * * * * * * *
# .........

echo -n "Enter the Line Number ="
read n
for ((i=0;i<n;i++))
do
        for ((j=n-1;j>i;j--))
        do
                echo -n "  "
        done
        for ((j=0;j<i*2+1;j++))
        do
                echo -n "* "
        done
        echo
done
```

Output:-

```
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 8b.sh
Enter the Line Number =7
            *
          * * *
        * * * * *
      * * * * * * *
    * * * * * * * * *
  * * * * * * * * * * *
* * * * * * * * * * * * *
```

Assignment No :- 5.iii

Program Statement:-

Write a shell / program to print a pattern.
```
 1
 0 1
 1 0 1
 0 1 0 1
 .........
```

Program Algorithm:-

Description:

This is a program to print a pattern. Here we take the lines numbers as input and prints the corresponding pattern.

Steps:

Step 1   print "Enter the Line Number ="
       input n
       i ← 0
       str ← ""

Step 2   Loop continue when I less than n true
           If i mod 2 equal to 0 then
                str ← "1 "str
           else
                str ← "0 "str
           [end of If]
           print str with new line.
           i ← i+1
       [end of Loop]

Step 3   Exit from the program.

Shell Script:-

```
# Write a shell / program to print the following pattern
# 1
# 0 1
# 1 0 1
# 0 1 0 1
#  .........
```

```
echo -n "Enter the Line Number ="
read n
str=""
for ((i=0;i<n;i++))
do
        if [ $(($i%2)) -eq 0 ]
        then
                str="1 "$str
        else
                str="0 "$str
        fi
        echo "$str"
done
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 8c.sh
Enter the Line Number =8
1
0 1
1 0 1
0 1 0 1
1 0 1 0 1
0 1 0 1 0 1
1 0 1 0 1 0 1
0 1 0 1 0 1 0 1

Assignment No :- 5.iv

Program Statement:-

Write a shell / program to print a pattern.
sinx = x - x^3/3! + x^5/5! - x^7/7! + ...

Program Algorithm:-

Description:

This is a program to print a pattern. Here we take the item numbers as input and prints the corresponding pattern.

Steps:

Step 1 print "Enter the term numbers ="
input n
i ← 1
print "Sin x = x "

Step 2 Loop continue when i less than n true
If i mod 2 equal to 0 then
print "+ " (2*i+1)/(2*i+1) "! "
else
print "- " (2*i+1)/(2*i+1) "! "
[end of If]
i ← i+1
[End of Loop]

Step 3 Exit from the program.

Shell Script:-

```
# Write a shell / program to print the following pattern
# sinx = x - x^3/3! + x^5/5! - x^7/7! + ......

echo -n "Enter the term numbers ="
read n
echo -n "Sin x  = x "
for ((i=1;i<n;i++))
do
        if [ $(($i%2)) -eq 0 ]
        then
                echo -n "+ x^$((2*$i+1))/$((2*$i+1))! "
```

```
        else
                echo -n "- x^$((2*$i+1))/$((2*$i+1))! "
        fi
done
echo
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 8d.sh
Enter the term numbers =10
Sin x = x - x^3/3! + x^5/5! - x^7/7! + x^9/9! - x^11/11! + x^13/13! - x^15/15! + x^17/17! - x^19/19!

Assignment No :- 6

Program Statement:-

Write a shell script /program to generate a possible combinations of 1,2 and 3.

Program Algorithm:-

Description:

This is a program to print the all possible combination of 1,2 and 3. Here we use 3 Loop to print the all possible combination.

Steps:

Step 1 print "All possible combinations of 1, 2 and 3 :-"

Step 2 for i in (1,2,3)

Step 3   for j in (1,2,3)

Step 4   for k in (1,2,3)
                                print value of ijk
                        [end of Loop]

             [end of Loop]

        [end of Loop]

Step 5 Exit from the program.

Shell Script:-

Write a shell script /program to generate a possible combinations of 1,2 and 3.

```
echo "All possible combinations of 1, 2 and 3 :-"
for i in 1 2 3
do
        for j in 1 2 3
        do
                for k in 1 2 3
                do
                        echo "$i$j$k"
                done
        done
done
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 10.sh
All possible combinations of 1, 2 and 3 :-
111
112
113
121
122
123
131
132
133
211
212
213
221
222
223
231
232
233
311
312
313
321
322
323
331
332
333

Assignment No :- 7

Program Statement:-

Write a menu driven shell script / program using switch statement.

Program Algorithm:-

Description:

This is a program to print a pattern.

Steps:

Step 1 print "1. Add Numbers.\n2. Subtract Numbers.\n3. Multiply Numbers.\n4. Divide Numbers.\n5. Exit."

Step 2 print "Enter Your choice ="
input n
print "Enter A ="
input a
print "Enter B ="
input b

Step 3 If n equal to 1 then
print "Ans of a+b =" a+b
goto **Step 9**
[End of if]

Step 4 If n equal to 2 then
print "Ans of a-b =" a-b
goto **Step 9**
[End of if]

Step 5 If n equal to 3 then
print "Ans of a*b =" a*b
goto **Step 9**
[End of if]

Step 6 If n equal to 4 then
print "Ans of a/b =" a/b
goto **Step 9**
[End of if]

Step 7 If n equal to 5 then
goto **Step 9**
[End of if]

Step 8 If n not equal to 1,2,3,4,5 then
          print "Worng choice"
          goto **Step 9**
     [End of if]

Step 9 Exit from the program.

Shell Script:-

```
# Write a menu driven shell script / program using switch statement that has the following
options :
# 1. Add numbers
# 2. Subtract numbers
# 3. Multiply numbers
# 4. Divide numbers
# 5. Exit

echo -e "1. Add Numbers.\n2. Subtract Numbers.\n3. Multiply Numbers.\n4. Divide
Numbers.\n5. Exit."
echo -n "Enter your Choice ="
read n
echo -n "Enter A ="
read a
echo -n "Enter B ="
read b

case $n in
        1)      echo "Ans of $a+$b =`echo "scale=2;$a+$b"|bc`"
                ;;
        2)      echo "Ans of $a-$b =`echo "scale=2;$a-$b"|bc`"
                ;;
        3)      echo "Ans of $a*$b =`echo "scale=2;$a*$b"|bc`"
                ;;
        4)      echo "Ans of $a/$b =`echo "scale=2;$a/$b"|bc`"
                ;;
        5)      exit
                ;;
        *)  echo "Wrong Choice."
                ;;
esac
```

Output:-

```
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 11.sh
1. Add Numbers.
2. Subtract Numbers.
3. Multiply Numbers.
4. Divide Numbers.
5. Exit.
```

Enter your Choice =1
Enter A =10
Enter B =35
Ans of 10+35 =45
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 11.sh
1. Add Numbers.
2. Subtract Numbers.
3. Multiply Numbers.
4. Divide Numbers.
5. Exit.
Enter your Choice =2
Enter A =48
Enter B =129
Ans of 48-129 =-81
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 11.sh
1. Add Numbers.
2. Subtract Numbers.
3. Multiply Numbers.
4. Divide Numbers.
5. Exit.
Enter your Choice =3
Enter A =30
Enter B =5
Ans of 30*5 =150
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 11.sh
1. Add Numbers.
2. Subtract Numbers.
3. Multiply Numbers.
4. Divide Numbers.
5. Exit.
Enter your Choice =9
Wrong Choice.
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 11.sh
1. Add Numbers.
2. Subtract Numbers.
3. Multiply Numbers.
4. Divide Numbers.
5. Exit.
Enter your Choice =4
Enter A =125
Enter B =6
Ans of 125/6 =20.83

Assignment No :- 8

Program Statement:-

Write a shell script / program to count number of lines and words in a file.

Program Algorithm:-

Description:

This is a program to count number of lines and words in a file. Here take a file name as input and we find the line number and word number of that file.

Steps:

Step 1 print "Enter the File name ="
input fn
ln ← 0
w ← 0
flag ← 0

Step 2 open the file fn in output mode

Step 3 Loop continue when read l true
[read l means that it read every line from the file that opens in output mode.]
i ← 1
Step 3.1   Loop starts
ch =`echo "$l"|cut –c $i`
[cut -c cut a character of the string from which location that passes into it and
returns that character.]
Step 3.1.1   If ch equal to nothing then
goto **Step 3.2**
[End of if]
Step 3.1.2   if ch equal to between one of them " ", ",", ".", ";", "?" then
if flag equal to 0 then
w ← w+1
flag ← 1
[end of If]
else
flag ← 0
[End of if]
i ← i+1
[End of Loop]
Step 3.2   if flag equal to 0 then
w ← w+1
[End of if]
ln ← ln +1

[End Of Loop]

Step 4 print in file fn words =w and line =ln

Step 5 Exit from the program.

Shell Script:-

Write a shell script / program to count number of lines and words in a file.

```
echo -n "Enter the File name ="
read fn
ln=0
w=0
flag=0
exec<$fn
while read l
do
        i=1
        while true
        do
                ch=`echo "$l"|cut -c $i`
                if [ "$ch" = "" ]
                then
                        break
                fi
                if [ "$ch" = " " -o "$ch" = "," -o "$ch" = "." -o "$ch" = ";" -o "$ch" = "?" ]
                then
                        if [ $flag -eq 0 ]
                        then
                                w=$(($w+1))
                                flag=1
                        fi
                else
                        flag=0
                fi
                i=$(($i+1))
        done
        if [ $flag -eq 0 ]
        then
                w=$(($w+1))
        fi
        ln=$(($ln+1))
done
echo "In file '$fn'"
echo "Words =$w"
echo "lines =$ln"
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 13.sh
Enter the File name =a.txt
In file 'a.txt'
Words =578
lines =184
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 13.sh
Enter the File name =13.sh
In file '13.sh'
Words =142
lines =40

Assignment No :- 9

Program Statement:-

Write a shell script / program to find the sum and average of first "N" numbers (20<=N=<50).

Program Algorithm:-

Description:

This is a program to find the sum and average of first "N" numbers (20<=N=<50).User will asked to input N. The program must check the validity of "N" as input on by user.

Steps:

Step 1   print "Enter the N (20<=N<=50) ="
        input n

Step 2   if n is greater than 50 OR less than 20 then
          print "Your data is not in range."
          goto **Step 6**

Step 3   sum ← 0
        i ← 1

Step 4   Loop continue when i less than or equal to n true
          sum ← sim + i
          i ← i+1
        [end of Loop]

Step 5   print "Sum =" sum
        print "Avarage =" sum/n

Step 6   Exit from the program.

Shell Script:-

Write a shell script / program to find the sum and average of first "N" numbers (20<=N=<50).User will asked to input N. The program must check the validity of "N" as input on by user.

```
echo -n "Enter the N (20<=N<=50) ="
read n
# Input condition checking
```

```
if [ $n -gt 50 -o $n -lt 20 ]
then
        echo "Your Entered Number is Not in Range."
        exit
fi
# Calculation
sum=0
for ((i=1;i<=$n;i++))
do
        sum=$(($sum+$i))
done
echo "Sum =$sum"
echo "Average =`echo "scale=2;$sum/$n"|bc`"
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 14.sh
Enter the N (20<=N<=50) =25
Sum =325
Average =13.00
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 14.sh
Enter the N (20<=N<=50) =30
Sum =465
Average =15.50
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 14.sh
Enter the N (20<=N<=50) =60
Your Entered Number is Not in Range.
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 14.sh
Enter the N (20<=N<=50) =10
Your Entered Number is Not in Range.

Assignment No :- 10

Program Statement:-

Write a shell script / program to print a text file in reverse way.

Program Algorithm:-

Description:

This is a program to print a text file in reverse way .Here we take a file name as a input and print that file in reverse way.

Steps:

Step 1 print "Enter a File Name ="
input fn
str ← ""

Step 2 open the file fn in output mode

Step 3 Loop continue when read l true
[read l means that it read every line from the file that opens in output mode.]
str ← l"\n"str
[End of Loop]

Step 4 print str

Step 5 Exit from the program.

Shell Script:-
Write a shell script / program to print a text file in reverse way.

```
echo -n "Enter the File name ="
read fn
str=""
exec<$fn
while read l
do
        str=$l"\n"$str
done
echo -e "$str"
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ cat 1.sh
Assignment No :- 1
Write a shell script / program to generate Fibonacci series up to a certain number.

```
echo -n "Enter the Extreme Limit ="
read n
a=0
b=1
while [ $a -le $n ]
do
        echo -n  "$a  "
        c=$(($a+$b))
        a=$b
        b=$c
done
echo
```
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 15.sh
Enter the File name =1.sh
echo
done
b=$c
a=$b
c=$(($a+$b))
echo -n "$a "
do
while [$a -le $n]
b=1
a=0
read n
echo -n "Enter the Extreme Limit ="

Write a shell script / program to generate Fibonacci series up to a certain number.
Assignment No :- 1

<u>Assignment No :- 11</u>

<u>Program Statement:-</u>

Write a shell script / program to find the sum of N numbers taken as parameter input.

<u>Program Algorithm:-</u>

<u>Description:</u>

This is a program to find the sum of N numbers taken as parameter input. Here we take the values form the terminal and find their Sum.

<u>Steps:</u>

Step 1 If there are no argument passes then
          print "No Argument Passes."
          goto **Step 5**
    [end of If]

Step 2 s ← 0

Step 3 Loop starts for i in argument list
          s ← s+i
    [End of Loop]

Step 4 print "Sum of the Numbers =" s

Step 5 Exit from the program.

<u>Shell Script:-</u>

Write a shell script / program to find the sum of N numbers taken as parameter input.

```
if [ $# -eq 0 ]
then
        echo "No Arguments Passes."
        exit
fi
s=0
echo -n "Arguments Passes as the Parameter:- "
for i in $*
do
        echo -n "$i  "
```

```
        s=$(($s+$i))
done
echo -e "\nSum of that Numbers =$s"
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 16.sh
No Arguments Passes.
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 16.sh 1 2 3 4 5 6
Arguments Passes as the Parameter:- 1 2 3 4 5 6
Sum of that Numbers =21
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 16.sh 10 23 34 21 643 27
Arguments Passes as the Parameter:- 10 23 34 21 643 27
Sum of that Numbers =758

Assignment No :- 12

Program Statement:-

Write a shell script / program to rename a group of files.

Program Algorithm:-

Description:

This is a program to rename a group of files for example, rename all files where file name end with .HTM so that they end with .HTML.

Steps:

Step 1   print "Enter the Existing file Extension ="
       input efe
       print "Enter the Converting file Extension ="
       input cfe

Step 2   for i in `ls *efe`
       [ls command find the files and directories that in the current location now ls *efe menas those files or directories that ended with efe content]
              ch ← `echo "$i"| cut –d'.' –f 1`
              [cut –d'.' –f does the string divided into sub fields on basis of '.' delimiter and returns the fields which we want.]
              ch ← ch cfe
              mv i ch
              [mv this command move the first file to the second file]
       [end of Loop]

Step 3   print "Complete conversion."

Step 4   Exit from the program.

Shell Script:-

Write a shell script / program to rename a group of files for example, rename all files where file name end with .HTM so that they end with .HTML.

```
echo -n "Enter the Existing file Extension ="
read efe
echo -n "Enter the Converting file Extension ="
read cfe
for i in `ls *$efe`
do
```

```
        ch=`echo "$i"|cut -d'.' -f 1`
        ch=$ch$cfe
        mv $i $ch
done
echo "Complete conversion"
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ ls
10.sh 12.sh 14.sh 16.sh 18.sh   19.sh 20.sh 22.sh 24.sh 26   28.sh 2.sh   31.sh 3.sh
5.sh   7.sh   8b.sh 8d.sh a.txt
11.sh 13.sh 15.sh 17.sh 18student.txt 1.sh   21.sh 23.sh 25.sh 27.sh 29.sh 30.sh 32.sh
4.sh   6.sh   8a.sh 8c.sh 9.sh
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 17.sh
Enter the Existing file Extension =.sh
Enter the Converting file Extension =.c
Complete conversion
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ ls
10.c 12.c 14.c 16.c 18.c   19.c 20.c 22.c 24.c 26   28.c 2.c   31.c 3.c 5.c 7.c   8b.c
8d.c a.txt
11.c 13.c 15.c 17.c 18student.txt 1.c   21.c 23.c 25.c 27.c 29.c 30.c 32.c 4.c 6.c 8a.c
8c.c 9.c
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 17.sh
Enter the Existing file Extension =.c
Enter the Converting file Extension =.sh
Complete conversion
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ ls
10.sh 12.sh 14.sh 16.sh 18.sh   19.sh 20.sh 22.sh 24.sh 26   28.sh 2.sh   31.sh 3.sh
5.sh   7.sh   8b.sh 8d.sh a.txt
11.sh 13.sh 15.sh 17.sh 18student.txt 1.sh   21.sh 23.sh 25.sh 27.sh 29.sh 30.sh 32.sh
4.sh   6.sh   8a.sh 8c.sh 9.sh

Assignment No :- 13

Program Statement:-

Write a shell script to the division awarded to each student.

Program Algorithm:-

Description:

This is a program to the division awarded to each student. The students are awarded division as per following rules:- (1) Percentage above or equal to 60-1st division. (2) Percentage between 50 to 59 - 2nd division. (3) Percentage between 40 to 49 - 3rd division. (4) percentage lesa than 40 -FAIL.

Steps:

Step 1 print "Data In Student File :-"
       print the file 18student.txt
       print "Students Divisions :-"

Step 2 open the file 18student.txt in output mode
       input l
       [read l means that it read every line from the file that opens in output mode.]

Step 3 Loop continue when read l true
       [read l means that it read every line from the file that opens in output mode.]
            set l
            nm ← $1
            p ← ($2+$3+$4+$5)/4
            print nm

Step 3.1   if p greater than or equal to 60 then
                print "1st division"
            [end of if]

Step 3.2   else
                if p greater than or equal to 50 then
                    print "2nd division"

Step 3.3   else
                   if p greater than or equal to 40 then
                       print "3rd division"

Step 3.4   else
                       print "Fail ."
                  [end of if]
               [end of if]
           [end of if]

Step 4 Exit from the program.

Shell Script:-

A student examination files containing the following format:
Name sub1 sub2 sub3 sub4
The students are awarded division as per following rules :
i) Percentage above or equal to 60-1st division.
ii) Percentage between 50 to 59 - 2nd division.
iii) Percentage between 40 to 49 - 3rd division.
iv) percentage lesa than 40 -FAIL.
Write a shell script to the division awarded to each student.

```
echo "Data In Student File :-"
cat 18student.txt
echo
echo "Students Divisions :-"
exec<18student.txt
read l
while read l
do
        set $l
        nm=$1
        p=`echo "scale=2;($2+$3+$4+$5)/4"|bc`
        echo -n $nm"     "
        if [ 1 -eq `echo "$p>=60"|bc` ]
        then
                echo "1st division."
        elif [ 1 -eq `echo "$p>=50"|bc` ]
        then
                echo "2nd division."
        elif [ 1 -eq `echo "$p>=40"|bc` ]
        then
                echo "3rd division."
        else
                echo "Fail."
        fi
done
```

Output:-

```
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 18.sh
Data In Student File :-
NAME SUB_1(Marks) SUB_2(Marks) SUB_3(Marks) SUB_4(Marks)
Susovan 30 30 40 100
Shuvendu 30 100 40 30
Sourav 100 30 30 40
Sanada 80 80 80 80
Priya 80 80 80 80
Kanisha 80 80 80 80
Bikram 30 30 40 10
```

Students Divisions :-
Susovan   2nd division.
Shuvendu   2nd division.
Sourav   2nd division.
Sanada   1st division.
Priya   1st division.
Kanisha   1st division.
Bikram   Fail.

Assignment No :- 14

Program Statement:-

Write a shell script to find sort of n numbers of an array in ascending order.

Program Algorithm:-

Description:

This is a program to find sort of n numbers of an array in ascending order. Here we take total no of numbers and the numbers to sort them is ascending order.

Steps:

Step 1   print "Enter the Size of Array ="
         input n
         print "Enter the Elements :-"
         input a[]
         [read all elements one by one]
         print a[]
         i ← 0

Step 2   Loop continue when i less than n true
             j ← i+1
Step 2.1   Loop continue when j less than n true
                     if a[i] greater than a[j] then
                             temp ← a[i]
                             a[i] ← a[j]
                             a[j] ← temp
                     [end of if]
                     j ← j+1
                 [end of Loop]
                 i ← i+1
         [end of Loop]

Step 3   print "Elements After Sorting :-"
         print a[]

Step 4   Exit from the program.

Shell Script:-

Write a shell script to find sort of n numbers of an array in ascending order.

echo -n "Enter the Size of Array ="

```
read n
echo "Enter the Elements :- "
for ((i=0;i<n;i++))
do
        echo -n "A[$i] ="
        read a[$i]
done
echo "Elements Are :-"
for ((i=0;i<n;i++))
do
        echo -n "${a[$i]} "
done
for ((i=0;i<n;i++))
do
        for ((j=i+1;j<n;j++))
        do
                if [ ${a[$i]} -gt ${a[$j]} ]
                then
                        temp=${a[$i]}
                        a[$i]=${a[$j]}
                        a[$j]=$temp
                fi
        done
done
echo -e "\nElements After Sorting:-"
for ((i=0;i<n;i++))
do
        echo -n "${a[$i]} "
done
echo
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 23.sh
Enter the Size of Array =4
Enter the Elements :-
A[0] =1
A[1] =9
A[2] =2
A[3] =6
Elements Are :-
1 9 2 6
Elements After Sorting:-
1 2 6 9
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 23.sh
Enter the Size of Array =9
Enter the Elements :-
A[0] =9
A[1] =3
A[2] =1

A[3] =5
A[4] =34
A[5] =0
A[6] =23
A[7] =45
A[8] =82
Elements Are :-
9 3 1 5 34 0 23 45 82
Elements After Sorting:-
0 1 3 5 9 23 34 45 82
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 23.sh
Enter the Size of Array =8
Enter the Elements :-
A[0] =8
A[1] =7
A[2] =6
A[3] =5
A[4] =4
A[5] =3
A[6] =2
A[7] =1
Elements Are :-
8 7 6 5 4 3 2 1
Elements After Sorting:-
1 2 3 4 5 6 7 8

Assignment No :- 15

Program Statement:-

Write a shell script to find a factorial of a number using recursive process.

Program Algorithm:-

Description:

This is a program to find a factorial of a number using recursive process.

Steps:

Step 1 fac() function

Step 1.1   if n equal to 0 then
                        goto **Step 2**
                  [end of if]
Step 1.2   f ← f*n
                  n ← n-1
Step 1.3   **call fac function**

Step 2 print "Enter a Number ="
        input n
        f ← 1
        print "Factorial of n is ="

step 3 call fac
        print f

Step 4 Exit from the program.

Shell Script:-

Write a shell script to find a factorial of a number using recursive process.

```
fac()
{
        if [ $n -eq 0 ]
        then
                return
        fi
        f=$(($f*$n))
        n=$(($n-1))
        fac
```

```
}
```

echo -n "Enter the Number ="
read n
f=1
echo -n "Factorial of $n is"
fac
echo -n " $f"
echo

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 27.sh
Enter the Number =4
Factorial of 4 is 24
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 27.sh
Enter the Number =10
Factorial of 10 is 3628800
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 27.sh
Enter the Number =6
Factorial of 6 is 720
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 27.sh
Enter the Number =12
Factorial of 12 is 479001600

Assignment No :- 16

Program Statement:-

Write a shell script to find the no. of word that containing vowel in text file.

Program Algorithm:-

Description:

This is a program to find the no. of word that containing vowel in text file.

Steps:

Step 1 print "Enter the File name ="
input fn
str ← ""

Step 2 open the file fn in output mode

Step 3 Loop continue when read l true
[read l means that it read every line from the file that opens in output mode.]
Step 3.1   for i in l
ch ← `echo "$i"|grep –i [aeiou]`
[here grep -i finds that string is present into that fie or not and if not exist then returns it otherwise return nothing.]
if ch not equals to nothing then
str ← ch"\n"str
[end of if]
[end of Loop]
[End of Loop]

Step 4 ch ← `echo –e "$str"|wc -l `
 [wc –l returns the total line number of that file passes throw the parameter]

Step 5 ch ← `echo "$ch"|cut -d' ' -f 1`
 [cut –d'.' –f does the string divided into sub fields on basis of ' ' delimiter and   returns the fields which we want.]
 print "The number of words that have vowels is " ch

Step 6 Exit from the program.

Shell Script:-

Write a shell script to find the no. of word that containing vowel in text file.

```
echo -n "Enter the File Name ="
read fn
str=""
exec<$fn
while read l
do
        for i in $l
        do
                ch=`echo "$i"|grep -i [aeiou]`
                if [ "$ch" != "" ]
                then
                        str=$ch"\n"$str
                fi
        done
done
ch=`echo –e "$str"|wc -l `
ch=`echo "$ch"|cut -d' ' -f 1`
echo "In File '$fn' the number of words that containing vowels is $ch"
```

Output:-

susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 31.sh
Enter the File Name =4.sh
In File '4.sh' the number of words that containing vowels is 28
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 31.sh
Enter the File Name =5.sh
In File '5.sh' the number of words that containing vowels is 51
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 31.sh
Enter the File Name =a.txt
In File 'a.txt' the number of words that containing vowels is 756
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 31.sh
Enter the File Name =6.sh
In File '6.sh' the number of words that containing vowels is 56
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 31.sh
Enter the File Name =17.sh
In File '17.sh' the number of words that containing vowels is 54

Assignment No :- 17

Program Statement:-

Write a shell script to find a large name to its shorted representation.

Program Algorithm:-

Description:

This is a program to find a large name to its shorted representation.

Steps:

Step 1 print "Enter a Name ="
input n
l ← `echo "$n" | wc -w`
[wc –w returns the word count from the file that passes throw by parameter.]
l ← numeric vlue of l
str ← ""
i ← 1

Step 2 Loop continue when i less than l true
ch ← `echo "$n"|cut –d' ' –f i`
[cut –d'.' –f does the string divided into sub fields on basis of ' ' delimiter and   returns the fields which we want.]
ch ← `echo "$ch"|cut -c 1`
[cut -c cut a character of the string from which location that passes into it and returns that character.]
str ← str ch "."
i ← i+1
[end of Loop]

Step 3 ch ← `echo $n|cut -d' ' -f $i`
[cut –d'.' –f does the string divided into sub fields on basis of ' ' delimiter and   returns the fields which we want.]
str ← str ch
print "Short from of the name = " str

Step 4 Exit from the program.

Shell Script:-

Write a shell script to find a large name to its shorted representation.

echo -n "Enter a Name ="

```
read n
l=`echo "$n"|wc -w`
l=`expr $l`
str=""
for ((i=1;i<l;i++))
do
        ch=`echo $n|cut -d' ' -f $i`
        ch=`echo "$ch"|cut -c 1`
        str=$str$ch"."
done
ch=`echo $n|cut -d' ' -f $i`
str=$str$ch
echo "Short from of the name =$str"
```

Output:-

```
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 32.sh
Enter a Name =Susovan Das
Short from of the name =S.Das
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 32.sh
Enter a Name =Sapen Kumar Dutta
Short from of the name =S.K.Dutta
susovan@susovan-Inspiron-3542:~/sh_programs/Assignment$ sh 32.sh
Enter a Name =Aritra Roy
Short from of the name =A.Roy
```