

1.Insert Data Into MySQL Using MySQLi

Example (MySQLi Object-oriented)

```
<?php
$servername = "localhost";
$username = "root";
$password = "";
$dbname = "test";          //database name

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);

// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

$sql = "INSERT INTO Teacher (firstname, lastname, email) VALUES ('John', 'Doe', 'john@example.com')";

if ($conn->query($sql) === TRUE) {
    echo "New record created successfully";
} else {
    echo "Error: " . $sql . "<br>" . $conn->error;
}

$conn->close();
?>
```

Example (MySQLi Procedural)

```
<?php
$servername = "localhost";
$username = "root";
$password = "";
$dbname = "test";

// Create connection
$conn = mysqli_connect($servername, $username, $password, $dbname);
// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}
```

```

$sql = "INSERT INTO MyGuests (firstname, lastname, email) VALUES ('John', 'Doe', 'john@example.com')";

if (mysqli_query($conn, $sql)) {
    echo "New record created successfully";
} else {
    echo "Error: " . $sql . "<br>" . mysqli_error($conn);
}

mysqli_close($conn);
?>

```

Example (MySQLi with Prepared Statements)

```

<?php
$servername = "localhost";
$username = "root";
$password = "";
$dbname = "test";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);

// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

// prepare and bind
$stmt = $conn->prepare("INSERT INTO MyGuests (firstname, lastname, email) VALUES (?, ?, ?)");
$stmt->bind_param("sss", $firstname, $lastname, $email);

// set parameters and execute
$firstname = "John";
$lastname = "Doe";
$email = "john@example.com";
$stmt->execute();

$firstname = "Mary";
$lastname = "Moe";
$email = "mary@example.com";
$stmt->execute();

$firstname = "Julie";
$lastname = "Dooley";
$email = "julie@example.com";
$stmt->execute();

echo "New records created successfully";

$stmt->close();

```

```
$conn->close();  
?>
```

Code lines to explain from the example above:

```
"INSERT INTO MyGuests (firstname, lastname, email) VALUES (?, ?, ?)"
```

In our SQL, we insert a question mark (?) where we want to substitute in an integer, string, double or blob value.

Then, have a look at the bind_param() function:

```
$stmt->bind_param("sss", $firstname, $lastname, $email);
```

This function binds the parameters to the SQL query and tells the database what the parameters are. The "sss" argument lists the types of data that the parameters are. The s character tells mysql that the parameter is a string.

The argument may be one of four types:

- i - integer
- d - double
- s - string
- b - BLOB

2. Select Data With MySQLi

Example (MySQLi Object-oriented)

```
<?php  
$servername = "localhost";  
$username = "username";  
$password = "password";  
$dbname = "myDB";  
  
// Create connection  
$conn = new mysqli($servername, $username, $password, $dbname);  
// Check connection  
if ($conn->connect_error) {  
    die("Connection failed: " . $conn->connect_error);  
}  
  
$sql = "SELECT id, firstname, lastname FROM MyGuests";  
$result = $conn->query($sql);  
  
if ($result->num_rows > 0) {  
    // output data of each row  
    while($row = $result->fetch_assoc()) {  
        echo "id: " . $row["id"]. " - Name: " . $row["firstname"]. " " .
```

```

$row["lastname"]. "<br>";
    }
} else {
    echo "0 results";
}
$conn->close();
?>

```

Code lines to explain from the example above:

First, we set up an SQL query that selects the id, firstname and lastname columns from the MyGuests table. The next line of code runs the query and puts the resulting data into a variable called \$result.

Then, the function `num_rows()` checks if there are more than zero rows returned.

If there are more than zero rows returned, the function `fetch_assoc()` puts all the results into an associative array that we can loop through. The `while()` loop loops through the result set and outputs the data from the id, firstname and lastname columns.

Example (MySQLi Procedural)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = mysqli_connect($servername, $username, $password, $dbname);
// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

$sql = "SELECT id, firstname, lastname FROM MyGuests";
$result = mysqli_query($conn, $sql);

if (mysqli_num_rows($result) > 0) {
    // output data of each row
    while($row = mysqli_fetch_assoc($result)) {
        echo "id: " . $row["id"]. " - Name: " . $row["firstname"]. " " . $row["lastname"]. "<br>";
    }
} else {
    echo "0 results";
}

mysqli_close($conn);
?>

```

Example (MySQLi Object-oriented) To be displayed in HTML Page

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);
// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

$sql = "SELECT id, firstname, lastname FROM MyGuests";
$result = $conn->query($sql);

if ($result->num_rows > 0) {
    echo "<table><tr><th>ID</th><th>Name</th></tr>";
    // output data of each row
    while($row = $result->fetch_assoc())
    {
        echo "<tr><td>".$row["id"]."</td><td>".$row["firstname"].".".$row["lastname"]."</td></tr>";
    }
    echo "</table>";
} else {
    echo "0 results";
}
$conn->close();
?>
```

3. Update Data In a MySQL Table Using MySQLi

Example (MySQLi Object-oriented)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);
// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}
```

```

}

$sql = "UPDATE MyGuests SET lastname='Doe' WHERE id=2";

if ($conn->query($sql) === TRUE) {
    echo "Record updated successfully";
} else {
    echo "Error updating record: " . $conn->error;
}

$conn->close();
?>

```

Example (MySQLi Procedural)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = mysqli_connect($servername, $username, $password, $dbname);
// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

$sql = "UPDATE MyGuests SET lastname='Doe' WHERE id=2";

if (mysqli_query($conn, $sql)) {
    echo "Record updated successfully";
} else {
    echo "Error updating record: " . mysqli_error($conn);
}

mysqli_close($conn);
?>

```

4.Delete Data From a MySQL Table Using MySQLi

Example (MySQLi Object-oriented)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

```

```

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);
// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

// sql to delete a record
$sql = "DELETE FROM MyGuests WHERE id=3";

if ($conn->query($sql) === TRUE) {
    echo "Record deleted successfully";
} else {
    echo "Error deleting record: " . $conn->error;
}

$conn->close();
?>

```

Example (MySQLi Procedural)

```

<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = mysqli_connect($servername, $username, $password, $dbname);
// Check connection
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

// sql to delete a record
$sql = "DELETE FROM MyGuests WHERE id=3";

if (mysqli_query($conn, $sql)) {
    echo "Record deleted successfully";
} else {
    echo "Error deleting record: " . mysqli_error($conn);
}

mysqli_close($conn);
?>

```