Two-column and Footnote Fixture

Left column

Routing policy should have one authority. A parser should preserve reading order. Column marker: LEFT-COLUMN-END.

Routing policy should have one authority. A parser should preserve reading order. Column marker: LEFT-COLUMN-END.

Routing policy should have one authority. A parser should preserve reading order. Column marker: LEFT-COLUMN-END.

Routing policy should have one authority. A parser should preserve reading order. Column marker: LEFT-COLUMN-END.

Routing policy should have one authority. A parser should preserve reading order. Column marker: LEFT-COLUMN-END.

Routing policy should have one authority. A parser should preserve reading order. Column marker: LEFT-COLUMN-END.

Routing policy should have one authority. A parser should preserve reading order. Column marker: LEFT-COLUMN-END.

Routing policy should have one authority. A parser should preserve reading order. Column marker: LEFT-COLUMN-END.

Right column

Synchronization propagates deletions. Independent backups remain necessary.[1] Column marker: RIGHT-COLUMN-END.

Synchronization propagates deletions. Independent backups remain necessary.[1] Column marker: RIGHT-COLUMN-END.

Synchronization propagates deletions. Independent backups remain necessary.[1] Column marker: RIGHT-COLUMN-END.

Synchronization propagates deletions. Independent backups remain necessary.[1] Column marker: RIGHT-COLUMN-END.

Synchronization propagates deletions. Independent backups remain necessary.[1] Column marker: RIGHT-COLUMN-END.

Synchronization propagates deletions. Independent backups remain necessary.[1] Column marker: RIGHT-COLUMN-END.

Synchronization propagates deletions. Independent backups remain necessary.[1] Column marker: RIGHT-COLUMN-END.

Synchronization propagates deletions. Independent backups remain necessary.[1] Column marker: RIGHT-COLUMN-END.

[1] A synchronization replica is not a historical recovery copy.