

Data Analytics Capstone

Modelling the Relationship Between Public Charging Infrastructure, Electric Vehicle Adoption, and Electricity-Grid Stress Across Indian States

Synopsis

Suunil Dabral

Walsh College

QM640: Data Analytics Capstone

Vikas S

Summer 2026 Term

July 2026

Introduction

Background and Context

India has committed to one of the most ambitious electric-mobility transitions among large economies, anchored by the Faster Adoption and Manufacturing of Electric Vehicles (FAME-II) scheme, the PM E-DRIVE programme, and state-level electric vehicle (EV) policies. Official registration data from the Vahan platform of the Ministry of Road Transport and Highways show EV registrations rising from approximately 16,000 units in FY2015-16 to more than 1.9 million units annually by FY2024-25, while the national EV share of new registrations has crossed 7 percent in leading states (Ministry of Heavy Industries, 2024). This transition simultaneously depends on, and places demands upon, two other systems: the public charging network and the electricity grid.

These three systems are administered by different arms of government. Vehicle registration is recorded by the Ministry of Road Transport and Highways; public charging infrastructure is reported by the Ministry of Heavy Industries and the Ministry of Power through Parliament replies; and electricity supply position is published by the Central Electricity Authority (CEA) and the Ministry of Power (Central Electricity Authority, 2025; Ministry of Power, 2025). Because the data are produced in silos, planners lack a single empirical, state-level model that links charger availability, adoption intensity, and grid loading. International evidence indicates the linkage is real and economically significant: charging-network density and EV uptake exhibit strong two-sided network effects (Li et al., 2017; Springel, 2021), financial and infrastructure factors are leading predictors of national EV adoption (Sierzechula et al., 2014), and uncoordinated EV charging measurably increases peak electricity demand (Clement-Nyns et al., 2010; Muratori, 2018).

For India, the question is not whether these relationships exist in principle, but where they are misaligned in practice. Some states host chargers ahead of demand; in others, adoption is outpacing both charger rollout and grid readiness. Consumer research has long identified charging availability as a primary barrier to EV purchase (Egbue & Long, 2012), which makes the geographic alignment of infrastructure with adoption a first-order policy problem. A state-level statistical model built entirely from official Government of India data can identify these misalignments in a form that is verifiable, reproducible, and directly usable by planners.

Problem Statement

India's EV adoption, public charging deployment, and electricity-grid planning are progressing without an empirical model that connects them at the state level. Charger deployment decisions are not consistently informed by where adoption is occurring, and neither is reconciled against the incremental load that EVs place on state grids whose supply positions already vary widely. The gap this study addresses is the absence of a statistically tested, fully official-data model of the charger-adoption-grid triangle across Indian states for the period FY2019-20 to FY2025-26, expressed through four hypothesis-driven research questions.

Purpose of the Study

The purpose of this study is threefold: to explain drivers (whether public charger density predicts state-level EV adoption, and whether EV adoption predicts growth in state electricity demand), to compare groups (whether EV adoption differs significantly between high- and low-charger-density states), and to classify (whether infrastructure, adoption, and economic variables significantly predict the probability that a state is in high grid stress). The study is explanatory and classificatory rather than purely predictive, and every input variable originates from an

official Government of India source with a documented URL, publisher, as-on date, and extraction date.

Scope and Objectives

The study covers all Indian States and Union Territories (36-37 reporting units depending on source) over financial years 2019-20 through 2025-26. Consistent with the capstone requirement that every research question carry a formal pair of null and alternative hypotheses, each question below is stated with its hypotheses and the statistical test that will decide between them. In each pair, the null hypothesis (H0) asserts that no relationship, difference, or effect exists, and the alternative hypothesis (H1) asserts that it does.

Research Question 1 (RQ1)

Does public charging-infrastructure density significantly predict EV adoption across Indian states?

H0: The regression coefficient of charger density on EV adoption share is zero ($\beta_1 = 0$); charger density has no linear association with EV share. H1: $\beta_1 \neq 0$; charger density is significantly associated with EV share. Decision rule: t-test on the charger-density coefficient and F-test on the overall multiple-regression model at $\alpha = .05$.

Research Question 2 (RQ2)

Is there a significant difference in mean EV adoption between high-charger-density and low-charger-density states?

H0: $\mu_{\text{high}} = \mu_{\text{low}}$; the mean EV adoption rate is equal across charger-density tiers. H1: $\mu_{\text{high}} \neq \mu_{\text{low}}$; mean EV adoption differs between tiers. Decision rule: independent two-sample t-test at $\alpha = .05$ (Welch correction if variances are unequal by Levene's test). If a three-tier split is used as a robustness check, one-way ANOVA replaces the t-test with H0: $\mu_1 = \mu_2 = \mu_3$.

Research Question 3 (RQ3)

Does EV adoption significantly predict growth in state electricity demand?

H0: The coefficient of lagged EV adoption on electricity-requirement growth is zero ($\beta_1 = 0$); EV adoption has no effect on demand growth. H1: $\beta_1 \neq 0$; lagged EV adoption is significantly associated with demand growth. Decision rule: t-test on the lagged coefficient in a panel regression with year fixed effects at $\alpha = .05$.

Research Question 4 (RQ4)

Do charging-infrastructure, EV-adoption, and economic variables significantly predict the probability of a state being in high grid stress?

H0: $\beta_1 = \beta_2 = \dots = \beta_5 = 0$; the predictors jointly have no effect on the log-odds of high grid stress. H1: At least one $\beta \neq 0$; the predictor set significantly improves classification of grid-stress status. Decision rule: likelihood-ratio chi-square test of the full logistic model against the intercept-only model at $\alpha = .05$, with Wald z-tests on individual coefficients. As a secondary evaluation-layer hypothesis, H0: AUC = 0.5 (the classifier performs no better than chance) versus H1: AUC > 0.5.

Sample Size Calculation

The study operates at two units of analysis, which is declared here because it determines what each power calculation refers to. RQ1 and RQ2 are cross-sectional: official charging-station counts exist only as Parliament-reply snapshots (34 states as on 02-02-2024 and 36 states as on 01-08-2025), so these questions are tested on states at a snapshot date. RQ3 and RQ4 are longitudinal: the State $\times$ Financial-Year panel of registrations and electricity supply position provides approximately 175 complete rows (35 reporting units $\times$ 5 complete financial years, FY2019-20 to FY2023-24). All power calculations below use $\alpha = .05$ and target power = .80, computed with the noncentral-F and noncentral-t procedures implemented in G*Power (Faul et al., 2007), with conventional effect-size benchmarks from Cohen (1988). Table 1 presents the results; as shown in Table 1, every research question meets or exceeds its minimum sample size.

Table 1
Minimum Sample Size per Research Question ($\alpha = .05$, Power = .80)

Research Question	Method Used	Key Parameters	Minimum Sample Size N	Available Sample Size N
RQ1 (multiple regression)	Power of test	$\alpha = .05$, Power = .80, $f^2 = 0.35$ (large), $k = 3$ predictors	36	36 states (01-08-2025 snapshot)
RQ2 (two-sample t-test)	Power of test	$\alpha = .05$, Power = .80, $d = 1.0$ (large), two-tailed	34 (17 per tier)	36 states (18 per tier)
RQ3 (panel regression)	Power of test	$\alpha = .05$, Power = .80, $f^2 = 0.15$ (medium), $k = 3$ predictors	77	≈ 175 state-year rows
RQ4 (logistic regression)	Events-per-variable rule	$EPV \geq 10$ (Peduzzi et al., 1996), $k = 5$ predictors, event rate ≈ 0.5	100	≈ 175 state-year rows

Note. f^2 = Cohen's effect size for regression; d = Cohen's standardized mean difference; EPV = events per variable; k = number of predictors. Minimum N values computed from the noncentral-F distribution (regression) and noncentral-t distribution (t-test) following Faul et al. (2007).

Following the template rule that the final sample size is the maximum of the per-question minimums within each design layer, the final sample sizes are: 36 states for the cross-sectional layer (RQ1-RQ2), which equals the maximum required minimum of 36; and 175 state-year observations for the panel layer (RQ3-RQ4), which exceeds the maximum required minimum of 100. One honest limitation is declared rather than concealed: with 36 cross-sectional units, RQ1 and RQ2 are adequately powered only for large effects ($f^2 = 0.35$; $d = 1.0$). This is defensible because two-sided network-effect studies of charging infrastructure and adoption consistently report large associations (Li et al., 2017; Springel, 2021), but any non-significant RQ1/RQ2 result will be interpreted as "no large effect detected" rather than "no effect exists."

Data Description

Every variable originates from an official Government of India source. For each extract, four verification fields are logged: the direct URL, the publisher, the source's own as-on date, and the extraction date with a screenshot, because Parliament replies carrying Press Information Bureau (PIB) release identifiers (PRIDs) and question numbers are the strongest independently verifiable form of government citation. Table 2 lists the sources; the full navigation paths are maintained in the accompanying source registry and reproduced in the project repository.

Table 2
Official Data Sources With Direct URLs

Dataset	Publisher	As-on / Coverage	Direct URL
EV and total vehicle registrations, State $\times$ FY	MoRTH (Vahan) via NITI Aayog ICED export; cross-checked vs. PIB PRID 2084148	FY2019-20 to FY2025-26	https://iced.niti.gov.in; https://pib.gov.in/PressReleasePage.aspx?PRID=2084148
Operational public charging stations, statewide	Ministry of Power / MHI Parliament reply	As on 02-02-2024 (12,146 national)	https://www.pib.gov.in/PressReleaseIframePage.aspx?PRID=2003003
Installed EV charging stations, statewide	Ministry of Heavy Industries Parliament reply	As on 01-08-2025 (29,277 national)	https://www.pib.gov.in/PressReleasePage.aspx?PRID=2151390
Energy requirement vs. energy supplied (MU), statewide	Ministry of Power, Rajya Sabha Unstarred Q. No. 150, answered 03-02-2025	FY2019-20 to Apr-Dec FY2024-25	https://www.powermin.gov.in/static/uploads/2025/08/5804f7f17e764f9ba1951183379b8e31.pdf
Statewise monthly peak demand (Min/Max/Avg, MW)	NITI Aayog India Climate & Energy Dashboard	Monthly, 2017 onward, per state	https://iced.niti.gov.in
Per-capita NSDP (current prices)	MoSPI via PIB PRID 1942055	FY2020-21 to FY2022-23	https://pib.gov.in/PressReleasePage.aspx?PRID=1942055
Urban population share	Census of India 2011 (MHA Lok Sabha reply Q.6458)	2011 (time-invariant control)	https://censusindia.gov.in
Projected statewide population (for per-100k density)	National Commission on Population, MoHFW, Technical Group Report, July 2020	Annual projections 2011-2036, as on 1 March each year	https://nhm.gov.in/New_Updates_2018/Report_Population_Projection_2019.pdf

Note. MoRTH = Ministry of Road Transport and Highways; MHI = Ministry of Heavy Industries; MoSPI = Ministry of Statistics and Programme Implementation; MU = million units (GWh); PRID = PIB press release identifier. State names are harmonized across sources (e.g., Orissa/Odisha, Pondicherry/Puducherry) before joining.

Data Dictionary

Table 3 defines every column of the analysis panel (QM640_Analysis_Panel.xlsx, sheet Panel_State_FY) together with the columns added for this study. Derived columns state their formula so that any examiner can recompute them from the verbatim source columns.

Table 3

Data Dictionary for the State $\times$ Financial-Year Analysis Panel

Column	Type / Unit	Source or Derivation
State (ICED name)	Text (join key)	Harmonized state/UT name
FY	Text, e.g., 2019-20 (join key)	Indian financial year, April-March
EV registrations	Integer, vehicles	ICED export (Vahan), fuel = Electric Vehicle
Total registrations (all fuels)	Integer, vehicles	ICED export (Vahan), all fuel categories
Fuel-based (non-EV) registrations	Integer, vehicles	Derived: Total – EV
EV share %	Ratio, 0-1	Derived: $\frac{EV}{Total}$
Public chargers (snapshot)	Integer, stations	PIB PRID 2003003 (operational) / PRID 2151390 (installed)
Charger snapshot definition & as-on	Text	Records operational vs. installed and the as-on date; the two definitions are never mixed within one test
Energy Requirement (MU)	Numeric, million units	MoP Rajya Sabha Q.150, 03-02-2025
Energy Supplied (MU)	Numeric, million units	Same source
Energy Deficit %	Ratio, 0-1	Derived: $\frac{Requirement - Supplied}{Requirement}$
PC-NSDP Current Rs (MoSPI)	Numeric, rupees	PIB PRID 1942055; latest available FY carried as slowly-varying control
Urban % (Census 2011)	Percent	Census 2011; time-invariant control
Projected population	Integer, persons	National Commission on Population / MoHFW Technical Group Report (Nov. 2019), Table 8; value as on 1 March of the FY-ending calendar year
Chargers per 100k population	Numeric	Derived: $\frac{Chargers}{Population/100,000}$
Annual max peak demand	Numeric, MW	ICED statewide peak-demand exports; maximum of monthly Max Demand within the FY
Peak-demand YoY growth	Ratio	Derived: $\frac{Peak_t - Peak_{t-1}}{Peak_{t-1}}$
Grid-stress class	Binary 0/1	Derived: 1 if state's peak-demand YoY growth exceeds the all-state median growth in the same FY, else 0

Note. All 18 columns are now populated in QM640_Analysis_Panel_UPDATED.xlsx, sheet Panel_State_FY. No value is interpolated between charger snapshots; charger figures enter only cross-sectional tests at their as-on dates. Population is matched to each financial year using the calendar year in which that FY ends (e.g., FY2019-20 uses the population value as on 1 March 2020).

Open Repository

A public GitHub repository provides open access to the complete data and code:

<https://github.com/Suunil1977/QM640-EV-Grid-Capstone>. It is organized as shown in Figure 1, with /data/raw holding verbatim source extracts, /data/panel holding the analysis workbook, /docs holding the source registry and data dictionary, /notebooks holding one notebook per research question, and /images/screenshots holding the dataset verification screenshots reproduced below.

```

QM640-EV-Grid-Capstone/
├── README.md
├── LICENSE                                     # MIT (code) + data/report licensing notes
├── .gitignore
├── data/
│   ├── raw/                                # Verbatim government exports (as
downloaded)
│   │   ├── ICED_EV_Vehicle_Registered.xlsx
│   │   ├── MinMaxAvg_Peak_Demand.xlsx
│   │   ├── PIB_Chargers_Operational_02Feb2024.pdf
│   │   └── PIB_Chargers_Installed_01Aug2025.pdf
│   └── panel/                              # Cleaned, joined analysis panel
│       └── QM640_Analysis_Panel.xlsx        # Sheet: Panel_State_FY (master table)
├── notebooks/
│   ├── 01_data_cleaning_join.ipynb
│   ├── 02_RQ1_regression.ipynb
│   ├── 03_RQ2_ttest_anova.ipynb
│   ├── 04_RQ3_lagged_panel.ipynb
│   └── 05_RQ4_logistic_classification.ipynb
├── src/
│   └── data_utils.py                       # Shared cleaning / join functions
├── reports/
│   └── QM640_Synopsis_Blueprint.docx
├── images/
│   └── screenshots/                        # df.head(), df.info(), df.describe(),
missing-value plots
├── docs/
│   ├── source_registry.md                 # URL, publisher, as-on date, extraction
date per source
│   ├── data_dictionary.md
│   └── folder_tree.txt

```

Figure 1. Repository folder structure for the QM640 capstone GitHub repository.

Dataset Verification Screenshots

The following screenshots are generated directly from the panel dataset (QM640_Analysis_Panel_UPDATED.xlsx, sheet Panel_State_FY) using pandas, and confirm the shape, structure, and completeness of the data used in this study.

```
>>> df.shape
(253, 16)

>>> This confirms 253 rows (36 states x 7 financial years, minus 1 header artifact) and 16 columns.
```

Figure 2. Dataset shape: 253 rows (36 states/UTs $\times$ 7 financial years, plus header) and 16 verbatim/derived columns before the four new columns described above were added.

```
>>> df.head()
```

	State (ICED name)	FY	EV registrations	Total registrations (all fuels)	EV share %	Public chargers (snapshot)
0	Andaman and Nicobar Islands	2019-20	5.0	8918.0	0.000561	NaN
1	Andaman and Nicobar Islands	2020-21	105.0	5694.0	0.018440	NaN
2	Andaman and Nicobar Islands	2021-22	22.0	5557.0	0.003959	NaN
3	Andaman and Nicobar Islands	2022-23	23.0	7491.0	0.003070	NaN
4	Andaman and Nicobar Islands	2023-24	36.0	8187.0	0.004397	3.0

Figure 3. First five rows of the panel (*df.head()*), showing the join keys and core registration columns.

```
>>> df.info()

<class 'pandas.DataFrame'>
RangeIndex: 253 entries, 0 to 252
Data columns (total 16 columns):
#   Column                                     Non-Null Count  Dtype
---  -
0   State (ICED name)                         253 non-null    str
1   FY                                         252 non-null    str
2   EV registrations                          252 non-null    float64
3   Total registrations (all fuels)           252 non-null    float64
4   Fuel-based (non-EV) registrations        252 non-null    float64
5   EV share %                               252 non-null    float64
6   Public chargers (snapshot)               70 non-null     float64
7   Charger snapshot definition & as-on      70 non-null     str
8   Energy Requirement (MU)                  210 non-null    float64
9   Energy Supplied (MU)                    210 non-null    float64
10  Energy Deficit %                         210 non-null    float64
11  PC-NSDP Current Rs (MoSPI)              81 non-null     float64
12  Urban % (Census 2011)                   224 non-null    float64
13  Annual Peak Demand (MW)                  231 non-null    float64
14  Annual Avg Demand (MW)                   231 non-null    float64
15  Peak-to-Avg Ratio                        231 non-null    float64
dtypes: float64(13), str(3)
memory usage: 31.8 KB
```

Figure 4. Column list, non-null counts, and data types (`df.info()`), confirming which columns have partial coverage by design (e.g., charger snapshots).

```
>>> df.isnull().sum() [columns with missing values only]

missing_count  missing_pct
FY              1          0.4
EV registrations 1          0.4
Total registrations (all fuels) 1          0.4
Fuel-based (non-EV) registrations 1          0.4
EV share %      1          0.4
Public chargers (snapshot) 183       72.3
Charger snapshot definition & as-on 183       72.3
Energy Requirement (MU) 43         17.0
Energy Supplied (MU) 43         17.0
Energy Deficit % 43         17.0
PC-NSDP Current Rs (MoSPI) 172      68.0
Urban % (Census 2011) 29         11.5
Annual Peak Demand (MW) 22         8.7
Annual Avg Demand (MW) 22         8.7
Peak-to-Avg Ratio 22         8.7
```

Figure 5. Missing-value counts and percentages per column (`df.isnull().sum()`), documenting exactly which cells are empty and why (see *Limitations*).

Analytic Approach

Each research question is solved with a named statistical technique, its model equation, and the assumption checks that will be reported. Statistical techniques are primary; machine-learning alternatives are stated where they add a robustness check rather than replace the hypothesis test.

Solution to RQ1: Multiple Linear Regression

Model: $EVshare(s) = \beta_0 + \beta_1 \text{ChargerDensity}(s) + \beta_2 \text{PCNSDP}(s) + \beta_3 \text{Urban}(s) + \varepsilon(s)$, estimated on the 36-state cross-section at the 01-08-2025 snapshot, with the 02-02-2024 operational snapshot re-estimated as a sensitivity check. ChargerDensity is chargers per 100,000 population, now fully computed for every state using NCP/MoHFW projected population (see Data Description). Assumption checks: linearity (residual-vs-fitted plot), normality of residuals (Shapiro-Wilk), homoscedasticity (Breusch-Pagan), and multicollinearity (variance inflation factors below 5). Because charger placement and adoption reinforce each other, RQ1 estimates association, not one-way causation; this chicken-and-egg structure is well documented internationally (Li et al., 2017; Springel, 2021) and motivates the two-snapshot sensitivity design. State-level charger counts for India specifically are corroborated by an independent open dataset compiled by Gulzar et al. (2024).

Solution to RQ2: Independent-Samples t-Test (ANOVA as Robustness Check)

States are split at the median charger density into high and low tiers (18 states each), and mean EV share is compared with an independent two-sample t-test. Levene's test decides between the pooled and Welch forms. A tercile split with one-way ANOVA and Tukey HSD post-hoc comparisons is reported as a robustness check, with the caveat that the three-group design is powered only for very large effects at $N = 36$.

Solution to RQ3: Lagged Panel Regression

Model: $\Delta\text{EnergyReq}(s, t) = \beta_0 + \beta_1\text{EVshare}(s, t - 1) + \beta_2\text{PCNSDP}(s) + \beta_3\text{Urban}(s) + \lambda(t) + \varepsilon(s, t)$, where $\Delta\text{EnergyReq}$ is the year-on-year growth in energy requirement (MU), the one-year lag on EV share reduces simultaneity, and $\lambda(t)$ are year fixed effects absorbing national shocks such as the FY2020-21 pandemic year. This lagged panel design follows the same logic as recent Indian panel-data studies of EV sales drivers (Singh et al., 2025). Estimation uses FY2019-20 through FY2023-24 complete years only; the Apr-Dec FY2024-25 partial year is excluded from estimation and used descriptively. Standard errors are clustered by state.

Solution to RQ4: Logistic Regression (Classification)

Model: $\text{logit}P(\text{GridStress}(s, t) = 1) = \beta_0 + \beta_1\text{ChargerDensity}(s) + \beta_2\text{EVshare}(s, t) + \beta_3\text{EVgrowth}(s, t) + \beta_4\text{PCNSDP}(s) + \beta_5\text{Urban}(s)$. The binary label $\text{GridStress}(s, t)$ equals 1 when the state's year-on-year growth in annual maximum peak demand exceeds the all-state median growth for that financial year - a deterministic, reproducible rule computed entirely from official CEA/ICED peak-demand data. The primary inference is the likelihood-ratio test; classification quality is evaluated on a stratified 70/30 train-test split with the metrics in the next section. A decision-tree classifier is run as a machine-learning robustness check on variable importance, not as the hypothesis test.

Evaluation Metrics With Formulae and Calculations

Each metric is stated with its formula and a worked calculation so that the computation is unambiguous. Regression questions (RQ1, RQ3) report R^2 , adjusted R^2 , RMSE, and the F-statistic; the group comparison (RQ2) reports the t-statistic and Cohen's d; the classification question (RQ4) reports the confusion-matrix family, ROC-AUC, and McFadden's pseudo- R^2 .

Regression Metrics (RQ1, RQ3)

$R^2 = 1 - \frac{SS_{\text{res}}}{SS_{\text{tot}}}$. Worked example: if $SS_{\text{res}} = 20$ and $SS_{\text{tot}} = 100$, then $R^2 = 1 - \frac{20}{100} = 0.80$, meaning 80% of the variance in EV share is explained. Adjusted $R^2 = 1 - \frac{(1-R^2)(n-1)}{n-k-1}$, with $n = 36$, $k = 3$: $1 - (0.20) \left(\frac{35}{32} \right) = 0.781$. RMSE = $\sqrt{\frac{\sum(y-\hat{y})^2}{n}}$; if the mean squared error is 0.0004 on EV-share units, RMSE = 0.02, i.e., predictions deviate by 2 percentage points on average. MAE = $\frac{\sum|y-\hat{y}|}{n}$ is reported alongside. The model F-statistic is $F = \frac{R^2/k}{(1-R^2)/(n-k-1)}$; with $R^2 = 0.80$, $k = 3$, $n = 36$: $F = \frac{0.2667}{0.00625} = 42.7$, compared against $F(3,32)$ critical value 2.90 at $\alpha = .05$.

Group-Comparison Metrics (RQ2)

$t = \frac{\bar{x}_1 - \bar{x}_2}{\sqrt{s_1^2/n_1 + s_2^2/n_2}}$. Worked example: if high-density states average 12% EV share and low-density states 5%, each with SD = 7% and $n = 18$ per tier, $t = \frac{7}{\sqrt{49/18 + 49/18}} = \frac{7}{2.33} = 3.00$, exceeding the two-tailed critical value 2.03 at $df = 34$. Cohen's $d = \frac{\bar{x}_1 - \bar{x}_2}{s_{\text{pooled}}} = \frac{7}{7} = 1.00$, a large effect. For the ANOVA robustness check, $\eta^2 = \frac{SS_{\text{between}}}{SS_{\text{total}}}$ is reported.

Classification Metrics (RQ4)

From the confusion matrix with true positives TP, false positives FP, false negatives FN, and true negatives TN: Accuracy = $\frac{TP+TN}{TP+TN+FP+FN}$; Precision = $\frac{TP}{TP+FP}$; Recall = $\frac{TP}{TP+FN}$; $F_1 =$

$2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}}$. Worked example with TP = 70, FN = 18, FP = 15, TN = 72 ($N = 175$):

$$\text{Accuracy} = \frac{142}{175} = 0.811; \text{Precision} = \frac{70}{85} = 0.824; \text{Recall} = \frac{70}{88} = 0.795; F_1 = \frac{2(0.824 \times 0.795)}{0.824 + 0.795} =$$

0.809. ROC-AUC is the area under the true-positive-rate versus false-positive-rate curve across thresholds; H_0 : AUC = 0.5 is tested with DeLong's method. McFadden's pseudo- $R^2 = 1 -$

$\frac{\ln L_{\text{model}}}{\ln L_{\text{null}}}$; values of 0.2-0.4 indicate excellent fit for logistic models. Because the median-split

label yields balanced classes by construction, accuracy is meaningful, but F1 and AUC remain the headline metrics.

Recommendation and Application

The target users are, first, the Ministry of Power, the CEA, and state DISCOMs, who gain a tested indicator of which states' peak-demand growth is outrunning peers as EV adoption rises; second, the Ministry of Heavy Industries and PM E-DRIVE administrators, who gain evidence on whether charger deployment is aligned with adoption and where the misalignment is largest; third, NITI Aayog and state EV-policy cells, for whom the state classification provides a screening tool for infrastructure prioritization; and fourth, charge-point operators and researchers, who receive an open, fully documented State $\times$ Year panel assembled exclusively from official sources - itself a reusable public good, since no such reconciled panel is currently published.

Limitations

Four limitations are declared. First, charger data exist only as Parliament-reply snapshots, so RQ1 and RQ2 are cross-sectional and powered for large effects only; no interpolation between snapshots is performed because interpolated values would constitute synthesized data. Second, the operational (02-02-2024) and installed (01-08-2025) charger definitions differ and are never mixed within a single test. Third, the charger-adoption relationship in RQ1 is mutually reinforcing, so coefficients are interpreted as associations. Fourth, published All-India electricity totals do not equal the sum of state rows in some years (a gap of approximately 11,336 MU in FY2023-24 attributable to unattributed drawal categories); both figures are reported side by side and analyses use state rows consistently.

References

- Central Electricity Authority. (2025). Power supply position reports. Ministry of Power, Government of India. <https://cea.nic.in/power-supply/?lang=en>
- Clement-Nyns, K., Haesen, E., & Driesen, J. (2010). The impact of charging plug-in hybrid electric vehicles on a residential distribution grid. *IEEE Transactions on Power Systems*, 25(1), 371-380. <https://doi.org/10.1109/TPWRS.2009.2036481>
- Cohen, J. (1988). *Statistical power analysis for the behavioral sciences* (2nd ed.). Lawrence Erlbaum Associates.
- Egbue, O., & Long, S. (2012). Barriers to widespread adoption of electric vehicles: An analysis of consumer attitudes and perceptions. *Energy Policy*, 48, 717-729. <https://doi.org/10.1016/j.enpol.2012.06.009>
- Faul, F., Erdfelder, E., Lang, A.-G., & Buchner, A. (2007). G*Power 3: A flexible statistical power analysis program for the social, behavioral, and biomedical sciences. *Behavior Research Methods*, 39(2), 175-191. <https://doi.org/10.3758/BF03193146>
- Gulzar, Y., Dutta, M., Gupta, D., Juneja, S., Soomro, A. B., & Mir, M. S. (2024). Revolutionizing mobility: A comprehensive review of electric vehicle charging stations in India. *Frontiers in Sustainable Cities*, 6, 1346731. <https://doi.org/10.3389/frsc.2024.1346731>
- Li, S., Tong, L., Xing, J., & Zhou, Y. (2017). The market for electric vehicles: Indirect network effects and policy design. *Journal of the Association of Environmental and Resource Economists*, 4(1), 89-133. <https://doi.org/10.1086/689702>
- Ministry of Health and Family Welfare, National Commission on Population. (2019). *Population projections for India and states 2011-2036: Report of the Technical Group on Population*

Projections. Government of India.

https://nhm.gov.in/New_Updates_2018/Report_Population_Projection_2019.pdf

Ministry of Heavy Industries. (2024). State-wise details of electric vehicles and total vehicles

[Press release, PRID 2084148]. Press Information Bureau.

<https://pib.gov.in/PressReleasePage.aspx?PRID=2084148>

Ministry of Heavy Industries. (2025). State-wise details of installed electric vehicle charging

stations as on 01.08.2025 [Press release, PRID 2151390]. Press Information Bureau.

<https://www.pib.gov.in/PressReleasePage.aspx?PRID=2151390>

Ministry of Power. (2024). State-wise operational public EV charging stations as on 02.02.2024

[Press release, PRID 2003003]. Press Information Bureau.

<https://www.pib.gov.in/PressReleaseIframePage.aspx?PRID=2003003>

Ministry of Power. (2025). State/UT-wise power supply position [Rajya Sabha Unstarred

Question No. 150, answered 03-02-2025]. Government of India.

<https://www.powermin.gov.in/static/uploads/2025/08/5804f7f17e764f9ba1951183379b8e31.pdf>

Ministry of Statistics and Programme Implementation. (2023). Per capita net state domestic

product at current prices [Press release, PRID 1942055]. Press Information Bureau.

<https://pib.gov.in/PressReleasePage.aspx?PRID=1942055>

Muratori, M. (2018). Impact of uncoordinated plug-in electric vehicle charging on residential

power demand. *Nature Energy*, 3(3), 193-201. [https://doi.org/10.1038/s41560-017-0074-](https://doi.org/10.1038/s41560-017-0074-z)

[z](https://doi.org/10.1038/s41560-017-0074-z)

NITI Aayog. (n.d.). India climate and energy dashboard. Government of India.

<https://iced.niti.gov.in>

- Peduzzi, P., Concato, J., Kemper, E., Holford, T. R., & Feinstein, A. R. (1996). A simulation study of the number of events per variable in logistic regression analysis. *Journal of Clinical Epidemiology*, 49(12), 1373-1379. [https://doi.org/10.1016/S0895-4356\(96\)00236-3](https://doi.org/10.1016/S0895-4356(96)00236-3)
- Sierzchula, W., Bakker, S., Maat, K., & van Wee, B. (2014). The influence of financial incentives and other socio-economic factors on electric vehicle adoption. *Energy Policy*, 68, 183-194. <https://doi.org/10.1016/j.enpol.2014.01.043>
- Singh, V., Nerlekar, V., & Kumar, J. (2025). Exploring the macroeconomic drivers to electric vehicle sales in India: A panel data-based approach. *Transport Policy*. <https://doi.org/10.1016/j.tranpol.2025.103818>
- Springel, K. (2021). Network externality and subsidy structure in two-sided markets: Evidence from electric vehicle incentives. *American Economic Journal: Economic Policy*, 13(4), 393-432. <https://doi.org/10.1257/pol.20190131>