

OO Code Review Report

Brief Report of Processed OO Code:

| | |
|-------------------|-------------|
| Date | 14-04-2021 |
| Content Pack | DXC |
| Flow Count | 179 |
| System Properties | 42 |
| System Accounts | 10 |
| Error Count | 4700 |
| Warning Count | 3622 |

Detailed Report of Error Found in Flow Steps:

* Blank column denotes value is **not assigned** to variable.

| Flow Step | Variable Type | Variable Name | Assign From (*) | Default Value | Remarks |
|-------------------------|----------------------|----------------|--------------------------------|--|--|
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Get User Identifier | Flow Output Variable | userIdentifier | Result Field: userIdentifier | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Provider Details | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ADHost | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ADUsername | Result Field: providerUser | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ADPassword | Result Field: providerPassword | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ADPort | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ADProtocol | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Variable is defined but not assigned |

| | | | | | |
|---------------------------|----------------------|---------------------------|------------------------------|---|--|
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | headers | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParams | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | method | | GET | Variable is defined but not assigned |
| Get Provider Properties | Flow Output Variable | domain | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Update Component Property | Input Variable | onlyUpdate | | yes | Variable is defined but not assigned |
| Update Component Property | Input Variable | displayName | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | propertyName | | AD_DOMAIN | Variable is defined but not assigned |
| Update Component Property | Input Variable | valueType | | | Variable is defined but not assigned |

| | | | | | |
|---------------------------|----------------|----------------------|-------------------|------------|--------------------------------------|
| Update Component Property | Input Variable | separator | | , | Variable is defined but not assigned |
| Update Component Property | Input Variable | consumerVisible | | true | Variable is defined but not assigned |
| Update Component Property | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Component Property | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | authType | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Component Property | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | componentId | serverComponentId | | Input variable is using Prompt User |
| SQL Command | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| SQL Command | Input Variable | instance | | | Variable is defined but not assigned |
| SQL Command | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| SQL Command | Input Variable | dbClass | | | Variable is defined but not assigned |
| SQL Command | Input Variable | dbURL | | | Variable is defined but not assigned |
| SQL Command | Input Variable | timeout | | | Variable is defined but not assigned |

| | | | | | |
|--------------------------------|----------------------|---------------------------|--------------------------|------------|--|
| SQL Command | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| SQL Command | Input Variable | resultSetType | | | Variable is defined but not assigned |
| SQL Command | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| SQL Command | Flow Output Variable | guestOS | Result Field: outputText | N/A | Flow Output variable created in flow steps |
| SQL Command | Flow Output Variable | role | Result Field: outputText | N/A | Flow Output variable created in flow steps |
| SQL Command To Get Template | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | instance | | | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | dbClass | | | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | dbURL | | | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | timeout | | | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | resultSetType | | | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| SQL Command To Get Template | Flow Output Variable | Template | Result Field: outputText | N/A | Flow Output variable created in flow steps |
| SQL Command To get Custom Spec | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| SQL Command To get Custom Spec | Input Variable | instance | | | Variable is defined but not assigned |
| SQL Command To get Custom Spec | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| SQL Command To get Custom Spec | Input Variable | dbClass | | | Variable is defined but not assigned |
| SQL Command To get Custom Spec | Input Variable | dbURL | | | Variable is defined but not assigned |
| SQL Command To get Custom Spec | Input Variable | timeout | | | Variable is defined but not assigned |
| SQL Command To get Custom Spec | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| SQL Command To get Custom Spec | Input Variable | resultSetType | | | Variable is defined but not assigned |
| SQL Command To get Custom Spec | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| SQL Command To get Custom Spec | Flow Output Variable | customSpec | Result Field: outputText | N/A | Flow Output variable created in flow steps |

| | | | | | |
|------------------------------|----------------------|----------------------|---------------|---|--|
| Constuct Json | Flow Output Variable | failureJson | Input: field1 | N/A | Flow Output variable created in flow steps |
| Constuct Json | Flow Output Variable | failureJson | Input: field1 | N/A | Flow Output variable created in flow steps |
| Get HCM Authentication Token | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | tenantName | tenantName | | Input variable is using Prompt User |
| POST operation | Input Variable | url | | \${HCM/HCM-API-URL}rest/v1.0.0/serviceRequest | Variable is defined but not assigned |
| POST operation | Input Variable | authType | | Basic | Variable is defined but not assigned |
| POST operation | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| POST operation | Input Variable | characterSet | | | Variable is defined but not assigned |
| POST operation | Input Variable | headerNamesList | | Accept,Content-Type,X-Auth-Token | Variable is defined but not assigned |
| POST operation | Input Variable | headerValuesList | | application/json,application/json,{authToken} | Variable is defined but not assigned |
| POST operation | Input Variable | queryNamesList | | | Variable is defined but not assigned |
| POST operation | Input Variable | queryValuesList | | | Variable is defined but not assigned |
| POST operation | Input Variable | delimiter | | , | Variable is defined but not assigned |
| Request Id | Input Variable | jsonPathQuery | | \$.@uri | Variable is defined but not assigned |

| Request Id | Flow Output Variable | request_id | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
|---------------------|----------------------|------------------|-------------------------------|---|---|
| POST operation | Input Variable | url | | \${HCM/HCM-API-URL} service/subscription/\${s ubscriptionId}/cancel | Variable is defined but not assigned |
| POST operation | Input Variable | authType | | Basic | Variable is defined but not assigned |
| POST operation | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| POST operation | Input Variable | characterSet | | | Variable is defined but not assigned |
| POST operation | Input Variable | headerNamesList | | Accept,Content-Type,X- Auth-Token | Variable is defined but not assigned |
| POST operation | Input Variable | headerValuesList | | application/json,applicat ion/json,{authToken} | Variable is defined but not assigned |
| POST operation | Input Variable | queryNamesList | | | Variable is defined but not assigned |
| POST operation | Input Variable | delimiter | | , | Variable is defined but not assigned |
| Get User Identifier | Input Variable | csaUser | | \${CSA_OO_USER} | Variable is defined but not assigned |
| Get User Identifier | Input Variable | timeout | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Get User Identifier | Input Variable | proxy | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | authType | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | keystore | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | keystorePassword | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------|----------------------|----------------|---|--------------------------------------|
| Get User Identifier | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Get User Identifier | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | timeout | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | useCookies | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | proxy | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | userAgent | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | authType | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | keystore | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Finalize Service Component | Input Variable | componentId | componentId | | Input variable is using Prompt User |
| Finalize Service Component | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Initiate LifeCycle | Input Variable | url | | \${CSA_REST_URI}/life cycleengine/execute?userIdentifier=\${userIdentifier} | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | authType | | Basic | Variable is defined but not assigned |

| | | | | | |
|--------------------|----------------|------------------------|--|---|--------------------------------------|
| Initiate LifeCycle | Input Variable | body | | <?xml version="1.0" encoding="UTF-8" standalone="yes"?> <LifecycleExecutionRequest> <reverse>false</reverse> <serviceComponentId>\${parentComponentId}</serviceComponentId> <serviceInstanceId>\${serviceInstanceId}</serviceInstanceId> <targetStateName>DEPLOYED</targetStateName> </LifecycleExecutionRequest> ... | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | keystore | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | headers | | Accept:application/xml content-type:application/xml | Variable is defined but not assigned |

| | | | | | |
|--------------------|----------------|--------------------------|--|--|--------------------------------------|
| Initiate LifeCycle | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | queryParams | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | formParams | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | contentType | | application/xml | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Initiate LifeCycle | Input Variable | method | | POST | Variable is defined but not assigned |
| Get LCE Status | Input Variable | url | | \${CSA_REST_URI}/life cycleengine | Variable is defined but not assigned |
| Get LCE Status | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get LCE Status | Input Variable | queryParams | | userIdentifier=\${userIdentifier}&serviceInstanceId;=\${serviceInstanceId} | Variable is defined but not assigned |
| Get LCE Status | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Get LCE Status | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Get LCE Status | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Get LCE Status | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get LCE Status | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get LCE Status | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get LCE Status | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get LCE Status | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get LCE Status | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get LCE Status | Input Variable | keystore | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------|---------------------------|------------------------|--|--------------------------------------|
| Get LCE Status | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get LCE Status | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get LCE Status | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get LCE Status | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Get LCE Status | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Get LCE Status | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Get LCE Status | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Get LCE Status | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Get LCE Status | Input Variable | headers | | Accept:application/xml | Variable is defined but not assigned |
| Get LCE Status | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Get LCE Status | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get LCE Status | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get LCE Status | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Get LCE Status | Input Variable | method | | GET | Variable is defined but not assigned |
| Get ServiceInstanceDetails | Input Variable | csaApiUrl | | \${HCM/HCM-API-URL} | Variable is defined but not assigned |
| Filter Component ID | Input Variable | jsonPathQuery | | \$.components[?(@.displayName=='Server Project')].id | Variable is defined but not assigned |
| Filter Component ID | Input Variable | jsonPathQuery | | \$.components[?(@.displayName=='Virtual Server')].id | Variable is defined but not assigned |
| Array Size | Input Variable | array | serverComponentIdArray | | Input variable is using Prompt User |
| Array Iterator | Input Variable | array | serverComponentIdArray | | Input variable is using Prompt User |
| Get Artifact Properties | Input Variable | propertyNames | | name | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |

| | | | | | |
|-----------------------------------|----------------------|----------------------|-------------------|--------------|--|
| Get Artifact Properties | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | authType | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | artifactId | componentId | | Input variable is using Prompt User |
| Get Artifact Properties | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Cancel HCM Subscription | Flow Output Variable | hcmRequestId | Result: requestId | N/A | Flow Output variable created in flow steps |
| Modify Service Component Property | Input Variable | displayName | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | propertyName | | SERVER_COUNT | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | valueType | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | separator | | , | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | consumerVisible | | true | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | timeout | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | useCookies | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |

| | | | | | |
|-----------------------------------|----------------------|----------------------|----------------------------|-----------|--|
| Modify Service Component Property | Input Variable | proxy | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | userAgent | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | authType | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | keystore | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Modify Service Component Property | Input Variable | componentId | parentComponentId | | Input variable is using Prompt User |
| Modify Service Component Property | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Modify Service Component Property | Input Variable | values | serverCount | | Input variable is using Prompt User |
| Sleep | Input Variable | seconds | | 60 | Variable is defined but not assigned |
| Loop | Input Variable | count | | 30 | Variable is defined but not assigned |
| Loop | Input Variable | reset | | false | Variable is defined but not assigned |
| Loop | Input Variable | to | | \${count} | Variable is defined but not assigned |
| Loop | Input Variable | from | | 1 | Variable is defined but not assigned |
| Loop | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Loop | Flow Output Variable | hcmRequestId | Result Field: resultString | N/A | Flow Output variable created in flow steps |
| String Equals | Flow Output Variable | hcmRequestId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-------------------------|----------------------|-------------------------|----------------------------|--|---|
| Flow Inputs | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Flow Inputs | Input Variable | subscriptionDescription | | Subscription Started | Variable is defined but not assigned |
| Flow Inputs | Input Variable | action | | ORDER | Variable is defined but not assigned |
| Flow Inputs | Input Variable | requestPayload | requestPayload | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | offeringName | offeringName | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | authToken | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | authToken | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | catalogName | catalogName | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | subscriptionName | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | subscriptionName | | | Input variable is using Prompt User |
| POST operation | Input Variable | url | | \${HCM/HCM-API-URL}rest/v1.0.0/serviceRequest | Variable is defined but not assigned |
| POST operation | Input Variable | authType | | basic | Variable is defined but not assigned |
| POST operation | Input Variable | timeout | | | Variable is defined but not assigned |
| POST operation | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| POST operation | Input Variable | characterSet | | | Variable is defined but not assigned |
| Request Id | Input Variable | jsonPathQuery | | \$.@uri | Variable is defined but not assigned |
| Request Id | Flow Output Variable | request_id | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------------|---------------------------|--------------------------------|---|--|
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | headers | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParams | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | method | | GET | Variable is defined but not assigned |
| Get Provider Properties | Flow Output Variable | domain | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Provider Details | Flow Output Variable | ADuser | Result Field: providerUser | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ADPassword | Result Field: providerPassword | N/A | Flow Output variable created in flow steps |
| Get Artifact Properties | Input Variable | propertyNames | | AD_PROVIDER_ID | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | socketTimeout | | | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------|----------------------|----------------|--|--------------------------------------|
| Get Artifact Properties | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | authType | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | childComponentName | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | childComponentName | | | Input variable is using Prompt User |
| Http Client Get | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${parentComponentId} | Variable is defined but not assigned |
| Http Client Get | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParams | | userIdentifier=\${userIdentifier}&scope;=Baseplusone | Variable is defined but not assigned |
| Http Client Get | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyHost | | | Variable is defined but not assigned |

| | | | | | |
|--------------------------|----------------------|---------------------------|--------------------------------|-----------|--|
| Http Client Get | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Get | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | method | | GET | Variable is defined but not assigned |
| Get Component Properties | Flow Output Variable | propertyNameValuesList | Result: propertyNameValuesList | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | childComponentName | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | childComponentName | | | Input variable is using Prompt User |

| | | | | | |
|-----------------|----------------|------------------------|--|--|--------------------------------------|
| Http Client Get | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${parentComponentId} | Variable is defined but not assigned |
| Http Client Get | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParams | | userIdentifier=\${userIdentifier}&scope;=Baseplusone | Variable is defined but not assigned |
| Http Client Get | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Get | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |

| | | | | | |
|-----------------------------------|----------------------|-------------------------------|------------------------------------|---|--|
| Http Client Get | Input Variable | queryParamsAreURLEn coded | | false | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreFormE ncoded | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | method | | GET | Variable is defined but not assigned |
| Get Component Properties | Flow Output Variable | propertyNameValuesLis t | Result: propertyNameV aluesList | N/A | Flow Output variable created in flow steps |
| Http Client Get | Input Variable | url | | \${HCM/HCM-REST-UR L}artifact/\${componentI d}/resolveProperties?us erIdentifier=\${userIden tifier}&view;=propertyval ue | Variable is defined but not assigned |
| Http Client Get | Input Variable | userAgent | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustPassword | trustPassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Http Client Get | Input Variable | keystorePassword | keystorePassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Http Client Get | Flow Output Variable | propertyNameValuesLis t | Result Field: document | N/A | Flow Output variable created in flow steps |
| Get Current Date and Time | Input Variable | localeLang | | | Variable is defined but not assigned |
| Get Current Date and Time | Input Variable | localeCountry | | unix | Variable is defined but not assigned |
| Date Parser | Input Variable | date | | \${currentdate} | Variable is defined but not assigned |
| Date Parser | Input Variable | dateFormat | | MMM dd,yyyy hh:mm:ss aa | Variable is defined but not assigned |
| Date Parser | Input Variable | dateLocaleLang | | en | Variable is defined but not assigned |
| Date Parser | Input Variable | dateLocaleCountry | | US | Variable is defined but not assigned |
| Date Parser | Input Variable | outFormat | | yyyy-MM-dd'T'HH:mm:s s.S'Z' | Variable is defined but not assigned |
| Date Parser | Input Variable | outLocaleLang | | en | Variable is defined but not assigned |
| Date Parser | Input Variable | outLocaleCountry | | US | Variable is defined but not assigned |
| Date Parser | Flow Output Variable | subscriptionDate | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Authentication Using IDM Token | Input Variable | string | | { "passwordCredentials" : { "username" : "\${hcmUsername}", "password" : "\${hcmPassword}" }, "tenantName" : "\${tenantName}" } | Variable is defined but not assigned |

| | | | | | |
|--------------------------------|----------------------|------------------------|---------------------------|--|--|
| Authentication Using IDM Token | Flow Output Variable | authID | Result Field: document | N/A | Flow Output variable created in flow steps |
| Authentication Using IDM Token | Flow Output Variable | resultText | Result Field: resultText | N/A | Flow Output variable created in flow steps |
| Authentication Using IDM Token | Flow Output Variable | resultData | Result Field: document | N/A | Flow Output variable created in flow steps |
| Loop | Input Variable | count | | 4 | Variable is defined but not assigned |
| Loop | Input Variable | reset | | false | Variable is defined but not assigned |
| Loop | Input Variable | to | | \${count} | Variable is defined but not assigned |
| Loop | Input Variable | from | | 1 | Variable is defined but not assigned |
| Loop | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Sleep | Input Variable | seconds | | 15 | Variable is defined but not assigned |
| Error Handling | Input Variable | oorunId | | \${run_id} | Variable is defined but not assigned |
| Error Handling | Input Variable | constantFailureMessage | | Failed to get HCM Authentication Token | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | authToken | authToken | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | offeringName | offeringName | | Input variable is using Prompt User |
| Get Offering Details | Input Variable | string | | { "service_offering": { "keywords": ["\${offeringName}"], "fields": ["name"] } } | Variable is defined but not assigned |
| Get Offering Details | Flow Output Variable | keyValue | Result Field: document | N/A | Flow Output variable created in flow steps |
| Get Offering Details | Flow Output Variable | resultText | Result Field: resultText | N/A | Flow Output variable created in flow steps |
| Get Offering Details | Flow Output Variable | resultData | Result Field: document | N/A | Flow Output variable created in flow steps |
| JSON Path | Input Variable | jsonPathQuery | | \$.components | Variable is defined but not assigned |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable is using Prompt User |
| Array Iterator | Input Variable | array | jsonArray | | Input variable is using Prompt User |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.display_name=='Virtual Server')].id | Variable is defined but not assigned |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable is using Prompt User |

| | | | | | |
|-----------------------------|----------------|----------------------|-------------|--|--------------------------------------|
| Get Child Component Details | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${jsonElement}?userIdentifier=\${userIdentifier} | Variable is defined but not assigned |
| Get Child Component Details | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Child Component Details | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Get Child Component Details | Input Variable | encodeURL | | True | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | propertyNames | | name NETWORK | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | authType | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Artifact Properties | Input Variable | artifactId | jsonElement | | Input variable is using Prompt User |

| | | | | | |
|-------------------------|----------------------|------------------------|--------------------------------------|---|--|
| Get Artifact Properties | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Artifact Properties | Flow Output Variable | networkType | Result Field: propertyNameValuesList | N/A | Flow Output variable created in flow steps |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id=='\${jsonElement}')].resourceSubscription[*].serviceAction[?(@.displayName=='\${actionName}')].name | Variable is defined but not assigned |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable is using Prompt User |
| JSON Path | Flow Output Variable | actionId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id=='\${disk1componentId}')].resourceSubscription[*].serviceAction[?(@.displayName=='\${actionName}')].name | Variable is defined but not assigned |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable is using Prompt User |
| JSON Path | Flow Output Variable | actionId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id=='\${disk2componentId}')].resourceSubscription[*].serviceAction[?(@.displayName=='\${actionName}')].name | Variable is defined but not assigned |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable is using Prompt User |
| JSON Path | Flow Output Variable | actionId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id=='\${jsonElement}')].resourceSubscription[?(@.displayName=='Micro Focus Compute')].id | Variable is defined but not assigned |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable is using Prompt User |
| JSON Path | Flow Output Variable | resourceSubscriptionId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id=='\${disk2componentId}')].resourceSubscription[*].id | Variable is defined but not assigned |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable is using Prompt User |
| JSON Path | Flow Output Variable | resourceSubscriptionId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-----------------|----------------------|------------------------|----------------------------|---|---|
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id=='\${disk1componentId}').resourceSubscription[*]].id | Variable is defined but not assigned |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable is using Prompt User |
| JSON Path | Flow Output Variable | resourceSubscriptionId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | password | password | HCM-ADMIN-ACCOUNT : USERNAME | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Http Client Get | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | headers | | Accept:application/json X-Auth-token:\${X-Auth-Token} | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParams | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Http Client Get | Input Variable | method | | GET | Variable is defined but not assigned |
| Http Client Get | Flow Output Variable | serviceInstanceIdJSON | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | startDate | | 1600413726431 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | endDate | | | Variable is defined but not assigned |
| Date Parser | Input Variable | dateFormat | | unix | Variable is defined but not assigned |
| Date Parser | Input Variable | dateLocaleLang | | en | Variable is defined but not assigned |
| Date Parser | Input Variable | dateLocaleCountry | | US | Variable is defined but not assigned |
| Date Parser | Input Variable | outFormat | | yyyy-MM-dd'T'HH:mm:ss.S'Z' | Variable is defined but not assigned |
| Date Parser | Input Variable | outLocaleLang | | en | Variable is defined but not assigned |
| Date Parser | Input Variable | outLocaleCountry | | US | Variable is defined but not assigned |
| Date Parser | Flow Output Variable | subscriptionStartDate | Result Field: returnResult | N/A | Flow Output variable created in flow steps |

| | | | | | |
|----------------------------------|----------------------|----------------------|----------------------------|----------------------------|--|
| Date Parser | Input Variable | dateFormat | | unix | Variable is defined but not assigned |
| Date Parser | Input Variable | dateLocaleLang | | en | Variable is defined but not assigned |
| Date Parser | Input Variable | dateLocaleCountry | | US | Variable is defined but not assigned |
| Date Parser | Input Variable | outFormat | | yyyy-MM-dd'T'HH:mm:ss.S'Z' | Variable is defined but not assigned |
| Date Parser | Input Variable | outLocaleLang | | en | Variable is defined but not assigned |
| Date Parser | Input Variable | outLocaleCountry | | US | Variable is defined but not assigned |
| Date Parser | Flow Output Variable | subscriptionEndDate | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Service Subscription Details | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | authType | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Service Subscription Details | Input Variable | trustPassword | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------------|----------------------|----------------------|------------------------|--------|--|
| Get Service Subscription Details | Input Variable | svcSubscriptionId | svcSubscriptionId | | Input variable is using Prompt User |
| Get Service Subscription Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Service Subscription Details | Flow Output Variable | serviceOfferingName | Result Field: document | N/A | Flow Output variable created in flow steps |
| Get Service Subscription Details | Flow Output Variable | subscriptionDocument | Result Field: document | N/A | Flow Output variable created in flow steps |
| Get Service Subscription Details | Flow Output Variable | serviceInstanceId | Result Field: document | N/A | Flow Output variable created in flow steps |
| Get Artifact Details | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | authType | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Artifact Details | Input Variable | artifactId | serviceInstanceId | | Input variable is using Prompt User |
| Get Artifact Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |

| | | | | | |
|----------------------|----------------------|-------------------------|------------------------------|--|--|
| Get Artifact Details | Flow Output Variable | serviceInstanceDocument | Result Field: document | N/A | Flow Output variable created in flow steps |
| Get Artifact Details | Flow Output Variable | subscriptionOwner | Result Field: document | N/A | Flow Output variable created in flow steps |
| Get Artifact Details | Flow Output Variable | subscriptionOwnerId | Result Field: document | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | primaryEmail | primaryEmail | | Input variable is using Prompt User |
| LDAP Search | Input Variable | DN | | OU=MF_Users,{AD/AD-INT-BASE-DN} | Variable is defined but not assigned |
| LDAP Search | Input Variable | filter | | mail=\${primaryEmail} | Variable is defined but not assigned |
| LDAP Search | Input Variable | propertyNames | | employeeID | Variable is defined but not assigned |
| LDAP Search | Input Variable | delimiter | | , | Variable is defined but not assigned |
| LDAP Search | Input Variable | useSSL | | true | Variable is defined but not assigned |
| LDAP Search | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| LDAP Search | Input Variable | keyStore | | | Variable is defined but not assigned |
| LDAP Search | Input Variable | keyStorePassword | | | Variable is defined but not assigned |
| LDAP Search | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| LDAP Search | Input Variable | trustPassword | | | Variable is defined but not assigned |
| LDAP Search | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| EXT LDAP Search | Input Variable | DN | | OU=Personal,OU=Accounts,OU=VirtualSM,{AD/AD-EXT-BASE-DN} | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | filter | | employeeID=\${employeeID} | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | propertyNames | | sAMAccountName,userPrincipalName | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | delimiter | | , | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | useSSL | | true | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | keyStore | | | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | keyStorePassword | | | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | trustPassword | | | Variable is defined but not assigned |

| | | | | | |
|-----------------|----------------------|------------------|---------------------------------|--|---|
| EXT LDAP Search | Flow Output Variable | supAccount | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| EXT LDAP Search | Flow Output Variable | upn | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| EXT LDAP Search | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| INT LDAP Search | Input Variable | DN | | OU=Personal,OU=Acco unts,OU=VirtualSM,{A D/AD-INT-BASE-DN} | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | filter | | employeeID=\${employe eID} | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | propertyNames | | sAMAccountName,user PrincipalName | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | delimiter | | , | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | useSSL | | true | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | keyStore | | | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | keyStorePassword | | | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | trustPassword | | | Variable is defined but not assigned |
| INT LDAP Search | Flow Output Variable | supAccount | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| INT LDAP Search | Flow Output Variable | upn | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| INT LDAP Search | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| INT LDAP Search | Input Variable | DN | | OU=Personal,OU=Acco unts,OU=VirtualSM,{A D/AD-INT-BASE-DN} | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | filter | | employeeID=\${employe eID1} | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | propertyNames | | sAMAccountName,user PrincipalName | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | delimiter | | , | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | useSSL | | true | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | keyStore | | | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | keyStorePassword | | | Variable is defined but not assigned |

| | | | | | |
|-----------------|----------------------|------------------|------------------------------|--|--|
| INT LDAP Search | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| INT LDAP Search | Input Variable | trustPassword | | | Variable is defined but not assigned |
| INT LDAP Search | Flow Output Variable | supAccount | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| INT LDAP Search | Flow Output Variable | upn | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| INT LDAP Search | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| EXT LDAP Search | Input Variable | DN | | OU=Personal,OU=Accounts,OU=VirtualSM,{AD/AD-EXT-BASE-DN} | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | filter | | employeeID=\${employeeID1} | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | propertyNames | | sAMAccountName,userPrincipalName | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | delimiter | | , | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | useSSL | | true | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | keyStore | | | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | keyStorePassword | | | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| EXT LDAP Search | Input Variable | trustPassword | | | Variable is defined but not assigned |
| EXT LDAP Search | Flow Output Variable | supAccount | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| EXT LDAP Search | Flow Output Variable | upn | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| EXT LDAP Search | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | host | | \${AD/AD-HOSTNAME} | Variable is defined but not assigned |
| Flow Inputs | Input Variable | DN | | OU=Personal,OU=Accounts,OU=VirtualSM,{AD/AD-BASE-DN} | Variable is defined but not assigned |
| Flow Inputs | Input Variable | propertyNames | | cn,sAMAccountName,mail | Variable is defined but not assigned |
| Flow Inputs | Input Variable | port | | \${AD/AD-PORT} | Variable is defined but not assigned |
| LDAP Search | Input Variable | delimiter | | , | Variable is defined but not assigned |
| LDAP Search | Input Variable | useSSL | | true | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------------|-------------------|----------------------------|----------------------------------|--|
| LDAP Search | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| LDAP Search | Input Variable | keyStore | | | Variable is defined but not assigned |
| LDAP Search | Input Variable | keyStorePassword | | | Variable is defined but not assigned |
| LDAP Search | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| LDAP Search | Input Variable | trustPassword | | | Variable is defined but not assigned |
| LDAP Search | Flow Output Variable | supAccount | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| LDAP Search | Flow Output Variable | failureMessage | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | resourceBindingId | | 2c92d4ba7372ac330173bddd23126826 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | userIdentifier | | 6BC7CE65B5F74D08AA29C8FC40616451 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | site | | houston4 | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | authType | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | keystorePassword | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------------|----------------------|------------------------------|--|--|
| Get Candidate Providers | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Candidate Providers | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Candidate Providers | Flow Output Variable | xml | Result Field: document | N/A | Flow Output variable created in flow steps |
| XPath Query for Site | Input Variable | xpathQuery | | /ResourceBinding/candidateProvider/resourceProvider/property/displayName[text()='Site']/../values/value[text()='\${site}']/../../id/text() | Variable is defined but not assigned |
| XPath Query for Site | Input Variable | delimiter | | | Variable is defined but not assigned |
| XPath Query for Site | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| XPath Query for Site | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| XPath Query for Site | Flow Output Variable | resourceProviderId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Store Resource Details | Flow Output Variable | selectedSubnetpool | Input: field1 | N/A | Flow Output variable created in flow steps |
| Store Resource Details | Flow Output Variable | subentName | Input: field1 | N/A | Flow Output variable created in flow steps |
| Update Valid Provider Pool | Input Variable | resourceBindingXml | | <ResourceBinding> <id>\${resourceBindingId}</id> <validProvider> <resourceBinding> <id>\${resourceBindingId}</id> </resourceBinding> <resourceProvider> <id>\${resourceProviderId}</id> </resourceProvider> <validPool> <id>\${selectedSubnetpool}</id> </validPool> </validProvider> </ ... | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | useCookies | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------------|----------------------|---------------------------|--------|--|
| Update Valid Provider Pool | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | authType | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | resourceBindingId | resourceBindingId | | Input variable is using Prompt User |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get Candidate Providers | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyPassword | | | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------------|----------------------|------------------------------|---|--|
| Get Candidate Providers | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | authType | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | resourceBindingId | resourceBindingId | | Input variable is using Prompt User |
| Get Candidate Providers | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| XPath Query for Subnet | Input Variable | xpathQuery | | /ResourceBinding//candidateProvider/candidatePool/displayName[text()='\${subnet}']/../id/text() | Variable is defined but not assigned |
| XPath Query for Subnet | Input Variable | delimiter | | | Variable is defined but not assigned |
| XPath Query for Subnet | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| XPath Query for Subnet | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| XPath Query for Subnet | Flow Output Variable | resourcePoolID | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Resource Pool | Input Variable | resourceType | | IPv4 Address | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | proxy | | | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------------|----------------------|----------------------------|--------|--|
| Get Resource Pool | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | authType | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Store Resources | Flow Output Variable | Resources | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Resource Pool (CPU) | Input Variable | resourceType | | CPU | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | authType | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------|----------------------|--|-----------|--------------------------------------|
| Get Resource Pool (CPU) | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Resource Pool (CPU) | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | resourceType | | MEMORY | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | authType | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Resource Pool (Memory) | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | resourceType | | STORAGE | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | useCookies | | | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------------|----------------------|----------------------------|--|--|
| Get Resource Pool (Storage) | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | authType | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Resource Pool (Storage) | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Store Resources | Flow Output Variable | Resources | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | requestReference | requestReference | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | subscriptionName | subscriptionName | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | actionProperty | actionProperty | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | authToken | authToken | | Input variable is using Prompt User |
| POST operation | Input Variable | url | | \${HCM/HCM-API-URL}urest/v1.0.0/serviceRequest | Variable is defined but not assigned |
| POST operation | Input Variable | authType | | Basic | Variable is defined but not assigned |
| POST operation | Input Variable | timeout | | | Variable is defined but not assigned |
| POST operation | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| POST operation | Input Variable | characterSet | | | Variable is defined but not assigned |
| Request Id | Input Variable | jsonPathQuery | | \$.@uri | Variable is defined but not assigned |

| | | | | | |
|---------------------|----------------------|----------------------|----------------------------|--|--|
| Request Id | Flow Output Variable | request_id | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | childComponentName | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | childComponentName | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | jsonObject | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | jsonObject | | | Input variable is using Prompt User |
| Get User Identifier | Input Variable | csaUser | | \${CSA_OO_USER} | Variable is defined but not assigned |
| Get User Identifier | Input Variable | timeout | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get User Identifier | Input Variable | proxy | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | authType | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | keystore | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get User Identifier | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${parentComponentId} | Variable is defined but not assigned |

| | | | | | |
|-----------------|----------------|---------------------------|--|--|--------------------------------------|
| Http Client Get | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParams | | userIdentifier=\${userIdentifier}&scope;=Baseplusone | Variable is defined but not assigned |
| Http Client Get | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Get | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |

| | | | | | |
|---------------------------|----------------|----------------------|------------------|-----------|--------------------------------------|
| Http Client Get | Input Variable | method | | GET | Variable is defined but not assigned |
| Update Component Property | Input Variable | onlyUpdate | | yes | Variable is defined but not assigned |
| Update Component Property | Input Variable | displayName | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | valueType | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | separator | | , | Variable is defined but not assigned |
| Update Component Property | Input Variable | consumerVisible | | true | Variable is defined but not assigned |
| Update Component Property | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Component Property | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | authType | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Component Property | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Component Property | Input Variable | componentId | childComponentId | | Input variable is using Prompt User |
| Get Object Keys | Input Variable | object | jsonObject | | Input variable is using Prompt User |
| Array Iterator | Input Variable | array | objectKeys | | Input variable is using Prompt User |

| | | | | | |
|-----------------------|----------------|------------------|----------------|---|--------------------------------------|
| Get Value from Object | Input Variable | object | jsonObject | | Input variable is using Prompt User |
| Get Value from Object | Input Variable | key | propertyName | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | resourcePoolID | resourcePoolID | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | resourceType | resourceType | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | availableValue | availableValue | | Input variable is using Prompt User |
| Http Client Get | Input Variable | url | | \${CSA_REST_URI}/artifact/\${resourcePoolID}?userIdentifier=\${userIdentifier} | Variable is defined but not assigned |
| Http Client Get | Input Variable | userAgent | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | url | | \${CSA_REST_URI}/artifact/\${resourcePoolID}?userIdentifier=\${userIdentifier}&_action_=merge | Variable is defined but not assigned |
| Http Client Put | Input Variable | timeout | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | useCookies | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | file | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | userAgent | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | string | | <ResourcePool> <name>\${name}</name> <displayName>\${displayName}</displayName> <poolReference>\${poolReference}</poolReference> <resourceProvider> <id>\${providerId}</id></resourceProvider> \${actionNode} <state> <name>ACTIVE</name> </state> <disabled>\${disabledState}</disabled> ... | Variable is defined but not assigned |
| Http Client Put | Input Variable | delimiter | | , | Variable is defined but not assigned |

| | | | | | |
|-----------------------|----------------------|--------------------|------------------------|---|--|
| Http Client Put | Flow Output Variable | document | Result Field: document | N/A | Flow Output variable created in flow steps |
| Set Error Message | Flow Output Variable | errorMessage | Input: myValue | N/A | Flow Output variable created in flow steps |
| Get Resource Capacity | Input Variable | xml | document | | Input variable is using Prompt User |
| Set Error Message | Flow Output Variable | errorMessage | Input: myValue | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | resourceBindingId | resourceBindingId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | resourceBindingXml | resourceBindingXml | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Http Client Put | Input Variable | url | | \$(CSA_REST_URI)/artifact/\${resourceBindingId}?userIdentifier=\${userIdentifier}&scope;=view&view;=validproviderspools | Variable is defined but not assigned |
| Http Client Put | Input Variable | timeout | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | useCookies | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | file | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | userAgent | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | string | | \$(resourceBindingXml) | Variable is defined but not assigned |
| Http Client Put | Input Variable | delimiter | | , | Variable is defined but not assigned |
| Http Client Put | Input Variable | chunked | | true | Variable is defined but not assigned |
| Http Client Put | Flow Output Variable | document | Result Field: document | N/A | Flow Output variable created in flow steps |
| Http Client Post | Input Variable | url | | \$(HCM/HCM-API-URL)resource/pool/\${ss}/capacity | Variable is defined but not assigned |
| Http Client Post | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Post | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |

| | | | | | |
|------------------|----------------|--------------------------|--|-----------|--------------------------------------|
| Http Client Post | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Http Client Post | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | tlsVersion | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | allowedCyphers | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Post | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Post | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Post | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParams | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | formParams | | | Variable is defined but not assigned |

| | | | | | |
|------------------|----------------|-------------------------|----------|---|--------------------------------------|
| Http Client Post | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | body | | { "name": null, "description": null, "ext": { "csa_used_by_csa": 0, "csa_available_to_csa": 0 }, "availability": { "displayName": "Available", "ext": { "csa_name_key": "AVAILABLE" } }, "type": { "ext": { ... | Variable is defined but not assigned |
| Http Client Post | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Http Client Post | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Http Client Post | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | method | | POST | Variable is defined but not assigned |
| JSON Path | Input Variable | jsonPathQuery | | \$.type.name | Variable is defined but not assigned |
| JSON Path | Input Variable | json | response | | Input variable is using Prompt User |
| Http Client Post | Input Variable | url | | \$(HCM/HCM-API-URL)resource/pool/ | Variable is defined but not assigned |
| Http Client Post | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Post | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Http Client Post | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | tlsVersion | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | allowedCyphers | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustPassword | | | Variable is defined but not assigned |

| | | | | | |
|------------------|----------------|--------------------------|--|---|--------------------------------------|
| Http Client Post | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Post | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Post | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Post | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParams | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | formParams | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | body | | { "name": "\${resource_pool_name}", "description": null, "enabled": true, "poolReference": "\${resource_pool_name}", "syncAction": null, "provider": { "@self": "/c sa/api/resource/provider/\${provider_id}" } } | Variable is defined but not assigned |
| Http Client Post | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Http Client Post | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Http Client Post | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | method | | POST | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------------|---------------------------|---------------|---|--|
| creating resource pool Info | Flow Output Variable | res_pool_Info | Input: field1 | N/A | Flow Output variable created in flow steps |
| Add Resource Type | Input Variable | Key_name | | IPV4_ADDRESS | Variable is defined but not assigned |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Get Provider Properties | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | headers | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParams | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | method | | GET | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------------|------------------|--------------------------------|---|--|
| Get Provider Properties | Flow Output Variable | error_message | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Provider Details | Flow Output Variable | error_message | Result Field: errorMessage | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamHostname | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamPort | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamProtocol | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamUsername | Result Field: providerUser | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamPassword | Result Field: providerPassword | N/A | Flow Output variable created in flow steps |
| List Iterator | Flow Output Variable | error_message | Result Field: exception | N/A | Flow Output variable created in flow steps |
| String Comparator | Flow Output Variable | error_message | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| fetching provider prop | Flow Output Variable | provider_prop | Input: field1 | N/A | Flow Output variable created in flow steps |
| fetch subnet | Input Variable | xpathQuery | | /ResourceProvider/property/displayName[text()=\$\${ss}]/../values/displayName[text()="subnet"]/../value/text() | Variable is defined but not assigned |
| fetch subnet | Input Variable | delimiter | | | Variable is defined but not assigned |
| fetch subnet | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| fetching provider prop | Flow Output Variable | provider_prop1 | Input: field1 | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | Resource_pool_id | | 2c92d4ba7372ac330173e66ce8077eed | Variable is defined but not assigned |
| Http Client Get | Input Variable | url | | https://mc4t02870.itcs.softwaregrp.net:443/csa/api/resource/pool/\${Resource_pool_id}/capacity | Variable is defined but not assigned |
| Http Client Get | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Get | Input Variable | username | | admin | Variable is defined but not assigned |
| Http Client Get | Input Variable | password | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |

| | | | | | |
|-----------------|----------------|---------------------------|--|--------|--------------------------------------|
| Http Client Get | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | tlsVersion | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | allowedCyphers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Http Client Get | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Get | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParams | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |

| | | | | | |
|------------------|----------------------|------------------------|---------------|--|--|
| Http Client Get | Input Variable | method | | GET | Variable is defined but not assigned |
| Do Nothing | Flow Output Variable | resource_used | Input: field1 | N/A | Flow Output variable created in flow steps |
| Do Nothing | Flow Output Variable | resource_available | Input: field1 | N/A | Flow Output variable created in flow steps |
| Http Client Post | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/filter | Variable is defined but not assigned |
| Http Client Post | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Post | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Http Client Post | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | tlsVersion | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | allowedCyphers | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Post | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Post | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Post | Input Variable | headers | | Accept:application/json content-type:application/json | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------------|--------------------------|----------------------------|---------------------------------------|--|
| Http Client Post | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParams | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | formParams | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | body | | { "providerId": "\${providerId}" } | Variable is defined but not assigned |
| Http Client Post | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Http Client Post | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | method | | POST | Variable is defined but not assigned |
| Http Client Post | Flow Output Variable | error_message | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Loop | Input Variable | reset | | false | Variable is defined but not assigned |
| Loop | Input Variable | to | | \${count} | Variable is defined but not assigned |
| Loop | Input Variable | from | | 0 | Variable is defined but not assigned |
| Loop | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Loop | Flow Output Variable | error_message | Result Field: exception | N/A | Flow Output variable created in flow steps |
| query provder name | Input Variable | jsonPathQuery | | \$.members[\${current_element}].name | Variable is defined but not assigned |
| query provder name | Input Variable | json | response | | Input variable is using Prompt User |
| JSON Path | Input Variable | jsonPathQuery | | \$.members[\${current_element}] | Variable is defined but not assigned |
| JSON Path | Input Variable | json | response | | Input variable is using Prompt User |
| Subtraction | Flow Output Variable | error_message | Result Field: result | N/A | Flow Output variable created in flow steps |
| fetching resource pool list | Flow Output Variable | resorce_pool_list | Input: field1 | N/A | Flow Output variable created in flow steps |
| Http Client Get | Input Variable | url | | \${HCM/HCM-API-URL}resource/provider/ | Variable is defined but not assigned |

| | | | | | |
|-----------------|----------------|------------------------|--|-----------|--------------------------------------|
| Http Client Get | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Get | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | tlsVersion | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | allowedCyphers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Get | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParams | | | Variable is defined but not assigned |

| | | | | | |
|--------------------|----------------------|-------------------------------|-------------------------------|--|--|
| Http Client Get | Input Variable | queryParamsAreURLEn coded | | false | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreFormE ncoded | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | method | | GET | Variable is defined but not assigned |
| Http Client Get | Flow Output Variable | error_message | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Loop | Input Variable | reset | | false | Variable is defined but not assigned |
| Loop | Input Variable | to | | \${count} | Variable is defined but not assigned |
| Loop | Input Variable | from | | 0 | Variable is defined but not assigned |
| Loop | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Loop | Flow Output Variable | error_message | Result Field: result | N/A | Flow Output variable created in flow steps |
| query provder name | Input Variable | jsonPathQuery | | \$.members[\${current_e lement}].name | Variable is defined but not assigned |
| query provder name | Input Variable | json | returnResult | | Input variable is using Prompt User |
| Get provider id | Flow Output Variable | provider_id | Input: field1 | N/A | Flow Output variable created in flow steps |
| JSON Path | Input Variable | jsonPathQuery | | \$.members[\${current_e lement}] | Variable is defined but not assigned |
| JSON Path | Input Variable | json | returnResult | | Input variable is using Prompt User |
| JSON Path | Flow Output Variable | error_message | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Http Client Put | Input Variable | url | | https://\${lpamUrl}:443/w api/v1.4/\${buildUrl} | Variable is defined but not assigned |
| Http Client Put | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Put | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client Put | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |

| | | | | | |
|-----------------|----------------------|------------------------|---------------------------|-----------------|--|
| Http Client Put | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Put | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Put | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Put | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Put | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Put | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Put | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Put | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | body | | \${payloadJson} | Variable is defined but not assigned |
| Http Client Put | Input Variable | contentType | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Http Client Put | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Http Client Put | Input Variable | method | | PUT | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | url | url | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | username | username | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | password | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | ipAddress | ipAddress | | Input variable is using Prompt User |

| | | | | | |
|-----------------------------|----------------------|-----------------|----------------------------|--|--|
| Flow Inputs | Input Variable | hostName | hostName | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | domain | domain | | Input variable is using Prompt User |
| API Call to Add Host Record | Input Variable | url | | <code>\${url}/wapi/v1.4/record:host?_return_type=xml</code> | Variable is defined but not assigned |
| API Call to Add Host Record | Input Variable | body | | <code>{ "ipv4addrs":[{"ipv4addr": "\${ipAddress}"}, {"name": "\${hostName}.\${domain}", "configure_for_dns": true, "view": "\${view}" } }</code> | Variable is defined but not assigned |
| API Call to Add Host Record | Input Variable | method | | POST | Variable is defined but not assigned |
| API Call to Add Host Record | Flow Output Variable | hostrecordXML | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Set Success Message | Flow Output Variable | returnResult | Input: field1 | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | url | url | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | username | username | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | password | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | network | network | | Input variable is using Prompt User |
| API Call to Find Network | Input Variable | url | | <code>\${url}/wapi/v1.4/network?network=\${network}&_return_type=xml&_return_fields=network,extattrs,options</code> | Variable is defined but not assigned |
| API Call to Find Network | Input Variable | username | username | | Input variable is using Prompt User |
| API Call to Find Network | Input Variable | password | password | | Input variable is using Prompt User |
| API Call to Find Network | Flow Output Variable | returnResultXML | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| API Call to Find Network | Flow Output Variable | networkRef | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| API Call to Find Network | Flow Output Variable | extattr | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| API Call to Find Network | Flow Output Variable | routers | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| API Call to Find Network | Flow Output Variable | dnsServers | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Set Success Message | Flow Output Variable | returnResult | Input: field1 | N/A | Flow Output variable created in flow steps |
| SQL Command | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| SQL Command | Input Variable | instance | | | Variable is defined but not assigned |

| | | | | | |
|-----------------|----------------------|---------------------------|------------------------------|---|--|
| SQL Command | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| SQL Command | Input Variable | dbClass | | | Variable is defined but not assigned |
| SQL Command | Input Variable | dbURL | | | Variable is defined but not assigned |
| SQL Command | Input Variable | timeout | | | Variable is defined but not assigned |
| SQL Command | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| SQL Command | Input Variable | resultSetType | | | Variable is defined but not assigned |
| SQL Command | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| SQL Command | Flow Output Variable | errorMsg | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Fetch Host Name | Flow Output Variable | hostname | Input: field1 | N/A | Flow Output variable created in flow steps |
| Http Client Get | Input Variable | url | | https://ipam.softwaregrp.net/wapi/v2.6/ipv4address?network=15.120.170.0/23&status;=UNUSED | Variable is defined but not assigned |
| Http Client Get | Input Variable | username | | api-itsm-cloud | Variable is defined but not assigned |
| Http Client Get | Input Variable | password | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | authType | | basic | Variable is defined but not assigned |
| Http Client Get | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | timeout | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxy | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | userAgent | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystorePassword | | | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------|-------------------|--|------------------------|--------------------------------------|
| Http Client Get | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | headerNamesList | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | headerValuesList | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryNamesList | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryValuesList | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | delimiter | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | useCookies | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | useCookies | | | Input variable is using Prompt User |
| Http Client Get | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | followRedirects | | | Input variable is using Prompt User |
| Http Client Get | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | encodeURL | | | Input variable is using Prompt User |
| Http Client Get | Input Variable | characterSet | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | characterSet | | | Input variable is using Prompt User |
| Http Client Get | Input Variable | trustAllRoots | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustAllRoots | | | Input variable is using Prompt User |
| JSON Path | Input Variable | json | | | Variable is defined but not assigned |
| JSON Path | Input Variable | json | | | Input variable is using Prompt User |
| JSON Path | Input Variable | jsonPathQuery | | | Variable is defined but not assigned |
| JSON Path | Input Variable | jsonPathQuery | | | Input variable is using Prompt User |
| Get Candidate Providers | Input Variable | resourceBindingId | | [TOKEN:RSC_BINDING_ID] | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | useCookies | | | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------------|----------------------|--------------------------------|--------|--|
| Get Candidate Providers | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | authType | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | userIdentifier | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | userIdentifier | | | Input variable is using Prompt User |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Get Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Provider Details | Flow Output Variable | ipamHostname | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamPort | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamProtocol | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamUsername | Result Field: providerUser | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamPassword | Result Field: providerPassword | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-------------------------|----------------|---------------------------|--|---|--------------------------------------|
| Get Provider Properties | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | headers | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParams | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | method | | GET | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------------|-----------------|----------------------------|--|--|
| XPath Query for Zone | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='zone']/../value/text() | Variable is defined but not assigned |
| XPath Query for Zone | Input Variable | delimiter | | | Variable is defined but not assigned |
| XPath Query for Zone | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| XPath Query for Zone | Flow Output Variable | zone | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| XPath Query for SubnetMask | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='subnetMask']/../value/text() | Variable is defined but not assigned |
| XPath Query for SubnetMask | Input Variable | delimiter | | | Variable is defined but not assigned |
| XPath Query for SubnetMask | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| XPath Query for SubnetMask | Flow Output Variable | subnetMask | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| XPath Query for GatewayIp | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='gatewayIp']/../value/text() | Variable is defined but not assigned |
| XPath Query for GatewayIp | Input Variable | delimiter | | | Variable is defined but not assigned |

| | | | | | |
|---------------------------|----------------------|-----------------|----------------------------|--|--|
| XPath Query for GatewayIp | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| XPath Query for GatewayIp | Flow Output Variable | gatewayIp | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| XPath Query for Site | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='site']/../value/text() | Variable is defined but not assigned |
| XPath Query for Site | Input Variable | delimiter | | | Variable is defined but not assigned |
| XPath Query for Site | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| XPath Query for Site | Flow Output Variable | site | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| XPath Query for VLAN | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='vlan']/../value/text() | Variable is defined but not assigned |
| XPath Query for VLAN | Input Variable | delimiter | | | Variable is defined but not assigned |
| XPath Query for VLAN | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| XPath Query for VLAN | Flow Output Variable | vLan | Result Field: returnResult | N/A | Flow Output variable created in flow steps |

| | | | | | |
|----------------------------|----------------------|-----------------|----------------------------|--|--|
| XPath Query for Datacenter | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='datacenter']/../value/text() | Variable is defined but not assigned |
| XPath Query for Datacenter | Input Variable | delimiter | | | Variable is defined but not assigned |
| XPath Query for Datacenter | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| XPath Query for Datacenter | Flow Output Variable | IpamdataCenter | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| XPath Query for Satellite | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='Satellite']/../value/text() | Variable is defined but not assigned |
| XPath Query for Satellite | Input Variable | delimiter | | | Variable is defined but not assigned |
| XPath Query for Satellite | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| XPath Query for Satellite | Flow Output Variable | satellite | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Resource Pool | Input Variable | resourceType | | IPv4 Address | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | proxyPort | | | Variable is defined but not assigned |

| | | | | | |
|-------------------|----------------------|----------------------|-----------------------------|---|--|
| Get Resource Pool | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | authType | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Resource Pool | Input Variable | resourcePoolID | resourcePoolID | | Input variable is using Prompt User |
| Get Resource Pool | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Resource Pool | Flow Output Variable | subnet | Result Field: poolReference | N/A | Flow Output variable created in flow steps |
| Http Client Get | Input Variable | url | | \${IPAM/Protocol}://\${IPAM/IPAM_Hostname}/wapi/v2.6/ipv4address?network=\${subnet}&status=UNUSED&_max_results=100000 | Variable is defined but not assigned |
| Http Client Get | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Get | Input Variable | username | | api-itsm-cloud | Variable is defined but not assigned |
| Http Client Get | Input Variable | password | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPassword | | | Variable is defined but not assigned |

| | | | | | |
|-------------------|----------------------|---------------------------|----------------------------|-----------|--|
| Http Client Get | Input Variable | tlsVersion | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | allowedCyphers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Get | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParams | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | method | | GET | Variable is defined but not assigned |
| Http Client Get | Flow Output Variable | error_message | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Do Nothing | Flow Output Variable | update_status | Input: field1 | N/A | Flow Output variable created in flow steps |
| String Comparator | Flow Output Variable | error_message | Result Field: returnResult | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-----------------|----------------|------------------------|--|--|--------------------------------------|
| JSON Path | Input Variable | jsonPathQuery | | \$.[?(@.network=='\${subnet}')].status | Variable is defined but not assigned |
| Flow Inputs | Input Variable | subnet | | 15.120.128.0/21 | Variable is defined but not assigned |
| Http Client Get | Input Variable | url | | https://ipam.softwaregrp.net/wapi/v2.6/ipv4address?network=\${subnet}&status=USED&_max_results=10000 | Variable is defined but not assigned |
| Http Client Get | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Get | Input Variable | username | | api-itsm-cloud | Variable is defined but not assigned |
| Http Client Get | Input Variable | password | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | tlsVersion | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | allowedCyphers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------------|---------------------------|--------------------------------|--|--|
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Get | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParams | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | method | | GET | Variable is defined but not assigned |
| Array Iterator | Input Variable | array | response | | Input variable is using Prompt User |
| JSON Path | Input Variable | jsonPathQuery | | \$.status | Variable is defined but not assigned |
| Do Nothing | Flow Output Variable | unused_ip | Input: field1 | N/A | Flow Output variable created in flow steps |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Get Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Provider Details | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamHostname | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamPort | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamProtocol | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamUsername | Result Field: providerUser | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamPassword | Result Field: providerPassword | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Input Variable | url | | \$(HCM/HCM-REST-URL)artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------------|---------------------------|----------------------------|---|--|
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | headers | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParams | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | method | | GET | Variable is defined but not assigned |
| Get Provider Properties | Flow Output Variable | failureMessage | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| XPath Query for Subnet | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='site']/../value[text()='\${site}']/../values/displayName[text()='subnet']/../value/text() | Variable is defined but not assigned |
| XPath Query for Subnet | Input Variable | delimiter | | | Variable is defined but not assigned |

| | | | | | |
|------------------------|----------------------|-----------------|------------------------------|---|---|
| XPath Query for Subnet | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| XPath Query for Subnet | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| XPath Query for Subnet | Flow Output Variable | subnet | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Find Network | Input Variable | url | url | | Input variable is using Prompt User |
| Find Network | Input Variable | username | username | | Input variable is using Prompt User |
| Find Network | Input Variable | password | password | | Input variable is using Prompt User |
| Find Network | Input Variable | network | network | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | url | url | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | username | username | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | password | password | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | networkRef | networkRef | | Input variable is using Prompt User |
| Get Next Available IP | Flow Output Variable | nextIp | Result: availableIpXML | N/A | Flow Output variable created in flow steps |
| Add Host Record | Input Variable | url | url | | Input variable is using Prompt User |
| Add Host Record | Input Variable | ipAddress | nextIp | | Input variable is using Prompt User |
| Add Host Record | Input Variable | hostName | hostname | | Input variable is using Prompt User |
| Add Host Record | Input Variable | domain | zone | | Input variable is using Prompt User |
| Add Host Record | Flow Output Variable | hostRecord | Result: hostrecordXML | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | resourcePoolID | | 2c92d4ba7372ac3301740599dbe73c1d | Variable is defined but not assigned |
| Flow Inputs | Input Variable | usedValue | | 100 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | availableValue | | 200 | Variable is defined but not assigned |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |

| | | | | | |
|----------------------------------|----------------|----------------------|----------------|--------------|--------------------------------------|
| Update Resource Pool Capacity | Input Variable | resourceType | | IPV4_ADDRESS | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | authType | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Update Resource Pool Utilization | Input Variable | resourceType | | IPV4_ADDRESS | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyUsername | | | Variable is defined but not assigned |

| | | | | | |
|--|----------------|----------------------|----------------|----------|--------------------------------------|
| Update Resource Pool Utilization | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | authType | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | resourcePoolID | resourcePoolID | | Input variable is using Prompt User |
| Update Resource Pool Utilization | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Update Resource Pool Utilization | Input Variable | usedValue | usedValue | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | host | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | attachableType | | SERVER | Variable is defined but not assigned |
| Flow Inputs | Input Variable | separator | | , | Variable is defined but not assigned |
| Attach Software Policy | Input Variable | attachableType | | SERVER | Variable is defined but not assigned |
| Attach Software Policy | Input Variable | separator | | , | Variable is defined but not assigned |
| Attach Software Policy | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Attach Software Policy | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Attach Software Policy | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Remediate Server For Software Policies | Input Variable | wait | | 360000 | Variable is defined but not assigned |
| Remediate Server For Software Policies | Input Variable | rebootOption | | suppress | Variable is defined but not assigned |
| Remediate Server For Software Policies | Input Variable | continueOnFailure | | false | Variable is defined but not assigned |
| Remediate Server For Software Policies | Input Variable | separator | | , | Variable is defined but not assigned |

| | | | | | |
|--|----------------------|----------------|------------------------------|-----------|--|
| Remediate Server For Software Policies | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Remediate Server For Software Policies | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Remediate Server For Software Policies | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Remediate Server For Software Policies | Flow Output Variable | jobId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Remediate Server For Software Policies | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | jobID | | \${jobId} | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Wait for Job | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Wait for Job | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Detach Software Policy | Input Variable | attachableType | | SERVER | Variable is defined but not assigned |
| Detach Software Policy | Input Variable | separator | | , | Variable is defined but not assigned |
| Detach Software Policy | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Detach Software Policy | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Detach Software Policy | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Detach Software Policy | Input Variable | coreVersion | coreVersion | | Input variable is using Prompt User |
| Detach Software Policy | Input Variable | policyName | policyName | | Input variable is using Prompt User |
| Detach Software Policy | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| jobs | Input Variable | serverName | | | Variable is defined but not assigned |
| jobs | Input Variable | separator | | , | Variable is defined but not assigned |
| jobs | Flow Output Variable | sucessServers | Result Field: successServers | N/A | Flow Output variable created in flow steps |
| jobs | Flow Output Variable | failureMessage | Result Field: failureMessage | N/A | Flow Output variable created in flow steps |
| jobs | Flow Output Variable | failureServer | Result Field: failureServers | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-----------------------------------|----------------------|-------------------------------|------------------------------|--------|--|
| Flow Inputs | Input Variable | host | host | | Input variable is using Prompt User |
| Start Server Script | Input Variable | scriptToRunID | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHosts | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHostSearchOperator | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetUser | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetPassword | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetDomain | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | args | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessRecipients | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | ticketId | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTailOutputSize | | | Variable is defined but not assigned |
| Start Server Script | Flow Output Variable | failureMeesage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Script Job Result | Flow Output Variable | failureMessage | Result Field: error | N/A | Flow Output variable created in flow steps |
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | 180000 | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Wait for Job | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Exit code check | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | serverName | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Remediate Policies Job Result | Input Variable | serverName | | | Variable is defined but not assigned |
| Get Remediate Policies Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Remediate Policies Job Result | Flow Output Variable | jobResult | Result Field: Result | N/A | Flow Output variable created in flow steps |
| Count | Input Variable | from | | 1 | Variable is defined but not assigned |

| | | | | | |
|-----------------------|----------------------|-------------------------------|------------------------------|--------|--|
| Count | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Count | Input Variable | reset | | false | Variable is defined but not assigned |
| Decode Servers | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Decode Servers | Input Variable | coreVersion | coreVersion | | Input variable is using Prompt User |
| Decode Servers | Flow Output Variable | failureMessage | Result Field: failureServers | N/A | Flow Output variable created in flow steps |
| Decode Servers | Flow Output Variable | successServers | Result Field: successServers | N/A | Flow Output variable created in flow steps |
| Decode Servers | Flow Output Variable | failureServers | Result Field: failureServers | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | corePassword | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptToRunID | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHostSearchOperator | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetUser | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetPassword | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetDomain | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | args | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessRecipients | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | ticketId | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTailOutputSize | | | Variable is defined but not assigned |
| Start Server Script | Flow Output Variable | failureMessage | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Start Server Script | Flow Output Variable | jobid | Result Field: id | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Script Job Result | Flow Output Variable | failureMessage | Result Field: summary | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Flow Output Variable | output | Result Field: output | N/A | Flow Output variable created in flow steps |
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | 600000 | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |

| | | | | | |
|--------------------------------------|----------------------|----------------------------------|---------------------------------|---|---|
| Exit code check | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | coreUsername | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | corePassword | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| OverallStatus | Input Variable | jsonPathQuery | | \$.baseSteps[0].overallS erverStatus | Variable is defined but not assigned |
| ServerID | Input Variable | jsonPathQuery | | \$.serverId: | Variable is defined but not assigned |
| Collect Server Names for Failures | Flow Output Variable | failureServers | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Collect Server Name for Success | Flow Output Variable | successServers | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| coGet Server VO | Input Variable | matching | | Begins With | Variable is defined but not assigned |
| coGet Server VO | Input Variable | delimiter | | ; | Variable is defined but not assigned |
| coGet Server VO | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| coGet Server VO | Input Variable | coreVersion | coreVersion | | Input variable is using Prompt User |
| coGet Server VO | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| coGet Server VO | Input Variable | matching | | Begins With | Variable is defined but not assigned |
| coGet Server VO | Input Variable | delimiter | | ; | Variable is defined but not assigned |
| coGet Server VO | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| coGet Server VO | Input Variable | coreVersion | coreVersion | | Input variable is using Prompt User |
| coGet Server VO | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Start Server Script | Input Variable | scriptToRunID | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHostSearchOpera tor | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetUser | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetPassword | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetDomain | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessReci pents | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | ticketId | | | Variable is defined but not assigned |

| | | | | | |
|-----------------------|----------------------|-------------------------------|------------------------------|--------|--|
| Start Server Script | Input Variable | scriptTailOutputSize | | | Variable is defined but not assigned |
| Start Server Script | Flow Output Variable | failureMessage | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Start Server Script | Flow Output Variable | jobid | Result Field: id | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Script Job Result | Flow Output Variable | failureMessage | Result Field: summary | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Flow Output Variable | output | Result Field: output | N/A | Flow Output variable created in flow steps |
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Exit code check | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | host | host | | Input variable is using Prompt User |
| Start Server Script | Input Variable | scriptToRunID | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHostSearchOperator | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetUser | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetPassword | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetDomain | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | args | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessRecipients | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | ticketId | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTailOutputSize | | | Variable is defined but not assigned |
| Start Server Script | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Script Job Result | Flow Output Variable | failureMessage | Result Field: error | N/A | Flow Output variable created in flow steps |
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | 180000 | Variable is defined but not assigned |

| | | | | | |
|--|----------------------|-------------------|------------------------------|-----------|--|
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Wait for Job | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Exit code check | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | attachableType | | SERVER | Variable is defined but not assigned |
| Flow Inputs | Input Variable | separator | | , | Variable is defined but not assigned |
| Attach Software Policy | Input Variable | attachableType | | SERVER | Variable is defined but not assigned |
| Attach Software Policy | Input Variable | separator | | , | Variable is defined but not assigned |
| Attach Software Policy | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Attach Software Policy | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Attach Software Policy | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Remediate Server For Software Policies | Input Variable | serverName | | | Variable is defined but not assigned |
| Remediate Server For Software Policies | Input Variable | wait | | 360000 | Variable is defined but not assigned |
| Remediate Server For Software Policies | Input Variable | rebootOption | | suppress | Variable is defined but not assigned |
| Remediate Server For Software Policies | Input Variable | continueOnFailure | | false | Variable is defined but not assigned |
| Remediate Server For Software Policies | Input Variable | separator | | , | Variable is defined but not assigned |
| Remediate Server For Software Policies | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Remediate Server For Software Policies | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Remediate Server For Software Policies | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Remediate Server For Software Policies | Flow Output Variable | jobId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | jobID | | \${jobId} | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Wait for Job | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |

| | | | | | |
|------------------------|----------------------|----------------|------------------------------|--|--|
| Wait for Job | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Detach Software Policy | Input Variable | attachableType | | SERVER | Variable is defined but not assigned |
| Detach Software Policy | Input Variable | separator | | , | Variable is defined but not assigned |
| Detach Software Policy | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Detach Software Policy | Input Variable | policyName | policyName | | Input variable is using Prompt User |
| Detach Software Policy | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| jobs | Input Variable | serverName | | | Variable is defined but not assigned |
| jobs | Input Variable | separator | | , | Variable is defined but not assigned |
| jobs | Flow Output Variable | failureMessage | Result Field: failureServers | N/A | Flow Output variable created in flow steps |
| jobs | Flow Output Variable | sucessServers | Result Field: successServers | N/A | Flow Output variable created in flow steps |
| jobs | Flow Output Variable | failureServer | Result Field: failureServers | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | host | host | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | username | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | username | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | password | | | Input variable is using Prompt User |
| SSH Command | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Command | Input Variable | username | | postgres | Variable is defined but not assigned |
| SSH Command | Input Variable | command | | psql -t -P format=unaligned -c 'show hba_file' | Variable is defined but not assigned |
| SSH Command | Input Variable | timeout | | 90000 | Variable is defined but not assigned |
| SSH Command | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| SSH Command | Input Variable | pty | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | connectTimeout | | 10000 | Variable is defined but not assigned |
| SSH Command | Input Variable | keepAlive | | 0 | Variable is defined but not assigned |
| SSH Command | Input Variable | closeSession | | false | Variable is defined but not assigned |

| | | | | | |
|---------------------|----------------|------------------|-----------|--|--------------------------------------|
| SSH Command | Input Variable | useGlobalContext | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Command | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Shell Logon | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | username | username | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | password | password | | Input variable is using Prompt User |
| Configure Postgress | Input Variable | port | | 22 | Variable is defined but not assigned |
| Configure Postgress | Input Variable | command | | send sudo yum install -y expect expectEndsWith : send HCMAdmin+123 expectEndsWith \$ send sudo passwd postgres expectEndsWith password: send HCMAdmin+123 expectendswith password: send HCMAdmin+123 expectEndsWith \$ send su - postgres expectendswith Password: send HCMAdmin+123 expectEndsWith \$ send psq ... | Variable is defined but not assigned |
| Configure Postgress | Input Variable | timeout | | 5400000 | Variable is defined but not assigned |
| Configure Postgress | Input Variable | readTimeout | | 3600000 | Variable is defined but not assigned |
| Configure Postgress | Input Variable | host | host | | Input variable is using Prompt User |
| Configure Postgress | Input Variable | username | username | | Input variable is using Prompt User |
| Configure Postgress | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Shell Logoff | Input Variable | sessionId | sessionId | | Input variable is using Prompt User |
| SSH Command | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Command | Input Variable | username | | postgres | Variable is defined but not assigned |
| SSH Command | Input Variable | command | | psql -t -P format=unaligned -c 'show hba_file' | Variable is defined but not assigned |

| | | | | | |
|------------------|----------------|------------------|----------|--|--------------------------------------|
| SSH Command | Input Variable | timeout | | 90000 | Variable is defined but not assigned |
| SSH Command | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| SSH Command | Input Variable | pty | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | connectTimeout | | 10000 | Variable is defined but not assigned |
| SSH Command | Input Variable | keepAlive | | 0 | Variable is defined but not assigned |
| SSH Command | Input Variable | closeSession | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | useGlobalContext | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Command | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Shell Logon | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | username | username | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | password | password | | Input variable is using Prompt User |
| Create Databases | Input Variable | port | | 22 | Variable is defined but not assigned |
| Create Databases | Input Variable | command | | send su - postgres expectendswith Password: send HCMAdmin+123 expectEndsWith \$ send psql -U postgres expectEndsWith # send create user dcaadmin login password 'HCMAdmin+123'; expectEndsWith # send CREATE DATABASE dca_db with OWNER='dcaadmin'; expectEndsWith # send CREATE DATABASE ucmdb with OWNER='d ... | Variable is defined but not assigned |
| Create Databases | Input Variable | timeout | | 5400000 | Variable is defined but not assigned |
| Create Databases | Input Variable | readTimeout | | 3600000 | Variable is defined but not assigned |
| Create Databases | Input Variable | host | host | | Input variable is using Prompt User |
| Create Databases | Input Variable | username | username | | Input variable is using Prompt User |

| | | | | | |
|-------------------|----------------|------------------|-----------|---|--------------------------------------|
| Create Databases | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Shell Logoff | Input Variable | sessionId | sessionId | | Input variable is using Prompt User |
| Update configFile | Input Variable | port | | 22 | Variable is defined but not assigned |
| Update configFile | Input Variable | command | | send su - postgres expectendswith Password: send HCMAAdmin+123 expectEndsWith \$ send echo '# Required by DCA components' >> \${hbaConfig} expectEndsWith \$ send echo 'host dca_db dcaadmin 0.0.0.0/0 md5' >> \${hbaConfig} expectEndsWith \$ send echo 'host ucldb dcaadmin 0.0.0.0/0 md5' >> \${hbaConfig} expec ... | Variable is defined but not assigned |
| Update configFile | Input Variable | timeout | | 5400000 | Variable is defined but not assigned |
| Update configFile | Input Variable | readTimeout | | 3600000 | Variable is defined but not assigned |
| Update configFile | Input Variable | host | host | | Input variable is using Prompt User |
| Update configFile | Input Variable | username | username | | Input variable is using Prompt User |
| Update configFile | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Command | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Command | Input Variable | username | | postgres | Variable is defined but not assigned |
| SSH Command | Input Variable | command | | systemctl list-units grep postgresql | Variable is defined but not assigned |
| SSH Command | Input Variable | timeout | | 90000 | Variable is defined but not assigned |
| SSH Command | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| SSH Command | Input Variable | pty | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | connectTimeout | | 10000 | Variable is defined but not assigned |
| SSH Command | Input Variable | keepAlive | | 0 | Variable is defined but not assigned |
| SSH Command | Input Variable | closeSession | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | useGlobalContext | | false | Variable is defined but not assigned |

| | | | | | |
|-------------|----------------|------------------|----------|------------------------------|--------------------------------------|
| SSH Command | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Command | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Command | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Command | Input Variable | username | | postgres | Variable is defined but not assigned |
| SSH Command | Input Variable | command | | systemctl stop firewallld | Variable is defined but not assigned |
| SSH Command | Input Variable | timeout | | 90000 | Variable is defined but not assigned |
| SSH Command | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| SSH Command | Input Variable | pty | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | connectTimeout | | 10000 | Variable is defined but not assigned |
| SSH Command | Input Variable | keepAlive | | 0 | Variable is defined but not assigned |
| SSH Command | Input Variable | closeSession | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | useGlobalContext | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Command | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Command | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Command | Input Variable | username | | postgres | Variable is defined but not assigned |
| SSH Command | Input Variable | command | | systemctl disable firewallld | Variable is defined but not assigned |
| SSH Command | Input Variable | timeout | | 90000 | Variable is defined but not assigned |
| SSH Command | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| SSH Command | Input Variable | pty | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | connectTimeout | | 10000 | Variable is defined but not assigned |
| SSH Command | Input Variable | keepAlive | | 0 | Variable is defined but not assigned |
| SSH Command | Input Variable | closeSession | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | useGlobalContext | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | host | host | | Input variable is using Prompt User |

| | | | | | |
|------------------------|----------------|-------------|----------|---|--------------------------------------|
| SSH Command | Input Variable | password | password | | Input variable is using Prompt User |
| Create configFile | Input Variable | port | | 22 | Variable is defined but not assigned |
| Create configFile | Input Variable | command | | send sudo su - expectendswith \${username}: send HCMAdmin+123 expectEndsWith # send echo '### KERNEL TUNING FOR DCA POSTGRESQL ###' > / etc/sysctl.d/90-postgresql.conf expectEndsWith # send echo " >> /etc/sysctl.d/90-postgresql.conf expectEndsWith # send echo '# Size of a shared memory segment' >> /e ... | Variable is defined but not assigned |
| Create configFile | Input Variable | timeout | | 1500 | Variable is defined but not assigned |
| Create configFile | Input Variable | readTimeout | | 1500 | Variable is defined but not assigned |
| Create configFile | Input Variable | host | host | | Input variable is using Prompt User |
| Create configFile | Input Variable | username | username | | Input variable is using Prompt User |
| Create configFile | Input Variable | password | password | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | host | host | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | username | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | username | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | password | | | Input variable is using Prompt User |
| Configure CDF Postgres | Input Variable | username | username | | Input variable is using Prompt User |
| Configure CDF Postgres | Input Variable | password | password | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | host | host | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | username | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | username | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | | | Variable is defined but not assigned |

| | | | | | |
|------------------|----------------|------------------|----------|---|--------------------------------------|
| Flow Inputs | Input Variable | password | | | Input variable is using Prompt User |
| SSH Command | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Command | Input Variable | username | | postgres | Variable is defined but not assigned |
| SSH Command | Input Variable | command | | psql -t -P format=unaligned -c 'show hba_file' | Variable is defined but not assigned |
| SSH Command | Input Variable | timeout | | 90000 | Variable is defined but not assigned |
| SSH Command | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| SSH Command | Input Variable | pty | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | connectTimeout | | 10000 | Variable is defined but not assigned |
| SSH Command | Input Variable | keepAlive | | 0 | Variable is defined but not assigned |
| SSH Command | Input Variable | closeSession | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | useGlobalContext | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Command | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Shell Logon | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | username | username | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | password | password | | Input variable is using Prompt User |
| Create Databases | Input Variable | port | | 22 | Variable is defined but not assigned |
| Create Databases | Input Variable | command | | send su - postgres expectendswith Password: send HCMAdmin+123 expectEndsWith \$ send psql -U postgres expectEndsWith # send create user hcmadmin login password 'HCMAdmin+123' inherit; expectEndsWith # send GRANT cdfidmuser to postgres; expectEndsWith # send create database csa with owner=hcmadmin; ex ... | Variable is defined but not assigned |

| | | | | | |
|-------------------|----------------|--------------|-----------|--|--------------------------------------|
| Create Databases | Input Variable | timeout | | 5400000 | Variable is defined but not assigned |
| Create Databases | Input Variable | readTimeout | | 3600000 | Variable is defined but not assigned |
| Create Databases | Input Variable | host | host | | Input variable is using Prompt User |
| Create Databases | Input Variable | username | username | | Input variable is using Prompt User |
| Create Databases | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Shell Logoff | Input Variable | sessionId | sessionId | | Input variable is using Prompt User |
| Update configFile | Input Variable | port | | 22 | Variable is defined but not assigned |
| Update configFile | Input Variable | command | | <pre> send su - postgres expectendswith Password: send HCMAAdmin+123 expectEndsWith \$ send echo 'hostnoss! all all 0.0.0.0/0 trust' >> \${hbaConfig} expectEndsWith \$ send sed -e '/max_connectio ns/s/^/#/1' -i \${sqlConfig} expectEndsWith \$ send sed -e '/shared_buffers/s/^/#/1' -i \${sqlConfig} expectEndsWith \$... </pre> | Variable is defined but not assigned |
| Update configFile | Input Variable | timeout | | 12000 | Variable is defined but not assigned |
| Update configFile | Input Variable | readTimeout | | 12000 | Variable is defined but not assigned |
| Update configFile | Input Variable | host | host | | Input variable is using Prompt User |
| Update configFile | Input Variable | username | username | | Input variable is using Prompt User |
| Update configFile | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Command | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Command | Input Variable | username | | postgres | Variable is defined but not assigned |
| SSH Command | Input Variable | command | | systemctl list-units grep postgresql | Variable is defined but not assigned |
| SSH Command | Input Variable | timeout | | 90000 | Variable is defined but not assigned |
| SSH Command | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| SSH Command | Input Variable | pty | | false | Variable is defined but not assigned |

| | | | | | |
|-------------|----------------|------------------|----------|-----------------------------|--------------------------------------|
| SSH Command | Input Variable | connectTimeout | | 10000 | Variable is defined but not assigned |
| SSH Command | Input Variable | keepAlive | | 0 | Variable is defined but not assigned |
| SSH Command | Input Variable | closeSession | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | useGlobalContext | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Command | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Command | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Command | Input Variable | username | | postgres | Variable is defined but not assigned |
| SSH Command | Input Variable | command | | systemctl stop firewalld | Variable is defined but not assigned |
| SSH Command | Input Variable | timeout | | 90000 | Variable is defined but not assigned |
| SSH Command | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| SSH Command | Input Variable | pty | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | connectTimeout | | 10000 | Variable is defined but not assigned |
| SSH Command | Input Variable | keepAlive | | 0 | Variable is defined but not assigned |
| SSH Command | Input Variable | closeSession | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | useGlobalContext | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Command | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Command | Input Variable | port | | 22 | Variable is defined but not assigned |
| SSH Command | Input Variable | username | | postgres | Variable is defined but not assigned |
| SSH Command | Input Variable | command | | systemctl disable firewalld | Variable is defined but not assigned |
| SSH Command | Input Variable | timeout | | 90000 | Variable is defined but not assigned |
| SSH Command | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| SSH Command | Input Variable | pty | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | connectTimeout | | 10000 | Variable is defined but not assigned |

| | | | | | |
|-------------------------------|----------------|------------------|----------|--|--------------------------------------|
| SSH Command | Input Variable | keepAlive | | 0 | Variable is defined but not assigned |
| SSH Command | Input Variable | closeSession | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | useGlobalContext | | false | Variable is defined but not assigned |
| SSH Command | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Command | Input Variable | password | password | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | host | host | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | username | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | username | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | password | | | Input variable is using Prompt User |
| Configure HCM Postgres | Input Variable | configpath | | /var/lib/pgsql/10/data/pg_hba.conf | Variable is defined but not assigned |
| Flow Inputs | Input Variable | username | | sup_rajeshsingh | Variable is defined but not assigned |
| Flow Inputs | Input Variable | password | | | Variable is defined but not assigned |
| Yum Update all | Input Variable | port | | 22 | Variable is defined but not assigned |
| Yum Update all | Input Variable | command | | echo \${password} sudo -S yum update -y | Variable is defined but not assigned |
| Yum Update all | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Yum Update all | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Yum Update all | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Yum Update all | Input Variable | host | host | | Input variable is using Prompt User |
| Yum Install postgresql-server | Input Variable | port | | 22 | Variable is defined but not assigned |
| Yum Install postgresql-server | Input Variable | command | | echo \${password} sudo -S yum install -y postgresql10-server postgresql10 postgresql10-contrib | Variable is defined but not assigned |
| Yum Install postgresql-server | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Yum Install postgresql-server | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Yum Install postgresql-server | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |

| | | | | | |
|-------------------------------------|----------------|----------------|------|---|--------------------------------------|
| Yum Install postgresql-server | Input Variable | host | host | | Input variable is using Prompt User |
| Initialize the DB | Input Variable | port | | 22 | Variable is defined but not assigned |
| Initialize the DB | Input Variable | command | | echo \${password} sudo -S /usr/pgsq-10/bin/postgresql-10-setup initdb | Variable is defined but not assigned |
| Initialize the DB | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Initialize the DB | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Initialize the DB | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Initialize the DB | Input Variable | host | host | | Input variable is using Prompt User |
| Start the DB | Input Variable | port | | 22 | Variable is defined but not assigned |
| Start the DB | Input Variable | command | | echo \${password} sudo -S systemctl start postgresql-10.service | Variable is defined but not assigned |
| Start the DB | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Start the DB | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Start the DB | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Start the DB | Input Variable | host | host | | Input variable is using Prompt User |
| Start the Service at System Startup | Input Variable | port | | 22 | Variable is defined but not assigned |
| Start the Service at System Startup | Input Variable | command | | echo \${password} sudo -S systemctl enable postgresql-10.service | Variable is defined but not assigned |
| Start the Service at System Startup | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Start the Service at System Startup | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Start the Service at System Startup | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Start the Service at System Startup | Input Variable | host | host | | Input variable is using Prompt User |
| check the Service Status | Input Variable | port | | 22 | Variable is defined but not assigned |
| check the Service Status | Input Variable | command | | echo \${password} sudo -S systemctl status postgresql-10.service | Variable is defined but not assigned |
| check the Service Status | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |

| | | | | | |
|-------------------------------|----------------|----------------|------|---|--------------------------------------|
| check the Service Status | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| check the Service Status | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | port | | 22 | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | command | | echo \${password} sudo -S yum install -y ht tps://download.postgres ql.org/pub/repos/yum/re porpms/EL-7-x86_64/p gdg-redhat-repo-latest. noarch.rpm | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | host | host | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | username | | sup_rajeshsingh | Variable is defined but not assigned |
| Flow Inputs | Input Variable | password | | | Variable is defined but not assigned |
| Yum Update all | Input Variable | port | | 22 | Variable is defined but not assigned |
| Yum Update all | Input Variable | command | | echo \${password} sudo -S yum update -y | Variable is defined but not assigned |
| Yum Update all | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Yum Update all | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Yum Update all | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Yum Update all | Input Variable | host | host | | Input variable is using Prompt User |
| Yum Install postgresql-server | Input Variable | port | | 22 | Variable is defined but not assigned |
| Yum Install postgresql-server | Input Variable | command | | echo \${password} sudo -S yum install -y postgresql10-server postgresql10 postgresql10-contrib | Variable is defined but not assigned |
| Yum Install postgresql-server | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Yum Install postgresql-server | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Yum Install postgresql-server | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Yum Install postgresql-server | Input Variable | host | host | | Input variable is using Prompt User |

| | | | | | |
|-------------------------------------|----------------|----------------|------|--|--------------------------------------|
| Initialize the DB | Input Variable | port | | 22 | Variable is defined but not assigned |
| Initialize the DB | Input Variable | command | | echo \${password} sudo -S /usr/pgsql-10/bin/postgresql-10-setup initdb | Variable is defined but not assigned |
| Initialize the DB | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Initialize the DB | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Initialize the DB | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Initialize the DB | Input Variable | host | host | | Input variable is using Prompt User |
| Start the DB | Input Variable | port | | 22 | Variable is defined but not assigned |
| Start the DB | Input Variable | command | | echo \${password} sudo -S systemctl start postgresql-10.service | Variable is defined but not assigned |
| Start the DB | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Start the DB | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Start the DB | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Start the DB | Input Variable | host | host | | Input variable is using Prompt User |
| Start the Service at System Startup | Input Variable | port | | 22 | Variable is defined but not assigned |
| Start the Service at System Startup | Input Variable | command | | echo \${password} sudo -S systemctl enable postgresql-10.service | Variable is defined but not assigned |
| Start the Service at System Startup | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Start the Service at System Startup | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Start the Service at System Startup | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Start the Service at System Startup | Input Variable | host | host | | Input variable is using Prompt User |
| check the Service Status | Input Variable | port | | 22 | Variable is defined but not assigned |
| check the Service Status | Input Variable | command | | echo \${password} sudo -S systemctl status postgresql-10.service | Variable is defined but not assigned |
| check the Service Status | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| check the Service Status | Input Variable | timeout | | 300000 | Variable is defined but not assigned |

| | | | | | |
|--------------------------|----------------|----------------|------|--|--------------------------------------|
| check the Service Status | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | port | | 22 | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | command | | echo \${password} sudo -S rpm -Uvh https://yum.postgresql.org/10/redhat/rhel-7-x86_64/pgdg-centos10-10-2.noarch.rpm | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Setup Repo for PG 10 | Input Variable | host | host | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | username | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | username | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | password | | | Input variable is using Prompt User |
| Start the DB | Input Variable | port | | 22 | Variable is defined but not assigned |
| Start the DB | Input Variable | command | | echo \${password} sudo -S systemctl start postgresql | Variable is defined but not assigned |
| Start the DB | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Start the DB | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Start the DB | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Start the DB | Input Variable | host | host | | Input variable is using Prompt User |
| check the Service Status | Input Variable | port | | 22 | Variable is defined but not assigned |
| check the Service Status | Input Variable | command | | echo \${password} sudo -S systemctl status postgresql | Variable is defined but not assigned |
| check the Service Status | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| check the Service Status | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| check the Service Status | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Sleep for 15 sec | Input Variable | seconds | | 15 | Variable is defined but not assigned |

| | | | | | |
|--------------------------|----------------|----------------|------|---|--------------------------------------|
| Loop | Input Variable | count | | 5 | Variable is defined but not assigned |
| Loop | Input Variable | reset | | false | Variable is defined but not assigned |
| Loop | Input Variable | to | | \${count} | Variable is defined but not assigned |
| Loop | Input Variable | from | | 1 | Variable is defined but not assigned |
| Loop | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Sleep for 15 sec | Input Variable | seconds | | 15 | Variable is defined but not assigned |
| Start the DB | Input Variable | port | | 22 | Variable is defined but not assigned |
| Start the DB | Input Variable | command | | echo \${password} sudo -S systemctl start postgresql | Variable is defined but not assigned |
| Start the DB | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Start the DB | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Start the DB | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Start the DB | Input Variable | host | host | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | username | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | username | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | password | | | Input variable is using Prompt User |
| Stop the DB | Input Variable | port | | 22 | Variable is defined but not assigned |
| Stop the DB | Input Variable | command | | echo \${password} sudo -S systemctl stop postgresql | Variable is defined but not assigned |
| Stop the DB | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Stop the DB | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Stop the DB | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Stop the DB | Input Variable | host | host | | Input variable is using Prompt User |
| check the Service Status | Input Variable | port | | 22 | Variable is defined but not assigned |
| check the Service Status | Input Variable | command | | echo \${password} sudo -S systemctl status postgresql | Variable is defined but not assigned |

| | | | | | |
|---------------------------|----------------|----------------|----------|---|--------------------------------------|
| check the Service Status | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| check the Service Status | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| check the Service Status | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Sleep for 15 sec | Input Variable | seconds | | 15 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | username | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | username | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | password | | | Input variable is using Prompt User |
| Yum Remove Postgresql | Input Variable | port | | 22 | Variable is defined but not assigned |
| Yum Remove Postgresql | Input Variable | command | | echo \${password} sudo -S yum remove -y postgresql10.x86_64 po stgresql10-libs.x86_64 postgresql10-contrib.x8 6_64 | Variable is defined but not assigned |
| Yum Remove Postgresql | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Yum Remove Postgresql | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Yum Remove Postgresql | Input Variable | connectTimeout | | 300000 | Variable is defined but not assigned |
| Yum Remove Postgresql | Input Variable | host | host | | Input variable is using Prompt User |
| Remove Postgres Directory | Input Variable | port | | 22 | Variable is defined but not assigned |
| Remove Postgres Directory | Input Variable | command | | send su - postgres expectendswith Password: send HCMAAdmin+123 expectEndsWith \$ send rm -rf /var/lib/pgsql/10/ | Variable is defined but not assigned |
| Remove Postgres Directory | Input Variable | timeout | | 12000 | Variable is defined but not assigned |
| Remove Postgres Directory | Input Variable | readTimeout | | 12000 | Variable is defined but not assigned |
| Remove Postgres Directory | Input Variable | host | host | | Input variable is using Prompt User |
| Remove Postgres Directory | Input Variable | username | username | | Input variable is using Prompt User |
| Remove Postgres Directory | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | port | | 22 | Variable is defined but not assigned |

| | | | | | |
|-------------------------------|----------------|------------------|-------------|--|--------------------------------------|
| SSH Shell Logon | Input Variable | host | host | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | username | username | | Input variable is using Prompt User |
| SSH Shell Logon | Input Variable | password | password | | Input variable is using Prompt User |
| SSH Shell Logoff | Input Variable | sessionId | sessionId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | provider | | Micro Focus InfoBlox | Variable is defined but not assigned |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Update Resource Pool Capacity | Input Variable | resourceType | | IPV4_ADDRESS | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| JSON Path | Input Variable | jsonPathQuery | | \$.[?(@.name=='Houston vCenter')].self | Variable is defined but not assigned |
| Get Provider ID | Input Variable | url | | \${HCM/HCM-API-URL}resource/provider/ | Variable is defined but not assigned |
| Get Provider ID | Input Variable | authType | | Basic | Variable is defined but not assigned |

| | | | | | |
|--------------------|----------------|---------------------------|--|---|--------------------------------------|
| Get Provider ID | Input Variable | tlsVersion | | TLSv1.2 | Variable is defined but not assigned |
| Get Provider ID | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Variable is defined but not assigned |
| Get Provider ID | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Provider ID | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Provider ID | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Provider ID | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Provider ID | Input Variable | headers | | | Variable is defined but not assigned |
| Get Provider ID | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get Provider ID | Input Variable | queryParams | | | Variable is defined but not assigned |
| Get Provider ID | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Provider ID | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Get Provider ID | Input Variable | method | | GET | Variable is defined but not assigned |
| Query Pool Name | Input Variable | jsonPathQuery | | \$.name | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/filter | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |

| | | | | | |
|--------------------|----------------|------------------------|--|--|--------------------------------------|
| Get Resource Pools | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | tlsVersion | | TLSv1.2 | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256... | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | headers | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |

| | | | | | |
|--------------------------------|----------------------|-----------------------------|------------------------------------|--|--|
| Get Resource Pools | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | queryParams | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | formParams | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | body | | { "providerId": "\${providerIdResult}" } | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Get Resource Pools | Input Variable | method | | POST | Variable is defined but not assigned |
| Query Pool Id | Input Variable | jsonPathQuery | | \$.[?(@.name=='\${ss}')] .self | Variable is defined but not assigned |
| Get Resource Pool From vCenter | Input Variable | overrideNRAS | | RAS_Win_Path | Variable is defined but not assigned |
| Get Resource Pool From vCenter | Flow Output Variable | resourceCapacityListvCenter | Result Field: resourceCapacityList | N/A | Flow Output variable created in flow steps |
| Update Resource Pool Capacity | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | authType | | | Variable is defined but not assigned |

| | | | | | |
|-------------------------------|----------------|----------------------|--|-----------|--------------------------------------|
| Update Resource Pool Capacity | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | authType | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |

| | | | | | |
|-------------------------------|----------------------|----------------------|---------------------------|-----------------------------------|--|
| Update Resource Pool Capacity | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | authType | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Resource Pool Capacity | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Create New Resource Pool | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/ | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | tlsVersion | | | Variable is defined but not assigned |

| | | | | | |
|--------------------------|----------------|--------------------------|--|-----------|--------------------------------------|
| Create New Resource Pool | Input Variable | allowedCyphers | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | keystore | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | headers | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | queryParams | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | formParams | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | sourceFile | | | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------------|----------------------|---------------------------|--|--|
| Create New Resource Pool | Input Variable | body | | { "name": "\${ss}", "description": "vCenter Cluster", "enabled": true, "poolReference": "\${ss}", "syncAction": null, "provider": { "@self": "/csa/api/resource/provider/\${providerIdResult}" } } | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Create New Resource Pool | Input Variable | method | | POST | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Add Resource Type - Storage | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/\${resPoolId}/capacity | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | tlsVersion | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | allowedCyphers | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | keystore | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------|--------------------------|--|---|--------------------------------------|
| Add Resource Type - Storage | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | headers | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | queryParams | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | formParams | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | body | | { "name": "\${ss}", "description": "vCenter Cluster", "ext": { "csa_used_by_csa": 0, "csa_available_to_csa": 0 }, "availability": { "displayName": "Available", "ext": { "csa_name_key": "AVAILABLE" } }, "type": { ... | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Add Resource Type - Storage | Input Variable | method | | POST | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/\${resPoolId}/capacity | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------|--------------------------|--|-----------|--------------------------------------|
| Add Resource Type - CPU | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | tlsVersion | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | allowedCyphers | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | keystore | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | headers | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | queryParams | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | formParams | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------|----------------------|--|---|--------------------------------------|
| Add Resource Type - CPU | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | body | | { "name": "\${ss}", "description": "vCenter Cluster", "ext": { "csa_used_by_csa": 0, "csa_available_to_csa": 0 }, "availability": { "displayName": "Available", "ext": { "csa_name_key": "AVAILABLE" } }, "type": { ... | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Add Resource Type - CPU | Input Variable | method | | POST | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/\${resPoolId}/capacity | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | tlsVersion | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | allowedCyphers | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | keystore | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------------|--------------------------|---------------------------|---|--|
| Add Resource Type - Memory | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | headers | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | queryParams | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | formParams | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | body | | { "name": "\${ss}", "description": "vCenter Cluster", "ext": { "csa_used_by_csa": 0, "csa_available_to_csa": 0 }, "availability": { "displayName": "Available", "ext": { "csa_name_key": "AVAILABLE" } }, "type": { ... | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Add Resource Type - Memory | Input Variable | method | | POST | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |

| | | | | | |
|-------------------------|----------------------|----------------------|--------------------------------|--|--|
| Get Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Provider Details | Flow Output Variable | SACore | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | SAPort | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | SAProtocol | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | SAUsername | Result Field: providerUser | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | SAPassword | Result Field: providerPassword | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Input Variable | url | | \$(HCM/HCM-REST-URL)artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256... | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | headers | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParams | | | Variable is defined but not assigned |

| | | | | | |
|---------------------------|----------------------|-------------------------------|-------------------------------|---|---|
| Get Provider Properties | Input Variable | queryParamsAreURLEn coded | | false | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreFormE ncoded | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | method | | GET | Variable is defined but not assigned |
| Get Provider Properties | Flow Output Variable | SACoreVersion | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Cancel VM | Flow Output Variable | hcmRequestId | Result: hcmRequestId | N/A | Flow Output variable created in flow steps |
| Error Handling | Input Variable | oorunId | | \${run_id} | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Update Device Comments | Input Variable | smaxHostname | | \${SMAX/SMAX-HOSTN AME} | Variable is defined but not assigned |
| Update Device Comments | Input Variable | smaxTenantId | | \${SMAX/SMAX-TENAN T-ID} | Variable is defined but not assigned |
| Update Device Comments | Input Variable | comment | | SMAX Request: \${requestId} to Cancel VM '\${vmName}' in HCM SubscriptionId \${subscriptionId} is performed SUCCESSFULLY. | Variable is defined but not assigned |
| Update Device Comments | Input Variable | smaxHostname | | \${SMAX/SMAX-HOSTN AME} | Variable is defined but not assigned |
| Update Device Comments | Input Variable | smaxTenantId | | \${SMAX/SMAX-TENAN T-ID} | Variable is defined but not assigned |
| Update Device Comments | Input Variable | comment | | SMAX Request: \${requestId} to Cancel VM '\${vmName}' in HCM SubscriptionId \${subscriptionId} has FAILED. | Variable is defined but not assigned |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HC MConsumerURL}subscr iption/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | instance | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | dbClass | | | Variable is defined but not assigned |

| | | | | | |
|------------------------------|----------------------|---------------------------|------------------------------|--|--|
| INSERT Request Data | Input Variable | dbURL | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | timeout | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | resultSetType | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| INSERT Request Data | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| INSERT Request Data | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | instance | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | dbClass | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | dbURL | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | timeout | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | resultSetType | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| INSERT Request Data | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Resolved : success | Input Variable | subscriptionUUID | | ec4a804a-4003-4a35-8379-f08c537be954 | Variable is defined but not assigned |
| Get HCM Authentication Token | Flow Output Variable | tenantName | Input: tenantName | N/A | Flow Output variable created in flow steps |
| Get Offering | Input Variable | authToken | authToken | | Input variable is using Prompt User |
| Create Subscription | Input Variable | subscriptionName | | Server: SMAX Request \${requestId} | Variable is defined but not assigned |

| | | | | | |
|------------------------------|----------------------|-------------------------|---------------------------|--|--|
| Create Subscription | Input Variable | subscriptionDescription | | Subscription created from SMAX Service Request \${requestId}. This is owned by \${requestorEmail} | Variable is defined but not assigned |
| Create Subscription | Input Variable | action | | ORDER | Variable is defined but not assigned |
| Create Subscription | Input Variable | startDate | | | Variable is defined but not assigned |
| Create Subscription | Input Variable | endDate | | | Variable is defined but not assigned |
| Create Subscription | Flow Output Variable | resultReqId | Result: requestId | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Supplemental Account | Input Variable | primaryEmail | requestorEmail | | Input variable is using Prompt User |
| Resolved : success | Input Variable | subscriptionUUID | | ec4a804a-4003-4a35-8379-f08c537be954 | Variable is defined but not assigned |
| Get HCM Authentication Token | Input Variable | tenantName | | \$(HCM/TENANT-NAME } | Variable is defined but not assigned |
| Http Client Get | Input Variable | url | | \$(HCM/HCM-API-URL)consumption/v2/instance/\${serviceInstanceId} | Variable is defined but not assigned |
| Trigger Public Action | Input Variable | subscriptionName | | | Variable is defined but not assigned |
| Trigger Public Action | Flow Output Variable | hcmRequestId | Result: requestId | N/A | Flow Output variable created in flow steps |
| Error Handling | Input Variable | oorunId | | \${run_id} | Variable is defined but not assigned |
| Error Handling | Input Variable | constantFailureMessage | | Failed to perform User action due to issue with SMAX/HCM API Queries | Variable is defined but not assigned |
| Error Handling | Input Variable | oorunId | | \${run_id} | Variable is defined but not assigned |
| Error Handling | Input Variable | constantFailureMessage | | Failed to perform User-Actions | Variable is defined but not assigned |
| Update Device Comments | Input Variable | smaxHostname | | \$(SMAX/SMAX-HOSTNAME} | Variable is defined but not assigned |
| Update Device Comments | Input Variable | smaxTenantId | | \$(SMAX/SMAX-TENANT-ID} | Variable is defined but not assigned |

| | | | | | |
|-------------------------------|----------------|------------------------|--|--|--------------------------------------|
| Update Device Comments | Input Variable | comment | | SMAX Request: \${requestId} to '\${actionName}' for \${vmName} is performed SUCCESSFULLY. | Variable is defined but not assigned |
| Update Device Comments | Input Variable | smaxHostname | | \${SMAX/SMAX-HOSTNAME} | Variable is defined but not assigned |
| Update Device Comments | Input Variable | smaxTenantId | | \${SMAX/SMAX-TENANT-ID} | Variable is defined but not assigned |
| Update Device Comments | Input Variable | comment | | SMAX Request: \${requestId} to '\${actionName}' for \${vmName} has FAILED. | Variable is defined but not assigned |
| Error Handling | Input Variable | oorunId | | \${run_id} | Variable is defined but not assigned |
| Error Handling | Input Variable | constantFailureMessage | | Failed to perform User action due to issue with SMAX/HCM API Queries | Variable is defined but not assigned |
| Do Nothing With Two Responses | Input Variable | offeringNames | | MICRO FOCUS DEV, Micro Focus MSSQL Database, Micro Focus ORACLE Database, Micro Focus Oracle Database | Variable is defined but not assigned |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |

| | | | | | |
|--------------------------|----------------------|---------------------------|------------------------------|--|--|
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | instance | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | dbClass | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | dbURL | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | timeout | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | resultSetType | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| INSERT Request Data | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| INSERT Request Data | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | instance | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | dbClass | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | dbURL | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | timeout | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | resultSetType | | | Variable is defined but not assigned |
| INSERT Request Data | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| INSERT Request Data | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Supplemental Account | Input Variable | networkType | | INT | Variable is defined but not assigned |
| Get Supplemental Account | Input Variable | primaryEmail | requestorEmail | | Input variable is using Prompt User |
| Error : failure | Input Variable | failureMessage | | { "runId": "\${run_id}", "failureMessage": "Public Action Failure: \${failureMessage}" } | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------------|----------------------|----------------------|--|--|
| Resolved : success | Input Variable | subscriptionUUID | | ec4a804a-4003-4a35-8379-f08c537be954 | Variable is defined but not assigned |
| Error : failure | Input Variable | failureMessage | | { "runId": "\${run_id}", "failureMessage": "Public Action Failure: \${failureMessage}" } | Variable is defined but not assigned |
| Error : failure | Input Variable | failureMessage | | { "runId": "\${run_id}", "failureMessage": "Public Action Failure: \${failureMessage}" } | Variable is defined but not assigned |
| Flow Inputs | Input Variable | requestId | requestId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | smaxModelId | smaxModelId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | smaxTenantId | smaxTenantId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | smaxReqId | smaxReqId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | subscriptionId | subscriptionId | | Input variable is using Prompt User |
| Sleep | Input Variable | seconds | | 60 | Variable is defined but not assigned |
| Get Service Request Details | Input Variable | url | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HC MURL}/csa/api/service/mpp-request/\${requestId} | Variable is defined but not assigned |
| Get Service Request Details | Input Variable | headerNamesList | | Accept | Variable is defined but not assigned |
| Get Service Request Details | Input Variable | headerValuesList | | application/json | Variable is defined but not assigned |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HC MConsumerURL}subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| UpdateRequest | Flow Output Variable | subscriptionStatus | Input: serviceStatus | N/A | Flow Output variable created in flow steps |
| Get Subscription Details | Input Variable | url | | \${csaApiUrl}service/subscription/\${subscriptionId} | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------------|---------------------------|------------------------|--|--|
| Get Subscription Details | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | headers | | Accept:application/json | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | queryParams | | | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | formParams | | | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | method | | GET | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| UpdateRequest | Flow Output Variable | subscriptionStatus | Input: serviceStatus | N/A | Flow Output variable created in flow steps |
| Filter Subscription Id | Input Variable | json | | \${requestDetails} | Variable is defined but not assigned |
| Filter Subscription Id | Input Variable | jsonPathQuery | | subscription.id | Variable is defined but not assigned |
| GET Properties | Flow Output Variable | subscriptionURL | Input: field1 | N/A | Flow Output variable created in flow steps |
| Post FailureMessage to SMAX | Flow Output Variable | failureMessage1 | Result: failureMessage | N/A | Flow Output variable created in flow steps |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | serviceStatus | | SUCCESS | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------------|---------------------------|------------------------|--|--|
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| UpdateRequest | Flow Output Variable | subscriptionStatus | Input: serviceStatus | N/A | Flow Output variable created in flow steps |
| GET SubscriptionId | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| GET SubscriptionId | Input Variable | instance | | | Variable is defined but not assigned |
| GET SubscriptionId | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| GET SubscriptionId | Input Variable | dbClass | | | Variable is defined but not assigned |
| GET SubscriptionId | Input Variable | dbURL | | | Variable is defined but not assigned |
| GET SubscriptionId | Input Variable | timeout | | | Variable is defined but not assigned |
| GET SubscriptionId | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| GET SubscriptionId | Input Variable | resultSetType | | | Variable is defined but not assigned |
| GET SubscriptionId | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| UpdateRequest | Flow Output Variable | subscriptionStatus | Input: serviceStatus | N/A | Flow Output variable created in flow steps |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| UpdateRequest | Flow Output Variable | subscriptionStatus | Input: serviceStatus | N/A | Flow Output variable created in flow steps |
| Post FailureMessage to SMAX | Flow Output Variable | failureMessage1 | Result: failureMessage | N/A | Flow Output variable created in flow steps |

| | | | | | |
|---------------------------------|----------------------|----------------------|----------------------|--|--|
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | serviceStatus | | SUCCESS | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| UpdateRequest | Flow Output Variable | subscriptionStatus | Input: serviceStatus | N/A | Flow Output variable created in flow steps |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | serviceStatus | | SUCCESS | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| UpdateRequest | Flow Output Variable | subscriptionStatus | Input: serviceStatus | N/A | Flow Output variable created in flow steps |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Variable is defined but not assigned |
| UpdateRequest | Input Variable | serviceStatus | | FAILURE | Variable is defined but not assigned |
| UpdateRequest | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| UpdateRequest | Flow Output Variable | subscriptionStatus | Input: serviceStatus | N/A | Flow Output variable created in flow steps |
| Subscription Details_InstanceID | Flow Output Variable | UserID | Result Field: userID | N/A | Flow Output variable created in flow steps |
| JSON Path | Input Variable | jsonPathQuery | | \$.components..properties.[?(@.name=="FailureMessage")].value | Variable is defined but not assigned |
| JSON Path | Input Variable | json | InstanceDetails | | Input variable is using Prompt User |
| Http Client | Input Variable | string | | | Variable is defined but not assigned |
| Http Client | Input Variable | authType | | Basic | Variable is defined but not assigned |

| | | | | | |
|-------------|----------------|---------------------------|--|------------------------|--------------------------------------|
| Http Client | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Http Client | Input Variable | kerberosLoginConfFile | | | Variable is defined but not assigned |
| Http Client | Input Variable | kerberosSkipPortForLookup | | true | Variable is defined but not assigned |
| Http Client | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Http Client | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client | Input Variable | headers | | X-AUTH-Token:\${Token} | Variable is defined but not assigned |
| Http Client | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client | Input Variable | queryParams | | | Variable is defined but not assigned |

| | | | | | |
|-----------------------------------|----------------------|----------------------------------|-----------------------|---|--|
| Http Client | Input Variable | queryParamsAreURLEn coded | | false | Variable is defined but not assigned |
| Http Client | Input Variable | queryParamsAreFormE ncoded | | true | Variable is defined but not assigned |
| Http Client | Input Variable | formParams | | | Variable is defined but not assigned |
| Http Client | Input Variable | formParamsAreURLEnc oded | | false | Variable is defined but not assigned |
| Http Client | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Http Client | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Http Client | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Http Client | Input Variable | multipartBodies | | | Variable is defined but not assigned |
| Http Client | Input Variable | multipartBodiesContent Type | | text/plain; charset=ISO-8859-1 | Variable is defined but not assigned |
| Http Client | Input Variable | multipartValuesAreURL Encoded | | false | Variable is defined but not assigned |
| Http Client | Input Variable | multipartFiles | | | Variable is defined but not assigned |
| Http Client | Input Variable | multipartFilesContentTy pe | | application/octet-stream | Variable is defined but not assigned |
| Http Client | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Http Client | Input Variable | method | | GET | Variable is defined but not assigned |
| Get Failure Message From Array | Flow Output Variable | message | Result Field: message | N/A | Flow Output variable created in flow steps |
| set constant value | Flow Output Variable | message | Input: field1 | N/A | Flow Output variable created in flow steps |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.stat us=="\${failureCompone ntStatus}")].properties.[?(@.name=="FailureMe ssage")].value | Variable is defined but not assigned |
| JSON Path | Input Variable | json | InstanceDetails | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | smaxPassword | smaxPassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Create Entity | Input Variable | sawUrl | | https://\${smaxHostnam e} | Variable is defined but not assigned |
| Create Entity | Input Variable | tenantId | | \${smaxTenantId} | Variable is defined but not assigned |
| Create Entity | Flow Output Variable | returnResult | Result: returnResult | N/A | Flow Output variable created in flow steps |
| Create Entity | Flow Output Variable | entityJSON | Result: entityJSON | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-----------------|----------------------|----------------------|----------------------------|---|--|
| Create Entity | Flow Output Variable | errorJSON | Result: errorJSON | N/A | Flow Output variable created in flow steps |
| Create Entity | Flow Output Variable | entityId | Result: createdId | N/A | Flow Output variable created in flow steps |
| Create Entity | Flow Output Variable | opStatus | Result: opStatus | N/A | Flow Output variable created in flow steps |
| Create Entity | Input Variable | sawUrl | | https://\${SMAX/SMAX-HOSTNAME} | Variable is defined but not assigned |
| Create Entity | Input Variable | tenantId | | \${SMAX/SMAX-TENANT-ID} | Variable is defined but not assigned |
| Create Entity | Input Variable | inputJSON | | { "entity_type": "Subscription", "properties": { "DisplayLabel": "\${upn} new \${hostname}", "Description" : "this entity is subscribed to the requestor", "SubscribedToDevice": "\${DeviceId}", "Subscriber" : "\${subscriberId}", "StartDate": \${startDate}, "Status": "Active", "PhaseId" : " ... | Variable is defined but not assigned |
| Create Entity | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Create Entity | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Create Entity | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Create Entity | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Create Entity | Input Variable | headers | | | Variable is defined but not assigned |
| Create Entity | Input Variable | contentType | | | Variable is defined but not assigned |
| Create Entity | Input Variable | ssoToken | ssoToken | | Input variable is using Prompt User |
| Query Entities | Input Variable | url | | https://\${SMAX/SMAX-HOSTNAME}/rest/\${SMAX/SMAX-TENANT-ID}/ems/Device | Variable is defined but not assigned |
| Query Entities | Input Variable | method | | GET | Variable is defined but not assigned |
| Query Entities | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${tenantId} | Variable is defined but not assigned |
| Query Entities | Input Variable | responseCharacterSet | | UTF-8 | Variable is defined but not assigned |
| Query Entities | Flow Output Variable | returnResult | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| collect message | Flow Output Variable | message | Result Field: returnResult | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-----------------------|----------------------|----------------------|----------------------------|---|--|
| Flow Inputs | Input Variable | subscriberId | subscriberId | | Input variable is using Prompt User |
| Get Entity | Input Variable | sawUrl | | https://\${SMAX/SMAX-HOSTNAME} | Variable is defined but not assigned |
| Get Entity | Input Variable | tenantId | | \${SMAX/SMAX-TENANT-ID} | Variable is defined but not assigned |
| Get Entity | Input Variable | entityType | | Person | Variable is defined but not assigned |
| Get Entity | Input Variable | fields | | Name,Id,Upn | Variable is defined but not assigned |
| Get Entity | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Entity | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Entity | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Get Entity | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${tenantId} | Variable is defined but not assigned |
| Get Entity | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get Entity | Input Variable | ssoToken | ssoToken | | Input variable is using Prompt User |
| Get Value from Object | Input Variable | key | | properties.Upn | Variable is defined but not assigned |
| Get Value from Object | Input Variable | object | entityJSON | | Input variable is using Prompt User |
| Get Value from Object | Flow Output Variable | upn | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | sawUrl | | https://\${SMAX/SMAX-HOSTNAME}/auth/authentication-endpoint/authenticate/login?TENANTID=\${SMAX/SMAX-TENANT-ID} | Variable is defined but not assigned |
| Get SSO Token | Input Variable | sawUrl | | https://\${SMAX/SMAX-HOSTNAME}/auth/authentication-endpoint/authenticate/login?TENANTID=\${SMAX/SMAX-TENANT-ID} | Variable is defined but not assigned |
| Get SSO Token | Input Variable | headers | | | Variable is defined but not assigned |
| Get SSO Token | Flow Output Variable | ssoToken | Result Field: ssoToken | N/A | Flow Output variable created in flow steps |
| Sleep | Input Variable | seconds | | 5 | Variable is defined but not assigned |
| Counter | Input Variable | from | | 1 | Variable is defined but not assigned |
| Counter | Input Variable | to | | 2 | Variable is defined but not assigned |

| | | | | | |
|------------------------------|----------------------|----------------------|----------------------------|--|---|
| Counter | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Counter | Input Variable | reset | | false | Variable is defined but not assigned |
| Get EMS Entity | Input Variable | url | | https://\${SMAX/SMAX-HOSTNAME}/rest/\${SMAX/SMAX-TENANT-ID}/ems/Person | Variable is defined but not assigned |
| Get EMS Entity | Input Variable | method | | GET | Variable is defined but not assigned |
| JSON Path | Input Variable | jsonPathQuery | | \$.entities[0].properties.Id | Variable is defined but not assigned |
| JSON Path | Flow Output Variable | userId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get EMS Entity | Input Variable | url | | https://\${SMAX/SMAX-HOSTNAME}/rest/\${SMAX/SMAX-TENANT-ID}/ems/Person | Variable is defined but not assigned |
| Get EMS Entity | Input Variable | method | | GET | Variable is defined but not assigned |
| JSON Path | Input Variable | jsonPathQuery | | \$.entities[0].properties.Id | Variable is defined but not assigned |
| JSON Path | Flow Output Variable | userId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get HCM Authentication Token | Input Variable | tenantName | | \${HCM/TENANT-NAME} | Variable is defined but not assigned |
| Build JSON | Flow Output Variable | failureMessage | Input: field1 | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | smaxPassword | smaxPassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Update Entities | Input Variable | sawUrl | | https://\${smaxHostname} | Variable is defined but not assigned |
| Update Entities | Input Variable | tenantId | | \${smaxTenantId} | Variable is defined but not assigned |
| Update Entities | Input Variable | inputJSON | | { "entity_type":"Device", "properties":{"Id":"\${entityId}", "PhaseId":"pRetire" } } | Variable is defined but not assigned |
| Update Entities | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Entities | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Entities | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Update Entities | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Update Entities | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${tenantId} | Variable is defined but not assigned |

| | | | | | |
|-----------------|----------------|---------------------------|--|------------|--------------------------------------|
| Update Entities | Input Variable | contentType | | | Variable is defined but not assigned |
| Update Entities | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Update Entities | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client | Input Variable | string | | | Variable is defined but not assigned |
| Http Client | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Http Client | Input Variable | kerberosLoginConfFile | | | Variable is defined but not assigned |
| Http Client | Input Variable | kerberosSkipPortForLookup | | true | Variable is defined but not assigned |
| Http Client | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Http Client | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------------|------------------------------|----------------------------|--------------------------------|--|
| Http Client | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client | Input Variable | headers | | X-AUTH-Token:\${Token} | Variable is defined but not assigned |
| Http Client | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client | Input Variable | queryParams | | | Variable is defined but not assigned |
| Http Client | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Http Client | Input Variable | formParams | | | Variable is defined but not assigned |
| Http Client | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Http Client | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Http Client | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Http Client | Input Variable | multipartBodies | | | Variable is defined but not assigned |
| Http Client | Input Variable | multipartBodiesContentType | | text/plain; charset=ISO-8859-1 | Variable is defined but not assigned |
| Http Client | Input Variable | multipartValuesAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client | Input Variable | multipartFiles | | | Variable is defined but not assigned |
| Http Client | Input Variable | multipartFilesContentType | | application/octet-stream | Variable is defined but not assigned |
| Http Client | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Http Client | Input Variable | method | | GET | Variable is defined but not assigned |
| JSON Path - Instance ID | Input Variable | jsonPathQuery | | \$.instanceId | Variable is defined but not assigned |
| JSON Path - Instance ID | Input Variable | json | subscriptionDetails | | Input variable is using Prompt User |
| JSON Path - Instance ID | Flow Output Variable | InstanceId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| JSON Path - UserID | Input Variable | jsonPathQuery | | \$.ownerUid | Variable is defined but not assigned |
| JSON Path - UserID | Input Variable | json | subscriptionDetails | | Input variable is using Prompt User |
| JSON Path - UserID | Flow Output Variable | userId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |

| | | | | | |
|----------------------|----------------------|----------------------|-------------------------------|--|---|
| Http Client Post Raw | Input Variable | url | | https://\${smaxHostnam e}/rest/\${smaxTenantId} /collaboration/comment s/Device/\${entityId} | Variable is defined but not assigned |
| Http Client Post Raw | Input Variable | body | | { "IsSystem": false, "Body": "\${comment}", "AttachmentIds": [], "PrivacyType": "PUBLIC", "Submitter": { "UserId": \${userId} }, "ActualInterface": "API", "CommentFrom": "User", "CommentTo": "", "FunctionalPurpose": "StatusUpdate", "Media": "Unknown", "PersonParticipant": "", "CompanyVe ... | Variable is defined but not assigned |
| Http Client Post Raw | Input Variable | method | | POST | Variable is defined but not assigned |
| Http Client Post Raw | Input Variable | headers | | Cookie:LWSSO_COOK IE_KEY=\${ssoToken}; TENANTID=\${smaxTen antId} | Variable is defined but not assigned |
| Http Client Post Raw | Flow Output Variable | returnResult | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Flow Inputs | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Flow Inputs | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Flow Inputs | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Flow Inputs | Input Variable | failureMessage | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | customString | | | Variable is defined but not assigned |

| | | | | | |
|----------------|----------------|------------------------|--|---|--------------------------------------|
| Flow Inputs | Input Variable | smaxRequestId | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | smaxRequestId | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | serviceStatus | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | serviceStatus | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | tenantId | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | tenantId | | | Input variable is using Prompt User |
| Get SSO Token | Input Variable | sawUrl | | \${Integrations/Micro Focus/Service Management Automation X/SMAX/SMAXBaseUrl}\${Integrations/Micro Focus/Service Management Automation X/SMAX/SMAXLoginURI}?TENANTID=\${tenantId} | Variable is defined but not assigned |
| Get SSO Token | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Get SSO Token | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| POST operation | Input Variable | url | | \${Integrations/Micro Focus/Service Management Automation X/SMAX/SMAXBaseUrl}/rest/\${tenantId}/ems/bulk | Variable is defined but not assigned |
| POST operation | Input Variable | authType | | anonymous | Variable is defined but not assigned |
| POST operation | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| POST operation | Input Variable | encodeURL | | false | Variable is defined but not assigned |
| POST operation | Input Variable | file | | | Variable is defined but not assigned |
| POST operation | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| POST operation | Input Variable | characterSet | | | Variable is defined but not assigned |
| POST operation | Input Variable | headerNamesList | | Accept,Content-Type,Cookie | Variable is defined but not assigned |
| POST operation | Input Variable | headerValuesList | | application/json,application/json,LWSSO_COOKIE_KEY=\${ssoTokenResult} | Variable is defined but not assigned |
| POST operation | Input Variable | queryNamesList | | | Variable is defined but not assigned |

| | | | | | |
|----------------------|----------------------|--------------------------|----------------------------|---|--|
| POST operation | Input Variable | queryValuesList | | | Variable is defined but not assigned |
| POST operation | Input Variable | delimiter | | , | Variable is defined but not assigned |
| POST operation | Flow Output Variable | requestDetails | Result Field: document | N/A | Flow Output variable created in flow steps |
| Http Client Post Raw | Input Variable | url | | https://\${smaxHostname}/rest/\${smaxTenantId}/collaboration/comments/SystemElement/\${entityId} | Variable is defined but not assigned |
| Http Client Post Raw | Input Variable | body | | { "IsSystem": false, "Body": "\${comment}", "AttachmentIds": [], "PrivacyType": "PUBLIC", "Submitter": { "UserId": \${userId} }, "ActualInterface": "API", "CommentFrom": "User", "CommentTo": "", "FunctionalPurpose": "StatusUpdate", "Media": "Unknown", "PersonParticipant": "", "CompanyVe ... | Variable is defined but not assigned |
| Http Client Post Raw | Input Variable | method | | POST | Variable is defined but not assigned |
| Http Client Post Raw | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${smaxTenantId} | Variable is defined but not assigned |
| Http Client Post Raw | Flow Output Variable | returnResult | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Http Client Post | Input Variable | url | | \${protocol}://\${cmdbHost}:\${cmdbPort}/rest-api/dataModel | Variable is defined but not assigned |
| Http Client Post | Input Variable | authType | | anonymous | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Post | Input Variable | headers | | Authorization: Bearer \${authToken} | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParams | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | formParams | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | contentType | | application/json | Variable is defined but not assigned |

| | | | | | |
|----------------------------------|----------------------|--------------------------|------------------------------|--|--|
| Http Client Post | Input Variable | method | | POST | Variable is defined but not assigned |
| Http Client Post | Flow Output Variable | returnResult | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Http Client Post | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Http Client Post | Input Variable | url | | \${protocol}://\${cndbHost}:\${cndbPort}/rest-api/authenticate | Variable is defined but not assigned |
| Http Client Post | Input Variable | authType | | anonymous | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Post | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParams | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | formParams | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | body | | { "username": "\${username}", "password": "\${password}", "clientContext": "1" } | Variable is defined but not assigned |
| Http Client Post | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Http Client Post | Input Variable | method | | POST | Variable is defined but not assigned |
| Http Client Post | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Value from Object | Input Variable | key | | token | Variable is defined but not assigned |
| Get Value from Object | Input Variable | object | returnResult | | Input variable is using Prompt User |
| Get Value from Object | Flow Output Variable | authToken | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Filtered Object List by Type | Input Variable | logicalOperator | | | Variable is defined but not assigned |
| Get Filtered Object List by Type | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Filtered Object List by Type | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Filtered Object List by Type | Input Variable | rootContext | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------------|----------------------|-------------------------------|------------------------------|------------------------------------|---|
| Get Filtered Object List by Type | Input Variable | certificateVerifier | | true | Variable is defined but not assigned |
| Get Filtered Object List by Type | Input Variable | certificateHostnameVerifier | | true | Variable is defined but not assigned |
| Get Filtered Object List by Type | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Filtered Object List by Type | Flow Output Variable | cild | Result Field: CIs | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | host | | mc4t02911.itcs.softwar egrp.net | Variable is defined but not assigned |
| Flow Inputs | Input Variable | coreHost | | mc4t02911.itcs.softwar egrp.net | Variable is defined but not assigned |
| Flow Inputs | Input Variable | corePort | | 443 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | coreProtocol | | https | Variable is defined but not assigned |
| Flow Inputs | Input Variable | coreUsername | | admin | Variable is defined but not assigned |
| Flow Inputs | Input Variable | corePassword | | opsware_01 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | corePassword | | opsware_01 | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Start Server Script | Input Variable | scriptToRunID | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHostSearchOperator | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetUser | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetPassword | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetDomain | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTimeout | | 300 | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessRecipients | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | ticketId | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTailOutputSize | | | Variable is defined but not assigned |
| Start Server Script | Flow Output Variable | jobid | Result Field: id | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Script Job Result | Flow Output Variable | summary | Result Field: summary | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Flow Output Variable | output | Result Field: output | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-----------------------|----------------------|-------------------------------|-----------------------|--|---|
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | 300000 | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | corePassword | corePassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Start Server Script | Input Variable | scriptToRunID | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHostSearchOperator | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetUser | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetPassword | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetDomain | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTimeout | | 600 | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessRecipients | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | ticketId | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTailOutputSize | | | Variable is defined but not assigned |
| Start Server Script | Flow Output Variable | jobid | Result Field: id | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Script Job Result | Flow Output Variable | summary | Result Field: summary | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Flow Output Variable | output | Result Field: output | N/A | Flow Output variable created in flow steps |
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | 700000 | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | childComponentName | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | childComponentName | | | Input variable is using Prompt User |
| Http Client Get | Input Variable | url | | \$(HCM/HCM-REST-URL)artifact/\${parentComponentId} | Variable is defined but not assigned |
| Http Client Get | Input Variable | authType | | Basic | Variable is defined but not assigned |

| | | | | | |
|-----------------|----------------|---------------------------|--|--|--------------------------------------|
| Http Client Get | Input Variable | queryParams | | userIdentifier=\${userIdentifier}&scope;=Baseplusone | Variable is defined but not assigned |
| Http Client Get | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystore | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Http Client Get | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Get | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | headers | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | method | | GET | Variable is defined but not assigned |

| | | | | | |
|--------------------------|----------------------|------------------------|--------------------------------|---|--|
| Get Component Properties | Flow Output Variable | propertyNameValuesList | Result: propertyNameValuesList | N/A | Flow Output variable created in flow steps |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Get Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Provider Details | Flow Output Variable | ipamHostname | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamPort | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamProtocol | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamUsername | Result Field: providerUser | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | ipamPassword | Result Field: providerPassword | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | headers | | | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------------|---------------------------|----------------------------|-------|---|
| Get Provider Properties | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParams | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | method | | GET | Variable is defined but not assigned |
| Get Provider Properties | Flow Output Variable | zone | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Flow Output Variable | gatewayIp | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Flow Output Variable | subnetMask | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Flow Output Variable | exception | Result Field: exception | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Flow Output Variable | networkType1 | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Flow Output Variable | dataCenter1 | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Flow Output Variable | site1 | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Flow Output Variable | vlan1 | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Flow Output Variable | subnet1 | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Flow Output Variable | xml | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Find Network | Input Variable | url | url | | Input variable is using Prompt User |
| Find Network | Input Variable | username | username | | Input variable is using Prompt User |
| Find Network | Input Variable | password | password | | Input variable is using Prompt User |
| Find Network | Input Variable | network | network | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | url | url | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | username | username | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | password | password | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | networkRef | networkRef | | Input variable is using Prompt User |

| | | | | | |
|-----------------------|----------------------|----------------|---------------------------|-----|---|
| Get Next Available IP | Flow Output Variable | nextIp | Result: availableIpXML | N/A | Flow Output variable created in flow steps |
| Add Host Record | Input Variable | url | url | | Input variable is using Prompt User |
| Add Host Record | Input Variable | ipAddress | nextIp | | Input variable is using Prompt User |
| Add Host Record | Input Variable | hostName | hostname | | Input variable is using Prompt User |
| Add Host Record | Input Variable | domain | zone | | Input variable is using Prompt User |
| Add Host Record | Flow Output Variable | hostRecord | Result: hostrecordXML | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Find Network | Input Variable | url | url | | Input variable is using Prompt User |
| Find Network | Input Variable | username | username | | Input variable is using Prompt User |
| Find Network | Input Variable | password | password | | Input variable is using Prompt User |
| Find Network | Input Variable | network | network | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | url | url | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | username | username | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | password | password | | Input variable is using Prompt User |
| Get Next Available IP | Input Variable | networkRef | networkRef | | Input variable is using Prompt User |
| Get Next Available IP | Flow Output Variable | nextIp | Result: availableIpXML | N/A | Flow Output variable created in flow steps |
| Add Host Record | Input Variable | url | url | | Input variable is using Prompt User |
| Add Host Record | Input Variable | ipAddress | nextIp | | Input variable is using Prompt User |
| Add Host Record | Input Variable | hostName | hostname | | Input variable is using Prompt User |
| Add Host Record | Input Variable | domain | zone | | Input variable is using Prompt User |
| Add Host Record | Flow Output Variable | hostRecord | Result: hostrecordXML | N/A | Flow Output variable created in flow steps |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Get Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Provider Details | Flow Output Variable | vcenterHost | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-------------------------|----------------------|---------------------------|--------------------------------|---|--|
| Get Provider Details | Flow Output Variable | vcenterUsername | Result Field: providerUser | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | vcenterPassword | Result Field: providerPassword | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | vcenterPort | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Details | Flow Output Variable | vcenterProtocol | Result Field: providerSAP | N/A | Flow Output variable created in flow steps |
| Get Provider Properties | Input Variable | url | | \$(HCM/HCM-REST-URL)artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | headers | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParams | | | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |

| | | | | | |
|--------------------------|----------------------|---------------|----------------------------|--------------|---|
| Get Provider Properties | Input Variable | method | | GET | Variable is defined but not assigned |
| Get Provider Properties | Flow Output Variable | dataCenter | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | datacenter | | PSO | Variable is defined but not assigned |
| List Datacenters | Input Variable | port | | 443 | Variable is defined but not assigned |
| List Datacenters | Input Variable | protocol | | https | Variable is defined but not assigned |
| List Datacenters | Input Variable | closeSession | | true | Variable is defined but not assigned |
| List Datacenters | Input Variable | propsType | | Datacenter | Variable is defined but not assigned |
| List Datacenters | Input Variable | host | host | | Input variable is using Prompt User |
| List Datacenters | Input Variable | user | user | | Input variable is using Prompt User |
| List Datacenters | Input Variable | password | password | | Input variable is using Prompt User |
| Array Iterator | Input Variable | array | datacenterArray | | Input variable is using Prompt User |
| Get Value from Object | Input Variable | key | | value | Variable is defined but not assigned |
| Get Value from Object | Input Variable | object | datacenterElement | | Input variable is using Prompt User |
| Get Value from Object | Input Variable | key | | name | Variable is defined but not assigned |
| Get Value from Object | Input Variable | object | datacenterElement | | Input variable is using Prompt User |
| Get Value from Object | Flow Output Variable | datacenterId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Variable is defined but not assigned |
| Flow Inputs | Input Variable | vpassword | vpassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Get Cluster Internal ID | Input Variable | host | | localhost | Variable is defined but not assigned |
| Get Cluster Internal ID | Flow Output Variable | clusterId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Datastores Freespace | Input Variable | password | vpassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| List Iterator | Flow Output Variable | datastoreName | Result: ss | N/A | Flow Output variable created in flow steps |
| List Iterator | Flow Output Variable | datastoreId | Result: ss | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-------------------------------------|----------------------|-------------------|------------------------------|------------------------------|---|
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Variable is defined but not assigned |
| Flow Inputs | Input Variable | vpassword | vpassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Simple Search:Get Cluster ID | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Simple Search:Get Cluster ID | Input Variable | propsType | | ClusterComputeResource | Variable is defined but not assigned |
| Simple Search:Get Cluster ID | Input Variable | connectionTimeout | | | Variable is defined but not assigned |
| Simple Search:Get Cluster ID | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Simple Search:Get Cluster ID | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Simple Search:Get Cluster ID | Flow Output Variable | clusterId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Datastores Freespace | Input Variable | password | vpassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Get Datastores Freespace | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| List Iterator | Flow Output Variable | datastoreName | Result: ss | N/A | Flow Output variable created in flow steps |
| List Iterator | Flow Output Variable | datastoreId | Result: ss | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | host | | \${vCenter/VCENTER-HOSTNAME} | Variable is defined but not assigned |
| Flow Inputs | Input Variable | diskSizeGB | | 300 | Variable is defined but not assigned |
| Get Datastores Freespace | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| List Iterator | Flow Output Variable | datastoreName | Result: ss | N/A | Flow Output variable created in flow steps |
| List Iterator | Flow Output Variable | datastoreId | Result: ss | N/A | Flow Output variable created in flow steps |
| Get Datastores With Info | Input Variable | host | host | | Input variable is using Prompt User |
| Get Datastores With Info | Input Variable | user | user | | Input variable is using Prompt User |
| Get Datastores With Info | Input Variable | password | password | | Input variable is using Prompt User |
| Output datastoreList | Flow Output Variable | dataStoreList | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Output datastoreList | Flow Output Variable | dataStoreList | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterProtocol | | https | Variable is defined but not assigned |

| | | | | | |
|-------------------------------------|----------------|------------------|-----------------|------------|--------------------------------------|
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterPort | | 443 | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | closeSession | | true | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | vmIdentifierType | | vmid | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | vmDiskSizeUnit | | GB | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | diskPath | | | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | diskMode | | persistent | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | thinProvision | | true | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | eagerZero | | false | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | diskSCSINode | | | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | controllerType | | | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterHost | vCenterHost | | Input variable is using Prompt User |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterUsername | vCenterUsername | | Input variable is using Prompt User |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterPassword | vCenterPassword | | Input variable is using Prompt User |
| vCenter Add Disk To Virtual Machine | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| vCenter Add Disk To Virtual Machine | Input Variable | vmDatacenter | datacenter | | Input variable is using Prompt User |
| vCenter Add Disk To Virtual Machine | Input Variable | vmDiskSize | diskSizeGB | | Input variable is using Prompt User |
| Counter | Input Variable | from | | 1 | Variable is defined but not assigned |
| Counter | Input Variable | to | | 1 | Variable is defined but not assigned |
| Counter | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Counter | Input Variable | reset | | false | Variable is defined but not assigned |

| | | | | | |
|-------------------------------------|----------------|------------------|-----------------|---|--------------------------------------|
| Add Windows Disk | Input Variable | command | | echo SELECT DISK 1 > \${vCenter/WINDOWS-DISKPART-LOCATION} & echo ATTRIBUTES DISK CLEAR READONLY >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo ONLINE DISK >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo CONVERT MBR >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo CREATE PARTITION PRIMARY >> \${vCenter/ ... | Variable is defined but not assigned |
| Counter | Input Variable | from | | 1 | Variable is defined but not assigned |
| Counter | Input Variable | to | | 20 | Variable is defined but not assigned |
| Counter | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Counter | Input Variable | reset | | false | Variable is defined but not assigned |
| Sleep | Input Variable | seconds | | 15 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | vCenterHost | vCenterHost | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vCenterUsername | vCenterUsername | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vCenterPassword | vCenterPassword | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | diskSizeGB | diskSizeGB | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | ipAddress | ipAddress | | Input variable is using Prompt User |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterProtocol | | https | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterPort | | 443 | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | closeSession | | true | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | vmIdentifierType | | vmid | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | vmDiskSizeUnit | | GB | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | diskPath | | | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | diskMode | | persistent | Variable is defined but not assigned |

| | | | | | |
|-------------------------------------|----------------|------------------|-----------------|--|--------------------------------------|
| vCenter Add Disk To Virtual Machine | Input Variable | thinProvision | | true | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | eagerZero | | false | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | diskSCSINode | | | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | controllerType | | | Variable is defined but not assigned |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterHost | vCenterHost | | Input variable is using Prompt User |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterUsername | vCenterUsername | | Input variable is using Prompt User |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterPassword | vCenterPassword | | Input variable is using Prompt User |
| vCenter Add Disk To Virtual Machine | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| vCenter Add Disk To Virtual Machine | Input Variable | vmDatacenter | datacenter | | Input variable is using Prompt User |
| vCenter Add Disk To Virtual Machine | Input Variable | vmDiskSize | diskSizeGB | | Input variable is using Prompt User |
| Add Windows Disk | Input Variable | command | | echo SELECT DISK \${totalDisks} > \${vCenter/WINDOWS-DISKPART-LOCATION} & echo ATTRIBUTES DISK CLEAR READONLY >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo ONLINE DISK >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo CONVERT MBR >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo CREATE PARTITION PRIMARY > ... | Variable is defined but not assigned |
| Sleep | Input Variable | seconds | | 15 | Variable is defined but not assigned |
| Counter | Input Variable | from | | 1 | Variable is defined but not assigned |
| Counter | Input Variable | to | | 20 | Variable is defined but not assigned |
| Counter | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Counter | Input Variable | reset | | false | Variable is defined but not assigned |
| Windows Command | Input Variable | currentDirectory | | | Variable is defined but not assigned |
| Windows Command | Input Variable | outputPath | | | Variable is defined but not assigned |
| Windows Command | Input Variable | characterSet | | | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------------|---------------------|-----------------|---|--|
| Windows Command | Input Variable | outputCharacterSet | | | Variable is defined but not assigned |
| Windows Command | Input Variable | timeout | | | Variable is defined but not assigned |
| Windows Command | Input Variable | debugPath | | true | Variable is defined but not assigned |
| Windows Command | Input Variable | command | | diskpart /s \${vCenter/WINDOWS-DISKPART-LOCATION} | Variable is defined but not assigned |
| Windows Command | Input Variable | currentDirectory | | | Variable is defined but not assigned |
| Windows Command | Input Variable | outputPath | | | Variable is defined but not assigned |
| Windows Command | Input Variable | characterSet | | | Variable is defined but not assigned |
| Windows Command | Input Variable | outputCharacterSet | | | Variable is defined but not assigned |
| Windows Command | Input Variable | timeout | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | vCenterHost | vCenterHost | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vCenterUsername | vCenterUsername | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vCenterPassword | vCenterPassword | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | virtualMachine | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | virtualMachine | | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | datacenter | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | datacenter | | | Input variable is using Prompt User |
| Get Device Numbers For Type | Input Variable | vmIdentifierType | | vmid | Variable is defined but not assigned |
| Get Device Numbers For Type | Input Variable | deviceType | | hardDisk | Variable is defined but not assigned |
| Do Nothing | Flow Output Variable | totalDisks | Input: field1 | N/A | Flow Output variable created in flow steps |
| Cluster Details | Flow Output Variable | selectedClusterName | Input: field1 | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Variable is defined but not assigned |
| Sript Content -1 | Input Variable | file | | C:\Vcenter\Getcluster.ps1 | Variable is defined but not assigned |
| Sript Content -1 | Input Variable | contents | | Connect-VIServer \${viServer} -User \${userName} -Password \${password} Get-Datacenter Get-Cluster Select Name* | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------------|----------------------|---------------------------|--|--|
| Script Content -1 | Input Variable | delimiter | | | Variable is defined but not assigned |
| Script Content -1 | Input Variable | overwrite | | True | Variable is defined but not assigned |
| Script Content -1 | Input Variable | characterSet | | | Variable is defined but not assigned |
| Script Content -2 | Input Variable | file | | C:\Vcenter\cluster.ps1 | Variable is defined but not assigned |
| Script Content -2 | Input Variable | contents | | Connect-VIServer \${viServer} -User \${userName} -Password \${password} \$clusterName = "\${ss}" foreach(\$cluster in Get-Cluster -Name \$clusterName) { \$esx = \$cluster Get-VMHost \$ds = Get-Datastore -VMHost \$esx where {\$_ .Type -eq "VMFS"} \$cluster Select @N=" VCName";E={\$cluster.U id. ... | Variable is defined but not assigned |
| Script Content -2 | Input Variable | delimiter | | | Variable is defined but not assigned |
| Script Content -2 | Input Variable | overwrite | | True | Variable is defined but not assigned |
| Script Content -2 | Input Variable | characterSet | | | Variable is defined but not assigned |
| collect Details of cluster | Flow Output Variable | resourceCapacityList | Input: field1 | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| FS Delete-1 | Input Variable | source | | C:\Vcenter\Getcluster.p s1 | Variable is defined but not assigned |
| FS Delete-1 | Input Variable | user | | | Variable is defined but not assigned |
| FS Delete-1 | Input Variable | password | | | Variable is defined but not assigned |
| FS Delete-2 | Input Variable | source | | C:\Vcenter\cluster.ps1 | Variable is defined but not assigned |
| FS Delete-2 | Input Variable | user | | | Variable is defined but not assigned |
| FS Delete-2 | Input Variable | password | | | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Script Content -3 | Input Variable | file | | C:\Vcenter\cluster1.ps1 | Variable is defined but not assigned |

| | | | | | |
|-------------------|----------------|-------------------|----------|---|--|
| Script Content -3 | Input Variable | contents | | Connect-VIServer -Server \${viServer} -Protocol https -User \${userName} -Password \${password} \$clusterName = "\${ss}" \$vms = Get-cluster \$clustername get-vm \$VMvCPUCount = \$vms Where-Object PowerState -eq PoweredOn Measure-Object -Sum -Property numcpu Select-Object Sum echo \$VMvCPUCount \$n ... | Variable is defined but not assigned |
| Script Content -3 | Input Variable | delimiter | | | Variable is defined but not assigned |
| Script Content -3 | Input Variable | overwrite | | True | Variable is defined but not assigned |
| Script Content -3 | Input Variable | characterSet | | | Variable is defined but not assigned |
| FS Delete-3 | Input Variable | source | | C:\Vcenter\cluster1.ps1 | Variable is defined but not assigned |
| FS Delete-3 | Input Variable | user | | | Variable is defined but not assigned |
| FS Delete-3 | Input Variable | password | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | password | password | 7YIL!Kq4Bvuc | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Advanced Search | Input Variable | protocol | | https | Variable is defined but not assigned |
| Advanced Search | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Advanced Search | Input Variable | propsType | | ClusterResourceUsage Summary | Variable is defined but not assigned |
| Advanced Search | Input Variable | propsPathset | | GetResourceUsage | Variable is defined but not assigned |
| Advanced Search | Input Variable | propsRootObjType | | ClusterComputeResour ce | Variable is defined but not assigned |
| Advanced Search | Input Variable | propsRootObj | | domain-c7 | Variable is defined but not assigned |
| Advanced Search | Input Variable | connectionTimeout | | | Variable is defined but not assigned |
| Advanced Search | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| List Clusters | Input Variable | closeSession | | false | Variable is defined but not assigned |
| List Clusters | Input Variable | propsType | | ClusterComputeResour ce | Variable is defined but not assigned |

| | | | | | |
|-------------------------------|----------------------|---------------------|---------------------------|-------------------------------------|---|
| List Clusters | Input Variable | propsPathset | | name,overallStatus,hos t,summary | Variable is defined but not assigned |
| List Clusters | Input Variable | propsRootObjType | | | Variable is defined but not assigned |
| List Clusters | Input Variable | propsRootObj | | | Variable is defined but not assigned |
| List Clusters | Input Variable | closeSession | | false | Variable is defined but not assigned |
| List Clusters | Input Variable | propsType | | domain-c7 | Variable is defined but not assigned |
| List Clusters | Input Variable | propsPathset | | usageSummary | Variable is defined but not assigned |
| List Clusters | Input Variable | propsRootObjType | | ClusterComputeResour ce | Variable is defined but not assigned |
| List Clusters | Input Variable | propsRootObj | | summary | Variable is defined but not assigned |
| Flow Inputs | Input Variable | selectedCluster | | | Variable is defined but not assigned |
| Get ClusterName | Flow Output Variable | selectedClusterName | Input: field1 | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | requestedCPU | | | Variable is defined but not assigned |
| Flow Inputs | Input Variable | selectedCluster | | | Variable is defined but not assigned |
| Get ClusterName | Flow Output Variable | selectedClusterName | Input: field1 | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Cluster Details | Flow Output Variable | selectedClusterName | Input: field1 | N/A | Flow Output variable created in flow steps |
| Get Row Index by Condition | Input Variable | worksheetName | | Sheet1 | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | hasHeader | | yes | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | firstRowIndex | | 0 | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | columnIndextoQuery | | 1 | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | operator | | == | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | value | value | | Input variable is using Prompt User |
| Modify Cell | Input Variable | columnIndex | | 0 | Variable is defined but not assigned |
| Modify Cell | Input Variable | newValue | | N | Variable is defined but not assigned |
| Modify Cell | Input Variable | columnDelimiter | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------------|--------------------|----------------------------|--------|--|
| Get Row Index by Condition | Input Variable | worksheetName | | Sheet1 | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | hasHeader | | yes | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | firstRowIndex | | 0 | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | columnIndextoQuery | | 0 | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | operator | | == | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | value | | N | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | excelFileName | excelFileName | | Input variable is using Prompt User |
| Modify Cell | Input Variable | worksheetName | | | Variable is defined but not assigned |
| Modify Cell | Input Variable | columnIndex | | 0 | Variable is defined but not assigned |
| Modify Cell | Input Variable | newValue | | Y | Variable is defined but not assigned |
| Modify Cell | Input Variable | columnDelimiter | | | Variable is defined but not assigned |
| Modify Cell | Input Variable | excelFileName | excelFileName | | Input variable is using Prompt User |
| Get Primary IP | Input Variable | columnIndex | | 1 | Variable is defined but not assigned |
| Get Primary IP | Input Variable | excelFileName | excelFileName | | Input variable is using Prompt User |
| Get Primary IP | Flow Output Variable | primaryIP | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Primary IP | Flow Output Variable | vmName | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get SubNet Mask | Input Variable | columnIndex | | 2 | Variable is defined but not assigned |
| Get SubNet Mask | Input Variable | excelFileName | excelFileName | | Input variable is using Prompt User |
| Get SubNet Mask | Flow Output Variable | subnetMask | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Gateway | Input Variable | columnIndex | | 3 | Variable is defined but not assigned |
| Get Gateway | Input Variable | excelFileName | excelFileName | | Input variable is using Prompt User |
| Get Gateway | Flow Output Variable | netGateway | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Primary DNS | Input Variable | columnIndex | | 4 | Variable is defined but not assigned |
| Get Primary DNS | Input Variable | excelFileName | excelFileName | | Input variable is using Prompt User |
| Get Primary DNS | Flow Output Variable | primaryDNS | Result Field: returnResult | N/A | Flow Output variable created in flow steps |

| | | | | | |
|----------------------------|----------------------|--------------------|----------------------------|--------------|--|
| Get Secondary DNS | Input Variable | columnIndex | | 5 | Variable is defined but not assigned |
| Get Secondary DNS | Input Variable | excelFileName | excelFileName | | Input variable is using Prompt User |
| Get Secondary DNS | Flow Output Variable | secondaryDNS | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Set Failure Message | Flow Output Variable | returnResult | Input: returnResult | N/A | Flow Output variable created in flow steps |
| Set Failure Message | Flow Output Variable | returnResult | Input: returnResult | N/A | Flow Output variable created in flow steps |
| Set Failure Message | Flow Output Variable | returnResult | Input: returnResult | N/A | Flow Output variable created in flow steps |
| Set Failure Message | Flow Output Variable | returnResult | Input: returnResult | N/A | Flow Output variable created in flow steps |
| Set Failure Message | Flow Output Variable | returnResult | Input: returnResult | N/A | Flow Output variable created in flow steps |
| Set Failure Message | Flow Output Variable | returnResult | Input: returnResult | N/A | Flow Output variable created in flow steps |
| Set Failure Message | Flow Output Variable | returnResult | Input: returnResult | N/A | Flow Output variable created in flow steps |
| Get Host Name | Input Variable | columnIndex | | 6 | Variable is defined but not assigned |
| Get Host Name | Input Variable | excelFileName | excelFileName | | Input variable is using Prompt User |
| Get Host Name | Flow Output Variable | hostname | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Set Failure Message | Flow Output Variable | returnResult | Input: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_WIN_PATH | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | worksheetName | | Sheet1 | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | hasHeader | | yes | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | firstRowIndex | | 0 | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | columnIndextoQuery | | 0 | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | operator | | != | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | value | | | Variable is defined but not assigned |
| Get Row Index by Condition | Input Variable | excelFileName | excelFileName | | Input variable is using Prompt User |
| Ping | Input Variable | hostname | | 16.32.12.36 | Variable is defined but not assigned |
| Ping | Input Variable | username | | admin | Variable is defined but not assigned |
| Ping | Input Variable | password | | | Variable is defined but not assigned |
| Ping | Input Variable | protocol | | local | Variable is defined but not assigned |

| | | | | | |
|--------------------------------|----------------------|----------------------|----------------------------|---------------|---|
| Ping | Input Variable | packetCount | | | Variable is defined but not assigned |
| Ping | Input Variable | packetSize | | | Variable is defined but not assigned |
| Ping | Input Variable | remoteOS | | WINDOWS | Variable is defined but not assigned |
| Ping | Input Variable | usernamePrompt | | | Variable is defined but not assigned |
| Ping | Input Variable | passwordPrompt | | | Variable is defined but not assigned |
| Ping | Input Variable | passwordPrompt | | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Ping | Input Variable | keyFile | | | Variable is defined but not assigned |
| Ping | Input Variable | timeout | | | Variable is defined but not assigned |
| Ping | Input Variable | ipVersion | | 4 | Variable is defined but not assigned |
| Modify Cell | Input Variable | worksheetName | | | Variable is defined but not assigned |
| Modify Cell | Input Variable | columnIndex | | 0 | Variable is defined but not assigned |
| Modify Cell | Input Variable | columnDelimiter | | | Variable is defined but not assigned |
| Modify Cell | Input Variable | excelFileName | excelFileName | | Input variable is using Prompt User |
| Get Primary IP | Input Variable | columnIndex | | 1 | Variable is defined but not assigned |
| Get Primary IP | Input Variable | excelFileName | excelFileName | | Input variable is using Prompt User |
| Get Primary IP | Flow Output Variable | primaryIP | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Primary IP | Flow Output Variable | vmName | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Get Details of NIC | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Get Details of NIC | Input Variable | vmIdentifierType | | Name | Variable is defined but not assigned |
| Get Details of NIC | Flow Output Variable | vlanId | Result Field: netPortGroup | N/A | Flow Output variable created in flow steps |
| Get Details of NIC | Flow Output Variable | macAddress | Result Field: netMacAddr | N/A | Flow Output variable created in flow steps |
| Construct Final CustomSpec Xml | Flow Output Variable | customizationSpecXml | Result Field: Field_1 | N/A | Flow Output variable created in flow steps |
| Build DNS Server List Xml | Input Variable | xmlElementName | | dnsServerList | Variable is defined but not assigned |
| Build DNS Server List Xml | Input Variable | list | dnsServerIpList | | Input variable is using Prompt User |

| | | | | | |
|---|----------------------|----------------------|------------------------------------|-----------|---|
| Build Gateway List Xml | Input Variable | xmlElementName | | gateway | Variable is defined but not assigned |
| Build Gateway List Xml | Input Variable | list | gatewayIpList | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Get Power State | Input Variable | vmIdentifierType | | vmid | Variable is defined but not assigned |
| Get Power State | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Get Power State | Flow Output Variable | failureMesssage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Sleep 30 sec | Input Variable | seconds | | 30 | Variable is defined but not assigned |
| Loop | Input Variable | count | | 10 | Variable is defined but not assigned |
| Loop | Input Variable | reset | | false | Variable is defined but not assigned |
| Loop | Input Variable | to | | \${count} | Variable is defined but not assigned |
| Loop | Input Variable | from | | 1 | Variable is defined but not assigned |
| Loop | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Linux Mount points | Flow Output Variable | MountPoint1 | Input: field1 | N/A | Flow Output variable created in flow steps |
| Linux Mount points | Flow Output Variable | mountPoint2 | Input: field2 | N/A | Flow Output variable created in flow steps |
| Windows Mount points | Flow Output Variable | MountPoint1 | Input: field1 | N/A | Flow Output variable created in flow steps |
| Windows Mount points | Flow Output Variable | mountPoint2 | Input: field2 | N/A | Flow Output variable created in flow steps |
| Export Guest Customization Spec | Input Variable | host | host | | Input variable is using Prompt User |
| vCenter Build Fixed IP CustomSpec XML(Custom) | Input Variable | customizationSpec | | | Variable is defined but not assigned |
| vCenter Build Fixed IP CustomSpec XML(Custom) | Flow Output Variable | customizationSpecXml | Result Field: customizationSpecXml | N/A | Flow Output variable created in flow steps |
| vCenter Build Fixed IP CustomSpec XML(Custom) | Flow Output Variable | customizationSpec | Input: customizationSpec | N/A | Flow Output variable created in flow steps |
| Repalce Domain | Flow Output Variable | customSpecXml | Result: xml | N/A | Flow Output variable created in flow steps |
| Export Guest Customization Spec | Input Variable | host | host | | Input variable is using Prompt User |
| Export Guest Customization Spec | Flow Output Variable | customizationSpecXml | Result Field: returnResult | N/A | Flow Output variable created in flow steps |

| | | | | | |
|---------------------------------|----------------------|-----------------------|----------------------------|---|--|
| Export Guest Customization Spec | Flow Output Variable | customizationSpecXml1 | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Variable is defined but not assigned |
| Script Content -1 | Input Variable | file | | C:\Vcenter\Getcluster.ps1 | Variable is defined but not assigned |
| Script Content -1 | Input Variable | contents | | Connect-VIServer \${viServer} -User \${userName} -Password \${password} Get-Datacenter Get-Cluster Select Name* | Variable is defined but not assigned |
| Script Content -1 | Input Variable | delimiter | | | Variable is defined but not assigned |
| Script Content -1 | Input Variable | overwrite | | True | Variable is defined but not assigned |
| Script Content -1 | Input Variable | characterSet | | | Variable is defined but not assigned |
| Script Content -2 | Input Variable | file | | C:\Vcenter\cluster.ps1 | Variable is defined but not assigned |
| Script Content -2 | Input Variable | contents | | Connect-VIServer \${viServer} -User \${userName} -Password \${password} \$clusterName = "\${ss}" foreach(\$cluster in Get-Cluster -Name \$clusterName) { \$esx = \$cluster Get-VMHost \$ds = Get-Datastore -VMHost \$esx where {\$_.Type -eq "VMFS"} \$cluster Select @N=" VCname";E={\$cluster.U id. ... | Variable is defined but not assigned |
| Script Content -2 | Input Variable | delimiter | | | Variable is defined but not assigned |
| Script Content -2 | Input Variable | overwrite | | True | Variable is defined but not assigned |
| Script Content -2 | Input Variable | characterSet | | | Variable is defined but not assigned |
| Get Element Matching | Input Variable | delimiter | | | Variable is defined but not assigned |
| Get Element Matching | Input Variable | matchType | | Contains | Variable is defined but not assigned |
| Get cluster that matches | Flow Output Variable | selectedCluster | Input: field1 | N/A | Flow Output variable created in flow steps |
| FS Delete-1 | Input Variable | source | | C:\Vcenter\Getcluster.ps1 | Variable is defined but not assigned |
| FS Delete-1 | Input Variable | user | | | Variable is defined but not assigned |
| FS Delete-1 | Input Variable | password | | | Variable is defined but not assigned |

| | | | | | |
|---|----------------------|------------------|--------------------------------|------------------------|--|
| FS Delete-2 | Input Variable | source | | C:\Vcenter\cluster.ps1 | Variable is defined but not assigned |
| FS Delete-2 | Input Variable | user | | | Variable is defined but not assigned |
| FS Delete-2 | Input Variable | password | | | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get Cluster Internal ID | Flow Output Variable | clusterId | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Selection Process of ESXi | Input Variable | requestedCPU | | | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-2) | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-2) | Flow Output Variable | diskSize1 | Result: propertyNameValuesList | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-2) | Flow Output Variable | MountPoint1 | Result: propertyNameValuesList | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-3) | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-3) | Flow Output Variable | diskSize2 | Result: propertyNameValuesList | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-3) | Flow Output Variable | mountPoint2 | Result: propertyNameValuesList | N/A | Flow Output variable created in flow steps |
| Extend Disk-2 | Input Variable | async | | false | Variable is defined but not assigned |
| Extend Disk-2 | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Extend Disk-2 | Input Variable | vmIdentifierType | | Name | Variable is defined but not assigned |
| Extend Disk-2 | Input Variable | deviceNumber | | 2 | Variable is defined but not assigned |
| Extend Disk-2 | Input Variable | uuid | | | Variable is defined but not assigned |
| Extend Disk-3 | Input Variable | async | | false | Variable is defined but not assigned |
| Extend Disk-3 | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Extend Disk-3 | Input Variable | vmIdentifierType | | Name | Variable is defined but not assigned |
| Extend Disk-3 | Input Variable | deviceNumber | | 3 | Variable is defined but not assigned |
| Extend Disk-3 | Input Variable | uuid | | | Variable is defined but not assigned |
| Extend Disk-3 | Flow Output Variable | failureMessage | Result Field: returnResult | N/A | Flow Output variable created in flow steps |

| | | | | | |
|--|----------------------|------------------|------------------------------|---|--|
| Update Child Component Properties-Disk-1 | Input Variable | jsonObject | | { "SIZE": "\${diskSize1}", "MOUNT_POINT": "\${MountPoint1}" } | Variable is defined but not assigned |
| Update Child Component Properties-Disk-1 | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Update Child Component Properties-Disk-2 | Input Variable | jsonObject | | { "SIZE": "\${diskSize2}", "MOUNT_POINT": "\${mountPoint2}" } | Variable is defined but not assigned |
| Update Child Component Properties-Disk-2 | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Sleep | Input Variable | seconds | | 60 | Variable is defined but not assigned |
| Sleep | Input Variable | seconds | | 60 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | virtualMachine | | vm-11947 | Variable is defined but not assigned |
| List Virtual Machines | Input Variable | port | | 443 | Variable is defined but not assigned |
| List Virtual Machines | Input Variable | protocol | | https | Variable is defined but not assigned |
| List Virtual Machines | Input Variable | closeSession | | false | Variable is defined but not assigned |
| List Virtual Machines | Input Variable | propsType | | VirtualMachine | Variable is defined but not assigned |
| List Virtual Machines | Input Variable | propsPathset | | runtime.host | Variable is defined but not assigned |
| List Virtual Machines | Input Variable | propsRootObjType | | VirtualMachine | Variable is defined but not assigned |
| List Virtual Machines | Input Variable | host | vCenterHost | | Input variable is using Prompt User |
| List Virtual Machines | Input Variable | password | vCenterPassword | | Input variable is using Prompt User |
| List Virtual Machines | Flow Output Variable | esxHost | Result Field: array | N/A | Flow Output variable created in flow steps |
| Get Virtual Machine Details | Input Variable | port | | 443 | Variable is defined but not assigned |
| Get Virtual Machine Details | Input Variable | protocol | | https | Variable is defined but not assigned |
| Get Virtual Machine Details | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Get Virtual Machine Details | Input Variable | propsType | | VirtualMachine | Variable is defined but not assigned |
| Get Virtual Machine Details | Input Variable | propsPathset | | guest.guestFamily,name,config.template | Variable is defined but not assigned |
| Get Virtual Machine Details | Input Variable | propsRootObjType | | VirtualMachine | Variable is defined but not assigned |
| Get Virtual Machine Details | Input Variable | host | vCenterHost | | Input variable is using Prompt User |

| | | | | | |
|---|----------------------|---------------------------|--------------------------------|------------|--|
| Get Virtual Machine Details | Input Variable | user | vCenterUsername | | Input variable is using Prompt User |
| Get Virtual Machine Details | Input Variable | password | vCenterPassword | | Input variable is using Prompt User |
| Get Virtual Machine Details | Flow Output Variable | guestFamily | Result Field: guestFamily | N/A | Flow Output variable created in flow steps |
| Get Virtual Machine | Input Variable | port | | 443 | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | protocol | | https | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | vmDatacenter | | | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | hostSystem | | | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | vmIdentifierType | | vmid | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | getDetailed | | false | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | connectionTimeout | | | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | host | vCenterHost | | Input variable is using Prompt User |
| Get Virtual Machine | Input Variable | password | vCenterPassword | | Input variable is using Prompt User |
| Get Virtual Machine | Flow Output Variable | datacenter | Result Field: inventoryPath | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-2) | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-2) | Flow Output Variable | diskSize1 | Result: propertyNameValuesList | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-2) | Flow Output Variable | MountPoint1 | Result: propertyNameValuesList | N/A | Flow Output variable created in flow steps |
| SQL Command To Get Template | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | instance | | | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | dbClass | | | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | dbURL | | | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | timeout | | | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |

| | | | | | |
|---|----------------------|----------------------|---------------------------------|----------|--|
| SQL Command To Get Template | Input Variable | resultSetType | | | Variable is defined but not assigned |
| SQL Command To Get Template | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| SQL Command To Get Template | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| SQL Command To Get Template | Flow Output Variable | osDiskSize | Result Field: outputText | N/A | Flow Output variable created in flow steps |
| threshold Calc | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| threshold Calc | Flow Output Variable | threshtoldSpace | Input: fiedl5 | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-3) | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-3) | Flow Output Variable | diskSize2 | Result: propertyNameV aluesList | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (disk-3) | Flow Output Variable | mountPoint2 | Result: propertyNameV aluesList | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Reboot Guest | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Reboot Guest | Input Variable | vmIdentifierType | | VMID | Variable is defined but not assigned |
| Reboot Guest | Input Variable | host | host | | Input variable is using Prompt User |
| Reboot Guest | Input Variable | password | password | | Input variable is using Prompt User |
| Count | Input Variable | from | | 1 | Variable is defined but not assigned |
| Count | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Count | Input Variable | reset | | false | Variable is defined but not assigned |
| Set Power State | Input Variable | vmIdentifierType | | VMID | Variable is defined but not assigned |
| Set Power State | Flow Output Variable | powerState | Input: vmPowerState | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | virtualMachine | | vm-11948 | Variable is defined but not assigned |
| Get Power State | Input Variable | port | | 443 | Variable is defined but not assigned |
| Get Power State | Input Variable | protocol | | https | Variable is defined but not assigned |
| Get Power State | Input Variable | vmIdentifierType | | vmid | Variable is defined but not assigned |
| Get Power State | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Get Power State | Input Variable | host | vCenterHost | | Input variable is using Prompt User |

| | | | | | |
|---------------------------------|----------------|------------------|-----------------|-----------|--------------------------------------|
| Get Power State | Input Variable | password | vCenterPassword | | Input variable is using Prompt User |
| Get Power State | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| vCenter Restart Virtual Machine | Input Variable | vCenterProtocol | | https | Variable is defined but not assigned |
| vCenter Restart Virtual Machine | Input Variable | vCenterPort | | 443 | Variable is defined but not assigned |
| vCenter Restart Virtual Machine | Input Variable | closeSession | | true | Variable is defined but not assigned |
| vCenter Restart Virtual Machine | Input Variable | vmIdentifierType | | vmid | Variable is defined but not assigned |
| vCenter Restart Virtual Machine | Input Variable | vmDatacenter | | | Variable is defined but not assigned |
| vCenter Restart Virtual Machine | Input Variable | waitGuest | | true | Variable is defined but not assigned |
| vCenter Restart Virtual Machine | Input Variable | poolingRetries | | 10 | Variable is defined but not assigned |
| vCenter Restart Virtual Machine | Input Variable | poolingInterval | | 10 | Variable is defined but not assigned |
| vCenter Restart Virtual Machine | Input Variable | vCenterHost | vCenterHost | | Input variable is using Prompt User |
| vCenter Restart Virtual Machine | Input Variable | vCenterUsername | vCenterUsername | | Input variable is using Prompt User |
| vCenter Restart Virtual Machine | Input Variable | vCenterPassword | vCenterPassword | | Input variable is using Prompt User |
| vCenter Restart Virtual Machine | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Set Power State | Input Variable | port | | 443 | Variable is defined but not assigned |
| Set Power State | Input Variable | protocol | | https | Variable is defined but not assigned |
| Set Power State | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Set Power State | Input Variable | async | | false | Variable is defined but not assigned |
| Set Power State | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Set Power State | Input Variable | vmIdentifierType | | vmid | Variable is defined but not assigned |
| Set Power State | Input Variable | vmPowerState | | poweredOn | Variable is defined but not assigned |
| Set Power State | Input Variable | host | vCenterHost | | Input variable is using Prompt User |
| Set Power State | Input Variable | password | vCenterPassword | | Input variable is using Prompt User |
| Set Power State | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Sleep | Input Variable | seconds | | 15 | Variable is defined but not assigned |

| | | | | | |
|-----------------|----------------------|------------------|------------------------------|-------|--|
| Counter | Input Variable | from | | 1 | Variable is defined but not assigned |
| Counter | Input Variable | to | | 60 | Variable is defined but not assigned |
| Counter | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Counter | Input Variable | reset | | false | Variable is defined but not assigned |
| Get Power State | Input Variable | port | | 443 | Variable is defined but not assigned |
| Get Power State | Input Variable | protocol | | https | Variable is defined but not assigned |
| Get Power State | Input Variable | vmIdentifierType | | vmid | Variable is defined but not assigned |
| Get Power State | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Get Power State | Input Variable | host | vCenterHost | | Input variable is using Prompt User |
| Get Power State | Input Variable | password | vCenterPassword | | Input variable is using Prompt User |
| Get Power State | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Hold Result | Flow Output Variable | xml | Input: field1 | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | host | host | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | user | user | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | password | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Set CPU Count | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Set CPU Count | Input Variable | async | | false | Variable is defined but not assigned |
| Set CPU Count | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Set CPU Count | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Set CPU Count | Input Variable | user | user | | Input variable is using Prompt User |
| Set CPU Count | Input Variable | password | password | | Input variable is using Prompt User |
| Set CPU Count | Input Variable | vmCpuCount | vmCpuCount | | Input variable is using Prompt User |
| Set CPU Count | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Set Memory Size | Input Variable | closeSession | | true | Variable is defined but not assigned |

| | | | | | |
|---------------------|----------------------|---------------------------|----------------------------------|-------|--|
| Set Memory Size | Input Variable | async | | false | Variable is defined but not assigned |
| Set Memory Size | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Set Memory Size | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Set Memory Size | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Set Flow Variables | Flow Output Variable | providerName | Input: providerName | N/A | Flow Output variable created in flow steps |
| Set Flow Variables | Flow Output Variable | datacenterName | Input: datacenterName | N/A | Flow Output variable created in flow steps |
| Set Flow Variables | Flow Output Variable | vmNamePrefix | Input: vmNamePrefix | N/A | Flow Output variable created in flow steps |
| Set Flow Variables | Flow Output Variable | vmFolder | Input: vmFolder | N/A | Flow Output variable created in flow steps |
| Set Flow Variables | Flow Output Variable | cpu | Input: cpu | N/A | Flow Output variable created in flow steps |
| Set Flow Variables | Flow Output Variable | memory | Input: memory | N/A | Flow Output variable created in flow steps |
| Set Flow Variables | Flow Output Variable | customizationTemplateName | Input: customizationTemplateName | N/A | Flow Output variable created in flow steps |
| Set Flow Variables | Flow Output Variable | virtualMachine | Input: virtualMachine | N/A | Flow Output variable created in flow steps |
| Set Flow Variables | Flow Output Variable | customizationTemplateName | Input: customizationTemplateName | N/A | Flow Output variable created in flow steps |
| Set Flow Variables | Flow Output Variable | virtualMachine | Input: virtualMachine | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | seconds | seconds | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | from | from | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | to | to | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | host | host | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | user | user | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | password | password | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | port | port | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | protocol | protocol | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | DATACENTER | DATACENTER | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | HOSTNAME | HOSTNAME | | Input variable is using Prompt User |
| Get Virtual Machine | Input Variable | closeSession | | false | Variable is defined but not assigned |

| | | | | | |
|-----------------------|----------------------|------------------|------------------------------|------------------------------|--|
| Get Virtual Machine | Input Variable | vmDatacenter | | \${DATACENTER} | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | vmIdentifierType | | NAME | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | virtualMachine | | \${HOSTNAME} | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | getDetailed | | false | Variable is defined but not assigned |
| Get Virtual Machine | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Guest Tools Status | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Guest Tools Status | Input Variable | propsType | | VirtualMachine | Variable is defined but not assigned |
| Guest Tools Status | Input Variable | propsPathset | | guest.toolsRunningStat us | Variable is defined but not assigned |
| Guest Tools Status | Input Variable | propsRootObjType | | VirtualMachine | Variable is defined but not assigned |
| Guest Tools Status | Input Variable | host | host | | Input variable is using Prompt User |
| Guest Tools Status | Input Variable | user | user | | Input variable is using Prompt User |
| Guest Tools Status | Input Variable | password | password | | Input variable is using Prompt User |
| Guest Tools Status | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Sleep | Input Variable | seconds | | 300 | Variable is defined but not assigned |
| Get Guest Info | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Get Guest Info | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Get Guest Info | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Get Guest Info | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Guest Info | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Sleep Loop for 30 min | Input Variable | seconds | | 30 | Variable is defined but not assigned |
| Sleep Loop for 30 min | Input Variable | to | | 60 | Variable is defined but not assigned |
| Sleep 5 min | Input Variable | seconds | | 300 | Variable is defined but not assigned |
| Loop | Input Variable | count | | 10 | Variable is defined but not assigned |
| Loop | Input Variable | reset | | false | Variable is defined but not assigned |
| Loop | Input Variable | to | | \${count} | Variable is defined but not assigned |

| | | | | | |
|----------------|----------------|----------------|--|--|--------------------------------------|
| Loop | Input Variable | from | | 1 | Variable is defined but not assigned |
| Loop | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Sleep 30 sec | Input Variable | seconds | | 30 | Variable is defined but not assigned |
| Sleep 2 min | Input Variable | seconds | | 120 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | projectId | | mfdev_p00009 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | projectName | | mfdev_p00009-Applicat ion | Variable is defined but not assigned |
| Flow Inputs | Input Variable | role | | wa | Variable is defined but not assigned |
| Flow Inputs | Input Variable | requestingUser | | srinivas.rn2@microfocu s.com | Variable is defined but not assigned |
| Flow Inputs | Input Variable | approvers | | srinivas.rn2@microfocu s.com | Variable is defined but not assigned |
| Flow Inputs | Input Variable | hidden | | false | Variable is defined but not assigned |
| Flow Inputs | Input Variable | company | | MFI | Variable is defined but not assigned |
| Create Project | Input Variable | method | | POST | Variable is defined but not assigned |
| Create Project | Input Variable | authType | | basic | Variable is defined but not assigned |
| Create Project | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:e ncodingStyle="http://sch emas.xmlsoap.org/soap /encoding/" xmlns:soap ="http://schemas.xmlso ap.org/soap/envelope/" xmlns:soapenc="http://s chemas.xmlsoap.org/so ap/encoding/" xmlns:xs d="http://www.w3.org/2 001/XMLSchema" xmlns:xsi="http://www. ... | Variable is defined but not assigned |
| Create Project | Input Variable | headers | | SOAPAction:http://vsmli stener.houston.software grp.net/API/V2/SoapSer vices#CreateProject | Variable is defined but not assigned |
| Create Project | Input Variable | contentType | | text/xml; charset=UTF-8 | Variable is defined but not assigned |
| Create Project | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Create Project | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Create Project | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |

| | | | | | |
|----------------|----------------|----------------------|--|--|--------------------------------------|
| Create Project | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Create Project | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Create Project | Input Variable | connectTimeout | | 30 | Variable is defined but not assigned |
| Create Project | Input Variable | socketTimeout | | 120 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | groupName | | wa_mfdev_p00009 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | requestingUser | | srinivas.rn2@microfocus.com | Variable is defined but not assigned |
| Flow Inputs | Input Variable | primaryUpn | | sup_srinivasrn3@microfocus.com | Variable is defined but not assigned |
| Flow Inputs | Input Variable | expiration | | 2999-01-01 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | company | | MFI | Variable is defined but not assigned |
| Create User | Input Variable | method | | POST | Variable is defined but not assigned |
| Create User | Input Variable | authType | | basic | Variable is defined but not assigned |
| Create User | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Variable is defined but not assigned |
| Create User | Input Variable | headers | | SOAPAction:http://vsmli.stener.houston.softwargrp.net/API/V2/SoapServices#CreateUser | Variable is defined but not assigned |
| Create User | Input Variable | contentType | | text/xml; charset=UTF-8 | Variable is defined but not assigned |
| Create User | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Create User | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Create User | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Create User | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Create User | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |

| | | | | | |
|----------------|----------------------|----------------|----------------------------|--|--|
| Create User | Input Variable | connectTimeout | | 30 | Variable is defined but not assigned |
| Create User | Input Variable | socketTimeout | | 120 | Variable is defined but not assigned |
| Create User | Flow Output Variable | vsmFaultstring | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Sleep | Input Variable | seconds | | 15 | Variable is defined but not assigned |
| Loop | Input Variable | count | | 8 | Variable is defined but not assigned |
| Loop | Input Variable | reset | | false | Variable is defined but not assigned |
| Loop | Input Variable | to | | \${count} | Variable is defined but not assigned |
| Loop | Input Variable | from | | 1 | Variable is defined but not assigned |
| Loop | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | projectId | | mf4icsa_p00001 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | company | | MFI | Variable is defined but not assigned |
| Delete Project | Input Variable | method | | POST | Variable is defined but not assigned |
| Delete Project | Input Variable | authType | | basic | Variable is defined but not assigned |
| Delete Project | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Variable is defined but not assigned |
| Delete Project | Input Variable | headers | | SOAPAction:http://vsmli stener.houston.software grp.net/API/V2/SoapSer vices#DeleteProject | Variable is defined but not assigned |
| Delete Project | Input Variable | contentType | | text/xml; charset=UTF-8 | Variable is defined but not assigned |
| Delete Project | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Delete Project | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Delete Project | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |

| | | | | | |
|-------------------|----------------|----------------------|--|--|--------------------------------------|
| Delete Project | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Delete Project | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Delete Project | Input Variable | connectTimeout | | 30 | Variable is defined but not assigned |
| Delete Project | Input Variable | socketTimeout | | 120 | Variable is defined but not assigned |
| Delete User | Input Variable | method | | POST | Variable is defined but not assigned |
| Delete User | Input Variable | authType | | basic | Variable is defined but not assigned |
| Delete User | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Variable is defined but not assigned |
| Delete User | Input Variable | headers | | SOAPAction:http://vsmli stener.houston.software grp.net/API/VRO/Soap Services#QueryProject | Variable is defined but not assigned |
| Delete User | Input Variable | contentType | | text/xml; charset=UTF-8 | Variable is defined but not assigned |
| Delete User | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Delete User | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Delete User | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Delete User | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Delete User | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Delete User | Input Variable | connectTimeout | | 30 | Variable is defined but not assigned |
| Delete User | Input Variable | socketTimeout | | 120 | Variable is defined but not assigned |
| Host Registration | Input Variable | method | | POST | Variable is defined but not assigned |
| Host Registration | Input Variable | authType | | basic | Variable is defined but not assigned |

| | | | | | |
|---------------------------|----------------|----------------------|--------------|--|--------------------------------------|
| Host Registration | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Variable is defined but not assigned |
| Host Registration | Input Variable | headers | | SOAPAction:http://vsmli.stener.houston.software.grp.net/API/V2/SoapServices#HostRegistration | Variable is defined but not assigned |
| Host Registration | Input Variable | contentType | | text/xml; charset=UTF-8 | Variable is defined but not assigned |
| Host Registration | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Host Registration | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Host Registration | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Host Registration | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Host Registration | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Host Registration | Input Variable | connectTimeout | | 30 | Variable is defined but not assigned |
| Host Registration | Input Variable | socketTimeout | | 120 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | serverNames | serverNames | | Input variable is using Prompt User |
| Start Adhoc Server Script | Input Variable | sourceCodeType | | SH | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | scriptArguments | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | serverNames | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | loginDomain | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | username | | | Variable is defined but not assigned |

| | | | | | |
|---------------------------|----------------------|-------------------------------|-----------------------|--------|--|
| Start Adhoc Server Script | Input Variable | password | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | scriptTimeout | | 300000 | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | scriptTailOutputSize | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | separator | | , | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | ticketId | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | notificationFailureOwner | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | notificationSuccessOwner | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | notificationCancelOwner | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | notificationFailureRecipients | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | notificationSuccessRecipients | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | notificationCancelRecipients | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | scheduleDateYear | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | scheduleDateMonth | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | scheduleDateDayOfMonth | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | scheduleDateHour | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | scheduleDateMinute | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | scheduleDateSecond | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | scheduleDateTimezone | | | Variable is defined but not assigned |
| Start Adhoc Server Script | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Start Adhoc Server Script | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Start Adhoc Server Script | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Start Adhoc Server Script | Flow Output Variable | failureMessage | Result Field: Result | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Script Job Result | Flow Output Variable | failureMessage | Result Field: summary | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Flow Output Variable | output | Result Field: output | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-----------------|----------------------|----------------------|------------------------------|--|---|
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | 600000 | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Wait for Job | Flow Output Variable | failureMessage | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Exit code check | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | projectId | | mfdev_p00007 | Variable is defined but not assigned |
| Flow Inputs | Input Variable | company | | MFI | Variable is defined but not assigned |
| Query Project | Input Variable | method | | POST | Variable is defined but not assigned |
| Query Project | Input Variable | authType | | basic | Variable is defined but not assigned |
| Query Project | Input Variable | password | vsmPassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Query Project | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Variable is defined but not assigned |
| Query Project | Input Variable | headers | | SOAPAction:http://vsmli stener.houston.software grp.net/API/V2/SoapSer vices#QueryProject | Variable is defined but not assigned |
| Query Project | Input Variable | contentType | | text/xml; charset=UTF-8 | Variable is defined but not assigned |
| Query Project | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Query Project | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Query Project | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Query Project | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Query Project | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |

| | | | | | |
|-----------------------------------|----------------------|----------------------|---------------|--|---|
| Query Project | Input Variable | connectTimeout | | 30 | Variable is defined but not assigned |
| Query Project | Input Variable | socketTimeout | | 120 | Variable is defined but not assigned |
| Query Project | Input Variable | method | | POST | Variable is defined but not assigned |
| Query Project | Input Variable | authType | | basic | Variable is defined but not assigned |
| Query Project | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Variable is defined but not assigned |
| Query Project | Input Variable | headers | | SOAPAction:http://vsmli stener.houston.software grp.net/API/V2/SoapSer vices#QueryProject | Variable is defined but not assigned |
| Query Project | Input Variable | contentType | | text/xml; charset=UTF-8 | Variable is defined but not assigned |
| Query Project | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Query Project | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Query Project | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Query Project | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Query Project | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Query Project | Input Variable | connectTimeout | | 30 | Variable is defined but not assigned |
| Query Project | Input Variable | socketTimeout | | 120 | Variable is defined but not assigned |
| Convert environment to short name | Flow Output Variable | env | Input: field1 | N/A | Flow Output variable created in flow steps |
| Get VC OS Disk Size | Input Variable | offeringName | | | Variable is defined but not assigned |
| Get VC OS Disk Size | Input Variable | networkType | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | corePassword | corePassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |

| | | | | | |
|---------------------------|----------------------|---------------------------|------------------------------|--|--|
| Get Server VO | Input Variable | matching | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | serverID | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | delimiter | | | Variable is defined but not assigned |
| Create Project VSM | Input Variable | hidden | | false | Variable is defined but not assigned |
| Create User VSM | Input Variable | groupName | | \${role}_\${projectId} | Variable is defined but not assigned |
| Create User VSM | Input Variable | primaryUpn | | \${supAccount}@microfocus.com | Variable is defined but not assigned |
| Create User VSM | Input Variable | expiration | | 2999-01-01 | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | instance | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | dbClass | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | dbURL | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | timeout | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | resultSetType | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Flow Output Variable | failuremessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Linux - Add admin User | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Linux - Add admin User | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Linux - Add admin User | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Linux - Add admin User | Input Variable | serverNames | serverId | | Input variable is using Prompt User |
| Windows Add Admin | Input Variable | args | | -t \${hostName} -s MFI-AddProjectWinAdmins -a "\${projectId}" -z 5 | Variable is defined but not assigned |

| | | | | | |
|--------------------------|----------------------|-------------------------------|------------------------------|-----------|--|
| Get Supplemental Account | Input Variable | primaryEmail | requestorEmail | | Input variable is using Prompt User |
| Start Server Script | Input Variable | scriptToRunID | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHostSearchOperator | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetUser | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetPassword | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetDomain | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTimeout | | 300 | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessRecipients | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | ticketId | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTailOutputSize | | | Variable is defined but not assigned |
| Start Server Script | Flow Output Variable | failureMessage | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Start Server Script | Flow Output Variable | jobid | Result Field: id | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Script Job Result | Flow Output Variable | failureMessage | Result Field: summary | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Flow Output Variable | output | Result Field: output | N/A | Flow Output variable created in flow steps |
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | 600000 | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Exit code check | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Sleep 60 sec | Input Variable | seconds | | 60 | Variable is defined but not assigned |
| Loop | Input Variable | count | | 3 | Variable is defined but not assigned |
| Loop | Input Variable | reset | | false | Variable is defined but not assigned |
| Loop | Input Variable | to | | \${count} | Variable is defined but not assigned |
| Loop | Input Variable | from | | 1 | Variable is defined but not assigned |
| Loop | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |

| | | | | | |
|-------------------------------|----------------|----------------------------|----------|---|---|
| Error : failure | Input Variable | failureMessage | | Flow has tried execution of the script but failed to execute script check the VSM Group/Project | Variable is defined but not assigned |
| Flow Inputs | Input Variable | vlan | vlan | | Input variable is using Prompt User |
| Get Primary NIC Properties | Input Variable | childComponentName | | Primary NIC | Variable is defined but not assigned |
| Get CustomSpec XML | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Get Available Datastore (DXC) | Input Variable | vpassword | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Get Available Datastore (DXC) | Input Variable | overrideNRAS | | RAS_Win_Path | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | async | | false | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | taskTimeOut | | 3600 | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | vmIdentifierType | | Name | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | vmResourcePool | | | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | hostSystem | | | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | description | | | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | markAsTemplate | | false | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | thinProvision | | true | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | customizationTemplate Name | | | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | connectionTimeout | | 30 | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | socketTimeout | | 30 | Variable is defined but not assigned |
| Clone Virtual Machine | Input Variable | diskConfig | | | Variable is defined but not assigned |
| Get Task State | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Get Task State | Input Variable | host | host | | Input variable is using Prompt User |
| Get Task State | Input Variable | user | user | | Input variable is using Prompt User |
| Get Task State | Input Variable | password | password | | Input variable is using Prompt User |

| | | | | | |
|--------------------------------|----------------------|------------------------|----------------------------|--|--|
| Get Task State | Input Variable | port | port | | Input variable is using Prompt User |
| Get Task State | Input Variable | taskId | taskId | | Input variable is using Prompt User |
| Get Task State | Flow Output Variable | vmId | Result Field: taskResult | N/A | Flow Output variable created in flow steps |
| Set Power State | Input Variable | vmIdentifierType | | VMID | Variable is defined but not assigned |
| Set Power State | Flow Output Variable | powerState | Input: vmPowerState | N/A | Flow Output variable created in flow steps |
| Get Virtual Machine | Input Variable | vmIdentifierType | | vmid | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | getDetailed | | false | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | connectionTimeout | | | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | host | host | | Input variable is using Prompt User |
| Get Virtual Machine | Input Variable | password | password | | Input variable is using Prompt User |
| Get Virtual Machine | Flow Output Variable | vmUUID | Result Field: uuid | N/A | Flow Output variable created in flow steps |
| Task Success? | Flow Output Variable | failureMessage | Input: errorMessage | N/A | Flow Output variable created in flow steps |
| Update Primary NIC Properties | Input Variable | childComponentName | | Primary NIC | Variable is defined but not assigned |
| Update Primary NIC Properties | Input Variable | jsonObject | | { "MAC_ADDRESS": "\${netMacAddr}", "VLAN_ID": "\${netPortGroup}" } | Variable is defined but not assigned |
| Get properties for Disks | Input Variable | childComponentName1 | | Disk 1 | Variable is defined but not assigned |
| Get properties for Disks | Input Variable | childComponentName2 | | Disk 2 | Variable is defined but not assigned |
| Set Resources (CPU and Memory) | Flow Output Variable | cpu | Result Field: CPU | N/A | Flow Output variable created in flow steps |
| Set Resources (CPU and Memory) | Flow Output Variable | memoryMB | Result Field: memorysizeMB | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Input Variable | oorunId | | \${run_id} | Variable is defined but not assigned |
| Error Handling | Input Variable | constantFailureMessage | | Failed in Clone VM Step | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |

| | | | | | |
|--------------------|----------------------|------------------------|---------------------------|-------------------------|---|
| Check Power State | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Error Handling | Input Variable | oorunId | | \${run_id} | Variable is defined but not assigned |
| Error Handling | Input Variable | constantFailureMessage | | Failed in Clone VM Step | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get Details of NIC | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Get Details of NIC | Input Variable | vmIdentifierType | | Name | Variable is defined but not assigned |
| Get Details of NIC | Input Variable | deviceNumber | | 1 | Variable is defined but not assigned |
| Configure NIC | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Configure NIC | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Configure NIC | Input Variable | async | | true | Variable is defined but not assigned |
| Configure NIC | Input Variable | taskTimeout | | 800 | Variable is defined but not assigned |
| Configure NIC | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Configure NIC | Input Variable | deviceNumber | | 1 | Variable is defined but not assigned |
| Configure NIC | Input Variable | netNicType | | VmxNet3 | Variable is defined but not assigned |
| Configure NIC | Input Variable | netMacGeneration | | | Variable is defined but not assigned |
| Configure NIC | Input Variable | netMacAddr | | | Variable is defined but not assigned |
| Configure NIC | Input Variable | netWakeOnLan | | true | Variable is defined but not assigned |
| Configure NIC | Input Variable | connect | | true | Variable is defined but not assigned |
| Configure NIC | Input Variable | connectAtPowerOn | | true | Variable is defined but not assigned |
| Sleep | Input Variable | seconds | | 120 | Variable is defined but not assigned |
| Error Handling | Input Variable | oorunId | | \${run_id} | Variable is defined but not assigned |
| Error Handling | Input Variable | constantFailureMessage | | Failed in Clone VM Step | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |

| | | | | | |
|------------------|----------------|---------------------------|--|--|--------------------------------------|
| Sleep | Input Variable | seconds | | 60 | Variable is defined but not assigned |
| JSON Path | Input Variable | jsonPathQuery | | \$.Id | Variable is defined but not assigned |
| Http Client Get | Input Variable | url | | https://\${smaxHostname}/rest/\${smaxTenantId}/ems/ServiceComponent | Variable is defined but not assigned |
| Http Client Get | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Get | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Get | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken};TENANTID=\${smaxTenantId} | Variable is defined but not assigned |
| Http Client Get | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParams | | filter=DisplayLabel eq ('\${businessApplication}')&layout;=DisplayLabel | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Http Client Get | Input Variable | method | | GET | Variable is defined but not assigned |
| Http Client Post | Input Variable | url | | https://\${smaxHostname}/rest/\${smaxTenantId}/ems/bulk | Variable is defined but not assigned |
| Http Client Post | Input Variable | body | | { "relationships": [{ "name": "ServiceComponentContainsDevice", "firstEndpoint": { "ServiceComponent": "\${bussAppEntityId}" }, "secondEndpoint": { "Device": "\${entityId}" } }], "operation": "CREATE" } | Variable is defined but not assigned |
| Http Client Post | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Http Client Post | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Http Client Post | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |

| | | | | | |
|------------------|----------------------|--------------------------|---------------------------|--|--|
| Http Client Post | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Http Client Post | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Http Client Post | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken};TENANTID=\${smaxTenantId} | Variable is defined but not assigned |
| Http Client Post | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParams | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | formParams | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Http Client Post | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | contentType | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Http Client Post | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Http Client Post | Input Variable | method | | POST | Variable is defined but not assigned |
| Create Entity | Input Variable | sawUrl | | https://\${smaxHostname} | Variable is defined but not assigned |
| Create Entity | Input Variable | tenantId | | \${smaxTenantId} | Variable is defined but not assigned |
| Create Entity | Flow Output Variable | returnResult | Result: returnResult | N/A | Flow Output variable created in flow steps |
| Create Entity | Flow Output Variable | entityJSON | Result: entityJSON | N/A | Flow Output variable created in flow steps |
| Create Entity | Flow Output Variable | entityId | Result: createdId | N/A | Flow Output variable created in flow steps |
| Create Entity | Flow Output Variable | opStatus | Result: opStatus | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-----------------------|----------------------|-------------------------------|------------------------------|--------|--|
| Flow Inputs | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | serverNames | serverNames | | Input variable is using Prompt User |
| Get Script Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Script Job Result | Flow Output Variable | failureMessage | Result Field: summary | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Flow Output Variable | output | Result Field: output | N/A | Flow Output variable created in flow steps |
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | 600000 | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Wait for Job | Flow Output Variable | failureMessage | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Exit code check | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Start Server Script | Input Variable | scriptToRunID | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHosts | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHostSearchOperator | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetUser | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetPassword | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetDomain | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTimeout | | 600 | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationFailureOwner | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessOwner | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationFailureRecipients | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessRecipients | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | ticketId | | | Variable is defined but not assigned |

| | | | | | |
|---------------------|----------------------|-------------------------------|----------------------------|--------|--|
| Start Server Script | Input Variable | scriptTailOutputSize | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Start Server Script | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Start Server Script | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Start Server Script | Flow Output Variable | jobid | Result Field: id | N/A | Flow Output variable created in flow steps |
| Get Server VO | Input Variable | matching | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | serverID | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | delimiter | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Get Server VO | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | 600000 | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Wait for Job | Flow Output Variable | failureMessage | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Start Server Script | Input Variable | scriptToRunID | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHosts | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHostSearchOperator | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetUser | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetPassword | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetDomain | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTimeout | | 600 | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationFailureOwner | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessOwner | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationFailureRecipients | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessRecipients | | | Variable is defined but not assigned |

| | | | | | |
|------------------------|----------------------|----------------------|-----------------------|------------------------------------|--|
| Start Server Script | Input Variable | ticketId | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTailOutputSize | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Start Server Script | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Start Server Script | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Start Server Script | Flow Output Variable | jobid | Result Field: id | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Script Job Result | Flow Output Variable | failureMessage | Result Field: summary | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Flow Output Variable | output | Result Field: output | N/A | Flow Output variable created in flow steps |
| Loop | Input Variable | count | | 3 | Variable is defined but not assigned |
| Loop | Input Variable | reset | | false | Variable is defined but not assigned |
| Loop | Input Variable | to | | \${count} | Variable is defined but not assigned |
| Loop | Input Variable | from | | 1 | Variable is defined but not assigned |
| Loop | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Sleep | Input Variable | seconds | | 15 | Variable is defined but not assigned |
| Sleep | Input Variable | seconds | | 45 | Variable is defined but not assigned |
| Run Communication Test | Input Variable | attachableType | | SERVER | Variable is defined but not assigned |
| Run Communication Test | Input Variable | timeout | | | Variable is defined but not assigned |
| Run Communication Test | Input Variable | separator | | , | Variable is defined but not assigned |
| Run Communication Test | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Run Communication Test | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Run Communication Test | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Linux OA Agent Install | Input Variable | host | | | Variable is defined but not assigned |
| Linux OA Agent Install | Input Variable | policyName | | \${SA Policy/OA Policy Name Linux} | Variable is defined but not assigned |
| Linux OA Agent Install | Input Variable | policyID | | \${SA Policy/OA Policy ID Linux} | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------------|-----------------------------|---------------------------|--------------------------------------|--|
| Linux OA Agent Install | Input Variable | attachableType | | SERVER | Variable is defined but not assigned |
| Linux OA Agent Install | Input Variable | separator | | , | Variable is defined but not assigned |
| Windows OA Agent Install | Input Variable | policyName | | \${SA Policy/OA Policy Name Windows} | Variable is defined but not assigned |
| Windows OA Agent Install | Input Variable | policyID | | \${SA Policy/OA Policy ID Windows} | Variable is defined but not assigned |
| Get Server VO | Input Variable | matching | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | serverID | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | delimiter | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Get Server VO | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Add Relationship | Input Variable | rootContext | | | Variable is defined but not assigned |
| Add Relationship | Input Variable | keystore | | | Variable is defined but not assigned |
| Add Relationship | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Add Relationship | Input Variable | certificateVerifier | | true | Variable is defined but not assigned |
| Add Relationship | Input Variable | certificateHostnameVerifier | | true | Variable is defined but not assigned |
| Add Relationship | Input Variable | cmdbHost | cmdbHost | | Input variable is using Prompt User |
| Add Relationship | Input Variable | cmdbPort | cmdbPort | | Input variable is using Prompt User |
| Add Relationship | Input Variable | told | told | | Input variable is using Prompt User |
| Add Relationship | Input Variable | relationType | relationType | | Input variable is using Prompt User |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Search Business Application | Input Variable | objectType | | business_application | Variable is defined but not assigned |
| Search Business Application | Input Variable | conditionAttributes | | name | Variable is defined but not assigned |

| | | | | | |
|-----------------------------|----------------------|-----------------------------|---------------------------|------------------------|---|
| Search Business Application | Input Variable | conditionOperators | | == | Variable is defined but not assigned |
| Modify Object Attribute(s) | Input Variable | rootContext | | | Variable is defined but not assigned |
| Modify Object Attribute(s) | Input Variable | keystore | | | Variable is defined but not assigned |
| Modify Object Attribute(s) | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Modify Object Attribute(s) | Input Variable | certificateVerifier | | false | Variable is defined but not assigned |
| Modify Object Attribute(s) | Input Variable | certificateHostnameVerifier | | false | Variable is defined but not assigned |
| Modify Object Attribute(s) | Input Variable | cmdbHost | cmdbHost | | Input variable is using Prompt User |
| Modify Object Attribute(s) | Input Variable | cmdbPort | cmdbPort | | Input variable is using Prompt User |
| Modify Object Attribute(s) | Input Variable | protocol | protocol | | Input variable is using Prompt User |
| Modify Object Attribute(s) | Input Variable | objectType | objectType | | Input variable is using Prompt User |
| Modify Object Attribute(s) | Input Variable | objectId | objectId | | Input variable is using Prompt User |
| Modify Object Attribute(s) | Input Variable | cmdbVersion | cmdbVersion | | Input variable is using Prompt User |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| update Domain | Input Variable | rootContext | | | Variable is defined but not assigned |
| update Domain | Input Variable | objectType | | Node | Variable is defined but not assigned |
| update Domain | Input Variable | prop | | domain_name=\${domain} | Variable is defined but not assigned |
| update Domain | Input Variable | keystore | | | Variable is defined but not assigned |
| update Domain | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| update Domain | Input Variable | certificateVerifier | | false | Variable is defined but not assigned |
| update Domain | Input Variable | certificateHostnameVerifier | | false | Variable is defined but not assigned |
| update Domain | Input Variable | cmdbHost | cmdbHost | | Input variable is using Prompt User |
| update Domain | Input Variable | cmdbPort | cmdbPort | | Input variable is using Prompt User |
| Sleep 7 min | Input Variable | seconds | | 420 | Variable is defined but not assigned |
| Get Server VO | Input Variable | corePassword | corePassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |

| | | | | | |
|-----------------------------------|----------------------|-----------------|---------------------------|--------------------------|---|
| Get Server VO | Input Variable | matching | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | serverID | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | delimiter | | | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | corePassword | corePassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Update Server Information Windows | Input Variable | serverName | | | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | forceUpdate | | True | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | refetch | | True | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | separator | | , | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | agentVersion | | | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | customerId | | | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | description | | | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | managementIP | | | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | manufacturer | | | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | model | | | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | newServerName | | \${VMname}.\${dnsDomain} | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | osVersion | | | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | rebootRequired | | false | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | serialNumber | | | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | stage | | LIVE | Variable is defined but not assigned |
| Update Server Information Windows | Input Variable | use | | PRODUCTION | Variable is defined but not assigned |
| Sleep Loop for 30 min | Input Variable | seconds | | 30 | Variable is defined but not assigned |
| Sleep Loop for 30 min | Input Variable | to | | 30 | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |

| | | | | | |
|---------------------------------|----------------------|-----------------|---------------------------|------------|---|
| Update Server Information Linux | Input Variable | corePassword | corePassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Update Server Information Linux | Input Variable | serverName | | | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | forceUpdate | | True | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | refetch | | True | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | separator | | , | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | agentVersion | | | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | customerId | | | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | description | | | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | managementIP | | | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | manufacturer | | | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | model | | | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | newServerName | | | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | osVersion | | | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | rebootRequired | | false | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | serialNumber | | | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | stage | | LIVE | Variable is defined but not assigned |
| Update Server Information Linux | Input Variable | use | | PRODUCTION | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get Server VO | Input Variable | corePassword | corePassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Get Server VO | Input Variable | matching | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | serverID | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | delimiter | | | Variable is defined but not assigned |

| | | | | | |
|--------------------------------------|----------------------|---------------------------|------------------------------|--|--|
| Create Project VSM | Input Variable | hidden | | false | Variable is defined but not assigned |
| Create User VSM | Input Variable | expiration | | 2999-01-01 | Variable is defined but not assigned |
| Set Project Properties [New Project] | Flow Output Variable | projectName | Input: field2 | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Linux - Add admin User | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Linux - Add admin User | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Linux - Add admin User | Input Variable | corePassword | corePassword | | Input variable is using Prompt User |
| Linux - Add admin User | Input Variable | serverNames | serverId | | Input variable is using Prompt User |
| Windows Add Admin | Input Variable | args | | -t \${hostName} -s MFI-AddProjectWinAdmins -a "\${groupId}" -z 5 | Variable is defined but not assigned |
| DB To Check Project | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| DB To Check Project | Input Variable | instance | | | Variable is defined but not assigned |
| DB To Check Project | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| DB To Check Project | Input Variable | dbClass | | | Variable is defined but not assigned |
| DB To Check Project | Input Variable | dbURL | | | Variable is defined but not assigned |
| DB To Check Project | Input Variable | timeout | | | Variable is defined but not assigned |
| DB To Check Project | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| DB To Check Project | Input Variable | resultSetType | | | Variable is defined but not assigned |
| DB To Check Project | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| DB To Check Project | Flow Output Variable | errorMsg | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| DB To Check Project | Flow Output Variable | groupId | Result Field: outputText | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| SQL Command [Get Seq No.] | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | instance | | | Variable is defined but not assigned |

| | | | | | |
|---------------------------|----------------------|---------------------------|------------------------------|------------------------|--|
| SQL Command [Get Seq No.] | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | dbClass | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | dbURL | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | timeout | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | resultSetType | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| SQL Command [Get Seq No.] | Flow Output Variable | failuremessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| INSERT Project Name in DB | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| INSERT Project Name in DB | Input Variable | instance | | | Variable is defined but not assigned |
| INSERT Project Name in DB | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| INSERT Project Name in DB | Input Variable | dbClass | | | Variable is defined but not assigned |
| INSERT Project Name in DB | Input Variable | dbURL | | | Variable is defined but not assigned |
| INSERT Project Name in DB | Input Variable | timeout | | | Variable is defined but not assigned |
| INSERT Project Name in DB | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| INSERT Project Name in DB | Input Variable | resultSetType | | | Variable is defined but not assigned |
| INSERT Project Name in DB | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| INSERT Project Name in DB | Input Variable | groupId | | \${role}_\${projectId} | Variable is defined but not assigned |
| INSERT Project Name in DB | Flow Output Variable | errorMsg | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Update GroupOwnedType | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| Update GroupOwnedType | Input Variable | instance | | | Variable is defined but not assigned |
| Update GroupOwnedType | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| Update GroupOwnedType | Input Variable | dbClass | | | Variable is defined but not assigned |
| Update GroupOwnedType | Input Variable | dbURL | | | Variable is defined but not assigned |
| Update GroupOwnedType | Input Variable | timeout | | | Variable is defined but not assigned |

| | | | | | |
|-----------------------|----------------------|-------------------------------|------------------------------|-------------------------------|--|
| Update GroupOwnedType | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| Update GroupOwnedType | Input Variable | resultSetType | | | Variable is defined but not assigned |
| Update GroupOwnedType | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| Update GroupOwnedType | Flow Output Variable | errorMsg | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Update GroupOwnedType | Flow Output Variable | groupId | Result Field: outputText | N/A | Flow Output variable created in flow steps |
| Set Group Ownership | Input Variable | DbType | | PostgreSQL | Variable is defined but not assigned |
| Set Group Ownership | Input Variable | instance | | | Variable is defined but not assigned |
| Set Group Ownership | Input Variable | authenticationType | | sql | Variable is defined but not assigned |
| Set Group Ownership | Input Variable | dbClass | | | Variable is defined but not assigned |
| Set Group Ownership | Input Variable | dbURL | | | Variable is defined but not assigned |
| Set Group Ownership | Input Variable | timeout | | | Variable is defined but not assigned |
| Set Group Ownership | Input Variable | databasePoolingProperties | | | Variable is defined but not assigned |
| Set Group Ownership | Input Variable | resultSetType | | | Variable is defined but not assigned |
| Set Group Ownership | Input Variable | resultSetConcurrency | | | Variable is defined but not assigned |
| Set Group Ownership | Flow Output Variable | errorMsg | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Set Group Ownership | Flow Output Variable | groupId | Result Field: outputText | N/A | Flow Output variable created in flow steps |
| Start Server Script | Input Variable | scriptToRunID | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetHostSearchOperator | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetUser | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetPassword | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | targetDomain | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | args | | \${ipaddress} \${hostName} | Variable is defined but not assigned |
| Start Server Script | Input Variable | scriptTimeout | | 300 | Variable is defined but not assigned |
| Start Server Script | Input Variable | notificationSuccessRecipients | | | Variable is defined but not assigned |
| Start Server Script | Input Variable | ticketId | | | Variable is defined but not assigned |

| | | | | | |
|--------------------------|----------------------|----------------------|------------------------------|--|--|
| Start Server Script | Input Variable | scriptTailOutputSize | | | Variable is defined but not assigned |
| Start Server Script | Flow Output Variable | failureMessage | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Start Server Script | Flow Output Variable | jobid | Result Field: id | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Input Variable | separator | | , | Variable is defined but not assigned |
| Get Script Job Result | Flow Output Variable | failureMessage | Result Field: summary | N/A | Flow Output variable created in flow steps |
| Get Script Job Result | Flow Output Variable | output | Result Field: output | N/A | Flow Output variable created in flow steps |
| Wait for Job | Input Variable | status | | | Variable is defined but not assigned |
| Wait for Job | Input Variable | timeout | | 600000 | Variable is defined but not assigned |
| Wait for Job | Input Variable | frequency | | | Variable is defined but not assigned |
| Exit code check | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Server VO | Input Variable | matching | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | serverID | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | delimiter | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Get Server VO | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Get Candidate Providers | Input Variable | resourceBindingId | RSC_BINDING_ID | | Input variable is using Prompt User |
| Get Candidate Providers | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Resource Provider Id | Input Variable | xpathQuery | | //candidateProvider/resourceProvider/property/displayName[text() = "Network"]/../values/value[text() = "\${networkType}"]/../../resourceProvider/id/text() | Variable is defined but not assigned |
| Get Resource Provider Id | Input Variable | delimiter | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------------|----------------------|---------------------------|---|--|
| Get Resource Provider Id | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| Update Valid Providers | Input Variable | resourceBindingXML | | <ResourceBinding> <id>\${RSC_BINDING_ID}</id> <validProvider> <resourceBinding><id>\${RSC_BINDING_ID}</id></resourceBinding> <resourceProvider><id>\${resourceProviderId}</id></resourceProvider> </validProvider> </ResourceBinding> | Variable is defined but not assigned |
| Update Valid Providers | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Valid Providers | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Valid Providers | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Update Valid Providers | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Valid Providers | Input Variable | resourceBindingId | RSC_BINDING_ID | | Input variable is using Prompt User |
| Update Valid Providers | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | resourceBindingId | resourceBindingId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | networkType | networkType | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | site | site | | Input variable is using Prompt User |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Update Valid Provider Pool | Input Variable | resourceBindingXml | | <ResourceBinding> <id>\${resourceBindingId}</id> \${resourcePoolXML} </ResourceBinding> | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------------|----------------------|---------------------------|--------|--|
| Update Valid Provider Pool | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | authType | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | resourceBindingId | resourceBindingId | | Input variable is using Prompt User |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get Candidate Providers | Input Variable | timeout | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | useCookies | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | trustAllRoots | | false | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxy | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | encodeURL | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------------|----------------------|-------------------------------|---|--|
| Get Candidate Providers | Input Variable | userAgent | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | followRedirects | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | authType | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | x509HostnameVerifier | | strict | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Candidate Providers | Input Variable | resourceBindingId | resourceBindingId | | Input variable is using Prompt User |
| Get Candidate Providers | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Candidate Providers | Flow Output Variable | resourceProviderId | Result Field: document | N/A | Flow Output variable created in flow steps |
| XPath Query for Subnet | Input Variable | xpathQuery | | /ResourceBinding//candidateProvider/candidatePool/displayName[text()='\${element}']/../id/text() | Variable is defined but not assigned |
| XPath Query for Subnet | Input Variable | delimiter | | | Variable is defined but not assigned |
| XPath Query for Subnet | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| XPath Query for Subnet | Flow Output Variable | failureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get VM Threshold DiskSpace | Flow Output Variable | threshtoldSpaceGB | Result Field: threshtoldSpace | N/A | Flow Output variable created in flow steps |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |

| | | | | | |
|----------------------------|----------------|----------------------|-------------------|--|--------------------------------------|
| Update Valid Provider Pool | Input Variable | resourceBindingXml | | <ResourceBinding> <id>\${resourceBindingId}</id> <validProvider> <resourceBinding> <id>\${resourceBindingId}</id> </resourceBinding> <resourceProvider> <id>\${resourceProviderId}</id> </resourceProvider> <validPool> <id>\${selectedClusterpool}</id> </validPool> </validProvider> < ... | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | authType | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Valid Provider Pool | Input Variable | resourceBindingId | resourceBindingId | | Input variable is using Prompt User |
| Get Cluster Name | Input Variable | xpathQuery | | //ResourceBinding/candidateProvider/candidatePool/id[text()= \${selectedClusterpool}]/../displayName/text() | Variable is defined but not assigned |

| | | | | | |
|---------------------------------|----------------------|------------------|----------------------------|---|--|
| Get Cluster Name | Input Variable | delimiter | | | Variable is defined but not assigned |
| Get Cluster Name | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Variable is defined but not assigned |
| Get Cluster Name | Input Variable | xml | document1 | | Input variable is using Prompt User |
| Get Cluster Name | Flow Output Variable | clusetName | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Update Component Property - CPU | Input Variable | onlyUpdate | | yes | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | displayName | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | propertyName | | number_of_cpu | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | valueType | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | separator | | , | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | consumerVisible | | true | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | authType | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | keystorePassword | | | Variable is defined but not assigned |

| | | | | | |
|------------------------------------|----------------|----------------------|-------------------|-------------|--------------------------------------|
| Update Component Property - CPU | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Component Property - CPU | Input Variable | componentId | serverComponentId | | Input variable is using Prompt User |
| Update Component Property - Memory | Input Variable | onlyUpdate | | yes | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | displayName | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | propertyName | | memory_size | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | valueType | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | separator | | , | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | consumerVisible | | true | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | authType | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | trustKeystore | | | Variable is defined but not assigned |

| | | | | | |
|---------------------------------------|----------------|----------------------|-------------------|-----------|--------------------------------------|
| Update Component Property - Memory | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Component Property - Memory | Input Variable | componentId | serverComponentId | | Input variable is using Prompt User |
| Update Component Property - Disk Size | Input Variable | onlyUpdate | | yes | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | displayName | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | propertyName | | disk_size | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | valueType | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | separator | | , | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | consumerVisible | | true | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | authType | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Update Component Property - Disk Size | Input Variable | componentId | serverComponentId | | Input variable is using Prompt User |

| | | | | | |
|--------------------------------|----------------------|--------------------|----------------------------|---|---|
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Select Candidate Provider | Flow Output Variable | resourceProviderId | Result: resourceProviderId | N/A | Flow Output variable created in flow steps |
| Get guest OS From DB | Flow Output Variable | role | Result Field: role | N/A | Flow Output variable created in flow steps |
| Get guest OS From DB | Flow Output Variable | guestOS | Result: guestOS | N/A | Flow Output variable created in flow steps |
| IPAM Generate Hostname | Flow Output Variable | hostname | Result: hostname | N/A | Flow Output variable created in flow steps |
| IPAM Get Properties | Flow Output Variable | satelite | Result Field: satellite | N/A | Flow Output variable created in flow steps |
| IPAM Get Properties | Flow Output Variable | zone | Result: zone | N/A | Flow Output variable created in flow steps |
| IPAM Get Properties | Flow Output Variable | vlan | Result: vlan | N/A | Flow Output variable created in flow steps |
| IPAM Reserve Next available IP | Input Variable | url | | \${ipamProtocol}://\${ipamHostname}:\${ipamPort} | Variable is defined but not assigned |
| IPAM Reserve Next available IP | Flow Output Variable | ipAddress | Result Field: nextIp | N/A | Flow Output variable created in flow steps |
| Update Primary NIC Properties | Input Variable | childComponentName | | Primary NIC | Variable is defined but not assigned |
| Update Primary NIC Properties | Input Variable | jsonObject | | { "IP_ADDRESS": "\${ipAddress}", "GATEWAY": "\${gatewayIp}", "SUBNETMASK": "\${subnetMask}" } | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| IPAM Add Attributes | Input Variable | password | ipamPassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Date Parser | Input Variable | dateFormat | | unix | Variable is defined but not assigned |
| Date Parser | Input Variable | dateLocaleLang | | | Variable is defined but not assigned |
| Date Parser | Input Variable | dateLocaleCountry | | | Variable is defined but not assigned |
| Date Parser | Input Variable | outFormat | | yyyyMMdd | Variable is defined but not assigned |
| Date Parser | Input Variable | outLocaleLang | | | Variable is defined but not assigned |
| Date Parser | Input Variable | outLocaleCountry | | | Variable is defined but not assigned |

| | | | | | |
|-------------------------|----------------------|-----------------|---------------------------|---------------------------------|---|
| Release Lock | Input Variable | Lock_Id | | \${lockId} | Variable is defined but not assigned |
| Release Lock | Input Variable | Lock_Id | | \${lockId} | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Release Lock | Input Variable | Lock_Id | | \${lockId} | Variable is defined but not assigned |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Variable is defined but not assigned |
| Flow Inputs | Input Variable | adPassword | adPassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| LDAP Get Computer | Input Variable | filter | | (cn=\${hostname}) | Variable is defined but not assigned |
| LDAP Get Computer | Input Variable | propertyNames | | distinguishedName | Variable is defined but not assigned |
| LDAP Get Computer | Input Variable | searchScope | | onelevel | Variable is defined but not assigned |
| LDAP Add Property Value | Input Variable | propertyName | | servicePrincipalName | Variable is defined but not assigned |
| LDAP Add Property Value | Input Variable | propertyValue | | HOST/\${hostname}.\${adBaseDN} | Variable is defined but not assigned |
| LDAP Add Property Value | Input Variable | propertyName | | servicePrincipalName | Variable is defined but not assigned |
| LDAP Add Property Value | Input Variable | propertyValue | | HOST/\${hostname} | Variable is defined but not assigned |
| LDAP Add Property Value | Input Variable | propertyName | | servicePrincipalName | Variable is defined but not assigned |
| LDAP Add Property Value | Input Variable | propertyValue | | HOST/\${hostname}.\${domainAlt} | Variable is defined but not assigned |
| Create Computer Account | Input Variable | sAMAccountName | | \${hostname}\$ | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Sleep | Input Variable | seconds | | 15 | Variable is defined but not assigned |
| Sleep | Input Variable | seconds | | 15 | Variable is defined but not assigned |
| Loop | Input Variable | count | | 5 | Variable is defined but not assigned |
| Loop | Input Variable | reset | | false | Variable is defined but not assigned |
| Loop | Input Variable | to | | \${count} | Variable is defined but not assigned |
| Loop | Input Variable | from | | 1 | Variable is defined but not assigned |
| Loop | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |

| | | | | | |
|-----------------------|----------------|------------------------|--------------|---|--------------------------------------|
| Get Server VO | Input Variable | matching | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | serverID | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | delimiter | | | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | port | | 2222 | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | command | | /opsw/api/com/opsware/server/ServerService/method/decommissionself:i=\${serverId} | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | knownHostsPolicy | | allow | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | pty | | false | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | timeout | | 90000 | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | connectTimeout | | 10000 | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | useGlobalContext | | false | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | failOnPositiveExitCode | | | Variable is defined but not assigned |
| Deactivate Agent | Input Variable | host | CoreHost | | Input variable is using Prompt User |
| Deactivate Agent | Input Variable | username | coreUsername | | Input variable is using Prompt User |
| Delete Server from SA | Input Variable | port | | 2222 | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | command | | /opsw/api/com/opsware/server/ServerService/method/remove self:i=\${serverId} | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | proxyPort | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------|----------------------|------------------------|---------------------------|-----------------------------------|--|
| Delete Server from SA | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | privateKeyFile | | | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | knownHostsPolicy | | allow | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | characterSet | | UTF-8 | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | pty | | false | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | timeout | | 90000 | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | connectTimeout | | 10000 | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | keepAlive | | 0 | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | closeSession | | true | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | useGlobalContext | | false | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | failOnPositiveExitCode | | | Variable is defined but not assigned |
| Delete Server from SA | Input Variable | host | CoreHost | | Input variable is using Prompt User |
| Delete Server from SA | Input Variable | username | coreUsername | | Input variable is using Prompt User |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get Server VO | Input Variable | matching | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | serverID | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | delimiter | | | Variable is defined but not assigned |
| Get Server VO | Input Variable | coreHost | coreHost | | Input variable is using Prompt User |
| Get Server VO | Input Variable | coreUsername | coreUsername | | Input variable is using Prompt User |
| OA Agent Uninstall Linux | Input Variable | script | | \${SA/OA Agent Uninstall Linux} | Variable is defined but not assigned |
| OA Agent Uninstall Windows | Input Variable | script | | \${SA/OA Agent Unisntall Windows} | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-------------------------------|----------------------|----------------------|------------------------------|-------|---|
| Flow Inputs | Input Variable | smaxHostname | smaxHostname | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | smaxTenantId | smaxTenantId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | smaxUsername | smaxUsername | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | smaxPassword | smaxPassword | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | entityId | entityId | | Input variable is using Prompt User |
| Retire Device | Input Variable | smaxPassword | smaxPassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | trustAllRoots | trustAllRoots | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | x509HostnameVerifier | x509HostnameVerifier | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | trustKeystore | trustKeystore | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | trustPassword | trustPassword | | Input variable is using Prompt User |
| vCenter Unprovision Server | Input Variable | vmID | vmid | | Input variable is using Prompt User |
| vCenter Unprovision Server | Input Variable | host | host | | Input variable is using Prompt User |
| vCenter Unprovision Server | Input Variable | port | port | | Input variable is using Prompt User |
| vCenter Unprovision Server | Input Variable | user | user | | Input variable is using Prompt User |
| vCenter Unprovision Server | Input Variable | password | password | | Input variable is using Prompt User |
| vCenter Unprovision Server | Input Variable | protocol | protocol | | Input variable is using Prompt User |
| vCenter Unprovision Server | Input Variable | vmDatacenter | dataCenter | | Input variable is using Prompt User |
| vCenter Unprovision Server | Flow Output Variable | FailureMessage | Result Field: FailureMessage | N/A | Flow Output variable created in flow steps |
| Get Virtual Machine | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Get Virtual Machine | Input Variable | closeSession | | false | Variable is defined but not assigned |

| | | | | | |
|---|----------------------|--------------------|---------------------------|--------------|---|
| Get Virtual Machine | Input Variable | hostSystem | | | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | getDetailed | | true | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | connectionTimeout | | 30 | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | socketTimeout | | 30 | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Remove Host Record | Input Variable | connectTimeout | | | Variable is defined but not assigned |
| Remove Host Record | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Remove Host Record | Input Variable | useCookies | | | Variable is defined but not assigned |
| Remove Host Record | Input Variable | keepAlive | | | Variable is defined but not assigned |
| Remove Host Record | Input Variable | url | ipamUrl | | Input variable is using Prompt User |
| Remove Host Record | Input Variable | username | ipamUsername | | Input variable is using Prompt User |
| Remove Host Record | Input Variable | password | ipamPassword | | Input variable is using Prompt User |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get Child Component Properties (Bcakup Nic) | Input Variable | childComponentName | | Backup NIC | Variable is defined but not assigned |
| IPAM Remove Host Record | Input Variable | ipamPassword | ipamPasword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Variable is defined but not assigned |
| Flow Inputs | Input Variable | adPassword | adPassword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Get Supplemental Account | Input Variable | primaryEmail | requestorEmail | | Input variable is using Prompt User |
| Create User VSM | Input Variable | expiration | | 2999-01-01 | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |

| | | | | | |
|-------------------------------|----------------|---------------------------|----------------|---------------------------|--------------------------------------|
| Get Subscription Details | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | headers | | Accept:application/json | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | queryParams | | | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | formParams | | | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | contentType | | application/json | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | method | | GET | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Subscription Details | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| JSON Path | Input Variable | jsonPathQuery | | \$.ext.csa_owner_group[0] | Variable is defined but not assigned |
| Flow Inputs | Input Variable | vmDatacenter | vmDatacenter | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | providerId | providerId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vmName | vmName | | Input variable is using Prompt User |
| Get Current Date and Time | Input Variable | Field_2 | | \${in2} | Variable is defined but not assigned |
| Get Current Date and Time | Input Variable | Field_3 | | \${in3} | Variable is defined but not assigned |
| Get Current Date and Time | Input Variable | Field_4 | | \${in4} | Variable is defined but not assigned |
| Get Current Date and Time | Input Variable | Field_1 | | \${in1} | Variable is defined but not assigned |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Delete Snapshot | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Delete Snapshot | Input Variable | async | | false | Variable is defined but not assigned |

| | | | | | |
|--------------------------|----------------------|--------------------|----------------------------|--|--|
| Delete Snapshot | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Delete Snapshot | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Delete Snapshot | Input Variable | removeAllSnapshots | | true | Variable is defined but not assigned |
| Delete Snapshot | Input Variable | password | password | | Input variable is using Prompt User |
| Create Snapshot | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Create Snapshot | Input Variable | async | | false | Variable is defined but not assigned |
| Create Snapshot | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Create Snapshot | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Create Snapshot | Input Variable | snapshotName | | HCM Snapshot | Variable is defined but not assigned |
| Create Snapshot | Input Variable | description | | Snapshot taken by HCM on \${currentDateTime} | Variable is defined but not assigned |
| Create Snapshot | Input Variable | snapshotMem | | true | Variable is defined but not assigned |
| Create Snapshot | Input Variable | quiesce | | true | Variable is defined but not assigned |
| Get Snapshot | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Get Snapshot | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Get Snapshot | Input Variable | snapshotName | | | Variable is defined but not assigned |
| Get Snapshot | Input Variable | host | host | | Input variable is using Prompt User |
| Get Snapshot | Input Variable | password | password | | Input variable is using Prompt User |
| Get Snapshot | Flow Output Variable | SnapshotName | Result Field: snapshotInfo | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Set Message for Snapshot | Flow Output Variable | setSnapshot | Input: field1 | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | vmDatacenter | vmDatacenter | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | providerId | providerId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vmName | vmName | | Input variable is using Prompt User |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |

| | | | | | |
|--------------------------------|----------------------|--------------------|----------------------------|--|---|
| Get Resource Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Delete Snapshot | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Delete Snapshot | Input Variable | async | | false | Variable is defined but not assigned |
| Delete Snapshot | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Delete Snapshot | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Delete Snapshot | Input Variable | removeAllSnapshots | | true | Variable is defined but not assigned |
| Delete Snapshot | Input Variable | password | password | | Input variable is using Prompt User |
| Delete Snapshot | Flow Output Variable | result | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Delete Snapshot | Flow Output Variable | result | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Set Message for Snapshot | Flow Output Variable | setSnapshot | Input: field1 | N/A | Flow Output variable created in flow steps |
| IPAM Reserve Next available IP | Input Variable | url | | https://\${lpamHost}:\${lpamPort} | Variable is defined but not assigned |
| IPAM Reserve Next available IP | Input Variable | password | ipamPasword | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| IPAM Reserve Next available IP | Input Variable | connectTimeout | | | Variable is defined but not assigned |
| IPAM Reserve Next available IP | Input Variable | socketTimeout | | | Variable is defined but not assigned |
| Update Backup NIC Properties | Input Variable | childComponentName | | Backup NIC | Variable is defined but not assigned |
| Update Backup NIC Properties | Input Variable | jsonObject | | { "IP_ADDRESS": "\${nextIp}", "GATEWAY": "\${gatewayIp}", "SUBNETMASK": "\${subnetMask}", "VLAN_ID": "\${vLan}", "name": "\${hostRecord}", "domain_name": "\${zone}" } | Variable is defined but not assigned |
| Get Details of NIC 2 | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Get Details of NIC 2 | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Get Details of NIC 2 | Input Variable | deviceNumber | | 2 | Variable is defined but not assigned |
| Configure NIC | Input Variable | closeSession | | false | Variable is defined but not assigned |

| | | | | | |
|---------------------|----------------------|------------------|---------------------------|--|--|
| Configure NIC | Input Variable | async | | false | Variable is defined but not assigned |
| Configure NIC | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Configure NIC | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Configure NIC | Input Variable | deviceNumber | | 2 | Variable is defined but not assigned |
| Configure NIC | Input Variable | netMacGeneration | | Manual | Variable is defined but not assigned |
| Configure NIC | Input Variable | connect | | true | Variable is defined but not assigned |
| Configure NIC | Input Variable | connectAtPowerOn | | true | Variable is defined but not assigned |
| Configure NIC | Input Variable | user | vcenterUsername | | Input variable is using Prompt User |
| Configure NIC | Input Variable | password | vcenterPassword | | Input variable is using Prompt User |
| Configure NIC | Input Variable | virtualMachine | VMName | | Input variable is using Prompt User |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Sleep | Input Variable | seconds | | 90 | Variable is defined but not assigned |
| Update DNS Resolver | Input Variable | sourceCode | | NAMESERVERS=\${PROXY/NAMESERVERS} SEARCH_HOSTS=\${PROXY/SEARCH-HOSTS} configure_dns_name_server(){ IFS="," names=\$(sudo grep nameserver /etc/resolv.conf) for nameserver in \$NAMESERVERS; do nameserver_exists=\$(sudo grep nameserver /etc/resolv.conf grep \$nameserver) if ["\$nameserver_exis ... | Variable is defined but not assigned |
| Update DNS Resolver | Input Variable | sourceCodeType | | SH | Variable is defined but not assigned |
| Update DNS Resolver | Input Variable | scriptArguments | | | Variable is defined but not assigned |
| Update DNS Resolver | Input Variable | timeout | | 0 | Variable is defined but not assigned |
| Update DNS Resolver | Input Variable | target_host | VMName | | Input variable is using Prompt User |
| Get User Identifier | Flow Output Variable | cpuValue | Input: cpuValue | N/A | Flow Output variable created in flow steps |
| Set CPU Count | Input Variable | async | | false | Variable is defined but not assigned |

| | | | | | |
|-----------------|----------------------|------------------|--------------------------|-----------|--|
| Set CPU Count | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Set CPU Count | Input Variable | host | host | | Input variable is using Prompt User |
| Set CPU Count | Input Variable | user | user | | Input variable is using Prompt User |
| Set CPU Count | Input Variable | password | password | | Input variable is using Prompt User |
| Set CPU Count | Input Variable | vmIdentifierType | vmIdentifierType | | Input variable is using Prompt User |
| Set CPU Count | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Set CPU Count | Flow Output Variable | cpuValue | Input: vmCpuCount | N/A | Flow Output variable created in flow steps |
| Get Power State | Input Variable | password | password | | Input variable is using Prompt User |
| Get Power State | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Shutdown Guest | Input Variable | host | host | | Input variable is using Prompt User |
| Shutdown Guest | Input Variable | password | password | | Input variable is using Prompt User |
| Shutdown Guest | Input Variable | vmIdentifierType | vmIdentifierType | | Input variable is using Prompt User |
| Shutdown Guest | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Get Power State | Input Variable | host | host | | Input variable is using Prompt User |
| Get Power State | Input Variable | password | password | | Input variable is using Prompt User |
| Get Power State | Input Variable | vmIdentifierType | vmIdentifierType | | Input variable is using Prompt User |
| Get Power State | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Get Power State | Flow Output Variable | powerState | Result Field: powerState | N/A | Flow Output variable created in flow steps |
| Sleep | Input Variable | seconds | | 30 | Variable is defined but not assigned |
| Set Power State | Input Variable | async | | false | Variable is defined but not assigned |
| Set Power State | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Set Power State | Input Variable | vmPowerState | | poweredOn | Variable is defined but not assigned |
| Set Power State | Input Variable | host | host | | Input variable is using Prompt User |
| Set Power State | Input Variable | password | password | | Input variable is using Prompt User |
| Set Power State | Input Variable | vmIdentifierType | vmIdentifierType | | Input variable is using Prompt User |

| | | | | | |
|----------------------------------|----------------------|----------------------|---------------------------|-----------|--|
| Set Power State | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Sleep | Input Variable | seconds | | 60 | Variable is defined but not assigned |
| Get Resource Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Update Resource Pool Utilization | Input Variable | resourceType | | CPU | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | authType | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Extend Disk | Input Variable | async | | false | Variable is defined but not assigned |
| Extend Disk | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Extend Disk | Input Variable | uuid | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------------|----------------------|----------------------|---------------------------|-----------|--|
| Extend Disk | Input Variable | host | vcenterHost | | Input variable is using Prompt User |
| Extend Disk | Input Variable | user | vcenterUsername | | Input variable is using Prompt User |
| Extend Disk | Input Variable | password | vcenterPassword | | Input variable is using Prompt User |
| Extend Disk | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Extend Disk | Input Variable | diskSize | currentSize | | Input variable is using Prompt User |
| Extend Disk | Flow Output Variable | diskSize | Input: actualSize | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Is currentSize > actualSize? | Flow Output Variable | diskSize | Input: value2 | N/A | Flow Output variable created in flow steps |
| Subtraction | Flow Output Variable | diskSize | Input: value2 | N/A | Flow Output variable created in flow steps |
| Update Resource Pool Utilization | Input Variable | resourceType | | STORAGE | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | authType | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustKeystore | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------------|----------------------|------------------|---------------------------|---------|--|
| Update Resource Pool Utilization | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Extend Disk | Input Variable | async | | false | Variable is defined but not assigned |
| Extend Disk | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Extend Disk | Input Variable | uuid | | | Variable is defined but not assigned |
| Extend Disk | Input Variable | host | vcenterHost | | Input variable is using Prompt User |
| Extend Disk | Input Variable | user | vcenterUsername | | Input variable is using Prompt User |
| Extend Disk | Input Variable | password | vcenterPassword | | Input variable is using Prompt User |
| Extend Disk | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Extend Disk | Input Variable | diskSize | currentSize | | Input variable is using Prompt User |
| Extend Disk | Flow Output Variable | diskSize | Input: actualSize | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Is currentSize > actualSize? | Flow Output Variable | diskSize | Input: value2 | N/A | Flow Output variable created in flow steps |
| Subtraction | Flow Output Variable | diskSize | Input: value2 | N/A | Flow Output variable created in flow steps |
| Update Resource Pool Utilization | Input Variable | resourceType | | STORAGE | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | authType | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------------|----------------------|----------------------|-------------------|-----------|--|
| Update Resource Pool Utilization | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get User Identifier | Flow Output Variable | MemoryGB | Input: oldMemsize | N/A | Flow Output variable created in flow steps |
| Get Power State | Input Variable | host | host | | Input variable is using Prompt User |
| Get Power State | Input Variable | password | password | | Input variable is using Prompt User |
| Get Power State | Input Variable | vmIdentifierType | vmIdentifierType | | Input variable is using Prompt User |
| Get Power State | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Shutdown Guest | Input Variable | host | host | | Input variable is using Prompt User |
| Shutdown Guest | Input Variable | password | password | | Input variable is using Prompt User |
| Shutdown Guest | Input Variable | vmIdentifierType | vmIdentifierType | | Input variable is using Prompt User |
| Shutdown Guest | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Set Memory Size | Input Variable | async | | false | Variable is defined but not assigned |
| Set Memory Size | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Set Memory Size | Input Variable | host | host | | Input variable is using Prompt User |
| Set Memory Size | Input Variable | user | user | | Input variable is using Prompt User |
| Set Memory Size | Input Variable | password | password | | Input variable is using Prompt User |
| Set Memory Size | Input Variable | vmIdentifierType | vmIdentifierType | | Input variable is using Prompt User |
| Set Memory Size | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Set Memory Size | Input Variable | vmMemorySize | memoryMB | | Input variable is using Prompt User |
| Set Power State | Input Variable | async | | false | Variable is defined but not assigned |
| Set Power State | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Set Power State | Input Variable | vmPowerState | | poweredOn | Variable is defined but not assigned |

| | | | | | |
|----------------------------------|----------------------|------------------|---------------------------|--------|--|
| Set Power State | Input Variable | host | host | | Input variable is using Prompt User |
| Set Power State | Input Variable | password | password | | Input variable is using Prompt User |
| Set Power State | Input Variable | vmIdentifierType | vmIdentifierType | | Input variable is using Prompt User |
| Set Power State | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Get Power State | Input Variable | host | host | | Input variable is using Prompt User |
| Get Power State | Input Variable | password | password | | Input variable is using Prompt User |
| Get Power State | Input Variable | vmIdentifierType | vmIdentifierType | | Input variable is using Prompt User |
| Get Power State | Input Variable | virtualMachine | virtualMachine | | Input variable is using Prompt User |
| Get Power State | Flow Output Variable | powerState | Result Field: powerState | N/A | Flow Output variable created in flow steps |
| Sleep | Input Variable | seconds | | 30 | Variable is defined but not assigned |
| Convert to MB | Flow Output Variable | memSize | Input: field2 | N/A | Flow Output variable created in flow steps |
| Convert to MB | Flow Output Variable | MemoryMB | Input: field1 | N/A | Flow Output variable created in flow steps |
| Get Resource Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Sleep | Input Variable | seconds | | 60 | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Set Memory GB | Flow Output Variable | MemoryGB | Input: field2 | N/A | Flow Output variable created in flow steps |
| Set Memory GB | Flow Output Variable | MemoryMB | Input: field1 | N/A | Flow Output variable created in flow steps |
| Update Resource Pool Utilization | Input Variable | resourceType | | MEMORY | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | timeout | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | useCookies | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxy | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyPort | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | proxyUsername | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------------|----------------|----------------------|-------------|---|--------------------------------------|
| Update Resource Pool Utilization | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | encodeURL | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | userAgent | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | authType | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | kerberosConfFile | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | keystore | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Update Resource Pool Utilization | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Reverse Lifecycle | Input Variable | url | | \${HCM/HCM-CSA-URL}rest/lifecycleengine/execute?userIdentier=\${userIdentier} | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | contentType | | application/xml | Variable is defined but not assigned |

| | | | | | |
|-------------------|----------------|--------------------------|--|---|--------------------------------------|
| Reverse Lifecycle | Input Variable | body | | <?xml version="1.0" encoding="UTF-8" standalone="yes"?> <LifecycleExecutionRequest> <reverse>true</reverse> <serviceComponentId>\${SVC_COMPONENT_ID}</serviceComponentId> <serviceInstanceId>\${SVC_INSTANCE_ID}</serviceInstanceId> <targetStateName>RESERVED</targetStateName> </LifecycleExecutionRequest> | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | method | | POST | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | keystore | | | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | headers | | | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | queryParams | | | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | formParams | | | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |

| | | | | | |
|-----------------------|----------------|------------------------|--|--|--------------------------------------|
| Reverse Lifecycle | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Reverse Lifecycle | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | url | | \$(HCM/HCM-CSA-URL)rest/lifecycleengine | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | queryParams | | userIdentifier=\${userIdentifier}&serviceInstanceId;=\${SVC_INSTANCE_ID} | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | headers | | Accept:application/xml | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |

| | | | | | |
|-----------------------|----------------|---------------------------|--|---|--------------------------------------|
| Get Life Cycle Status | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | queryParamsAreFormEncoded | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | method | | GET | Variable is defined but not assigned |
| Count | Input Variable | from | | 1 | Variable is defined but not assigned |
| Count | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Count | Input Variable | reset | | false | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | url | | <code> \${HCM/HCM-CSA-URL}rest/lifecycleengine/execute?userIdentifier=\${userIdentifier} </code> | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | contentType | | application/xml | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | body | | <code> <?xml version="1.0" encoding="UTF-8" standalone="yes"?> <LifecycleExecutionRequest> <reverse>false</reverse> <serviceComponentId>\${SVC_COMPONENT_ID}</serviceComponentId> <serviceInstanceId>\${SVC_INSTANCE_ID}</serviceInstanceId> <targetStateName>DEPLOYED</targetStateName> </LifecycleExecutionRequest> </code> | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | method | | POST | Variable is defined but not assigned |

| | | | | | |
|------------------|----------------|--------------------------|--|------------|--------------------------------------|
| Deploy Lifecycle | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | keystore | | | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | headers | | | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | queryParams | | | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | queryParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | formParams | | | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | formParamsAreURLEncoded | | false | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | sourceFile | | | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | requestCharacterSet | | ISO-8859-1 | Variable is defined but not assigned |
| Deploy Lifecycle | Input Variable | chunkedRequestEntity | | | Variable is defined but not assigned |
| Count | Input Variable | from | | 1 | Variable is defined but not assigned |
| Count | Input Variable | to | | 150 | Variable is defined but not assigned |
| Count | Input Variable | incrementBy | | 1 | Variable is defined but not assigned |
| Count | Input Variable | reset | | false | Variable is defined but not assigned |

| | | | | | |
|-----------------------|----------------|------------------------|--|--|--------------------------------------|
| Get Life Cycle Status | Input Variable | url | | \${HCM/HCM-CSA-URL} rest/lifecycleengine | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | authType | | Basic | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | queryParams | | userIdentifier=\${userIdentifier}&serviceInstanceId;=\${SVC_INSTANCE_ID} | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | headers | | Accept:application/xml | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | preemptiveAuth | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | trustAllRoots | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | proxyHost | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | proxyPort | | 8080 | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | proxyUsername | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | proxyPassword | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | x509HostnameVerifier | | allow_all | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | trustKeystore | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | trustPassword | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | keystore | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | keystorePassword | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | connectTimeout | | 0 | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | socketTimeout | | 0 | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | useCookies | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | keepAlive | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | connectionsMaxPerRoute | | 2 | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | connectionsMaxTotal | | 20 | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | followRedirects | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | destinationFile | | | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | responseCharacterSet | | | Variable is defined but not assigned |

| | | | | | |
|----------------------------------|----------------------|-------------------------------|---------------------------|-------|---|
| Get Life Cycle Status | Input Variable | queryParamsAreURLEn coded | | false | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | queryParamsAreFormE ncoded | | true | Variable is defined but not assigned |
| Get Life Cycle Status | Input Variable | method | | GET | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | vmDatacenter | vmDatacenter | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | providerId | providerId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vmName | vmName | | Input variable is using Prompt User |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Set Flow Variable | Flow Output Variable | powerState | Input: myValue | N/A | Flow Output variable created in flow steps |
| Reboot Server | Input Variable | vmID | vmid | | Input variable is using Prompt User |
| Reboot Server | Input Variable | host | host | | Input variable is using Prompt User |
| Reboot Server | Input Variable | user | user | | Input variable is using Prompt User |
| Reboot Server | Input Variable | password | password | | Input variable is using Prompt User |
| Reboot Server | Input Variable | vmDatacenter | vmDatacenter | | Input variable is using Prompt User |
| Reboot Server | Input Variable | port | port | | Input variable is using Prompt User |
| Reboot Server | Input Variable | protocol | protocol | | Input variable is using Prompt User |
| Reboot Server | Flow Output Variable | status | Result Field: status | N/A | Flow Output variable created in flow steps |
| Get Resource Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | trustAllRoots | trustAllRoots | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | x509HostnameVerifier | x509HostnameVerifier | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | trustKeystore | trustKeystore | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | trustPassword | trustPassword | | Input variable is using Prompt User |
| Get Power State | Input Variable | host | host | | Input variable is using Prompt User |
| Get Power State | Input Variable | password | password | | Input variable is using Prompt User |
| Get Power State | Input Variable | virtualMachine | vmid | | Input variable is using Prompt User |

| | | | | | |
|-------------------------------|----------------------|-------------------|----------------------------|-------|---|
| Get Virtual Machine | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Get Virtual Machine | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | hostSystem | | | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | getDetailed | | true | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | connectionTimeout | | 30 | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | socketTimeout | | 30 | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | vmDatacenter | vmDatacenter | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | providerId | providerId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vmName | vmName | | Input variable is using Prompt User |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Revert To Snapshot | Input Variable | async | | false | Variable is defined but not assigned |
| Revert To Snapshot | Input Variable | taskTimeOut | | 800 | Variable is defined but not assigned |
| Revert To Snapshot | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Revert To Snapshot | Input Variable | snapshotName | | | Variable is defined but not assigned |
| Revert To Snapshot | Flow Output Variable | details | Result Field: returnResult | N/A | Flow Output variable created in flow steps |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Set Message for Snapshot | Flow Output Variable | setSnapshot | Input: field1 | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | vmDatacenter | vmDatacenter | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | providerId | providerId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vmName | vmName | | Input variable is using Prompt User |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |

| | | | | | |
|-------------------------------|----------------------|-------------------|---------------------------|-------|---|
| Get Resource Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | vmID | vmid | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | host | host | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | port | port | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | protocol | protocol | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | user | user | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | password | password | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | vmDatacenter | vmDatacenter | | Input variable is using Prompt User |
| vCenter Set Power State VM | Flow Output Variable | status | Result Field: status | N/A | Flow Output variable created in flow steps |
| Set Flow Variable | Flow Output Variable | powerState | Input: myValue | N/A | Flow Output variable created in flow steps |
| Get Virtual Machine | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Get Virtual Machine | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | hostSystem | | | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | getDetailed | | true | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | connectionTimeout | | 30 | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | socketTimeout | | 30 | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | vmDatacenter | vmDatacenter | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | providerId | providerId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vmName | vmName | | Input variable is using Prompt User |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| Set Flow Variable | Flow Output Variable | powerState | Input: myValue | N/A | Flow Output variable created in flow steps |
| Get Resource Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |

| | | | | | |
|-------------------------------|----------------------|----------------------|---------------------------------|-------|---|
| Get Resource Provider Details | Input Variable | trustAllRoots | trustAllRoots | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | x509HostnameVerifier | x509HostnameVerifier | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | trustKeystore | trustKeystore | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | trustPassword | trustPassword | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | vmID | vmid | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | host | host | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | user | user | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | password | password | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | vmDatacenter | vmDatacenter | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | port | port | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | protocol | protocol | | Input variable is using Prompt User |
| vCenter Set Power State VM | Flow Output Variable | PowerState | Result Field: currentPowerState | N/A | Flow Output variable created in flow steps |
| vCenter Set Power State VM | Flow Output Variable | status | Result Field: status | N/A | Flow Output variable created in flow steps |
| Get Virtual Machine | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Get Virtual Machine | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | hostSystem | | | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | getDetailed | | true | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | connectionTimeout | | 30 | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | socketTimeout | | 30 | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |
| Flow Inputs | Input Variable | providerId | providerId | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vmDatacenter | vmDatacenter | | Input variable is using Prompt User |
| Flow Inputs | Input Variable | vmName | vmName | | Input variable is using Prompt User |

| | | | | | |
|-------------------------------|----------------------|----------------------|---------------------------------|-------|---|
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | vmID | vmid | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | host | host | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | protocol | protocol | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | port | port | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | user | user | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | password | password | | Input variable is using Prompt User |
| vCenter Set Power State VM | Input Variable | vmDatacenter | vmDatacenter | | Input variable is using Prompt User |
| vCenter Set Power State VM | Flow Output Variable | PowerState | Result Field: currentPowerState | N/A | Flow Output variable created in flow steps |
| vCenter Set Power State VM | Flow Output Variable | status | Result Field: status | N/A | Flow Output variable created in flow steps |
| Get Resource Provider Details | Input Variable | userIdentifier | userIdentifier | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | trustAllRoots | trustAllRoots | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | x509HostnameVerifier | x509HostnameVerifier | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | trustKeystore | trustKeystore | | Input variable is using Prompt User |
| Get Resource Provider Details | Input Variable | trustPassword | trustPassword | | Input variable is using Prompt User |
| Set Flow Variable | Flow Output Variable | powerState | Input: myValue | N/A | Flow Output variable created in flow steps |
| Get Virtual Machine | Input Variable | password | password | | Input variable name contains sensitive keywords, but not OBFUSCATED |
| Get Virtual Machine | Input Variable | closeSession | | false | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | hostSystem | | | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | vmIdentifierType | | name | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | getDetailed | | true | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | connectionTimeout | | 30 | Variable is defined but not assigned |
| Get Virtual Machine | Input Variable | socketTimeout | | 30 | Variable is defined but not assigned |
| Error Handling | Flow Output Variable | failureMessage1 | Result Field: failureJson | N/A | Flow Output variable created in flow steps |

Detailed Report of Warning Found in Flow Steps:

* Blank column denotes value is **not assigned** to variable.

| Flow Step | Variable Type | Variable Name | Assign From (*) | Default Value | Remarks |
|-------------------------|----------------|--------------------------|-----------------|--|--|
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | url | | \$(HCM/HCM-REST-URL)artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256... | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------|----------------|---------------------------|------------------------|--|--|
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | username | ipamUsername | HCM-ADMIN-ACCOUNT : USERNAME | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | password | ipamPassword | HCM-ADMIN-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |
| AD Get Properties | Input Variable | providerId | ADproviderId | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | AD Flow failed to update AD Property AD_DOMAIN | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | onlyUpdate | | yes | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | propertyName | | AD_DOMAIN | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | values | domain | | Input variable name and Assign from values are not identical |
| Update Component Property | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | consumerVisible | | true | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | componentId | serverComponentId | | Input variable name and Assign from values are not identical |
| SQL Command | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------------|----------------|----------------------|----------------|---|---|
| SQL Command | Input Variable | Command | Command | SELECT "PLATFORM", "ROLE" FROM public." COMPUTE_OFFERING " WHERE "OFFERING_NAME" = '{offeringName}' AND "NETWORK" = '{networkType}'; | Hard-coded values present in use constant field |
| SQL Command | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| SQL Command To Get Template | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| SQL Command To Get Template | Input Variable | Command | Command | SELECT "TEMPLATE" FROM public."COMPU TE_OFFERING" WHERE "OFFERING_NAME" = '{offeringName}' AND "NETWORK" = '{networkType}'; | Hard-coded values present in use constant field |
| SQL Command To Get Template | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| SQL Command To get Custom Spec | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| SQL Command To get Custom Spec | Input Variable | Command | Command | SELECT "CUSTOM_SPEC" FROM public."COMPU TE_OFFERING" WHERE "OFFERING_NAME" = '{offeringName}' AND "NETWORK" = '{networkType}'; | Hard-coded values present in use constant field |
| SQL Command To get Custom Spec | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | failureMessage | failureMessage | flow failed due tooo blahhh | Hard-coded values present in use constant field |
| Get HCM Authentication Token | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get HCM Authentication Token | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get HCM Authentication Token | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get HCM Authentication Token | Input Variable | useCookies | | true | Hard-coded values present in use constant field |

| | | | | | |
|------------------------------|----------------|----------------------|----------------------|--|--|
| Get HCM Authentication Token | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| POST operation | Input Variable | url | | \${HCM/HCM-API-URL}urest/v1.0.0/serviceRequest | Hard-coded values present in use constant field |
| POST operation | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| POST operation | Input Variable | string | returnResult | { "requestReference":"\${subscriptionId}", "onBehalf":"\${onBehalf}", "action":"CANCEL_SUBSCRIPTION" } | Input variable name and Assign from values are not identical |
| POST operation | Input Variable | string | returnResult | { "requestReference":"\${subscriptionId}", "onBehalf":"\${onBehalf}", "action":"CANCEL_SUBSCRIPTION" } | Hard-coded values present in use constant field |
| POST operation | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| POST operation | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| POST operation | Input Variable | headerNamesList | | Accept,Content-Type,X-Auth-Token | Hard-coded values present in use constant field |
| POST operation | Input Variable | headerValuesList | | application/json,application/json,{authToken} | Hard-coded values present in use constant field |
| POST operation | Input Variable | delimiter | | , | Hard-coded values present in use constant field |
| POST operation | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| POST operation | Input Variable | password | csaPassword | HCM-SERVICE-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |
| Request Id | Input Variable | json | requestDetails | | Input variable name and Assign from values are not identical |
| Request Id | Input Variable | jsonPathQuery | | \$.@uri | Hard-coded values present in use constant field |
| POST operation | Input Variable | url | | \${HCM/HCM-API-URL}service/subscription/\${subscriptionId}/cancel | Hard-coded values present in use constant field |
| POST operation | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| POST operation | Input Variable | string | returnResult | {} | Input variable name and Assign from values are not identical |

| | | | | | |
|----------------------------|----------------|----------------------|----------------------|---|--|
| POST operation | Input Variable | string | returnResult | {} | Hard-coded values present in use constant field |
| POST operation | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| POST operation | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| POST operation | Input Variable | headerNamesList | | Accept,Content-Type,X-Auth-Token | Hard-coded values present in use constant field |
| POST operation | Input Variable | headerValuesList | | application/json,application/json,{authToken} | Hard-coded values present in use constant field |
| POST operation | Input Variable | queryValuesList | onBehalf | | Input variable name and Assign from values are not identical |
| POST operation | Input Variable | delimiter | | , | Hard-coded values present in use constant field |
| POST operation | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| POST operation | Input Variable | password | csaPassword | HCM-ADMIN-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | subscriptionId | subscriptionId | 2c92d4ba7372ac330173e201b2dd1783 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | vmName | vmName | testvm1 | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Finalize Service Component | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Finalize Service Component | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | url | | \${CSA_REST_URI}/life cycleengine/execute?userIdentifier=\${userIdentifier} | Hard-coded values present in use constant field |

| | | | | | |
|--------------------|----------------|------------------------|--|---|---|
| Initiate LifeCycle | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | body | | <?xml version="1.0" encoding="UTF-8" standalone="yes"?> <LifecycleExecutionRequest> <reverse>false</reverse> <serviceComponentId>\${parentComponentId}</serviceComponentId> <serviceInstanceId>\${serviceInstanceId}</serviceInstanceId> <targetStateName>DEPLOYED</targetStateName> </LifecycleExecutionRequest> ... | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | headers | | Accept:application/xml content-type:application/xml | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |

| | | | | | |
|--------------------|----------------|--------------------------|--|--|---|
| Initiate LifeCycle | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | contentType | | application/xml | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Initiate LifeCycle | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | url | | \${CSA_REST_URI}/life-cycleengine | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | queryParams | | userIdentifier=\${userIdentifier}&serviceInstanceId;=\${serviceInstanceId} | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------|----------------|---------------------------|------------------------|--|--|
| Get LCE Status | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | headers | | Accept:application/xml | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get LCE Status | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get ServiceInstanceDetails | Input Variable | csaApiUrl | | \${HCM/HCM-API-URL} | Hard-coded values present in use constant field |
| Get ServiceInstanceDetails | Input Variable | onBehalf | serviceInstanceOwner | | Input variable name and Assign from values are not identical |
| Filter Component ID | Input Variable | json | serviceInstanceJSON | | Input variable name and Assign from values are not identical |
| Filter Component ID | Input Variable | jsonPathQuery | | \$.components[?(@.displayName=='Server Project')].id | Hard-coded values present in use constant field |
| Filter Component ID | Input Variable | json | serviceInstanceJSON | | Input variable name and Assign from values are not identical |
| Filter Component ID | Input Variable | jsonPathQuery | | \$.components[?(@.displayName=='Virtual Server')].id | Hard-coded values present in use constant field |
| Array Size | Input Variable | array | serverComponentIdArray | | Input variable name and Assign from values are not identical |
| Array Iterator | Input Variable | array | serverComponentIdArray | | Input variable name and Assign from values are not identical |
| Get Artifact Properties | Input Variable | propertyNames | | name | Hard-coded values present in use constant field |
| Get Artifact Properties | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Get Artifact Properties | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Get Artifact Properties | Input Variable | artifactId | componentId | | Input variable name and Assign from values are not identical |
| Cancel HCM Subscription | Input Variable | onBehalf | serviceInstanceOwner | | Input variable name and Assign from values are not identical |

| | | | | | |
|-----------------------------------|----------------|-------------------------|-------------------|---|--|
| Modify Service Component Property | Input Variable | propertyName | | SERVER_COUNT | Hard-coded values present in use constant field |
| Modify Service Component Property | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Modify Service Component Property | Input Variable | consumerVisible | | true | Hard-coded values present in use constant field |
| Modify Service Component Property | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Modify Service Component Property | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Modify Service Component Property | Input Variable | componentId | parentComponentId | | Input variable name and Assign from values are not identical |
| Modify Service Component Property | Input Variable | values | serverCount | | Input variable name and Assign from values are not identical |
| Get Subscription Details | Input Variable | svcSubscriptionId | subscriptionId | | Input variable name and Assign from values are not identical |
| Sleep | Input Variable | seconds | | 60 | Hard-coded values present in use constant field |
| Loop | Input Variable | count | | 30 | Hard-coded values present in use constant field |
| Loop | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Loop | Input Variable | to | | \${count} | Hard-coded values present in use constant field |
| Loop | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Loop | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | subscriptionDescription | | Subscription Started | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | action | | ORDER | Hard-coded values present in use constant field |
| POST operation | Input Variable | url | | \${HCM/HCM-API-URL}rest/v1.0.0/serviceRequest | Hard-coded values present in use constant field |
| POST operation | Input Variable | authType | | basic | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|------------------|------------------|--|--|
| POST operation | Input Variable | string | payLoad | | Input variable name and Assign from values are not identical |
| POST operation | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| POST operation | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| POST operation | Input Variable | headerNamesList | headerNamesList | Accept,Content-Type,X-Auth-Token | Hard-coded values present in use constant field |
| POST operation | Input Variable | headerValuesList | headerValuesList | application/json,application/json,{authToken} | Hard-coded values present in use constant field |
| POST operation | Input Variable | delimiter | delimiter | , | Hard-coded values present in use constant field |
| POST operation | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| Request Id | Input Variable | json | requestDetails | | Input variable name and Assign from values are not identical |
| Request Id | Input Variable | jsonPathQuery | | \$.@uri | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|---------------------------|-------------------|---|--|
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | username | ipamUsername | HCM-ADMIN-ACCOUNT : USERNAME | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | password | ipamPassword | HCM-ADMIN-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |
| Get Artifact Properties | Input Variable | artifactId | serverComponentId | | Input variable name and Assign from values are not identical |
| Get Artifact Properties | Input Variable | propertyNames | | AD_PROVIDER_ID | Hard-coded values present in use constant field |
| Get Artifact Properties | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|---------------------------|--------------|--|---|
| Get Artifact Properties | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${parentComponentId} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParams | | userIdentifier=\${userIdentifier}&scope;=Baseplusone | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|--------------------------|------------------|--|--|
| Http Client Get | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Component Properties | Input Variable | componentId | childComponentId | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${parentComponentId} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParams | | userIdentifer=\${userIdentifer}&scope;=Baseplusone | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------|----------------|---------------------------|------------------|--|--|
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Component Properties | Input Variable | componentId | childComponentId | | Input variable name and Assign from values are not identical |
| Http Client Get | Input Variable | url | | \$(HCM/HCM-REST-URL)artifact/\${componentId}/resolveProperties?userId=\${userId}&view;=propertyvalue | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | followRedirects | followRedirects | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | headerNamesList | headerNamesList | Accept | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | headerValuesList | headerValuesList | application/xml | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | delimiter | delimiter | , | Hard-coded values present in use constant field |
| Get Current Date and Time | Input Variable | localeCountry | | unix | Hard-coded values present in use constant field |
| Date Parser | Input Variable | date | | \$(currentdate) | Hard-coded values present in use constant field |
| Date Parser | Input Variable | dateFormat | | MMM dd,yyyy hh:mm:ss aa | Hard-coded values present in use constant field |
| Date Parser | Input Variable | dateLocaleLang | | en | Hard-coded values present in use constant field |
| Date Parser | Input Variable | dateLocaleCountry | | US | Hard-coded values present in use constant field |
| Date Parser | Input Variable | outFormat | | yyyy-MM-dd'T'HH:mm:ss.S'Z' | Hard-coded values present in use constant field |
| Date Parser | Input Variable | outLocaleLang | | en | Hard-coded values present in use constant field |
| Date Parser | Input Variable | outLocaleCountry | | US | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------------|----------------|------------------------|----------------------|---|--|
| Flow Inputs | Input Variable | tenantName | tenantName | MFIDMZ | Hard-coded values present in use constant field |
| Authentication Using IDM Token | Input Variable | url | url | \${HCM/HCM-IDM-URL} idm-service/v2.0/tokens | Hard-coded values present in use constant field |
| Authentication Using IDM Token | Input Variable | authType | authType | basic | Hard-coded values present in use constant field |
| Authentication Using IDM Token | Input Variable | string | | { "passwordCredentials" : { "username" : "\${hcmUsername}", "password" : "\${hcmPassword}" }, "tenantName" : "\${tenantName}" } | Hard-coded values present in use constant field |
| Authentication Using IDM Token | Input Variable | timeout | connectTimeout | | Input variable name and Assign from values are not identical |
| Authentication Using IDM Token | Input Variable | proxy | proxyHost | | Input variable name and Assign from values are not identical |
| Authentication Using IDM Token | Input Variable | contentType | contentType | application/json | Hard-coded values present in use constant field |
| Authentication Using IDM Token | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Authentication Using IDM Token | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Loop | Input Variable | count | | 4 | Hard-coded values present in use constant field |
| Loop | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Loop | Input Variable | to | | \${count} | Hard-coded values present in use constant field |
| Loop | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Loop | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 15 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | | Failed to get HCM Authentication Token | Hard-coded values present in use constant field |

| | | | | | |
|----------------------|----------------|----------------------|-------------------------|--|--|
| Get Offering Details | Input Variable | url | url | \${HCM/HCM-API-URL} service/offering/container/filter?sort=name&start-index;=0 | Hard-coded values present in use constant field |
| Get Offering Details | Input Variable | authType | authType | basic | Hard-coded values present in use constant field |
| Get Offering Details | Input Variable | timeout | connectTimeout | | Input variable name and Assign from values are not identical |
| Get Offering Details | Input Variable | proxy | proxyHost | | Input variable name and Assign from values are not identical |
| Get Offering Details | Input Variable | string | | { "service_offering": { "keywords": ["\${offeringName}"], "fields": ["name"] } } | Hard-coded values present in use constant field |
| Get Offering Details | Input Variable | contentType | contentType | application/json | Hard-coded values present in use constant field |
| Get Offering Details | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Get Offering Details | Input Variable | headerNamesList | headerNamesList | Accept,Content-Type,X-Auth-Token | Hard-coded values present in use constant field |
| Get Offering Details | Input Variable | headerValuesList | headerValuesList | application/json,application/json,\${authToken} | Hard-coded values present in use constant field |
| Get Offering Details | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Get Offering Details | Input Variable | username | idmuser | HCM-ADMIN-ACCOUNT : USERNAME | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| JSON Path | Input Variable | jsonPathQuery | | \$.components | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable name and Assign from values are not identical |
| Array Iterator | Input Variable | array | jsonArray | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.displayName=='Virtual Server')].id | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable name and Assign from values are not identical |

| | | | | | |
|-----------------------------|----------------|----------------------|-------------------------|---|--|
| Get Child Component Details | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${jsonElement}?userIdentifier=\${userIdentifier} | Hard-coded values present in use constant field |
| Get Child Component Details | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Child Component Details | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Get Child Component Details | Input Variable | encodeURL | | True | Hard-coded values present in use constant field |
| Get Artifact Properties | Input Variable | propertyNames | | name NETWORK | Hard-coded values present in use constant field |
| Get Artifact Properties | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Get Artifact Properties | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Get Artifact Properties | Input Variable | artifactId | jsonElement | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id==`\${jsonElement}`)].resourceSubscription[*].serviceAction[?(@.displayName==`\${actionName}`)].name | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id==`\${disk1componentId}`)].resourceSubscription[*].serviceAction[?(@.displayName==`\${actionName}`)].name | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id==`\${disk2componentId}`)].resourceSubscription[*].serviceAction[?(@.displayName==`\${actionName}`)].name | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable name and Assign from values are not identical |

| | | | | | |
|-----------------|----------------|----------------------|-------------------------|---|--|
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id=='\${jsonElement}').resourceSubscription[?(@.displayName=='Micro Focus Compute')].id | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id=='\${disk2componentId}').resourceSubscription[*].id | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.id=='\${disk1componentId}').resourceSubscription[*].id | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | serviceInstanceDocument | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | csaApiUrl | csaApiUrl | \${HCM/HCM-API-URL} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | url | \${csaApiUrl}consumption/v2/instance/\${serviceInstanceId}?onBehalf=\${onBehalf} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | headers | | Accept:application/json X-Auth-token:\${X-Auth-Token} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | method | | GET | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------------|----------------|-------------------|-------------------|----------------------------------|--|
| Flow Inputs | Input Variable | startDate | | 1600413726431 | Hard-coded values present in use constant field |
| Date Parser | Input Variable | date | startDate | | Input variable name and Assign from values are not identical |
| Date Parser | Input Variable | dateFormat | | unix | Hard-coded values present in use constant field |
| Date Parser | Input Variable | dateLocaleLang | | en | Hard-coded values present in use constant field |
| Date Parser | Input Variable | dateLocaleCountry | | US | Hard-coded values present in use constant field |
| Date Parser | Input Variable | outFormat | | yyyy-MM-dd'T'HH:mm:ss.S'Z' | Hard-coded values present in use constant field |
| Date Parser | Input Variable | outLocaleLang | | en | Hard-coded values present in use constant field |
| Date Parser | Input Variable | outLocaleCountry | | US | Hard-coded values present in use constant field |
| Date Parser | Input Variable | date | endDate | | Input variable name and Assign from values are not identical |
| Date Parser | Input Variable | dateFormat | | unix | Hard-coded values present in use constant field |
| Date Parser | Input Variable | dateLocaleLang | | en | Hard-coded values present in use constant field |
| Date Parser | Input Variable | dateLocaleCountry | | US | Hard-coded values present in use constant field |
| Date Parser | Input Variable | outFormat | | yyyy-MM-dd'T'HH:mm:ss.S'Z' | Hard-coded values present in use constant field |
| Date Parser | Input Variable | outLocaleLang | | en | Hard-coded values present in use constant field |
| Date Parser | Input Variable | outLocaleCountry | | US | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | svcSubscriptionId | svcSubscriptionId | 2c90cfef745cea750175dbd13e507c3d | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Get Service Subscription Details | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------------|----------------|----------------------|-------------------|--|--|
| Get Service Subscription Details | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Get Artifact Details | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Get Artifact Details | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Get Artifact Details | Input Variable | artifactId | serviceInstanceId | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | networkType | networkType | INT | Hard-coded values present in use constant field |
| LDAP Search | Input Variable | DN | | OU=MF_Users,{AD/A D-INT-BASE-DN} | Hard-coded values present in use constant field |
| LDAP Search | Input Variable | filter | | mail=\${primaryEmail} | Hard-coded values present in use constant field |
| LDAP Search | Input Variable | propertyNames | | employeeID | Hard-coded values present in use constant field |
| LDAP Search | Input Variable | delimiter | | , | Hard-coded values present in use constant field |
| LDAP Search | Input Variable | useSSL | | true | Hard-coded values present in use constant field |
| LDAP Search | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | DN | | OU=Personal,OU=Accounts,OU=VirtualSM,{AD/AD-EXT-BASE-DN} | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | filter | | employeeID=\${employeeID} | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | propertyNames | | sAMAccountName,userPrincipalName | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | delimiter | | , | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | useSSL | | true | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| INT LDAP Search | Input Variable | DN | | OU=Personal,OU=Accounts,OU=VirtualSM,{AD/AD-INT-BASE-DN} | Hard-coded values present in use constant field |

| | | | | | |
|-----------------|----------------|---------------|--|--|---|
| INT LDAP Search | Input Variable | filter | | employeeID=\${employeeID} | Hard-coded values present in use constant field |
| INT LDAP Search | Input Variable | propertyNames | | sAMAccountName,userPrincipalName | Hard-coded values present in use constant field |
| INT LDAP Search | Input Variable | delimiter | | , | Hard-coded values present in use constant field |
| INT LDAP Search | Input Variable | useSSL | | true | Hard-coded values present in use constant field |
| INT LDAP Search | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| INT LDAP Search | Input Variable | DN | | OU=Personal,OU=Accounts,OU=VirtualSM,{AD/AD-INT-BASE-DN} | Hard-coded values present in use constant field |
| INT LDAP Search | Input Variable | filter | | employeeID=\${employeeID1} | Hard-coded values present in use constant field |
| INT LDAP Search | Input Variable | propertyNames | | sAMAccountName,userPrincipalName | Hard-coded values present in use constant field |
| INT LDAP Search | Input Variable | delimiter | | , | Hard-coded values present in use constant field |
| INT LDAP Search | Input Variable | useSSL | | true | Hard-coded values present in use constant field |
| INT LDAP Search | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | DN | | OU=Personal,OU=Accounts,OU=VirtualSM,{AD/AD-EXT-BASE-DN} | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | filter | | employeeID=\${employeeID1} | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | propertyNames | | sAMAccountName,userPrincipalName | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | delimiter | | , | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | useSSL | | true | Hard-coded values present in use constant field |
| EXT LDAP Search | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | host | | \${AD/AD-HOSTNAME} | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|----------------------|-------------------|---|---|
| Flow Inputs | Input Variable | DN | | OU=Personal,OU=Accounts,OU=VirtualSM,{AD/AD-BASE-DN} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | filter | filter | mail=anshul.jindal@microfocus.com | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | propertyNames | | cn,sAMAccountName,mail | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | port | | \${AD/AD-PORT} | Hard-coded values present in use constant field |
| LDAP Search | Input Variable | delimiter | | , | Hard-coded values present in use constant field |
| LDAP Search | Input Variable | useSSL | | true | Hard-coded values present in use constant field |
| LDAP Search | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | resourceBindingId | | 2c92d4ba7372ac330173bddd23126826 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | userIdentifier | | 6BC7CE65B5F74D08AA29C8FC40616451 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | site | | houston4 | Hard-coded values present in use constant field |
| Get Candidate Providers | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Candidate Providers | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| XPath Query for Site | Input Variable | xpathQuery | | /ResourceBinding/candidateProvider/resourceProvider/property/displayName[text()='Site']/../values/value[text()='\${site}']/../../id/text() | Hard-coded values present in use constant field |
| XPath Query for Site | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | resourceBindingId | resourceBindingId | 2c92d4ba7372ac3301741fca32fb2186 | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------|----------------|------------------------|------------------------|--|--|
| Flow Inputs | Input Variable | resourceProviderId | resourceProviderId | 2c92d41d71e9248a01723afd9f962582 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | serverComponentId | serverComponentId | 4a0742c4498693d19fbe05128602f9d2 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | networkType | networkType | INT | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Store Resource Pool Info | Input Variable | subnet | ss | | Input variable name and Assign from values are not identical |
| Store Resource Pool Info | Input Variable | candidatePooldata | document1 | | Input variable name and Assign from values are not identical |
| Update Valid Provider Pool | Input Variable | resourceBindingXml | | <ResourceBinding> <id>\${resourceBindingId}</id> <validProvider> <resourceBinding> <id>\${resourceBindingId}</id> </resourceBinding> <resourceProvider> <id>\${resourceProviderId}</id> </resourceProvider> <validPool> <id>\${selectedSubnetpool}</id> </validPool> </validProvider> </ ... | Hard-coded values present in use constant field |
| Update Valid Provider Pool | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Update Valid Provider Pool | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Update Valid Provider Pool | Input Variable | chunked | chunked | false | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to process Resource Pool Information | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to process Resource Pool Information | Hard-coded values present in use constant field |
| Get Candidate Providers | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------------|----------------|----------------------|--------------------|---|--|
| Get Candidate Providers | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| IPAM Network Selection Process | Input Variable | providerId | resourceProviderId | 2c92d41d71e9248a01723afd9f962582 | Input variable name and Assign from values are not identical |
| IPAM Network Selection Process | Input Variable | providerId | resourceProviderId | 2c92d41d71e9248a01723afd9f962582 | Hard-coded values present in use constant field |
| IPAM Network Selection Process | Input Variable | networkType | networkType | INT | Hard-coded values present in use constant field |
| XPath Query for Subnet | Input Variable | xml | candidatePooldata | | Input variable name and Assign from values are not identical |
| XPath Query for Subnet | Input Variable | xpathQuery | | /ResourceBinding//candidateProvider/candidatePool/displayName[text()='\${subnet}']/../id/text() | Hard-coded values present in use constant field |
| XPath Query for Subnet | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| Get Resource Pool | Input Variable | resourceType | | IPv4 Address | Hard-coded values present in use constant field |
| Get Resource Pool | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Get Resource Pool | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | resourcePoolID | resourcePoolID | 2c90cfa0742483e701742f310e1516d7 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | userIdentifier | userIdentifier | 6BC7CE65B5F74D08AA29C8FC40616451 | Hard-coded values present in use constant field |
| Get Resource Pool (CPU) | Input Variable | resourceType | | CPU | Hard-coded values present in use constant field |
| Get Resource Pool (CPU) | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Resource Pool (CPU) | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Resource Pool (Memory) | Input Variable | resourceType | | MEMORY | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------|----------------|----------------------|------------------|---|--|
| Get Resource Pool (Memory) | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Resource Pool (Memory) | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Resource Pool (Storage) | Input Variable | resourceType | | STORAGE | Hard-coded values present in use constant field |
| Get Resource Pool (Storage) | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Resource Pool (Storage) | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | action | action | ORDER | Hard-coded values present in use constant field |
| POST operation | Input Variable | url | | \${HCM/HCM-API-URL}rest/v1.0.0/serviceRequest | Hard-coded values present in use constant field |
| POST operation | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| POST operation | Input Variable | string | returnResult | { "requestReference": "\${requestReference}", "subscriptionName": "\${subscriptionName}", "action": "\${action}", "actionProperty": \${actionProperty}, "onBehalf" : "\${onBehalf}" } | Input variable name and Assign from values are not identical |
| POST operation | Input Variable | string | returnResult | { "requestReference": "\${requestReference}", "subscriptionName": "\${subscriptionName}", "action": "\${action}", "actionProperty": \${actionProperty}, "onBehalf" : "\${onBehalf}" } | Hard-coded values present in use constant field |
| POST operation | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| POST operation | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| POST operation | Input Variable | headerNamesList | headerNamesList | Accept,Content-Type,X-Auth-Token | Hard-coded values present in use constant field |
| POST operation | Input Variable | headerValuesList | headerValuesList | application/json,application/json,{authToken} | Hard-coded values present in use constant field |
| POST operation | Input Variable | delimiter | delimiter | , | Hard-coded values present in use constant field |

| | | | | | |
|---------------------|----------------|------------------------|----------------|--|--|
| POST operation | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| Request Id | Input Variable | json | requestDetails | | Input variable name and Assign from values are not identical |
| Request Id | Input Variable | jsonPathQuery | | \$.@uri | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${parentComponentId} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParams | | userIdentifer=\${userIdentifer}&scope;=Baseplusone | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------|----------------|---------------------------|----------------------|-----------|--|
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | onlyUpdate | | yes | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | values | value | | Input variable name and Assign from values are not identical |
| Update Component Property | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | consumerVisible | | true | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Update Component Property | Input Variable | componentId | childComponentId | | Input variable name and Assign from values are not identical |
| Get Object Keys | Input Variable | object | jsonObject | | Input variable name and Assign from values are not identical |
| Array Iterator | Input Variable | array | objectKeys | | Input variable name and Assign from values are not identical |
| Get Value from Object | Input Variable | object | jsonObject | | Input variable name and Assign from values are not identical |
| Get Value from Object | Input Variable | key | propertyName | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | trustAllRoots | trustAllRoots | false | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | x509HostnameVerifier | x509HostnameVerifier | strict | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|----------------------|----------------------|---|--|
| Http Client Get | Input Variable | url | | \${CSA_REST_URI}/artifact/\${resourcePoolID}?userIdentifier=\${userIdentifier} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | followRedirects | followRedirects | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | headerNamesList | headerNamesList | Accept | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | headerValuesList | headerValuesList | application/xml | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | delimiter | delimiter | , | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | url | | \${CSA_REST_URI}/artifact/\${resourcePoolID}?userIdentifier=\${userIdentifier}&_action_=merge | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | string | | <ResourcePool> <name>\${name}</name> <displayName>\${displayName}</displayName> <poolReference>\${poolReference}</poolReference> <resourceProvider> <id>\${providerId}</id></resourceProvider> \${actionNode} <state> <name>ACTIVE</name> </state> <disabled>\${disabledState}</disabled> ... | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | headerNamesList | headerNamesList | Accept,content-type | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | headerValuesList | headerValuesList | application/xml,application/xml | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | delimiter | | , | Hard-coded values present in use constant field |
| Get Resource Capacity | Input Variable | xpathExpression | xpathExpression | /ResourcePool/resourceCapacity | Hard-coded values present in use constant field |
| Get Resource Capacity | Input Variable | xml | document | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | trustAllRoots | trustAllRoots | false | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | x509HostnameVerifier | x509HostnameVerifier | strict | Hard-coded values present in use constant field |

| | | | | | |
|------------------|----------------|------------------------|------------------|---|---|
| Http Client Put | Input Variable | url | | \${CSA_REST_URI}/artifact/\${resourceBindingId}?userIdentifier=\${userIdentifier}&scope;=view&view;=validproviderspools | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | string | | \${resourceBindingXml} | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | headerNamesList | headerNamesList | Accept,content-type | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | headerValuesList | headerValuesList | application/xml,application/xml | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | delimiter | | , | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | chunked | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/\${ss}/capacity | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |

| | | | | | |
|------------------|----------------|--------------------------|--------------------|---|--|
| Http Client Post | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | body | | { "name": null, "description": null, "ext": { "csa_used_by_csa": 0, "csa_available_to_csa": 0 }, "availability": { "displayName": "Available", "ext": { "csa_name_key": "AVAILABLE" } }, "type": { "ext": { ... | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | method | | POST | Hard-coded values present in use constant field |
| JSON Path | Input Variable | jsonPathQuery | | \$.type.name | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | response | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | resource_pool_info | resource_pool_info | 15.120.128.0/21 2c92d41d71e9248a01723afd9f962582,15.120.240.0/21 2c92d41d71e9248a01723afd9f962582,NO NE 2c92d41d71e9248a01723afd9f962582,15.120.144.0/21 2c92d41d71e9248a01723afd9f962582 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/ | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |

| | | | | | |
|------------------|----------------|--------------------------|--|---|---|
| Http Client Post | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | body | | { "name": "\${resource_pool_name}", "description": null, "enabled": true, "poolReference": "\${resource_pool_name}", "syncAction": null, "provider": { "@self": "/c sa/api/resource/provider/\${provider_id}" } } | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | method | | POST | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|--------------------------|-------------|--|--|
| Add Resource Type | Input Variable | resource_pool_id | res_pool_id | | Input variable name and Assign from values are not identical |
| Add Resource Type | Input Variable | Key_name | | IPV4_ADDRESS | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | providerId | providerId | 2c92d41d71e9248a01723afd9f962582 | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256... | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|---------------------------|--------------|---|--|
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | username | ipamUsername | HCM-ADMIN-ACCOUNT : USERNAME | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | password | ipamPassword | HCM-ADMIN-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |
| fetch subnet | Input Variable | xpathQuery | | /ResourceProvider/property/displayName[text()=\$\${ss}]/../values/displayName[text()='subnet']/../value/text() | Hard-coded values present in use constant field |
| fetch subnet | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | Resource_pool_id | | 2c92d4ba7372ac330173e66ce8077eed | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | | https://mc4t02870.itscsoftwaregrp.net:443/csa/api/resource/pool/\${Resource_pool_id}/capacity | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | username | | admin | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |

| | | | | | |
|------------------|----------------|---------------------------|------------|---|---|
| Http Client Get | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | providerId | providerId | 2c92d41d71e9248a01723afd9f962582 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/filter | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |

| | | | | | |
|--------------------|----------------|--------------------------|----------|--|--|
| Http Client Post | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | headers | | Accept:application/json content-type:application/json | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | body | | { "providerId": "\${providerId}" } | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Loop | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Loop | Input Variable | to | | \${count} | Hard-coded values present in use constant field |
| Loop | Input Variable | from | | 0 | Hard-coded values present in use constant field |
| Loop | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| query provder name | Input Variable | jsonPathQuery | | \$.members[\${current_element}].name | Hard-coded values present in use constant field |
| query provder name | Input Variable | json | response | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.members[\${current_element}] | Hard-coded values present in use constant field |

| | | | | | |
|-----------------|----------------|---------------------------|----------|---------------------------------------|--|
| JSON Path | Input Variable | json | response | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | provider | provider | Micro Focus InfoBlox | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | | \${HCM/HCM-API-URL}resource/provider/ | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | method | | GET | Hard-coded values present in use constant field |

| | | | | | |
|--------------------|----------------|----------------------|---------------|--|--|
| Loop | Input Variable | count | tot_providers | | Input variable name and Assign from values are not identical |
| Loop | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Loop | Input Variable | to | | \${count} | Hard-coded values present in use constant field |
| Loop | Input Variable | from | | 0 | Hard-coded values present in use constant field |
| Loop | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| query provder name | Input Variable | jsonPathQuery | | \$.members[\${current_element}].name | Hard-coded values present in use constant field |
| query provder name | Input Variable | json | returnResult | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.members[\${current_element}] | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | returnResult | | Input variable name and Assign from values are not identical |
| Http Client Put | Input Variable | url | | https://\${lpamUrl}:443/wapi/v1.4/\${buildUrl} | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------|----------------|------------------------|------------------------|---|---|
| Http Client Put | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | body | | \${payloadJson} | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Http Client Put | Input Variable | method | | PUT | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | IPAM Flow failed to get IP Address/Add Host record | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | trustAllRoots | trustAllRoots | false | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | x509HostnameVerifier | x509HostnameVerifier | strict | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | url | | \${url}/wapi/v1.4/record:host?_return_type=xml | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | body | | { "ipv4addrs":[{"ipv4addr":"\${ipAddress}"}, {"name":"\${hostName}.\${domain}","configure_for_dns":true, "view":"\${view}"}] } | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | preemptiveAuth | preemptiveAuth | true | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | trustAllRoots | trustAllRoots | false | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | x509HostnameVerifier | x509HostnameVerifier | strict | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------|----------------|------------------------|------------------------|--|---|
| API Call to Add Host Record | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | connectionsMaxPerRoute | connectionsMaxPerRoute | 2 | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | connectionsMaxTotal | connectionsMaxTotal | 20 | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | requestCharacterSet | requestCharacterSet | ISO-8859-1 | Hard-coded values present in use constant field |
| API Call to Add Host Record | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | trustAllRoots | trustAllRoots | false | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | x509HostnameVerifier | x509HostnameVerifier | strict | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | url | | `\${url}/wapi/v1.4/network?network=\${network}&_return_type=xml&_return_fields=network,extattrs,options` | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | authType | authType | basic | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | trustAllRoots | trustAllRoots | false | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | timeout | timeout | 300000 | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | socketTimeout | socketTimeout | 300000 | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | x509HostnameVerifier | x509HostnameVerifier | strict | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | preemptiveAuth | preemptiveAuth | true | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|------------------------------|------------------------------|---|---|
| API Call to Find Network | Input Variable | kerberosSkipPortForLookup | kerberosSkipPortForLookup | true | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | connectionsMaxPerRoute | connectionsMaxPerRoute | 2 | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | connectionsMaxTotal | connectionsMaxTotal | 20 | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | queryParamsAreURLEncoded | queryParamsAreURLEncoded | false | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | queryParamsAreFormEncoded | queryParamsAreFormEncoded | true | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | formParamsAreURLEncoded | formParamsAreURLEncoded | false | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | requestCharacterSet | requestCharacterSet | ISO-8859-1 | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | multipartBodiesContentType | multipartBodiesContentType | text/plain; charset=ISO-8859-1 | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | multipartValuesAreURLEncoded | multipartValuesAreURLEncoded | false | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | multipartFilesContentType | multipartFilesContentType | application/octet-stream | Hard-coded values present in use constant field |
| API Call to Find Network | Input Variable | method | method | GET | Hard-coded values present in use constant field |
| SQL Command | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| SQL Command | Input Variable | Command | DB_Details/SQL_COMMAND | SELECT nextval('public."SERVER_COUNT_C"') | Hard-coded values present in use constant field |
| SQL Command | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | | https://ipam.softwaregrp.net/wapi/v2.6/ipv4address?network=15.120.170.0/23&status;=UNUSED | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|----------------------|----------------|--|--|
| Http Client Get | Input Variable | username | | api-itsm-cloud | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | | basic | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Get Candidate Providers | Input Variable | resourceBindingId | | [TOKEN:RSC_BINDING_ID] | Hard-coded values present in use constant field |
| Get Candidate Providers | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Get Candidate Providers | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | providerId | providerId | 2c92d41d71e9248a01723afd9f962582 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | resourcePoolID | resourcePoolID | 2c90cfef745cea750174a75e36a01864 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | networkType | networkType | INT | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|---------------------------|--------------|---|--|
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | username | ipamUsername | HCM-ADMIN-ACCOUNT : USERNAME | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | password | ipamPassword | HCM-ADMIN-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |
| XPath Query for Zone | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='zone']/../value/text() | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------|----------------|-----------------|--|--|---|
| XPath Query for Zone | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| XPath Query for SubnetMask | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='subnetMask']/../value/text() | Hard-coded values present in use constant field |
| XPath Query for SubnetMask | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| XPath Query for GatewayIp | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='gatewayIp']/../value/text() | Hard-coded values present in use constant field |
| XPath Query for GatewayIp | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| XPath Query for Site | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='site']/../value/text() | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------|----------------|-----------------|--|--|---|
| XPath Query for Site | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| XPath Query for VLAN | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='vlan']/../value/text() | Hard-coded values present in use constant field |
| XPath Query for VLAN | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| XPath Query for Datacenter | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='datacenter']/../value/text() | Hard-coded values present in use constant field |
| XPath Query for Datacenter | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| XPath Query for Satellite | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='subnet']/../value[text()='\${subnet}']/../values/displayName[text()='Satellite']/../value/text() | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------|----------------|----------------------|---------|---|---|
| XPath Query for Satellite | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| Get Resource Pool | Input Variable | resourceType | | IPv4 Address | Hard-coded values present in use constant field |
| Get Resource Pool | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Get Resource Pool | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | subnets | subnets | 15.120.128.0/21 2c92d4ba7372ac330174020adaf313e0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | | \${IPAM/Protocol}://\${IPAM/IPAM_Hostname}/wapi/v2.6/ipv4address?network=\${subnet}&status;=UNUSED&_max_results=100000 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | username | | api-itsm-cloud | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | useCookies | | true | Hard-coded values present in use constant field |

| | | | | | |
|-----------------|----------------|---------------------------|----------|--|--|
| Http Client Get | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | method | | GET | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | response | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.[?(@.network=='\${subnet}')].status | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | subnet | | 15.120.128.0/21 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | | https://ipam.softwaregrp.net/wapi/v2.6/ipv4address?network=\${subnet}&status=USED&_max_results=10000 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | username | | api-itsm-cloud | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|---------------------------|--------------|--|--|
| Http Client Get | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Array Iterator | Input Variable | array | response | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | json | returnResult | \${returnResult} | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | json | returnResult | \${returnResult} | Hard-coded values present in use constant field |
| JSON Path | Input Variable | jsonPathQuery | | \$.status | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | url | | \$(HCM/HCM-REST-URL)artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | authType | | Basic | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|---------------------------|--------------|--|--|
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256... | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | allowedCyphers | | | |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | username | ipamUsername | HCM-ADMIN-ACCOUNT : USERNAME | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | password | ipamPassword | HCM-ADMIN-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |

| | | | | | |
|------------------------|----------------|----------------------|----------------------|--|--|
| XPath Query for Subnet | Input Variable | xpathQuery | | /ResourceProvider/property/values/displayName[text()='networkType']/../value[text()='\${networkType}']/../values/displayName[text()='site']/../value[text()='\${site}']/../values/displayName[text()='subnet']/../value/text() | Hard-coded values present in use constant field |
| XPath Query for Subnet | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| Find Network | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Find Network | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Find Network | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Get Next Available IP | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Get Next Available IP | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Get Next Available IP | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | ipAddress | nextIp | | Input variable name and Assign from values are not identical |
| Add Host Record | Input Variable | hostName | hostname | | Input variable name and Assign from values are not identical |
| Add Host Record | Input Variable | domain | zone | | Input variable name and Assign from values are not identical |

| | | | | | |
|----------------------------------|----------------|----------------------|-----------------|------------------------------------|--|
| Flow Inputs | Input Variable | resourcePoolID | | 2c92d4ba7372ac3301740599dbe73c1d | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | usedValue | | 100 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | availableValue | | 200 | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | resourcePoolID | resourcePoolID | 2c92d4ba7372ac330173e66ce8077eed | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | resourceType | | IPV4_ADDRESS | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | availableValue | availableValue | 150 | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | resourceType | | IPV4_ADDRESS | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | coreUsername | coreUserDetails | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | coreProtocol | coreprotocol | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | policyName | policyName | \${SA Policy/OA Policy Name Linux} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | policyID | policyID | \${SA Policy/OA Policy ID Linux} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | attachableType | | SERVER | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | separator | | , | Hard-coded values present in use constant field |

| | | | | | |
|--|----------------|-----------------------|--------------|------------------|--|
| Attach Software Policy | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Attach Software Policy | Input Variable | attachableName | host | | Input variable name and Assign from values are not identical |
| Attach Software Policy | Input Variable | attachableType | | SERVER | Hard-coded values present in use constant field |
| Attach Software Policy | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | serverName | host | | Input variable name and Assign from values are not identical |
| Remediate Server For Software Policies | Input Variable | serverId | attachableID | \${attachableID} | Input variable name and Assign from values are not identical |
| Remediate Server For Software Policies | Input Variable | serverId | attachableID | \${attachableID} | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | softwarePoliciesNames | policyName | | Input variable name and Assign from values are not identical |
| Remediate Server For Software Policies | Input Variable | softwarePoliciesIDs | policyID | | Input variable name and Assign from values are not identical |
| Remediate Server For Software Policies | Input Variable | wait | | 360000 | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | rebootOption | | suppress | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | continueOnFailure | | false | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | | \${jobId} | Hard-coded values present in use constant field |

| | | | | | |
|------------------------|----------------|----------------|--------------|------------------|--|
| Detach Software Policy | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Detach Software Policy | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Detach Software Policy | Input Variable | attachableName | host | | Input variable name and Assign from values are not identical |
| Detach Software Policy | Input Variable | attachableID | attachableID | \${attachableID} | Hard-coded values present in use constant field |
| Detach Software Policy | Input Variable | attachableType | | SERVER | Hard-coded values present in use constant field |
| Detach Software Policy | Input Variable | separator | | , | Hard-coded values present in use constant field |
| jobs | Input Variable | JobIds | jobId | | Input variable name and Assign from values are not identical |
| jobs | Input Variable | coreProtocol | coreprotocol | | Input variable name and Assign from values are not identical |
| jobs | Input Variable | serverID | attachableID | | Input variable name and Assign from values are not identical |
| jobs | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | scriptToRun | script | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHostIds | host | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | jobId | jobid | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | jobid | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | timeout | | 180000 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | coreProtocol | coreprotocol | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | separator | | , | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------------------|----------------|--------------|-----------------------------|--------|--|
| Get Remediate Policies Job Result | Input Variable | jobId | Id | | Input variable name and Assign from values are not identical |
| Get Remediate Policies Job Result | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Get Remediate Policies Job Result | Input Variable | coreProtocol | coreprotocol | https | Input variable name and Assign from values are not identical |
| Get Remediate Policies Job Result | Input Variable | coreProtocol | coreprotocol | https | Hard-coded values present in use constant field |
| Get Remediate Policies Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | EPP_UNREACHABLE_ SLEEP | 45 | Input variable name and Assign from values are not identical |
| Sleep | Input Variable | seconds | EPP_UNREACHABLE_ SLEEP | 45 | Hard-coded values present in use constant field |
| Count | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Count | Input Variable | to | EPP_HPSA_RETRY | 3 | Input variable name and Assign from values are not identical |
| Count | Input Variable | to | EPP_HPSA_RETRY | 3 | Hard-coded values present in use constant field |
| Count | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Count | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Decode Servers | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Decode Servers | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | coreVersion | coreVersion | sas107 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | script | Port_check_script_Linu x | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | scriptToRun | script | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHosts | host | | Input variable name and Assign from values are not identical |

| | | | | | |
|--|----------------|---------------|--------------|-------------------------------------|--|
| Start Server Script | Input Variable | targetHostIds | host | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | jobId | jobid | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | jobid | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | timeout | | 600000 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Iterate the List of Servers Job Status | Input Variable | array | jobResult | | Input variable name and Assign from values are not identical |
| OverallStatus | Input Variable | json | serverResult | | Input variable name and Assign from values are not identical |
| OverallStatus | Input Variable | jsonPathQuery | | \$.baseSteps[0].overallServerStatus | Hard-coded values present in use constant field |
| ServerID | Input Variable | json | serverResult | | Input variable name and Assign from values are not identical |
| ServerID | Input Variable | jsonPathQuery | | \$.serverId: | Hard-coded values present in use constant field |
| coGet Server VO | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| coGet Server VO | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| coGet Server VO | Input Variable | agent | Agent_Name | | Input variable name and Assign from values are not identical |
| coGet Server VO | Input Variable | matching | | Begins With | Hard-coded values present in use constant field |
| coGet Server VO | Input Variable | serverID | serverId | | Input variable name and Assign from values are not identical |
| coGet Server VO | Input Variable | delimiter | | ; | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|---------------|--------------|---|--|
| coGet Server VO | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| coGet Server VO | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| coGet Server VO | Input Variable | agent | Agent_Name | | Input variable name and Assign from values are not identical |
| coGet Server VO | Input Variable | matching | | Begins With | Hard-coded values present in use constant field |
| coGet Server VO | Input Variable | serverID | serverId | | Input variable name and Assign from values are not identical |
| coGet Server VO | Input Variable | delimiter | | ; | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | script | script | MFIT UpdateServerVO.py | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | scriptToRun | script | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHosts | host | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHostIds | host | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | args | args | -n "\${nameServer}" -s Cloned -u "Cloud Application Server" | Hard-coded values present in use constant field |
| Get Script Job Result | Input Variable | jobId | jobid | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | jobid | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | scriptToRun | script | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHosts | host | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | jobId | jobid | | Input variable name and Assign from values are not identical |

| | | | | | |
|--|----------------|-----------------------|-----------------|--------------------------------------|--|
| Get Script Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | jobid | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | timeout | | 180000 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | coreUsername | coreUserDetails | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | coreProtocol | coreprotocol | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | policyName | policyName | \${SA Policy/OA Policy Name Windows} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | policyID | policyID | \${SA Policy/OA Policy ID Windows} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | attachableType | | SERVER | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Attach Software Policy | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Attach Software Policy | Input Variable | attachableName | host | | Input variable name and Assign from values are not identical |
| Attach Software Policy | Input Variable | attachableType | | SERVER | Hard-coded values present in use constant field |
| Attach Software Policy | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | serverId | attachableID | \${attachableID} | Input variable name and Assign from values are not identical |
| Remediate Server For Software Policies | Input Variable | serverId | attachableID | \${attachableID} | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | softwarePoliciesNames | policyName | | Input variable name and Assign from values are not identical |

| | | | | | |
|--|----------------|---------------------|--------------|------------------|--|
| Remediate Server For Software Policies | Input Variable | softwarePoliciesIDs | policyID | | Input variable name and Assign from values are not identical |
| Remediate Server For Software Policies | Input Variable | wait | | 360000 | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | rebootOption | | suppress | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | continueOnFailure | | false | Hard-coded values present in use constant field |
| Remediate Server For Software Policies | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | | \${jobId} | Hard-coded values present in use constant field |
| Detach Software Policy | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Detach Software Policy | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Detach Software Policy | Input Variable | attachableName | host | | Input variable name and Assign from values are not identical |
| Detach Software Policy | Input Variable | attachableID | attachableID | \${attachableID} | Hard-coded values present in use constant field |
| Detach Software Policy | Input Variable | attachableType | | SERVER | Hard-coded values present in use constant field |
| Detach Software Policy | Input Variable | separator | | , | Hard-coded values present in use constant field |
| jobs | Input Variable | JobIds | jobId | | Input variable name and Assign from values are not identical |
| jobs | Input Variable | coreProtocol | coreprotocol | | Input variable name and Assign from values are not identical |
| jobs | Input Variable | serverID | attachableID | | Input variable name and Assign from values are not identical |
| jobs | Input Variable | separator | | , | Hard-coded values present in use constant field |

| | | | | | |
|---------------------|----------------|------------------|--|--|---|
| SSH Command | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | username | | postgres | Hard-coded values present in use constant field |
| SSH Command | Input Variable | command | | psql -t -P format=unaligned -c 'show hba_file' | Hard-coded values present in use constant field |
| SSH Command | Input Variable | timeout | | 90000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | pty | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | connectTimeout | | 10000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | keepAlive | | 0 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | useGlobalContext | | false | Hard-coded values present in use constant field |
| SSH Shell Logon | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Configure Postgress | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Configure Postgress | Input Variable | command | | send sudo yum install -y expect expectEndsWith : send HCMAdmin+123 expectEndsWith \$ send sudo passwd postgres expectEndsWith password: send HCMAdmin+123 expectendswith password: send HCMAdmin+123 expectEndsWith \$ send su - postgres expectendswith Password: send HCMAdmin+123 expectEndsWith \$ send psq ... | Hard-coded values present in use constant field |

| | | | | | |
|---------------------|----------------|------------------|--|--|---|
| Configure Postgress | Input Variable | timeout | | 5400000 | Hard-coded values present in use constant field |
| Configure Postgress | Input Variable | readTimeout | | 3600000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | username | | postgres | Hard-coded values present in use constant field |
| SSH Command | Input Variable | command | | psql -t -P format=unaligned -c 'show hba_file' | Hard-coded values present in use constant field |
| SSH Command | Input Variable | timeout | | 90000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | pty | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | connectTimeout | | 10000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | keepAlive | | 0 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | useGlobalContext | | false | Hard-coded values present in use constant field |
| SSH Shell Logon | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Create Databases | Input Variable | port | | 22 | Hard-coded values present in use constant field |

| | | | | | |
|-------------------|----------------|-------------|--|--|---|
| Create Databases | Input Variable | command | | send su - postgres expectendswith Password: send HCMAdmin+123 expectEndsWith \$ send psql -U postgres expectEndsWith # send create user dcaadmin login password 'HCMAdmin+123'; expectEndsWith # send CREATE DATABASE dca_db with OWNER='dcaadmin'; expectEndsWith # send CREATE DATABASE ucmdb with OWNER='d ... | Hard-coded values present in use constant field |
| Create Databases | Input Variable | timeout | | 5400000 | Hard-coded values present in use constant field |
| Create Databases | Input Variable | readTimeout | | 3600000 | Hard-coded values present in use constant field |
| Update configFile | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Update configFile | Input Variable | command | | send su - postgres expectendswith Password: send HCMAdmin+123 expectEndsWith \$ send echo '# Required by DCA components' >> \${hbaConfig} expectEndsWith \$ send echo 'host dca_db dcaadmin 0.0.0.0/0 md5' >> \${hbaConfig} expectEndsWith \$ send echo 'host ucmdb dcaadmin 0.0.0.0/0 md5' >> \${hbaConfig} expec ... | Hard-coded values present in use constant field |
| Update configFile | Input Variable | timeout | | 5400000 | Hard-coded values present in use constant field |
| Update configFile | Input Variable | readTimeout | | 3600000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | username | | postgres | Hard-coded values present in use constant field |

| | | | | | |
|-------------|----------------|------------------|--|--------------------------------------|---|
| SSH Command | Input Variable | command | | systemctl list-units grep postgresql | Hard-coded values present in use constant field |
| SSH Command | Input Variable | timeout | | 90000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | pty | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | connectTimeout | | 10000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | keepAlive | | 0 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | useGlobalContext | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | username | | postgres | Hard-coded values present in use constant field |
| SSH Command | Input Variable | command | | systemctl stop firewallld | Hard-coded values present in use constant field |
| SSH Command | Input Variable | timeout | | 90000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | pty | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | connectTimeout | | 10000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | keepAlive | | 0 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | useGlobalContext | | false | Hard-coded values present in use constant field |

| | | | | | |
|-------------------|----------------|------------------|--|--|---|
| SSH Command | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | username | | postgres | Hard-coded values present in use constant field |
| SSH Command | Input Variable | command | | systemctl disable firewalld | Hard-coded values present in use constant field |
| SSH Command | Input Variable | timeout | | 90000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | pty | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | connectTimeout | | 10000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | keepAlive | | 0 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | useGlobalContext | | false | Hard-coded values present in use constant field |
| Create configFile | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Create configFile | Input Variable | command | | send sudo su - expectendswith \${username}: send HCMAAdmin+123 expectEndsWith # send echo '### KERNEL TUNING FOR DCA POSTGRESQL ###' > / etc/sysctl.d/90-postgres ql.conf expectEndsWith # send echo " >> /etc/sy sctl.d/90-postgresql.con f expectEndsWith # send echo '# Size of a shared memory segment' >> /e ... | Hard-coded values present in use constant field |
| Create configFile | Input Variable | timeout | | 1500 | Hard-coded values present in use constant field |
| Create configFile | Input Variable | readTimeout | | 1500 | Hard-coded values present in use constant field |

| | | | | | |
|------------------|----------------|------------------|--|---|---|
| SSH Command | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | username | | postgres | Hard-coded values present in use constant field |
| SSH Command | Input Variable | command | | psql -t -P format=unaligned -c 'show hba_file' | Hard-coded values present in use constant field |
| SSH Command | Input Variable | timeout | | 90000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | pty | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | connectTimeout | | 10000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | keepAlive | | 0 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | useGlobalContext | | false | Hard-coded values present in use constant field |
| SSH Shell Logon | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Create Databases | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Create Databases | Input Variable | command | | send su - postgres expectendswith Password: send HCMAAdmin+123 expectEndsWith \$ send psql -U postgres expectEndsWith # send create user hcmadmin login password 'HCMAAdmin+123' inherit; expectEndsWith # send GRANT cdfidmuser to postgres; expectEndsWith # send create database csa with owner=hcmadmin; ex ... | Hard-coded values present in use constant field |
| Create Databases | Input Variable | timeout | | 5400000 | Hard-coded values present in use constant field |

| | | | | | |
|-------------------|----------------|----------------|--|---|---|
| Create Databases | Input Variable | readTimeout | | 3600000 | Hard-coded values present in use constant field |
| Update configFile | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Update configFile | Input Variable | command | | send su - postgres expectendswith Password: send HCMAAdmin+123 expectEndsWith \$ send echo 'hostnoSSL all all 0.0.0.0/0 trust' >> \${hbaConfig} expectEndsWith \$ send sed -e '/max_connectio ns/s/^/#/1' -i \${sqlConfig} expectEndsWith \$ send sed -e '/shared_buffers/s/^/#/1' -i \${sqlConfig} expectEndsWith \$... | Hard-coded values present in use constant field |
| Update configFile | Input Variable | timeout | | 12000 | Hard-coded values present in use constant field |
| Update configFile | Input Variable | readTimeout | | 12000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | username | | postgres | Hard-coded values present in use constant field |
| SSH Command | Input Variable | command | | systemctl list-units grep postgresql | Hard-coded values present in use constant field |
| SSH Command | Input Variable | timeout | | 90000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | pty | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | connectTimeout | | 10000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | keepAlive | | 0 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | closeSession | | false | Hard-coded values present in use constant field |

| | | | | | |
|-------------|----------------|------------------|--|-----------------------------|---|
| SSH Command | Input Variable | useGlobalContext | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | username | | postgres | Hard-coded values present in use constant field |
| SSH Command | Input Variable | command | | systemctl stop firewalld | Hard-coded values present in use constant field |
| SSH Command | Input Variable | timeout | | 90000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | pty | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | connectTimeout | | 10000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | keepAlive | | 0 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | useGlobalContext | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | username | | postgres | Hard-coded values present in use constant field |
| SSH Command | Input Variable | command | | systemctl disable firewalld | Hard-coded values present in use constant field |
| SSH Command | Input Variable | timeout | | 90000 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | pty | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | connectTimeout | | 10000 | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------|----------------|------------------|----------|--|---|
| SSH Command | Input Variable | keepAlive | | 0 | Hard-coded values present in use constant field |
| SSH Command | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| SSH Command | Input Variable | useGlobalContext | | false | Hard-coded values present in use constant field |
| Install Postgres10 | Input Variable | host | host | 16.32.12.61 | Hard-coded values present in use constant field |
| Install Postgres10 | Input Variable | username | username | root | Hard-coded values present in use constant field |
| Configure HCM Postgres | Input Variable | configpath | | /var/lib/pgsql/10/data/pg_hba.conf | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | host | host | mc4t02958.itcs.softwar egrp.net | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | username | | sup_rajeshsingh | Hard-coded values present in use constant field |
| Yum Update all | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Yum Update all | Input Variable | command | | echo \${password} sudo -S yum update -y | Hard-coded values present in use constant field |
| Yum Update all | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Yum Update all | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Yum Update all | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Yum Install postgresql-server | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Yum Install postgresql-server | Input Variable | command | | echo \${password} sudo -S yum install -y postgresql10-server postgresql10 postgresql10-contrib | Hard-coded values present in use constant field |
| Yum Install postgresql-server | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Yum Install postgresql-server | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------------|----------------|----------------|--|--|---|
| Yum Install postgresql-server | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Initialize the DB | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Initialize the DB | Input Variable | command | | echo \${password} sudo -S /usr/pgsql-10/bin/postgresql-10-setup initdb | Hard-coded values present in use constant field |
| Initialize the DB | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Initialize the DB | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Initialize the DB | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | command | | echo \${password} sudo -S systemctl start postgresql-10.service | Hard-coded values present in use constant field |
| Start the DB | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Start the Service at System Startup | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Start the Service at System Startup | Input Variable | command | | echo \${password} sudo -S systemctl enable postgresql-10.service | Hard-coded values present in use constant field |
| Start the Service at System Startup | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Start the Service at System Startup | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Start the Service at System Startup | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | port | | 22 | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|----------------|------|---|---|
| check the Service Status | Input Variable | command | | echo \${password} sudo -S systemctl status postgresql-10.service | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Setup Repo for PG 10 | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Setup Repo for PG 10 | Input Variable | command | | echo \${password} sudo -S yum install -y ht tps://download.postgres ql.org/pub/repos/yum/re porpms/EL-7-x86_64/p gdg-redhat-repo-latest. noarch.rpm | Hard-coded values present in use constant field |
| Setup Repo for PG 10 | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Setup Repo for PG 10 | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Setup Repo for PG 10 | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | host | host | mc4t02958.its.softwar egrp.net | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | username | | sup_rajeshsingh | Hard-coded values present in use constant field |
| Yum Update all | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Yum Update all | Input Variable | command | | echo \${password} sudo -S yum update -y | Hard-coded values present in use constant field |
| Yum Update all | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Yum Update all | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Yum Update all | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------------|----------------|----------------|--|--|---|
| Yum Install postgresql-server | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Yum Install postgresql-server | Input Variable | command | | echo \${password} sudo -S yum install -y postgresql10-server postgresql10 postgresql10-contrib | Hard-coded values present in use constant field |
| Yum Install postgresql-server | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Yum Install postgresql-server | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Yum Install postgresql-server | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Initialize the DB | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Initialize the DB | Input Variable | command | | echo \${password} sudo -S /usr/pgsql-10/bin/postgresql-10-setup initdb | Hard-coded values present in use constant field |
| Initialize the DB | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Initialize the DB | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Initialize the DB | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | command | | echo \${password} sudo -S systemctl start postgresql-10.service | Hard-coded values present in use constant field |
| Start the DB | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Start the Service at System Startup | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Start the Service at System Startup | Input Variable | command | | echo \${password} sudo -S systemctl enable postgresql-10.service | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------------|----------------|----------------|--|--|---|
| Start the Service at System Startup | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Start the Service at System Startup | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Start the Service at System Startup | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | command | | echo \${password} sudo -S systemctl status postgresql-10.service | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Setup Repo for PG 10 | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Setup Repo for PG 10 | Input Variable | command | | echo \${password} sudo -S rpm -Uvh https: //yum.postgresql.org/10 /redhat/rhel-7-x86_64/p gdg-centos10-10-2.noar ch.rpm | Hard-coded values present in use constant field |
| Setup Repo for PG 10 | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Setup Repo for PG 10 | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Setup Repo for PG 10 | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | command | | echo \${password} sudo -S systemctl start postgresql | Hard-coded values present in use constant field |
| Start the DB | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|----------------|--|---|---|
| Start the DB | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | command | | echo \${password} sudo -S systemctl status postgresql | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Sleep for 15 sec | Input Variable | seconds | | 15 | Hard-coded values present in use constant field |
| Loop | Input Variable | count | | 5 | Hard-coded values present in use constant field |
| Loop | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Loop | Input Variable | to | | \${count} | Hard-coded values present in use constant field |
| Loop | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Loop | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Sleep for 15 sec | Input Variable | seconds | | 15 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | command | | echo \${password} sudo -S systemctl start postgresql | Hard-coded values present in use constant field |
| Start the DB | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Start the DB | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------|----------------|----------------|--|---|---|
| Stop the DB | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Stop the DB | Input Variable | command | | echo \${password} sudo -S systemctl stop postgresql | Hard-coded values present in use constant field |
| Stop the DB | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Stop the DB | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Stop the DB | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | command | | echo \${password} sudo -S systemctl status postgresql | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| check the Service Status | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Sleep for 15 sec | Input Variable | seconds | | 15 | Hard-coded values present in use constant field |
| Yum Remove Postgresql | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Yum Remove Postgresql | Input Variable | command | | echo \${password} sudo -S yum remove -y postgresql10.x86_64 po stgresql10-libs.x86_64 postgresql10-contrib.x8 6_64 | Hard-coded values present in use constant field |
| Yum Remove Postgresql | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Yum Remove Postgresql | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Yum Remove Postgresql | Input Variable | connectTimeout | | 300000 | Hard-coded values present in use constant field |
| Remove Postgres Directory | Input Variable | port | | 22 | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------|----------------|--------------------|-----------------------|--|--|
| Remove Postgres Directory | Input Variable | command | | send su - postgres expectendswith Password: send HCMAAdmin+123 expectEndsWith \$ send rm -rf /var/lib/pgsql/10/ | Hard-coded values present in use constant field |
| Remove Postgres Directory | Input Variable | timeout | | 12000 | Hard-coded values present in use constant field |
| Remove Postgres Directory | Input Variable | readTimeout | | 12000 | Hard-coded values present in use constant field |
| SSH Shell Logon | Input Variable | port | | 22 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | provider | | Micro Focus InfoBlox | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Resource Provider Id | Input Variable | provider | provider | Micro Focus InfoBlox | Hard-coded values present in use constant field |
| Get Resource pool Id | Input Variable | providerId | provider_id | 2c92d41d71e9248a017 23afd9f962582 | Input variable name and Assign from values are not identical |
| Get Resource pool Id | Input Variable | providerId | provider_id | 2c92d41d71e9248a017 23afd9f962582 | Hard-coded values present in use constant field |
| Get provider properties | Input Variable | providerId | provider_id | | Input variable name and Assign from values are not identical |
| Create Resource Pool | Input Variable | resource_pool_info | create_resource_pool | | Input variable name and Assign from values are not identical |
| IPAM Get Unused IP Add | Input Variable | subnets | ss | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | resourcePoolID | update_res_pool_id | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | resourceType | | IPV4_ADDRESS | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | availableValue | update_res_pool_count | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | authType | | Basic | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------|----------------|----------------------|----------------------|---|--|
| Update Resource Pool Capacity | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | trustKeystore | trustKeystore | false | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | json | jsonResult | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.[?(@.name=='Houston vCenter')].self | Hard-coded values present in use constant field |
| Get Provider ID | Input Variable | url | | \$(HCM/HCM-API-URL)resource/provider/ | Hard-coded values present in use constant field |
| Get Provider ID | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Provider ID | Input Variable | tlsVersion | | TLSv1.2 | Hard-coded values present in use constant field |
| Get Provider ID | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Hard-coded values present in use constant field |
| Get Provider ID | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Provider ID | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Provider ID | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider ID | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |

| | | | | | |
|--------------------|----------------|---------------------------|----------------|--|--|
| Get Provider ID | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Provider ID | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Provider ID | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Provider ID | Input Variable | username | ipamUsername | HCM-ADMIN-ACCOUNT : USERNAME | Input variable name and Assign from values are not identical |
| Get Provider ID | Input Variable | password | ipamPassword | HCM-ADMIN-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |
| Query Pool Name | Input Variable | json | poolJsonResult | | Input variable name and Assign from values are not identical |
| Query Pool Name | Input Variable | jsonPathQuery | | \$.name | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | url | | \$(HCM/HCM-API-URL)resource/pool/filter | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | tlsVersion | | TLSv1.2 | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256... | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------------|----------------|--------------------------|---------------|--|--|
| Get Resource Pools | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | body | | { "providerId": "\${providerIdResult}" } | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Get Resource Pools | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Query Pool Id | Input Variable | json | jsonForPoolId | | Input variable name and Assign from values are not identical |
| Query Pool Id | Input Variable | jsonPathQuery | | \$.[?(@.name=='\${ss}')] .self | Hard-coded values present in use constant field |
| Get Resource Pool From vCenter | Input Variable | overrideNRAS | | RAS_Win_Path | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------|----------------|------------------------|------------------------|-----------------------|--|
| Update Resource Pool Capacity | Input Variable | resourcePoolID | ssId | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | resourceType | type | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | availableValue | ssSpace | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | resourcePoolID | ssId | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | resourceType | type | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | availableValue | ssMemory | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | resourcePoolID | ssId | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | resourceType | type | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | availableValue | ssCpu | | Input variable name and Assign from values are not identical |
| Update Resource Pool Capacity | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Resource Pool Capacity | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed select Cluster | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|------------------------|------------------------|-----------------------------------|---|
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed select Cluster | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed select Cluster | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed select Cluster | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/ | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------|----------------|--------------------------|------------------------|--|---|
| Create New Resource Pool | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | body | | { "name": "\${ss}", "description": "vCenter Cluster", "enabled": true, "poolReference": "\${ss}", "syncAction": null, "provider": { "@self": "/csa/api/resource/provider/\${providerIdResult}" } } | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Create New Resource Pool | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed select Cluster | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/\${resPoolId}/capacity | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------|----------------|--------------------------|--|---|---|
| Add Resource Type - Storage | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | body | | { "name": "\${ss}", "description": "vCenter Cluster", "ext": { "csa_used_by_csa": 0, "csa_available_to_csa": 0 }, "availability": { "displayName": "Available", "ext": { "csa_name_key": "AVAILABLE" } }, "type": { ... | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Add Resource Type - Storage | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/\${resPoolId}/capacity | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|--------------------------|--|---|---|
| Add Resource Type - CPU | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | body | | { "name": "\${ss}", "description": "vCenter Cluster", "ext": { "csa_used_by_csa": 0, "csa_available_to_csa": 0 }, "availability": { "displayName": "Available", "ext": { "csa_name_key": "AVAILABLE" } }, "type": { ... | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Add Resource Type - CPU | Input Variable | method | | POST | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------|----------------|--------------------------|--|---|---|
| Add Resource Type - Memory | Input Variable | url | | \${HCM/HCM-API-URL}resource/pool/\${resPoolId}/capacity | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------|----------------|------------------------|------------------------|---|--|
| Add Resource Type - Memory | Input Variable | body | | { "name": "\${ss}", "description": "vCenter Cluster", "ext": { "csa_used_by_csa": 0, "csa_available_to_csa": 0 }, "availability": { "displayName": "Available", "ext": { "csa_name_key": "AVAILABLE" } }, "type": { ... | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Add Resource Type - Memory | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed select Cluster | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|---------------------------|----------------|---|--|
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | username | ipamUsername | HCM-ADMIN-ACCOUNT : USERNAME | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | password | ipamPassword | HCM-ADMIN-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | failureMessage | failureMessage | VM - '{vmName}' cancellation failed in HCM SubscriptionId \${subscriptionId}. Please refer to the OO flow for detailed error. | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | | \${run_id} | Hard-coded values present in use constant field |

| | | | | | |
|------------------------|----------------|------------------------|------------------------|---|--|
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | VM - '\${vmName}' cancellation failed in HCM SubscriptionId \${subscriptionId}. Please refer to the OO flow for detailed error. | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | smaxHostname | | \${SMAX/SMAX-HOSTNAME} | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | smaxTenantId | | \${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | comment | | SMAX Request: \${requestId} to Cancel VM '\${vmName}' in HCM SubscriptionId \${subscriptionId} is performed SUCCESSFULLY. | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | smaxHostname | | \${SMAX/SMAX-HOSTNAME} | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | smaxTenantId | | \${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | comment | | SMAX Request: \${requestId} to Cancel VM '\${vmName}' in HCM SubscriptionId \${subscriptionId} has FAILED. | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | smaxRequestId | requestId | | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |

| | | | | | |
|---------------------|----------------|--------------------|----------------------------|---|--|
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | failureMessage | failureMessage1 | | Input variable name and Assign from values are not identical |
| INSERT Request Data | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| INSERT Request Data | Input Variable | Command | DB_Details/SQL_COM MAND | INSERT INTO public."C SA_SUBSCR_REQUE ST"("REQUEST_ID", "SUBSCRIPTION_ID") VALUES ('\${hcmRequestId}', '\${subscriptionId}'); COMMIT; | Hard-coded values present in use constant field |
| INSERT Request Data | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| INSERT Request Data | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| INSERT Request Data | Input Variable | Command | DB_Details/SQL_COM MAND | INSERT INTO public."C SA_SUBSCR_REQUE ST"("REQUEST_ID", "SUBSCRIPTION_ID") VALUES ('\${hcmRequestId}', '\${subscriptionId}'); COMMIT; | Hard-coded values present in use constant field |
| INSERT Request Data | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | smaxRequestId | requestId | | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscr iption/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | SUCCESS | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | SUCCESS | Hard-coded values present in use constant field |

| | | | | | |
|------------------------------|----------------|-------------------------|---------------------|---|--|
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| Resolved : success | Input Variable | subscriptionUUID | | ec4a804a-4003-4a35-8379-f08c537be954 | Hard-coded values present in use constant field |
| Get HCM Authentication Token | Input Variable | tenantName | tenantName | \${HCM/PROVIDER-TENANT-NAME} | Hard-coded values present in use constant field |
| Get Offering | Input Variable | offeringName | offeringName | Micro Focus Compute | Hard-coded values present in use constant field |
| Create Subscription | Input Variable | offeringName | offeringLogicalName | | Input variable name and Assign from values are not identical |
| Create Subscription | Input Variable | catalogName | catalogName | MFI_CATALOG | Hard-coded values present in use constant field |
| Create Subscription | Input Variable | subscriptionName | | Server: SMAX Request \${requestId} | Hard-coded values present in use constant field |
| Create Subscription | Input Variable | subscriptionDescription | | Subscription created from SMAX Service Request \${requestId}. This is owned by \${requestorEmail} | Hard-coded values present in use constant field |
| Create Subscription | Input Variable | action | | ORDER | Hard-coded values present in use constant field |
| Create Subscription | Input Variable | onBehalf | supAccount | | Input variable name and Assign from values are not identical |
| Create Subscription | Input Variable | username | hcmUsername | HCM-SERVICE-ACCOUNT : USERNAME | Input variable name and Assign from values are not identical |
| Create Subscription | Input Variable | password | hcmPassword | HCM-SERVICE-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |

| | | | | | |
|--------------------------|----------------|------------------------|------------------------|--|--|
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to create HCM Server Subscription request | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | smaxRequestId | requestId | | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | failureMessage | failureMessage1 | | Input variable name and Assign from values are not identical |
| Get Supplemental Account | Input Variable | networkType | networkValue | INT | Input variable name and Assign from values are not identical |
| Get Supplemental Account | Input Variable | networkType | networkValue | INT | Hard-coded values present in use constant field |
| Get Supplemental Account | Input Variable | primaryEmail | requestorEmail | | Input variable name and Assign from values are not identical |
| Resolved : success | Input Variable | subscriptionUUID | | ec4a804a-4003-4a35-8379-f08c537be954 | Hard-coded values present in use constant field |

| | | | | | |
|------------------------------|----------------|------------------|------------------------|---|--|
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Get HCM Authentication Token | Input Variable | tenantName | | \${HCM/TENANT-NAME} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | | \${HCM/HCM-API-URL} consumption/v2/instance/\${serviceInstanceId} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | headerNamesList | headerNamesList | Accept,X-Auth-Token | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | headerValuesList | headerValuesList | application/json,\${authToken} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryNamesList | queryNamesList | onBehalf | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryValuesList | supAccount | \${subscriptionOwner} | Input variable name and Assign from values are not identical |
| Http Client Get | Input Variable | queryValuesList | supAccount | \${subscriptionOwner} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | delimiter | delimiter | , | Hard-coded values present in use constant field |
| Trigger Public Action | Input Variable | requestReference | resourceSubscriptionId | | Input variable name and Assign from values are not identical |
| Trigger Public Action | Input Variable | action | actionId | | Input variable name and Assign from values are not identical |
| Trigger Public Action | Input Variable | actionProperty | actionProperty | [] | Hard-coded values present in use constant field |
| Trigger Public Action | Input Variable | onBehalf | supAccount | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | failureMessage | failureMessage | \${constantFailureMessage} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | | \${run_id} | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------|----------------|------------------------|-------------------|---|--|
| Error Handling | Input Variable | constantFailureMessage | | Failed to perform User action due to issue with SMAX/HCM API Queries | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | | Failed to perform User-Actions | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | smaxHostname | | \${SMAX/SMAX-HOSTNAME} | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | smaxTenantId | | \${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | comment | | SMAX Request: \${requestId} to '\${actionName}' for \${vmName} is performed SUCCESSFULLY. | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | smaxHostname | | \${SMAX/SMAX-HOSTNAME} | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | smaxTenantId | | \${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Update Device Comments | Input Variable | comment | | SMAX Request: \${requestId} to '\${actionName}' for \${vmName} has FAILED. | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | svcSubscriptionId | subscriptionId | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | failureMessage | failureMessage | \${constantFailureMessage} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | | Failed to perform User action due to issue with SMAX/HCM API Queries | Hard-coded values present in use constant field |
| Do Nothing With Two Responses | Input Variable | offeringNames | | MICRO FOCUS DEV, Micro Focus MSSQL Database, Micro Focus ORACLE Database, Micro Focus Oracle Database | Hard-coded values present in use constant field |
| Do Nothing With Two Responses | Input Variable | onBehalf | subscriptionOwner | | Input variable name and Assign from values are not identical |

| | | | | | |
|---------------|----------------|----------------------|-----------------|--|--|
| UpdateRequest | Input Variable | smaxRequestId | requestId | | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | failureMessage | failureMessage1 | | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | requestId | | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |

| | | | | | |
|---------------|----------------|----------------------|-----------------|--|--|
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | failureMessage | failureMessage1 | | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | requestId | | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | failureMessage | failureMessage1 | | Input variable name and Assign from values are not identical |

| | | | | | |
|--------------------------|----------------|--------------------|------------------------|---|--|
| INSERT Request Data | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| INSERT Request Data | Input Variable | Command | DB_Details/SQL_COMMAND | INSERT INTO public."C SA_SUBSCR_REQUEST" ("REQUEST_ID", "SUBSCRIPTION_ID") VALUES ('\${hcmRequestId}', '\${subscriptionId}'); COMMIT; | Hard-coded values present in use constant field |
| INSERT Request Data | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| INSERT Request Data | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| INSERT Request Data | Input Variable | Command | DB_Details/SQL_COMMAND | INSERT INTO public."C SA_SUBSCR_REQUEST" ("REQUEST_ID", "SUBSCRIPTION_ID") VALUES ('\${hcmRequestId}', '\${subscriptionId}'); COMMIT; | Hard-coded values present in use constant field |
| INSERT Request Data | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| Get Supplemental Account | Input Variable | networkType | | INT | Hard-coded values present in use constant field |
| Get Supplemental Account | Input Variable | primaryEmail | requestorEmail | | Input variable name and Assign from values are not identical |
| Error : failure | Input Variable | failureMessage | | { "runId": "\${run_id}", "failureMessage": "Public Action Failure: \${failureMessage}" } | Hard-coded values present in use constant field |
| Resolved : success | Input Variable | subscriptionUUID | | ec4a804a-4003-4a35-8 379-f08c537be954 | Hard-coded values present in use constant field |
| Error : failure | Input Variable | failureMessage | | { "runId": "\${run_id}", "failureMessage": "Public Action Failure: \${failureMessage}" } | Hard-coded values present in use constant field |
| Error : failure | Input Variable | failureMessage | | { "runId": "\${run_id}", "failureMessage": "Public Action Failure: \${failureMessage}" } | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | field | field | \$.status | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 60 | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------|----------------|----------------------|----------------------|--|--|
| Get Service Request Details | Input Variable | url | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HC MURL)/csa/api/service/mpp-request/\${requestId} | Hard-coded values present in use constant field |
| Get Service Request Details | Input Variable | timeout | connectTimeout | | Input variable name and Assign from values are not identical |
| Get Service Request Details | Input Variable | followRedirects | followRedirects | true | Hard-coded values present in use constant field |
| Get Service Request Details | Input Variable | proxy | proxyHost | | Input variable name and Assign from values are not identical |
| Get Service Request Details | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Get Service Request Details | Input Variable | headerNamesList | | Accept | Hard-coded values present in use constant field |
| Get Service Request Details | Input Variable | headerValuesList | | application/json | Hard-coded values present in use constant field |
| Get Service Request Details | Input Variable | delimiter | delimiter | , | Hard-coded values present in use constant field |
| Get Service Request Details | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Get Service Request Details | Input Variable | password | codarpassword | HCM Credentials : PASSWORD | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \$(smaxReqId) | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \$(smaxReqId) | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HC MConsumerURL)subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \$(smaxTenantId) | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \$(smaxTenantId) | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Input variable name and Assign from values are not identical |

| | | | | | |
|--------------------------|----------------|---------------------------|-----------------|--|--|
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | failureMessage | failureMessage1 | | Input variable name and Assign from values are not identical |
| Get Subscription Details | Input Variable | url | | \${csaApiUrl}service/subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | headers | | Accept:application/json | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | method | | GET | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|----------------------|----------------|--|--|
| Get Subscription Details | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | INPROGRESS | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | INPROGRESS | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| Filter Subscription Id | Input Variable | json | | \${requestDetails} | Hard-coded values present in use constant field |
| Filter Subscription Id | Input Variable | jsonPathQuery | | subscription.id | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------|----------------|----------------------|------------------------|--|--|
| Post FailureMessage to SMAX | Input Variable | subscriptionID | subscriptionId | | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | | SUCCESS | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| GET SubscriptionId | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| GET SubscriptionId | Input Variable | Command | DB_Details/SQL_COMMAND | SELECT "SUBSCRIPTION_ID" FROM public."CSA_SUBSCR_REQUEST" WHERE "REQUEST_ID" = '\${requestId}'; | Hard-coded values present in use constant field |
| GET SubscriptionId | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |

| | | | | | |
|---------------|----------------|----------------------|----------------|--|--|
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | INPROGRESS | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | INPROGRESS | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------|----------------|----------------------|-----------------|--|--|
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | serviceStatus | FailedStatus | FAILURE | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | failureMessage | failureMessage1 | | Input variable name and Assign from values are not identical |
| Post FailureMessage to SMAX | Input Variable | subscriptionID | subscriptionId | | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Hard-coded values present in use constant field |

| | | | | | |
|---------------|----------------|----------------------|----------------|--|--|
| UpdateRequest | Input Variable | serviceStatus | | SUCCESS | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | subURL | | \${Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL}subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | | SUCCESS | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |

| | | | | | |
|---------------|----------------|----------------------|-----------------|--|--|
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | smaxRequestId | smaxReqId | \${smaxReqId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | subURL | | \$(Integrations/Micro Focus/Service Management Automation X/HCM/HCMConsumerURL)subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Input variable name and Assign from values are not identical |
| UpdateRequest | Input Variable | tenantId | smaxTenantId | \${smaxTenantId} | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | serviceStatus | | FAILURE | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| UpdateRequest | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| JSON Path | Input Variable | jsonPathQuery | | \$.components..properties.[?(@.name=="FailureMessage")].value | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | InstanceDetails | | Input variable name and Assign from values are not identical |
| Http Client | Input Variable | url | url | \$(HCM/HCM-CSA-URL)api/consumption/v2/instance/\${InstanceId}?onBehalf=\${supAccount} | Hard-coded values present in use constant field |

| | | | | | |
|-------------|----------------|---------------------------|--|------------------------|---|
| Http Client | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | kerberosSkipPortForLookup | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | headers | | X-Auth-Token:\${Token} | Hard-coded values present in use constant field |
| Http Client | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Http Client | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------------|----------------|-------------------------------|-----------------|---|--|
| Http Client | Input Variable | multipartBodiesContent Type | | text/plain; charset=ISO-8859-1 | Hard-coded values present in use constant field |
| Http Client | Input Variable | multipartValuesAreURL Encoded | | false | Hard-coded values present in use constant field |
| Http Client | Input Variable | multipartFilesContentTy pe | | application/octet-stream | Hard-coded values present in use constant field |
| Http Client | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Failure Message From Array | Input Variable | array | failureInfo | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.components[?(@.status=="\${failureComponentStatus}")].properties.[?(@.name=="FailureMessage")].value | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | InstanceDetails | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | smaxHostname | smaxHostname | \${SMAX/SMAX-HOSTNAME} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | smaxTenantId | smaxTenantId | \${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | requestorId | requestorId | 13129 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | globalId | globalId | 4ec58e5178247ec09eb35b840ad2322f | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | hostname | hostname | pso-12-92 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | environment | environment | Dev | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | osType | osType | Unix | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | assetModel | assetModel | 468041 | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | sawUrl | sawUrl | \${smaxHostname}/auth/authentication-endpoint/authenticate/login?TENANTID=\${smaxTenantId} | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | username | smaxUsername | | Input variable name and Assign from values are not identical |

| | | | | | |
|---------------|----------------|---------------------|---------------------|---|--|
| Get SSO Token | Input Variable | password | smaxPassword | | Input variable name and Assign from values are not identical |
| Create Entity | Input Variable | sawUrl | | https://\${smaxHostname} | Hard-coded values present in use constant field |
| Create Entity | Input Variable | tenantId | | \${smaxTenantId} | Hard-coded values present in use constant field |
| Create Entity | Input Variable | inputJSON | inputJSON | { "entity_type": "Device", "properties": { "SubType": "Server", "HostName": "\${hostname}" , "GlobalId": "\${globalId}", "OwnedByPerson": "\${requestorId}", "VirtualDevice": "true", "HCMSubscriptionId_c": "\${subscriptionId}", "NetworkType_c ... | Hard-coded values present in use constant field |
| Create Entity | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Create Entity | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| Create Entity | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| Create Entity | Input Variable | headers | headers | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${tenantId} | Hard-coded values present in use constant field |
| Create Entity | Input Variable | requestCharacterSet | requestCharacterSet | ISO-8859-1 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | subscriberId | subscriberId | 13129 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | subscriptionId | subscriptionId | 2c92d44d726e4b960172841e084f3bcf | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | cild | cild | 4ec58e5178247ec09eb35b840ad2322f | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | hostname | hostname | pso-12-92 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | requestId | requestId | 495452 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | serviceOfferingId | serviceOfferingId | 492262 | Hard-coded values present in use constant field |

| | | | | | |
|----------------|----------------|----------------------|----------------------|---|---|
| Flow Inputs | Input Variable | serviceDefinitionId | serviceDefinitionId | 491864 | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | sawUrl | sawUrl | \${SMAX/SP_SMAX_Hostname}/auth/authentication-endpoint/authenticate/login?TENANTID=\${SMAX/SP_SMAX_Tenant_Id} | Hard-coded values present in use constant field |
| Create Entity | Input Variable | sawUrl | | https://\${SMAX/SMAX-HOSTNAME} | Hard-coded values present in use constant field |
| Create Entity | Input Variable | tenantId | | \${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Create Entity | Input Variable | inputJSON | | { "entity_type": "Subscription", "properties": { "DisplayLabel": "\${upn} new \${hostname}", "Description" : "this entity is subscribed to the requestor", "SubscribedToDevice": "\${DeviceId}", "Subscriber" : "\${subscriberId}", "StartDate": \${startDate}, "Status": "Active", "PhaseId" : " ... | Hard-coded values present in use constant field |
| Create Entity | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Create Entity | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Create Entity | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Create Entity | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Query Entities | Input Variable | url | | https://\${SMAX/SMAX-HOSTNAME}/rest/\${SMAX/SMAX-TENANT-ID}/ems/Device | Hard-coded values present in use constant field |
| Query Entities | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Query Entities | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Query Entities | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |

| | | | | | |
|----------------|----------------|---------------------------|---------------------------|---|--|
| Query Entities | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| Query Entities | Input Variable | contentType | contentType | application/json | Hard-coded values present in use constant field |
| Query Entities | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${tenantId} | Hard-coded values present in use constant field |
| Query Entities | Input Variable | requestCharacterSet | requestCharacterSet | UTF-8 | Hard-coded values present in use constant field |
| Query Entities | Input Variable | responseCharacterSet | | UTF-8 | Hard-coded values present in use constant field |
| Query Entities | Input Variable | queryParams | queryParams | layout=id&size;=5&skip;=0&filter;=GlobalId+eq+'\${cild}' | Hard-coded values present in use constant field |
| Query Entities | Input Variable | queryParamsAreURLEncoded | queryParamsAreURLEncoded | false | Hard-coded values present in use constant field |
| Query Entities | Input Variable | queryParamsAreFormEncoded | queryParamsAreFormEncoded | false | Hard-coded values present in use constant field |
| Create Device | Input Variable | globalId | cild | | Input variable name and Assign from values are not identical |
| Create Device | Input Variable | requestorId | subscriberId | | Input variable name and Assign from values are not identical |
| Get SSO Token | Input Variable | sawUrl | sawUrl | \${SMAX/SMAX-HOSTNAME}/auth/authentication-endpoint/authenticate/login?TENANTID=\${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Get Entity | Input Variable | sawUrl | | https://\${SMAX/SMAX-HOSTNAME} | Hard-coded values present in use constant field |
| Get Entity | Input Variable | tenantId | | \${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Get Entity | Input Variable | entityType | | Person | Hard-coded values present in use constant field |
| Get Entity | Input Variable | entityId | subscriberId | | Input variable name and Assign from values are not identical |
| Get Entity | Input Variable | fields | | Name,Id,Upn | Hard-coded values present in use constant field |
| Get Entity | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|----------------------|------------|---|--|
| Get Entity | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Entity | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Get Entity | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${tenantId} | Hard-coded values present in use constant field |
| Get Value from Object | Input Variable | key | | properties.Upn | Hard-coded values present in use constant field |
| Get Value from Object | Input Variable | object | entityJSON | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | sawUrl | | https://\${SMAX/SMAX-HOSTNAME}/auth/authentication-endpoint/authenticate/login?TENANTID=\${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | sawUrl | | https://\${SMAX/SMAX-HOSTNAME}/auth/authentication-endpoint/authenticate/login?TENANTID=\${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 5 | Hard-coded values present in use constant field |
| Counter | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Counter | Input Variable | to | | 2 | Hard-coded values present in use constant field |
| Counter | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Counter | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | sawUrl | sawUrl | \${SMAX/SMAX-HOSTNAME}/auth/authentication-endpoint/authenticate/login?TENANTID=\${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | url | | https://\${SMAX/SMAX-HOSTNAME}/rest/\${SMAX/SMAX-TENANT-ID}/ems/Person | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | method | | GET | Hard-coded values present in use constant field |

| | | | | | |
|----------------|----------------|------------------------|------------------------|---|--|
| Get EMS Entity | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | connectionsMaxPerRoute | connectionsMaxPerRoute | 2 | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | connectionsMaxTotal | connectionsMaxTotal | 20 | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | followRedirects | followRedirects | true | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | headers | headers | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${tenantId} | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | queryParams | queryParams | filter=(Email startswith ('\${smaxEmail}'))&layout;=Id | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | resultJSON | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.entities[0].properties.Id | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | smaxUsername | smaxUsername | mithila.soppimath@microfocus.com | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | sawUrl | sawUrl | \${SMAX/SMAX-HOSTNAME}/auth/authentication-endpoint/authenticate/login?TENANTID=\${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | url | | https://\${SMAX/SMAX-HOSTNAME}/rest/\${SMAX/SMAX-TENANT-ID}/ems/Person | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | method | | GET | Hard-coded values present in use constant field |

| | | | | | |
|------------------------------|----------------|------------------------|------------------------|--|--|
| Get EMS Entity | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | connectionsMaxPerRoute | connectionsMaxPerRoute | 2 | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | connectionsMaxTotal | connectionsMaxTotal | 20 | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | followRedirects | followRedirects | true | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | headers | headers | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${tenantId} | Hard-coded values present in use constant field |
| Get EMS Entity | Input Variable | queryParams | queryParams | filter=(Upn startswith ('\${smaxUsername}'))&layout;=Id | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | resultJSON | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.entities[0].properties.Id | Hard-coded values present in use constant field |
| Get HCM Authentication Token | Input Variable | tenantName | | \${HCM/TENANT-NAME} | Hard-coded values present in use constant field |
| Component Details | Input Variable | Token | authToken | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | smaxHostname | smaxHostname | \${SMAX/SMAX-HOSTNAME} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | smaxTenantId | smaxTenantId | \${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |

| | | | | | |
|-----------------|----------------|---------------------------|--------------|---|--|
| Get SSO Token | Input Variable | sawUrl | sawUrl | \${smaxHostname}/auth/authentication-endpoint/authenticate/login?TENANTID=\${smaxTenantId} | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | username | smaxUsername | | Input variable name and Assign from values are not identical |
| Get SSO Token | Input Variable | password | smaxPassword | | Input variable name and Assign from values are not identical |
| Update Entities | Input Variable | sawUrl | | https://\${smaxHostname} | Hard-coded values present in use constant field |
| Update Entities | Input Variable | tenantId | | \${smaxTenantId} | Hard-coded values present in use constant field |
| Update Entities | Input Variable | inputJSON | | { "entity_type":"Device", "properties":{ "Id":"\${entityId}", "PhaseId":"pRetire" } } | Hard-coded values present in use constant field |
| Update Entities | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Entities | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Update Entities | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Update Entities | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Update Entities | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${tenantId} | Hard-coded values present in use constant field |
| Update Entities | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Http Client | Input Variable | url | url | \${HCM/HCM-CSA-URL}api/consumption/v2/subscription/\${subscriptionID}?onBehalf=\${supAccount} | Hard-coded values present in use constant field |
| Http Client | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | kerberosSkipPortForLookup | | true | Hard-coded values present in use constant field |

| | | | | | |
|-------------|----------------|------------------------------|--|--------------------------------|---|
| Http Client | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | headers | | X-AUTH-Token:\${Token} | Hard-coded values present in use constant field |
| Http Client | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Http Client | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Http Client | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Http Client | Input Variable | multipartBodiesContentType | | text/plain; charset=ISO-8859-1 | Hard-coded values present in use constant field |
| Http Client | Input Variable | multipartValuesAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client | Input Variable | multipartFilesContentType | | application/octet-stream | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|---------------|----------------------|---|--|
| Http Client | Input Variable | method | | GET | Hard-coded values present in use constant field |
| JSON Path - Instance ID | Input Variable | jsonPathQuery | | \$.instanceId | Hard-coded values present in use constant field |
| JSON Path - Instance ID | Input Variable | json | subscriptionDetails | | Input variable name and Assign from values are not identical |
| JSON Path - UserID | Input Variable | jsonPathQuery | | \$.ownerUid | Hard-coded values present in use constant field |
| JSON Path - UserID | Input Variable | json | subscriptionDetails | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | smaxHostname | smaxHostname | \${SMAX/SMAX-HOSTNAME} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | smaxTenantId | smaxTenantId | \${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | sawUrl | sawUrl | \${smaxHostname}/auth/authentication-endpoint/authenticate/login?TENANTID=\${smaxTenantId} | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | username | smaxUsername | | Input variable name and Assign from values are not identical |
| Get SSO Token | Input Variable | password | smaxPassword | | Input variable name and Assign from values are not identical |
| Http Client Post Raw | Input Variable | url | | https://\${smaxHostname}/rest/\${smaxTenantId}/collaboration/comments/Device/\${entityId} | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | body | | { "IsSystem": false, "Body": "\${comment}", "AttachmentIds": [], "PrivacyType": "PUBLIC", "Submitter": { "UserId": \${userId} }, "ActualInterface": "API", "CommentFrom": "User", "CommentTo": "", "FunctionalPurpose": "StatusUpdate", "Media": "Unknown", "PersonParticipant": "", "CompanyVe ... | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | proxyPort | SMAX/SMAX-PROXY-PORT | 8080 | Hard-coded values present in use constant field |

| | | | | | |
|----------------------|----------------|------------------------|------------------------|--|---|
| Http Client Post Raw | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | connectionsMaxPerRoute | connectionsMaxPerRoute | 2 | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | connectionsMaxTotal | connectionsMaxTotal | 20 | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${smaxTenantId} | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | requestCharacterSet | requestCharacterSet | ISO-8859-1 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |

| | | | | | |
|----------------|----------------|------------------------|----------------------|---|--|
| Get SSO Token | Input Variable | sawUrl | | \${Integrations/Micro Focus/Service Management Automation X/SMAX/S MAXBaseURL}\${Integrations/Micro Focus/Service Management Automation X/SMAX/S MAXLoginURI}?TENANTID=\${tenantId} | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | proxyPort | proxyPort | 8080 | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | trustAllRoots | trustAllRoots | false | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | x509HostnameVerifier | x509HostnameVerifier | strict | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | requestCharacterSet | requestCharacterSet | ISO-8859-1 | Hard-coded values present in use constant field |
| POST operation | Input Variable | url | | \${Integrations/Micro Focus/Service Management Automation X/SMAX/S MAXBaseURL}/rest/\${tenantId}/ems/bulk | Hard-coded values present in use constant field |
| POST operation | Input Variable | username | csaUsername | | Input variable name and Assign from values are not identical |
| POST operation | Input Variable | password | csaPassword | | Input variable name and Assign from values are not identical |
| POST operation | Input Variable | authType | | anonymous | Hard-coded values present in use constant field |

| | | | | | |
|----------------|----------------|----------------------|----------------------|--|--|
| POST operation | Input Variable | timeout | connectTimeout | | Input variable name and Assign from values are not identical |
| POST operation | Input Variable | proxy | proxyHost | | Input variable name and Assign from values are not identical |
| POST operation | Input Variable | encodeURL | | false | Hard-coded values present in use constant field |
| POST operation | Input Variable | string | customString | { "entities": [{ "entity_type": "Request", "properties": { "Id": "\${smaxRequestId}", "H CMSubscriptionStatus_ c": "\${serviceStatus}", " HCMSubscriptionLink_c ": "\${subURL}", "HCMFa ilureMessage_c": \${failur eMessage} } }], "operation": "UPDATE" } | Input variable name and Assign from values are not identical |
| POST operation | Input Variable | string | customString | { "entities": [{ "entity_type": "Request", "properties": { "Id": "\${smaxRequestId}", "H CMSubscriptionStatus_ c": "\${serviceStatus}", " HCMSubscriptionLink_c ": "\${subURL}", "HCMFa ilureMessage_c": \${failur eMessage} } }], "operation": "UPDATE" } | Hard-coded values present in use constant field |
| POST operation | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| POST operation | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| POST operation | Input Variable | headerNamesList | | Accept,Content-Type,C ookie | Hard-coded values present in use constant field |
| POST operation | Input Variable | headerValuesList | | application/json,applicat ion/json,LWSSO_COO KIE_KEY=\${ssoTokenR esult} | Hard-coded values present in use constant field |
| POST operation | Input Variable | delimiter | | , | Hard-coded values present in use constant field |
| POST operation | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | smaxHostname | smaxHostname | \${SMAX/SMAX-HOSTN AME} | Hard-coded values present in use constant field |

| | | | | | |
|----------------------|----------------|----------------------|----------------------|---|--|
| Flow Inputs | Input Variable | smaxTenantId | smaxTenantId | \${SMAX/SMAX-TENANT-ID} | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | sawUrl | sawUrl | \${smaxHostname}/auth/authentication-endpoint/authenticate/login?TENANTID=\${smaxTenantId} | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | username | smaxUsername | | Input variable name and Assign from values are not identical |
| Get SSO Token | Input Variable | password | smaxPassword | | Input variable name and Assign from values are not identical |
| Http Client Post Raw | Input Variable | url | | https://\${smaxHostname}/rest/\${smaxTenantId}/collaboration/comments/SystemElement/\${entityId} | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | body | | { "IsSystem": false, "Body": "\${comment}", "AttachmentIds": [], "PrivacyType": "PUBLIC", "Submitter": { "UserId": \${userId} }, "ActualInterface": "API", "CommentFrom": "User", "CommentTo": "", "FunctionalPurpose": "StatusUpdate", "Media": "Unknown", "PersonParticipant": "", "CompanyVe ... | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | proxyPort | SMAX/SMAX-PROXY-PORT | 8080 | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | connectTimeout | connectTimeout | 0 | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | socketTimeout | socketTimeout | 0 | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |

| | | | | | |
|----------------------|----------------|--------------------------|------------------------|---|---|
| Http Client Post Raw | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | connectionsMaxPerRoute | connectionsMaxPerRoute | 2 | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | connectionsMaxTotal | connectionsMaxTotal | 20 | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken}; TENANTID=\${smaxTenantId} | Hard-coded values present in use constant field |
| Http Client Post Raw | Input Variable | requestCharacterSet | requestCharacterSet | ISO-8859-1 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | cmdbHost | cmdbHost | mc4w01852.itcs.softwaregrp.net | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | cmdbPort | cmdbPort | 8443 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | username | username | hcm_integration | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | cmdbVersion | cmdbVersion | 11 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | url | | \${protocol}://\${cmdbHost}:\${cmdbPort}/rest-api/dataModel | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | authType | | anonymous | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | headers | | Authorization: Bearer \${authToken} | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |

| | | | | | |
|------------------|----------------|------------------------------|-------------|--|--|
| Http Client Post | Input Variable | body | payLoad | | Input variable name and Assign from values are not identical |
| Http Client Post | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | cmdbHost | cmdbHost | mc4w01852.itcs.softwar egrp.net | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | cmdbPort | cmdbPort | 8443 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | username | username | hcm_integration | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | cmdbVersion | cmdbVersion | 11 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | url | | \${protocol}://\${cmdbHo st}:\${cmdbPort}/rest-api /authenticate | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | authType | | anonymous | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | queryParamsAreURLEn coded | | false | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | formParamsAreURLEnc oded | | false | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | body | | { "username": "\${username}", "password": "\${password}", "clientContext": "1" } | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | method | | POST | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------------|----------------|---------------------------------|---------------------|---|--|
| Get Value from Object | Input Variable | key | | token | Hard-coded values present in use constant field |
| Get Value from Object | Input Variable | object | returnResult | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | cmdbHost | cmdbHost | mc4w01852.itcs.softwar egrp.net | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | cmdbPort | cmdbPort | 8443 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | username | username | hcm_integration | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | cmdbVersion | cmdbVersion | 11 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | objectType | objectType | ip_service_endpoint | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | conditionAttributes | conditionAttributes | name,display_label,ipse rver_address | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | conditionOperators | conditionOperators | like,like,like | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | conditionValues | instanceID | 15.120.139.147:80,15.1 20.139.147:80,15.120.1 39.147:80 | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | conditionValues | instanceID | 15.120.139.147:80,15.1 20.139.147:80,15.120.1 39.147:80 | Hard-coded values present in use constant field |
| Get Filtered Object List by Type | Input Variable | objectType | objectType | Business_application | Hard-coded values present in use constant field |
| Get Filtered Object List by Type | Input Variable | certificateVerifier | | true | Hard-coded values present in use constant field |
| Get Filtered Object List by Type | Input Variable | certificateHostnameVeri fier | | true | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | host | | mc4t02911.itcs.softwar egrp.net | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | coreHost | | mc4t02911.itcs.softwar egrp.net | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | corePort | | 443 | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|---------------|-------------------------|---|--|
| Flow Inputs | Input Variable | coreProtocol | | https | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | coreUsername | | admin | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | corePassword | | opsware_01 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | coreVersion | coreVersion | sas107 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | script | Port_check_script_Linux | Add IPAM Backup NIC | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | script | Port_check_script_Linux | Add IPAM Backup NIC | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | args | args | -t hcmmc4t06134 -s "ConfigureBackupInterface_LINUX" -a "15.120.240.241 255.255.248.0" -z 15 | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | scriptToRun | script | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHosts | host | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | scriptTimeout | | 300 | Hard-coded values present in use constant field |
| Get Script Job Result | Input Variable | jobId | jobid | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | jobid | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | timeout | | 300000 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | coreVersion | coreVersion | sas107 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | script | Port_check_script_Linux | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | scriptToRun | script | | Input variable name and Assign from values are not identical |

| | | | | | |
|-----------------------|----------------|----------------------|--------------|--|--|
| Start Server Script | Input Variable | targetHosts | host | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | scriptTimeout | | 600 | Hard-coded values present in use constant field |
| Get Script Job Result | Input Variable | jobId | jobid | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | jobid | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | timeout | | 700000 | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | | \${HCM/HCM-REST-URL}artifact/\${parentComponentId} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParams | | userIdentifier=\${userIdentifier}&scope;=Baseplusone | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|---------------------------|------------------|---|--|
| Http Client Get | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Component Properties | Input Variable | componentId | childComponentId | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | url | | \$(HCM/HCM-REST-URL)artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|---------------------------|----------------------|------------------------------|--|
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | username | ipamUsername | HCM-ADMIN-ACCOUNT : USERNAME | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | password | ipamPassword | HCM-ADMIN-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |
| Find Network | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Find Network | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Find Network | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Get Next Available IP | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Get Next Available IP | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Get Next Available IP | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | ipAddress | nextIp | | Input variable name and Assign from values are not identical |

| | | | | | |
|-------------------------|----------------|----------------------|----------------------|---|--|
| Add Host Record | Input Variable | hostName | hostname | | Input variable name and Assign from values are not identical |
| Add Host Record | Input Variable | domain | zone | | Input variable name and Assign from values are not identical |
| Find Network | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Find Network | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Find Network | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Get Next Available IP | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Get Next Available IP | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Get Next Available IP | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Add Host Record | Input Variable | ipAddress | nextIp | | Input variable name and Assign from values are not identical |
| Add Host Record | Input Variable | hostName | hostname | | Input variable name and Assign from values are not identical |
| Add Host Record | Input Variable | domain | zone | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | url | | \$(HCM/HCM-REST-URL)/artifact/\${providerId}?userIdentifier=\${userIdentifier}&scope;=view&view;=propertyinfo | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | authType | | Basic | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|---------------------------|--------------|---|--|
| Get Provider Properties | Input Variable | tlsVersion | | TLSv1.2 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | allowedCyphers | | TLS_DHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_DHE_RSA_WITH_AES_256_CBC_SHA256,TLS_DHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 ... | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Provider Properties | Input Variable | username | ipamUsername | HCM-ADMIN-ACCOUNT : USERNAME | Input variable name and Assign from values are not identical |
| Get Provider Properties | Input Variable | password | ipamPassword | HCM-ADMIN-ACCOUNT : PASSWORD | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | host | host | \${vCenter/VCENTER-HOSTNAME} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | datacenter | | PSO | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|--------------|-------------------|--|--|
| List Datacenters | Input Variable | port | | 443 | Hard-coded values present in use constant field |
| List Datacenters | Input Variable | protocol | | https | Hard-coded values present in use constant field |
| List Datacenters | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| List Datacenters | Input Variable | propsType | | Datacenter | Hard-coded values present in use constant field |
| Array Iterator | Input Variable | array | datacenterArray | | Input variable name and Assign from values are not identical |
| Get Value from Object | Input Variable | key | | value | Hard-coded values present in use constant field |
| Get Value from Object | Input Variable | object | datacenterElement | | Input variable name and Assign from values are not identical |
| Get Value from Object | Input Variable | key | | name | Hard-coded values present in use constant field |
| Get Value from Object | Input Variable | object | datacenterElement | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | diskSizeGB | diskSizeGB | 300 | Hard-coded values present in use constant field |
| Get Cluster Internal ID | Input Variable | script | script | C:\Get_Cluster_Id.ps1 ' \${selectedClusterName ' '{vhost}' ' \${vusername}' ' \${vpassword}' | Hard-coded values present in use constant field |
| Get Cluster Internal ID | Input Variable | host | | localhost | Hard-coded values present in use constant field |
| Get Datastores Freespace | Input Variable | host | vhost | | Input variable name and Assign from values are not identical |
| Get Datastores Freespace | Input Variable | user | vusername | | Input variable name and Assign from values are not identical |
| Get Datastores Freespace | Input Variable | password | vpassword | | Input variable name and Assign from values are not identical |
| Get Datastores Freespace | Input Variable | propsRootObj | clusterId | | Input variable name and Assign from values are not identical |

| | | | | | |
|------------------------------|----------------|------------------|---------------------|------------------------------|--|
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | diskSizeGB | diskSizeGB | 300 | Hard-coded values present in use constant field |
| Simple Search:Get Cluster ID | Input Variable | host | vhost | | Input variable name and Assign from values are not identical |
| Simple Search:Get Cluster ID | Input Variable | user | vusername | | Input variable name and Assign from values are not identical |
| Simple Search:Get Cluster ID | Input Variable | password | vpassword | | Input variable name and Assign from values are not identical |
| Simple Search:Get Cluster ID | Input Variable | port | vport | | Input variable name and Assign from values are not identical |
| Simple Search:Get Cluster ID | Input Variable | protocol | vprotocol | https | Input variable name and Assign from values are not identical |
| Simple Search:Get Cluster ID | Input Variable | protocol | vprotocol | https | Hard-coded values present in use constant field |
| Simple Search:Get Cluster ID | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Simple Search:Get Cluster ID | Input Variable | propsType | | ClusterComputeResource | Hard-coded values present in use constant field |
| Simple Search:Get Cluster ID | Input Variable | nameToMatch | selectedClusterName | | Input variable name and Assign from values are not identical |
| Get Datastores Freespace | Input Variable | host | vhost | | Input variable name and Assign from values are not identical |
| Get Datastores Freespace | Input Variable | user | vusername | | Input variable name and Assign from values are not identical |
| Get Datastores Freespace | Input Variable | password | vpassword | | Input variable name and Assign from values are not identical |
| Get Datastores Freespace | Input Variable | propsRootObj | clusterId | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | host | | \${vCenter/VCENTER-HOSTNAME} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | diskSizeGB | | 300 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | propsRootObjType | propsRootObjType | HostSystem | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------------|----------------|------------------|----------------|------------------------------|--|
| Flow Inputs | Input Variable | propsRootObj | propsRootObj | host-5054 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | host | host | \${vCenter/VCENTER-HOSTNAME} | Hard-coded values present in use constant field |
| Get Datastores With Info | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get Datastores With Info | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Datastores With Info | Input Variable | closeSession | closeSession | true | Hard-coded values present in use constant field |
| Get Datastores With Info | Input Variable | propsType | propsType | Datastore | Hard-coded values present in use constant field |
| Get Datastores With Info | Input Variable | propsPathset | propsPathset | info.name,info.freeSpace | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | vCenterHost | vCenterHost | \${vCenter/VCENTER-HOSTNAME} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | virtualMachine | virtualMachine | vm-12634 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | disk1SizeGB | disk1SizeGB | 15 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | disk2SizeGB | disk2SizeGB | 18 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | ipAddress | ipAddress | 16.32.12.84 | Hard-coded values present in use constant field |
| Get VM Information | Input Variable | vCenterHost | vCenterHost | \${vCenter/VCENTER-HOSTNAME} | Hard-coded values present in use constant field |
| Get VM Information | Input Variable | diskSizeGB | disk1SizeGB | | Input variable name and Assign from values are not identical |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterProtocol | | https | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterPort | | 443 | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | vmIdentifierType | | vmid | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------------|----------------|------------------|------------------|------------------------------|--|
| vCenter Add Disk To Virtual Machine | Input Variable | dataStore | datastoreName | | Input variable name and Assign from values are not identical |
| vCenter Add Disk To Virtual Machine | Input Variable | vmDiskSizeUnit | | GB | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | diskMode | | persistent | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | thinProvision | | true | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | eagerZero | | false | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | vmDatacenter | datacenter | | Input variable name and Assign from values are not identical |
| vCenter Add Disk To Virtual Machine | Input Variable | vmDiskSize | diskSizeGB | | Input variable name and Assign from values are not identical |
| Get Available Datastore | Input Variable | host | vCenterHost | \${vCenter/VCENTER-HOSTNAME} | Input variable name and Assign from values are not identical |
| Get Available Datastore | Input Variable | host | vCenterHost | \${vCenter/VCENTER-HOSTNAME} | Hard-coded values present in use constant field |
| Get Available Datastore | Input Variable | user | vCenterUsername | | Input variable name and Assign from values are not identical |
| Get Available Datastore | Input Variable | password | vCenterPassword | | Input variable name and Assign from values are not identical |
| Get Available Datastore | Input Variable | propsRootObjType | propsRootObjType | HostSystem | Hard-coded values present in use constant field |
| Get Available Datastore | Input Variable | propsRootObj | esxHost | | Input variable name and Assign from values are not identical |
| Reboot VM | Input Variable | vCenterHost | vCenterHost | \${vCenter/VCENTER-HOSTNAME} | Hard-coded values present in use constant field |
| Counter | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Counter | Input Variable | to | | 1 | Hard-coded values present in use constant field |
| Counter | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Counter | Input Variable | reset | | false | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------------|----------------|------------------|---------------|--|--|
| Counter | Input Variable | diskSizeGB | disk2SizeGB | | Input variable name and Assign from values are not identical |
| Add Windows Disk | Input Variable | virtualMachine | ipAddress | | Input variable name and Assign from values are not identical |
| Add Windows Disk | Input Variable | command | | echo SELECT DISK 1 > \${vCenter/WINDOWS-DISKPART-LOCATION} & echo ATTRIBUTES DISK CLEAR READONLY >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo ONLINE DISK >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo CONVERT MBR >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo CREATE PARTITION PRIMARY >> \${vCenter/ ... | Hard-coded values present in use constant field |
| Counter | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Counter | Input Variable | to | | 20 | Hard-coded values present in use constant field |
| Counter | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Counter | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 15 | Hard-coded values present in use constant field |
| Get VM Information | Input Variable | vCenterHost | vCenterHost | \${vCenter/VCENTER-HOSTNAME} | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterProtocol | | https | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | vCenterPort | | 443 | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | vmIdentifierType | | vmid | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | dataStore | datastoreName | | Input variable name and Assign from values are not identical |

| | | | | | |
|-------------------------------------|----------------|------------------|------------------|------------------------------|--|
| vCenter Add Disk To Virtual Machine | Input Variable | vmDiskSizeUnit | | GB | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | diskMode | | persistent | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | thinProvision | | true | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | eagerZero | | false | Hard-coded values present in use constant field |
| vCenter Add Disk To Virtual Machine | Input Variable | vmDatacenter | datacenter | | Input variable name and Assign from values are not identical |
| vCenter Add Disk To Virtual Machine | Input Variable | vmDiskSize | diskSizeGB | | Input variable name and Assign from values are not identical |
| Get Available Datastore | Input Variable | host | vCenterHost | \${vCenter/VCENTER-HOSTNAME} | Input variable name and Assign from values are not identical |
| Get Available Datastore | Input Variable | host | vCenterHost | \${vCenter/VCENTER-HOSTNAME} | Hard-coded values present in use constant field |
| Get Available Datastore | Input Variable | user | vCenterUsername | | Input variable name and Assign from values are not identical |
| Get Available Datastore | Input Variable | password | vCenterPassword | | Input variable name and Assign from values are not identical |
| Get Available Datastore | Input Variable | propsRootObjType | propsRootObjType | HostSystem | Hard-coded values present in use constant field |
| Get Available Datastore | Input Variable | propsRootObj | esxHost | | Input variable name and Assign from values are not identical |
| Reboot VM | Input Variable | vCenterHost | vCenterHost | \${vCenter/VCENTER-HOSTNAME} | Hard-coded values present in use constant field |
| Add Windows Disk | Input Variable | virtualMachine | ipAddress | | Input variable name and Assign from values are not identical |

| | | | | | |
|-----------------------------------|----------------|-------------|-----------------|--|--|
| Add Windows Disk | Input Variable | command | | echo SELECT DISK \${totalDisks} > \${vCenter/WINDOWS-DISKPART-LOCATION} & echo ATTRIBUTES DISK CLEAR READONLY >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo ONLINE DISK >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo CONVERT MBR >> \${vCenter/WINDOWS-DISKPART-LOCATION} & echo CREATE PARTITION PRIMARY > ... | Hard-coded values present in use constant field |
| Get Total Disks Attached To VM | Input Variable | vCenterHost | vCenterHost | \${vCenter/VCENTER-HOSTNAME} | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 15 | Hard-coded values present in use constant field |
| Counter | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Counter | Input Variable | to | | 20 | Hard-coded values present in use constant field |
| Counter | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Counter | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | command | command | dir | Hard-coded values present in use constant field |
| Windows Command | Input Variable | host | virtualMachine | | Input variable name and Assign from values are not identical |
| Windows Command | Input Variable | user | windowsUsername | | Input variable name and Assign from values are not identical |
| Windows Command | Input Variable | password | windowsPassword | | Input variable name and Assign from values are not identical |
| Windows Command | Input Variable | debugPath | | true | Hard-coded values present in use constant field |
| Windows Command | Input Variable | host | virtualMachine | | Input variable name and Assign from values are not identical |
| Windows Command | Input Variable | command | | diskpart /s \${vCenter/WINDOWS-DISKPART-LOCATION} | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------|----------------|------------------|-----------------|--|--|
| Windows Command | Input Variable | user | windowsUsername | | Input variable name and Assign from values are not identical |
| Windows Command | Input Variable | password | windowsPassword | | Input variable name and Assign from values are not identical |
| Get Device Numbers For Type | Input Variable | host | vCenterHost | | Input variable name and Assign from values are not identical |
| Get Device Numbers For Type | Input Variable | user | vCenterUsername | | Input variable name and Assign from values are not identical |
| Get Device Numbers For Type | Input Variable | password | vCenterPassword | | Input variable name and Assign from values are not identical |
| Get Device Numbers For Type | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get Device Numbers For Type | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Device Numbers For Type | Input Variable | closeSession | closeSession | true | Hard-coded values present in use constant field |
| Get Device Numbers For Type | Input Variable | vmIdentifierType | | vmid | Hard-coded values present in use constant field |
| Get Device Numbers For Type | Input Variable | vmDatacenter | datacenter | | Input variable name and Assign from values are not identical |
| Get Device Numbers For Type | Input Variable | deviceType | | hardDisk | Hard-coded values present in use constant field |
| Get Device Numbers For Type | Input Variable | totalDisks | totalDisks | 0 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | selectedCluster | selectedCluster | | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Hard-coded values present in use constant field |
| Sript Content -1 | Input Variable | file | | C:\Vcenter\Getcluster.ps1 | Hard-coded values present in use constant field |
| Sript Content -1 | Input Variable | contents | | Connect-VIServer \${viServer} -User \${userName} -Password \${password} Get-Datacenter Get-Cluster Select Name* | Hard-coded values present in use constant field |
| Sript Content -1 | Input Variable | overwrite | | True | Hard-coded values present in use constant field |

| | | | | | |
|--|----------------|----------------------------|----------------------------|---|---|
| Get cluster memory and diskspace details | Input Variable | script | script | C:\Vcenter\cluster.ps1 | Hard-coded values present in use constant field |
| Get cluster memory and diskspace details | Input Variable | host | host | localhost | Hard-coded values present in use constant field |
| Script Content -2 | Input Variable | file | | C:\Vcenter\cluster.ps1 | Hard-coded values present in use constant field |
| Script Content -2 | Input Variable | contents | | Connect-VIServer \${viServer} -User \${userName} -Password \${password} \$clusterName = "\${ss}" foreach(\$cluster in Get-Cluster -Name \$clusterName) { \$esx = \$cluster Get-VMHost \$ds = Get-Datastore -VMHost \$esx where {\$_ .Type -eq "VMFS"} \$cluster Select @{N=" VCName";E={\$cluster.U id. ... | Hard-coded values present in use constant field |
| Script Content -2 | Input Variable | overwrite | | True | Hard-coded values present in use constant field |
| Get Cluster Names | Input Variable | script | script | C:\Vcenter\Getcluster.p s1 | Hard-coded values present in use constant field |
| Get Cluster Names | Input Variable | host | host | localhost | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessag e | constantFailureMessag e | Failed select Cluster | Hard-coded values present in use constant field |
| FS Delete-1 | Input Variable | source | | C:\Vcenter\Getcluster.p s1 | Hard-coded values present in use constant field |
| FS Delete-2 | Input Variable | source | | C:\Vcenter\cluster.ps1 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessag e | constantFailureMessag e | Failed select Cluster | Hard-coded values present in use constant field |
| Script Content -3 | Input Variable | file | | C:\Vcenter\cluster1.ps1 | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------|----------------|--------------|----------|---|---|
| Script Content -3 | Input Variable | contents | | Connect-VIServer -Server \${viServer} -Protocol https -User \${userName} -Password \${password} \$clusterName = "\${ss}" \$vms = Get-cluster \$clustername get-vm \$VMvCPUCount = \$vms Where-Object PowerState -eq PoweredOn Measure-Object -Sum -Property numcpu Select-Object Sum echo \$VMvCPUCount \$n ... | Hard-coded values present in use constant field |
| Script Content -3 | Input Variable | overwrite | | True | Hard-coded values present in use constant field |
| Get cluster CPU Details | Input Variable | script | script | C:\Vcenter\cluster1.ps1 | Hard-coded values present in use constant field |
| Get cluster CPU Details | Input Variable | host | host | localhost | Hard-coded values present in use constant field |
| FS Delete-3 | Input Variable | source | | C:\Vcenter\cluster1.ps1 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | host | host | sft041x0005.itci.softwar egrp.net | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | user | user | svc_hcm-vcenter-prd | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | password | password | 7YIL!Kq4Bvuc | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Advanced Search | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Advanced Search | Input Variable | protocol | | https | Hard-coded values present in use constant field |
| Advanced Search | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Advanced Search | Input Variable | propsType | | ClusterResourceUsage Summary | Hard-coded values present in use constant field |
| Advanced Search | Input Variable | propsPathset | | GetResourceUsage | Hard-coded values present in use constant field |

| | | | | | |
|-----------------|----------------|------------------------|------------------------|---|--|
| Advanced Search | Input Variable | propsRootObjType | | ClusterComputeResource | Hard-coded values present in use constant field |
| Advanced Search | Input Variable | propsRootObj | | domain-c7 | Hard-coded values present in use constant field |
| List Clusters | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| List Clusters | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| List Clusters | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| List Clusters | Input Variable | propsType | | ClusterComputeResource | Hard-coded values present in use constant field |
| List Clusters | Input Variable | propsPathset | | name,overallStatus,host,summary | Hard-coded values present in use constant field |
| List Clusters | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| List Clusters | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| List Clusters | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| List Clusters | Input Variable | propsType | | domain-c7 | Hard-coded values present in use constant field |
| List Clusters | Input Variable | propsPathset | | usageSummary | Hard-coded values present in use constant field |
| List Clusters | Input Variable | propsRootObjType | | ClusterComputeResource | Hard-coded values present in use constant field |
| List Clusters | Input Variable | propsRootObj | | summary | Hard-coded values present in use constant field |
| Sort Cluster | Input Variable | selectedCluster | availableClusters | | Input variable name and Assign from values are not identical |
| Sort Cluster | Input Variable | selectedCluster | availableClusters | | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow unable to find valid ESXi cluster for the requested VM | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------|----------------|------------------------|------------------------|---|--|
| user inputs | Input Variable | selectedCluster | availableClusters | | Input variable name and Assign from values are not identical |
| user inputs | Input Variable | selectedCluster | availableClusters | | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow unable to find valid ESXI cluster for the requested VM | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | selectedCluster | selectedCluster | | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | excelFileName | excelFileName | \${vCenter/IPAM-FILE-LOCATION} | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | worksheetName | | Sheet1 | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | hasHeader | | yes | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | firstRowIndex | | 0 | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | columnIndextoQuery | | 1 | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | operator | | == | Hard-coded values present in use constant field |
| Modify Cell | Input Variable | rowIndex | rowResult | | Input variable name and Assign from values are not identical |
| Modify Cell | Input Variable | columnIndex | | 0 | Hard-coded values present in use constant field |
| Modify Cell | Input Variable | newValue | | N | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | excelFileName | excelFileName | \${vCenter/IPAM-FILE-LOCATION} | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | worksheetName | | Sheet1 | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | hasHeader | | yes | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | firstRowIndex | | 0 | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------|----------------|--------------------|-----------|----|--|
| Get Row Index by Condition | Input Variable | columnIndextoQuery | | 0 | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | operator | | == | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | value | | N | Hard-coded values present in use constant field |
| Modify Cell | Input Variable | rowIndex | rowResult | | Input variable name and Assign from values are not identical |
| Modify Cell | Input Variable | columnIndex | | 0 | Hard-coded values present in use constant field |
| Modify Cell | Input Variable | newValue | | Y | Hard-coded values present in use constant field |
| Get Primary IP | Input Variable | rowIndex | rowResult | | Input variable name and Assign from values are not identical |
| Get Primary IP | Input Variable | columnIndex | | 1 | Hard-coded values present in use constant field |
| Get SubNet Mask | Input Variable | rowIndex | rowResult | | Input variable name and Assign from values are not identical |
| Get SubNet Mask | Input Variable | columnIndex | | 2 | Hard-coded values present in use constant field |
| Get Gateway | Input Variable | rowIndex | rowResult | | Input variable name and Assign from values are not identical |
| Get Gateway | Input Variable | columnIndex | | 3 | Hard-coded values present in use constant field |
| Get Primary DNS | Input Variable | rowIndex | rowResult | | Input variable name and Assign from values are not identical |
| Get Primary DNS | Input Variable | columnIndex | | 4 | Hard-coded values present in use constant field |
| Get Secondary DNS | Input Variable | rowIndex | rowResult | | Input variable name and Assign from values are not identical |
| Get Secondary DNS | Input Variable | columnIndex | | 5 | Hard-coded values present in use constant field |
| Get Host Name | Input Variable | rowIndex | rowResult | | Input variable name and Assign from values are not identical |
| Get Host Name | Input Variable | columnIndex | | 6 | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------|----------------|--------------------|---------------|--------------------------------|--|
| Flow Inputs | Input Variable | excelFileName | excelFileName | \${vCenter/IPAM-FILE-LOCATION} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_WIN_PATH | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | worksheetName | | Sheet1 | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | hasHeader | | yes | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | firstRowIndex | | 0 | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | columnIndextoQuery | | 0 | Hard-coded values present in use constant field |
| Get Row Index by Condition | Input Variable | operator | | != | Hard-coded values present in use constant field |
| Ping | Input Variable | hostname | | 16.32.12.36 | Hard-coded values present in use constant field |
| Ping | Input Variable | username | | admin | Hard-coded values present in use constant field |
| Ping | Input Variable | targetHost | primaryIP | | Input variable name and Assign from values are not identical |
| Ping | Input Variable | protocol | | local | Hard-coded values present in use constant field |
| Ping | Input Variable | remoteOS | | WINDOWS | Hard-coded values present in use constant field |
| Ping | Input Variable | ipVersion | | 4 | Hard-coded values present in use constant field |
| Modify Cell | Input Variable | rowIndex | rowId | | Input variable name and Assign from values are not identical |
| Modify Cell | Input Variable | columnIndex | | 0 | Hard-coded values present in use constant field |
| Modify Cell | Input Variable | newValue | newValue | N | Hard-coded values present in use constant field |
| Get Primary IP | Input Variable | columnIndex | | 1 | Hard-coded values present in use constant field |
| Get Primary IP | Input Variable | rowIndex | rowResult | | Input variable name and Assign from values are not identical |

| | | | | | |
|------------------------------|----------------|------------------|-----------------|--------------------------------------|--|
| Flow Inputs | Input Variable | host | host | sft041x0005.itci.softwar egrp.net | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | user | user | svc_hcm-vcenter-prd | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | virtualMachine | virtualMachine | mc4t05047 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | vmDatacenter | vmDatacenter | sft041-WKLD-DC | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | deviceNumber | deviceNumber | 1 | Hard-coded values present in use constant field |
| Get Details of NIC | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get Details of NIC | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Details of NIC | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Get Details of NIC | Input Variable | vmIdentifierType | | Name | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | osType | osType | Linux | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | ipAddress | ipAddress | 10.1.0.38 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | subnetMask | subnetMask | 255.255.255.0 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | gatewayIpList | gatewayIpList | 10.1.0.1 | Hard-coded values present in use constant field |
| Build DNS Server List Xml | Input Variable | xmlElementName | | dnsServerList | Hard-coded values present in use constant field |
| Build DNS Server List Xml | Input Variable | delimiter | delimiter | , | Hard-coded values present in use constant field |
| Build DNS Server List Xml | Input Variable | list | dnsServerIpList | | Input variable name and Assign from values are not identical |

| | | | | | |
|------------------------|----------------|-------------------|-------------------|--------------------------------------|--|
| Build Gateway List Xml | Input Variable | xmlElementName | | gateway | Hard-coded values present in use constant field |
| Build Gateway List Xml | Input Variable | delimiter | delimiter | , | Hard-coded values present in use constant field |
| Build Gateway List Xml | Input Variable | list | gatewayIpList | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | user | user | svc_hcm-vcenter-prd | Hard-coded values present in use constant field |
| Get Power State | Input Variable | vmIdentifierType | | vmid | Hard-coded values present in use constant field |
| Get Power State | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Sleep 30 sec | Input Variable | seconds | | 30 | Hard-coded values present in use constant field |
| Loop | Input Variable | count | | 10 | Hard-coded values present in use constant field |
| Loop | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Loop | Input Variable | to | | \${count} | Hard-coded values present in use constant field |
| Loop | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Loop | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | offeringName | offeringName | Windows App Server 2012 R2 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | host | host | sft041x0005.itci.softwar egrp.net | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | serverComponentId | serverComponentId | 2c90cfef745cea750176 1ead00fc417e | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | SASatelite | SASatelite | 15.120.174.195 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | user | user | svc_hcm-vcenter-dev | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | gatewayIpList | gatewayIpList | 15.120.136.1 | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------------|----------------|----------------------------|----------------------------|----------------------|--|
| Flow Inputs | Input Variable | ipAddress | ipAddress | 15.120.139.115 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | subnetMask | subnetMask | 255.255.248.0 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | platform | platform | WINDOWS | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | dnsName | dnsName | itcs.softwaregrp.net | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | closeSession | closeSession | true | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | networkType | networkType | EXT | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | customizationTemplate Name | customizationTemplate Name | MFI-win2012-R2 | Hard-coded values present in use constant field |
| Export Guest Customization Spec | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Export Guest Customization Spec | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Export Guest Customization Spec | Input Variable | closeSession | closeSession | true | Hard-coded values present in use constant field |
| Repalce Domain | Input Variable | xml | customSpecXml | | Input variable name and Assign from values are not identical |
| Repalce Domain | Input Variable | DNS_NAME | dnsName | | Input variable name and Assign from values are not identical |
| Export Guest Customization Spec | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Export Guest Customization Spec | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Export Guest Customization Spec | Input Variable | closeSession | closeSession | true | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------|----------------|-----------|------------|--|--|
| Sript Content -1 | Input Variable | file | | C:\Vcenter\Getcluster.ps1 | Hard-coded values present in use constant field |
| Sript Content -1 | Input Variable | contents | | Connect-VIServer \${viServer} -User \${userName} -Password \${password} Get-Datacenter Get-Cluster Select Name* | Hard-coded values present in use constant field |
| Sript Content -1 | Input Variable | overwrite | | True | Hard-coded values present in use constant field |
| Get Cluster Names | Input Variable | script | script | C:\Vcenter\Getcluster.ps1 | Hard-coded values present in use constant field |
| Get Cluster Names | Input Variable | host | host | localhost | Hard-coded values present in use constant field |
| Get cluster available Details | Input Variable | script | script | C:\Vcenter\cluster.ps1 | Hard-coded values present in use constant field |
| Get cluster available Details | Input Variable | host | host | localhost | Hard-coded values present in use constant field |
| Script Content -2 | Input Variable | file | | C:\Vcenter\cluster.ps1 | Hard-coded values present in use constant field |
| Script Content -2 | Input Variable | contents | | Connect-VIServer \${viServer} -User \${userName} -Password \${password} \$clusterName = "\${ss}" foreach(\$cluster in Get-Cluster -Name \$clusterName) { \$esx = \$cluster Get-VMHost \$ds = Get-Datastore -VMHost \$esx where {\$_.Type -eq "VMFS"} \$cluster Select @{N=" VCname";E={\$cluster.U id. ... | Hard-coded values present in use constant field |
| Script Content -2 | Input Variable | overwrite | | True | Hard-coded values present in use constant field |
| Get Element Matching | Input Variable | list | sortedList | | Input variable name and Assign from values are not identical |
| Get Element Matching | Input Variable | delimiter | | | Hard-coded values present in use constant field |
| Get Element Matching | Input Variable | compareTo | sortDisk | | Input variable name and Assign from values are not identical |

| | | | | | |
|---|----------------|------------------------|------------------------|--|--|
| Get Element Matching | Input Variable | matchType | | Contains | Hard-coded values present in use constant field |
| FS Delete-1 | Input Variable | source | | C:\Vcenter\Getcluster.ps1 | Hard-coded values present in use constant field |
| FS Delete-2 | Input Variable | source | | C:\Vcenter\cluster.ps1 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed select Cluster | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed select Cluster | Hard-coded values present in use constant field |
| Get Cluster Internal ID | Input Variable | script | script | C:\Get_Cluster_Id.ps1 ' \${selectedClusterName}' ' {viServer}' ' {userName}' ' {password}' | Hard-coded values present in use constant field |
| Get Cluster Internal ID | Input Variable | host | host | localhost | Hard-coded values present in use constant field |
| Selection Process of ESXi | Input Variable | requestedMemory | memoryGB | | Input variable name and Assign from values are not identical |
| Selection Process of ESXi | Input Variable | requestedstorage | diskSpaceGB | | Input variable name and Assign from values are not identical |
| Selection Process of ESXi | Input Variable | selectedCluster | sortedList | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed select Cluster | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | childComponentName1 | childComponentName1 | Disk 1 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | childComponentName2 | childComponentName2 | Disk 2 | Hard-coded values present in use constant field |
| Get Child Component Properties (disk-2) | Input Variable | parentComponentId | serverComponentId | | Input variable name and Assign from values are not identical |

| | | | | | |
|---|----------------|--------------------|---------------------|-------|--|
| Get Child Component Properties (disk-2) | Input Variable | childComponentName | childComponentName1 | | Input variable name and Assign from values are not identical |
| Get Child Component Properties (disk-3) | Input Variable | parentComponentId | serverComponentId | | Input variable name and Assign from values are not identical |
| Get Child Component Properties (disk-3) | Input Variable | childComponentName | childComponentName2 | | Input variable name and Assign from values are not identical |
| Extend Disk-2 | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Extend Disk-2 | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Extend Disk-2 | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Extend Disk-2 | Input Variable | async | | false | Hard-coded values present in use constant field |
| Extend Disk-2 | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Extend Disk-2 | Input Variable | vmIdentifierType | | Name | Hard-coded values present in use constant field |
| Extend Disk-2 | Input Variable | diskSize | diskSize1 | | Input variable name and Assign from values are not identical |
| Extend Disk-2 | Input Variable | deviceNumber | | 2 | Hard-coded values present in use constant field |
| Extend Disk-3 | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Extend Disk-3 | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Extend Disk-3 | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Extend Disk-3 | Input Variable | async | | false | Hard-coded values present in use constant field |
| Extend Disk-3 | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Extend Disk-3 | Input Variable | vmIdentifierType | | Name | Hard-coded values present in use constant field |
| Extend Disk-3 | Input Variable | diskSize | diskSize2 | | Input variable name and Assign from values are not identical |

| | | | | | |
|--|----------------|--------------------|---------------------|---|--|
| Extend Disk-3 | Input Variable | deviceNumber | | 3 | Hard-coded values present in use constant field |
| Update Child Component Properties-Disk-1 | Input Variable | parentComponentId | serverComponentId | | Input variable name and Assign from values are not identical |
| Update Child Component Properties-Disk-1 | Input Variable | childComponentName | childComponentName1 | | Input variable name and Assign from values are not identical |
| Update Child Component Properties-Disk-1 | Input Variable | jsonObject | | { "SIZE": "\${diskSize1}", "MOUNT_POINT": "\${MountPoint1}" } | Hard-coded values present in use constant field |
| Update Child Component Properties-Disk-2 | Input Variable | parentComponentId | serverComponentId | | Input variable name and Assign from values are not identical |
| Update Child Component Properties-Disk-2 | Input Variable | childComponentName | childComponentName2 | | Input variable name and Assign from values are not identical |
| Update Child Component Properties-Disk-2 | Input Variable | jsonObject | | { "SIZE": "\${diskSize2}", "MOUNT_POINT": "\${mountPoint2}" } | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 60 | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 60 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | virtualMachine | | vm-11947 | Hard-coded values present in use constant field |
| List Virtual Machines | Input Variable | user | vCenterUsername | | Input variable name and Assign from values are not identical |
| List Virtual Machines | Input Variable | port | | 443 | Hard-coded values present in use constant field |
| List Virtual Machines | Input Variable | protocol | | https | Hard-coded values present in use constant field |
| List Virtual Machines | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| List Virtual Machines | Input Variable | propsType | | VirtualMachine | Hard-coded values present in use constant field |
| List Virtual Machines | Input Variable | propsPathset | | runtime.host | Hard-coded values present in use constant field |
| List Virtual Machines | Input Variable | propsRootObjType | | VirtualMachine | Hard-coded values present in use constant field |
| List Virtual Machines | Input Variable | propsRootObj | virtualMachine | | Input variable name and Assign from values are not identical |

| | | | | | |
|-----------------------------|----------------|------------------|-----------------|--|--|
| List Virtual Machines | Input Variable | diskSizeGB | disk1SizeGB | | Input variable name and Assign from values are not identical |
| List Virtual Machines | Input Variable | host | vCenterHost | | Input variable name and Assign from values are not identical |
| List Virtual Machines | Input Variable | password | vCenterPassword | | Input variable name and Assign from values are not identical |
| Get Virtual Machine Details | Input Variable | port | | 443 | Hard-coded values present in use constant field |
| Get Virtual Machine Details | Input Variable | protocol | | https | Hard-coded values present in use constant field |
| Get Virtual Machine Details | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Get Virtual Machine Details | Input Variable | propsType | | VirtualMachine | Hard-coded values present in use constant field |
| Get Virtual Machine Details | Input Variable | propsPathset | | guest.guestFamily,name,config.template | Hard-coded values present in use constant field |
| Get Virtual Machine Details | Input Variable | propsRootObjType | | VirtualMachine | Hard-coded values present in use constant field |
| Get Virtual Machine Details | Input Variable | propsRootObj | virtualMachine | | Input variable name and Assign from values are not identical |
| Get Virtual Machine Details | Input Variable | host | vCenterHost | | Input variable name and Assign from values are not identical |
| Get Virtual Machine Details | Input Variable | user | vCenterUsername | | Input variable name and Assign from values are not identical |
| Get Virtual Machine Details | Input Variable | password | vCenterPassword | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | user | vCenterUsername | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | port | | 443 | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | protocol | | https | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | vmIdentifierType | | vmid | Hard-coded values present in use constant field |

| | | | | | |
|---|----------------|---------------------|---------------------|---|--|
| Get Virtual Machine | Input Variable | getDetailed | | false | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | host | vCenterHost | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | password | vCenterPassword | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | childComponentName1 | childComponentName1 | Disk 1 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | childComponentName2 | childComponentName2 | Disk 2 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | bufferSapce | bufferSapce | 50 | Hard-coded values present in use constant field |
| Get Child Component Properties (disk-2) | Input Variable | parentComponentId | serverComponentId | | Input variable name and Assign from values are not identical |
| Get Child Component Properties (disk-2) | Input Variable | childComponentName | childComponentName1 | | Input variable name and Assign from values are not identical |
| SQL Command To Get Template | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| SQL Command To Get Template | Input Variable | Command | Command | SELECT "OS_DISK_SIZE" FROM public."COMPUTE_OFFERING" WHERE "OFFERING_NAME" = '\${offeringName}' AND "NETWORK" = '\${networkType}'; | Hard-coded values present in use constant field |
| SQL Command To Get Template | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| Get Child Component Properties (disk-3) | Input Variable | parentComponentId | serverComponentId | | Input variable name and Assign from values are not identical |
| Get Child Component Properties (disk-3) | Input Variable | childComponentName | childComponentName2 | | Input variable name and Assign from values are not identical |
| Resolved : success | Input Variable | result | Total | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |

| | | | | | |
|-----------------|----------------|------------------|-----------------------|-----------|--|
| Flow Inputs | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Reboot Guest | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Reboot Guest | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Reboot Guest | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Reboot Guest | Input Variable | vmIdentifierType | | VMID | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | EPP_UNREACHABLE_SLEEP | 20 | Input variable name and Assign from values are not identical |
| Sleep | Input Variable | seconds | EPP_UNREACHABLE_SLEEP | 20 | Hard-coded values present in use constant field |
| Count | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Count | Input Variable | to | EPP_HPSA_RETRY | 3 | Input variable name and Assign from values are not identical |
| Count | Input Variable | to | EPP_HPSA_RETRY | 3 | Hard-coded values present in use constant field |
| Count | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Count | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Set Power State | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Set Power State | Input Variable | async | async | false | Hard-coded values present in use constant field |
| Set Power State | Input Variable | taskTimeOut | taskTimeOut | 4800000 | Hard-coded values present in use constant field |
| Set Power State | Input Variable | vmIdentifierType | | VMID | Hard-coded values present in use constant field |
| Set Power State | Input Variable | vmPowerState | vmPowerState | poweredOn | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | virtualMachine | | vm-11948 | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------------|----------------|------------------|-----------------|-------|--|
| Get Power State | Input Variable | user | vCenterUsername | | Input variable name and Assign from values are not identical |
| Get Power State | Input Variable | port | | 443 | Hard-coded values present in use constant field |
| Get Power State | Input Variable | protocol | | https | Hard-coded values present in use constant field |
| Get Power State | Input Variable | vmIdentifierType | | vmid | Hard-coded values present in use constant field |
| Get Power State | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Get Power State | Input Variable | host | vCenterHost | | Input variable name and Assign from values are not identical |
| Get Power State | Input Variable | password | vCenterPassword | | Input variable name and Assign from values are not identical |
| vCenter Restart Virtual Machine | Input Variable | vCenterProtocol | | https | Hard-coded values present in use constant field |
| vCenter Restart Virtual Machine | Input Variable | vCenterPort | | 443 | Hard-coded values present in use constant field |
| vCenter Restart Virtual Machine | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| vCenter Restart Virtual Machine | Input Variable | vmIdentifierType | | vmid | Hard-coded values present in use constant field |
| vCenter Restart Virtual Machine | Input Variable | waitGuest | | true | Hard-coded values present in use constant field |
| vCenter Restart Virtual Machine | Input Variable | poolingRetries | | 10 | Hard-coded values present in use constant field |
| vCenter Restart Virtual Machine | Input Variable | poolingInterval | | 10 | Hard-coded values present in use constant field |
| Set Power State | Input Variable | user | vCenterUsername | | Input variable name and Assign from values are not identical |
| Set Power State | Input Variable | port | | 443 | Hard-coded values present in use constant field |
| Set Power State | Input Variable | protocol | | https | Hard-coded values present in use constant field |
| Set Power State | Input Variable | closeSession | | true | Hard-coded values present in use constant field |

| | | | | | |
|-----------------|----------------|------------------|-----------------|-----------|--|
| Set Power State | Input Variable | async | | false | Hard-coded values present in use constant field |
| Set Power State | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Set Power State | Input Variable | vmIdentifierType | | vmid | Hard-coded values present in use constant field |
| Set Power State | Input Variable | vmPowerState | | poweredOn | Hard-coded values present in use constant field |
| Set Power State | Input Variable | host | vCenterHost | | Input variable name and Assign from values are not identical |
| Set Power State | Input Variable | password | vCenterPassword | | Input variable name and Assign from values are not identical |
| Sleep | Input Variable | seconds | | 15 | Hard-coded values present in use constant field |
| Counter | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Counter | Input Variable | to | | 60 | Hard-coded values present in use constant field |
| Counter | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Counter | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Get Power State | Input Variable | user | vCenterUsername | | Input variable name and Assign from values are not identical |
| Get Power State | Input Variable | port | | 443 | Hard-coded values present in use constant field |
| Get Power State | Input Variable | protocol | | https | Hard-coded values present in use constant field |
| Get Power State | Input Variable | vmIdentifierType | | vmid | Hard-coded values present in use constant field |
| Get Power State | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Get Power State | Input Variable | host | vCenterHost | | Input variable name and Assign from values are not identical |
| Get Power State | Input Variable | password | vCenterPassword | | Input variable name and Assign from values are not identical |

| | | | | | |
|---------------------|----------------|------------------|----------|----------------|--|
| Flow Inputs | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Set CPU Count | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Set CPU Count | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Set CPU Count | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Set CPU Count | Input Variable | async | | false | Hard-coded values present in use constant field |
| Set CPU Count | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Set CPU Count | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | async | | false | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | vmMemorySize | memSize | | Input variable name and Assign from values are not identical |
| Resolved : success | Input Variable | memoryMB | memSize | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | vmDatacenter | | \${DATACENTER} | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | vmIdentifierType | | NAME | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|------------------|----------------|--------------------------|--|
| Get Virtual Machine | Input Variable | virtualMachine | | \${HOSTNAME} | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | getDetailed | | false | Hard-coded values present in use constant field |
| Guest Tools Status | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Guest Tools Status | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Guest Tools Status | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Guest Tools Status | Input Variable | propsType | | VirtualMachine | Hard-coded values present in use constant field |
| Guest Tools Status | Input Variable | propsPathset | | guest.toolsRunningStatus | Hard-coded values present in use constant field |
| Guest Tools Status | Input Variable | propsRootObjType | | VirtualMachine | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 300 | Hard-coded values present in use constant field |
| Get Guest Info | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Guest Info | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Get Guest Info | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Sleep Loop for 30 min | Input Variable | seconds | | 30 | Hard-coded values present in use constant field |
| Sleep Loop for 30 min | Input Variable | from | from | 1 | Hard-coded values present in use constant field |
| Sleep Loop for 30 min | Input Variable | to | | 60 | Hard-coded values present in use constant field |
| Wait For Guest State | Input Variable | DATACENTER | vmDatacenter | | Input variable name and Assign from values are not identical |
| Wait For Guest State | Input Variable | HOSTNAME | virtualMachine | | Input variable name and Assign from values are not identical |
| Sleep 5 min | Input Variable | seconds | | 300 | Hard-coded values present in use constant field |

| | | | | | |
|----------------|----------------|----------------|-------------|---|--|
| Loop | Input Variable | count | | 10 | Hard-coded values present in use constant field |
| Loop | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Loop | Input Variable | to | | \${count} | Hard-coded values present in use constant field |
| Loop | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Loop | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Sleep 30 sec | Input Variable | seconds | | 30 | Hard-coded values present in use constant field |
| Sleep 2 min | Input Variable | seconds | | 120 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | projectId | | mfdev_p00009 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | projectName | | mfdev_p00009-Applicat ion | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | role | | wa | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | requestingUser | | srinivas.rn2@microfocu s.com | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | approvers | | srinivas.rn2@microfocu s.com | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | hidden | | false | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | company | | MFI | Hard-coded values present in use constant field |
| Create Project | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Create Project | Input Variable | url | vsmProvider | https://vsmlistener.hous ton.softwaregrp.net/soa p-server/vsm_soap.pl | Input variable name and Assign from values are not identical |
| Create Project | Input Variable | url | vsmProvider | https://vsmlistener.hous ton.softwaregrp.net/soa p-server/vsm_soap.pl | Hard-coded values present in use constant field |
| Create Project | Input Variable | authType | | basic | Hard-coded values present in use constant field |

| | | | | | |
|----------------|----------------|----------------------|-------------|--|--|
| Create Project | Input Variable | username | vsmUsername | | Input variable name and Assign from values are not identical |
| Create Project | Input Variable | password | vsmPassword | | Input variable name and Assign from values are not identical |
| Create Project | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Hard-coded values present in use constant field |
| Create Project | Input Variable | headers | | SOAPAction:http://vsmli stener.houston.software grp.net/API/V2/SoapSer vices#CreateProject | Hard-coded values present in use constant field |
| Create Project | Input Variable | contentType | | text/xml; charset=UTF-8 | Hard-coded values present in use constant field |
| Create Project | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Create Project | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Create Project | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Create Project | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Create Project | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Create Project | Input Variable | connectTimeout | | 30 | Hard-coded values present in use constant field |
| Create Project | Input Variable | socketTimeout | | 120 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | groupName | | wa_mfdev_p00009 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | requestingUser | | srinivas.rn2@microfocu s.com | Hard-coded values present in use constant field |

| | | | | | |
|-------------|----------------|---------------|-------------|--|--|
| Flow Inputs | Input Variable | primaryUpn | | sup_srinivasrn3@micro focus.com | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | expiration | | 2999-01-01 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | company | | MFI | Hard-coded values present in use constant field |
| Create User | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Create User | Input Variable | url | vsmProvider | https://vsmlistener.hous ton.softwaregrp.net/soa p-server/vsm_soap.pl | Input variable name and Assign from values are not identical |
| Create User | Input Variable | url | vsmProvider | https://vsmlistener.hous ton.softwaregrp.net/soa p-server/vsm_soap.pl | Hard-coded values present in use constant field |
| Create User | Input Variable | authType | | basic | Hard-coded values present in use constant field |
| Create User | Input Variable | username | vsmUsername | | Input variable name and Assign from values are not identical |
| Create User | Input Variable | password | vsmPassword | | Input variable name and Assign from values are not identical |
| Create User | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:e ncodingStyle="http://sch emas.xmlsoap.org/soap /encoding/" xmlns:soap ="http://schemas.xmlso ap.org/soap/envelope/" xmlns:soapenc="http://s chemas.xmlsoap.org/so ap/encoding/" xmlns:xs d="http://www.w3.org/2 001/XMLSchema" xmlns:xsi="http://www. ... | Hard-coded values present in use constant field |
| Create User | Input Variable | headers | | SOAPAction:http://vsmli stener.houston.software grp.net/API/V2/SoapSer vices#CreateUser | Hard-coded values present in use constant field |
| Create User | Input Variable | contentType | | text/xml; charset=UTF-8 | Hard-coded values present in use constant field |
| Create User | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Create User | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |

| | | | | | |
|----------------|----------------|----------------------|-------------|---|--|
| Create User | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Create User | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Create User | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Create User | Input Variable | connectTimeout | | 30 | Hard-coded values present in use constant field |
| Create User | Input Variable | socketTimeout | | 120 | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 15 | Hard-coded values present in use constant field |
| Loop | Input Variable | count | | 8 | Hard-coded values present in use constant field |
| Loop | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Loop | Input Variable | to | | \${count} | Hard-coded values present in use constant field |
| Loop | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Loop | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | projectId | | mf4icsa_p00001 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | company | | MFI | Hard-coded values present in use constant field |
| Delete Project | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Delete Project | Input Variable | url | vsmProvider | https://vsmlistener.houston.softwaregrp.net/soap-server/vsm_soap.pl | Input variable name and Assign from values are not identical |
| Delete Project | Input Variable | url | vsmProvider | https://vsmlistener.houston.softwaregrp.net/soap-server/vsm_soap.pl | Hard-coded values present in use constant field |
| Delete Project | Input Variable | authType | | basic | Hard-coded values present in use constant field |
| Delete Project | Input Variable | username | vsmUsername | | Input variable name and Assign from values are not identical |

| | | | | | |
|----------------|----------------|----------------------|-------------|--|--|
| Delete Project | Input Variable | password | vsmPassword | | Input variable name and Assign from values are not identical |
| Delete Project | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Hard-coded values present in use constant field |
| Delete Project | Input Variable | headers | | SOAPAction:http://vsmlistener.houston.softwaregrp.net/API/V2/SoapServices#DeleteProject | Hard-coded values present in use constant field |
| Delete Project | Input Variable | contentType | | text/xml; charset=UTF-8 | Hard-coded values present in use constant field |
| Delete Project | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Delete Project | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Delete Project | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Delete Project | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Delete Project | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Delete Project | Input Variable | connectTimeout | | 30 | Hard-coded values present in use constant field |
| Delete Project | Input Variable | socketTimeout | | 120 | Hard-coded values present in use constant field |
| Delete User | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Delete User | Input Variable | url | vsmProvider | https://vsmlistener.houston.softwaregrp.net/soap-server/vsm_soap.pl | Input variable name and Assign from values are not identical |
| Delete User | Input Variable | url | vsmProvider | https://vsmlistener.houston.softwaregrp.net/soap-server/vsm_soap.pl | Hard-coded values present in use constant field |

| | | | | | |
|-------------------|----------------|----------------------|-------------|--|--|
| Delete User | Input Variable | authType | | basic | Hard-coded values present in use constant field |
| Delete User | Input Variable | username | vsmUsername | | Input variable name and Assign from values are not identical |
| Delete User | Input Variable | password | vsmPassword | | Input variable name and Assign from values are not identical |
| Delete User | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Hard-coded values present in use constant field |
| Delete User | Input Variable | headers | | SOAPAction:http://vsmli stener.houston.software grp.net/API/VRO/Soap Services#QueryProject | Hard-coded values present in use constant field |
| Delete User | Input Variable | contentType | | text/xml; charset=UTF-8 | Hard-coded values present in use constant field |
| Delete User | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Delete User | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Delete User | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Delete User | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Delete User | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Delete User | Input Variable | connectTimeout | | 30 | Hard-coded values present in use constant field |
| Delete User | Input Variable | socketTimeout | | 120 | Hard-coded values present in use constant field |
| Host Registration | Input Variable | method | | POST | Hard-coded values present in use constant field |

| | | | | | |
|-------------------|----------------|----------------------|-------------|--|--|
| Host Registration | Input Variable | url | vsmProvider | https://vsmlistener.houston.softwaregrp.net/soap-server/vsm_soap.pl | Input variable name and Assign from values are not identical |
| Host Registration | Input Variable | url | vsmProvider | https://vsmlistener.houston.softwaregrp.net/soap-server/vsm_soap.pl | Hard-coded values present in use constant field |
| Host Registration | Input Variable | authType | | basic | Hard-coded values present in use constant field |
| Host Registration | Input Variable | username | vsmUsername | | Input variable name and Assign from values are not identical |
| Host Registration | Input Variable | password | vsmPassword | | Input variable name and Assign from values are not identical |
| Host Registration | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Hard-coded values present in use constant field |
| Host Registration | Input Variable | headers | | SOAPAction:http://vsmlistener.houston.softwaregrp.net/API/V2/SoapServices#HostRegistration | Hard-coded values present in use constant field |
| Host Registration | Input Variable | contentType | | text/xml; charset=UTF-8 | Hard-coded values present in use constant field |
| Host Registration | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Host Registration | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Host Registration | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Host Registration | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Host Registration | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Host Registration | Input Variable | connectTimeout | | 30 | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------|----------------|----------------|--------------|---|--|
| Host Registration | Input Variable | socketTimeout | | 120 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Start Adhoc Server Script | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Start Adhoc Server Script | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Start Adhoc Server Script | Input Variable | sourceCodeType | | SH | Hard-coded values present in use constant field |
| Start Adhoc Server Script | Input Variable | serverIds | serverNames | | Input variable name and Assign from values are not identical |
| Start Adhoc Server Script | Input Variable | scriptTimeout | | 300000 | Hard-coded values present in use constant field |
| Start Adhoc Server Script | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Get Script Job Result | Input Variable | jobId | jobid | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | jobid | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | timeout | | 600000 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | projectId | | mfdev_p00007 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | company | | MFI | Hard-coded values present in use constant field |
| Query Project | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Query Project | Input Variable | url | vsmProvider | https://vsmlistener.houston.softwaregrp.net/soap-server/vsm_soap.pl | Input variable name and Assign from values are not identical |
| Query Project | Input Variable | url | vsmProvider | https://vsmlistener.houston.softwaregrp.net/soap-server/vsm_soap.pl | Hard-coded values present in use constant field |

| | | | | | |
|---------------|----------------|----------------------|-------------|--|--|
| Query Project | Input Variable | authType | | basic | Hard-coded values present in use constant field |
| Query Project | Input Variable | username | vsmUsername | | Input variable name and Assign from values are not identical |
| Query Project | Input Variable | password | vsmPassword | | Input variable name and Assign from values are not identical |
| Query Project | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Hard-coded values present in use constant field |
| Query Project | Input Variable | headers | | SOAPAction:http://vsmli stener.houston.software grp.net/API/V2/SoapSer vices#QueryProject | Hard-coded values present in use constant field |
| Query Project | Input Variable | contentType | | text/xml; charset=UTF-8 | Hard-coded values present in use constant field |
| Query Project | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Query Project | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Query Project | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Query Project | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Query Project | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Query Project | Input Variable | connectTimeout | | 30 | Hard-coded values present in use constant field |
| Query Project | Input Variable | socketTimeout | | 120 | Hard-coded values present in use constant field |
| Query Project | Input Variable | method | | POST | Hard-coded values present in use constant field |

| | | | | | |
|---------------|----------------|----------------------|-------------|--|--|
| Query Project | Input Variable | url | vsmProvider | https://vsmlistener.houston.softwaregrp.net/soap-server/vsm_soap.pl | Input variable name and Assign from values are not identical |
| Query Project | Input Variable | url | vsmProvider | https://vsmlistener.houston.softwaregrp.net/soap-server/vsm_soap.pl | Hard-coded values present in use constant field |
| Query Project | Input Variable | authType | | basic | Hard-coded values present in use constant field |
| Query Project | Input Variable | username | vsmUsername | | Input variable name and Assign from values are not identical |
| Query Project | Input Variable | password | vsmPassword | | Input variable name and Assign from values are not identical |
| Query Project | Input Variable | body | | <?xml version="1.0" encoding="UTF-8"?> <soap:Envelope soap:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www. ... | Hard-coded values present in use constant field |
| Query Project | Input Variable | headers | | SOAPAction:http://vsmlistener.houston.softwaregrp.net/API/V2/SoapServices#QueryProject | Hard-coded values present in use constant field |
| Query Project | Input Variable | contentType | | text/xml; charset=UTF-8 | Hard-coded values present in use constant field |
| Query Project | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Query Project | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Query Project | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Query Project | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Query Project | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Query Project | Input Variable | connectTimeout | | 30 | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------|----------------|------------------------|------------------------|---|--|
| Query Project | Input Variable | socketTimeout | | 120 | Hard-coded values present in use constant field |
| Select Environment | Input Variable | envirnoment | environmentBuild | | Input variable name and Assign from values are not identical |
| Get Server VO | Input Variable | agent | Host | | Input variable name and Assign from values are not identical |
| Create Project VSM | Input Variable | requestingUser | requestorEmail | | Input variable name and Assign from values are not identical |
| Create Project VSM | Input Variable | approvers | requestorEmail | | Input variable name and Assign from values are not identical |
| Create Project VSM | Input Variable | hidden | | false | Hard-coded values present in use constant field |
| Create User VSM | Input Variable | groupName | | \${role}_\${projectId} | Hard-coded values present in use constant field |
| Create User VSM | Input Variable | requestingUser | requestorEmail | | Input variable name and Assign from values are not identical |
| Create User VSM | Input Variable | primaryUpn | | \${supAccount}@microfocus.com | Hard-coded values present in use constant field |
| Create User VSM | Input Variable | expiration | | 2999-01-01 | Hard-coded values present in use constant field |
| Host Registration VSM | Input Variable | projectId | projectId1 | | Input variable name and Assign from values are not identical |
| Host Registration VSM | Input Variable | systems | Host | | Input variable name and Assign from values are not identical |
| SQL Command [Get Seq No.] | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| SQL Command [Get Seq No.] | Input Variable | Command | DB_Details/SQL_COMMAND | SELECT nextval('public."VSM_COUNT_S"'); | Hard-coded values present in use constant field |
| SQL Command [Get Seq No.] | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | VSM Registration flow failed | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|------------------------|------------------------|---|--|
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to get sup account | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | "Add Admin Users - failed" | Hard-coded values present in use constant field |
| Linux - Add admin User | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Linux - Add admin User | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Linux - Add admin User | Input Variable | sourceCode | sourceCode | /opt/LinuxCOE/bin/csa-post.pl /opt/mount1 /opt/mount2 MFI PROJ-\${projectId} APP \${domain} | Hard-coded values present in use constant field |
| Linux - Add admin User | Input Variable | serverNames | serverId | | Input variable name and Assign from values are not identical |
| Windows Add Admin | Input Variable | host | coreHost | | Input variable name and Assign from values are not identical |
| Windows Add Admin | Input Variable | script | script | start-script.py | Hard-coded values present in use constant field |
| Windows Add Admin | Input Variable | args | | -t \${hostName} -s MFI-AddProjectWinAdmins -a "\${projectId}" -z 5 | Hard-coded values present in use constant field |
| Get Supplemental Account | Input Variable | primaryEmail | requestorEmail | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | coreVersion | coreVersion | sas107 | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | scriptToRun | script | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHosts | host | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHostIds | host | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | scriptTimeout | | 300 | Hard-coded values present in use constant field |
| Get Script Job Result | Input Variable | jobId | jobId | | Input variable name and Assign from values are not identical |

| | | | | | |
|----------------------------|----------------|--------------------|-------------------|---|--|
| Get Script Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | jobid | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | timeout | | 600000 | Hard-coded values present in use constant field |
| Sleep 60 sec | Input Variable | seconds | | 60 | Hard-coded values present in use constant field |
| Loop | Input Variable | count | | 3 | Hard-coded values present in use constant field |
| Loop | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Loop | Input Variable | to | | \${count} | Hard-coded values present in use constant field |
| Loop | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Loop | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Error : failure | Input Variable | failureMessage | | Flow has tried execution of the script but failed to execute script check the VSM Group/Project | Hard-coded values present in use constant field |
| Get Primary NIC Properties | Input Variable | parentComponentId | serverComponentId | | Input variable name and Assign from values are not identical |
| Get Primary NIC Properties | Input Variable | childComponentName | | Primary NIC | Hard-coded values present in use constant field |
| Get CustomSpec XML | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get CustomSpec XML | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get CustomSpec XML | Input Variable | gatewayIpList | gatewayIP | | Input variable name and Assign from values are not identical |
| Get CustomSpec XML | Input Variable | subnetMask | subnetmask | | Input variable name and Assign from values are not identical |
| Get CustomSpec XML | Input Variable | closeSession | | true | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------------|----------------|-------------------------------|------------------|----------------------------|--|
| Get CustomSpec XML | Input Variable | customizationTemplate Name | customSpec | | Input variable name and Assign from values are not identical |
| Get CustomSpec XML | Input Variable | dnsName | dnsDomain | | Input variable name and Assign from values are not identical |
| Get CustomSpec XML | Input Variable | platform | platForm | | Input variable name and Assign from values are not identical |
| Get CustomSpec XML | Input Variable | networkType | networkType | EXT | Hard-coded values present in use constant field |
| Get Available Datastore (DXC) | Input Variable | vhost | host | | Input variable name and Assign from values are not identical |
| Get Available Datastore (DXC) | Input Variable | vusername | user | | Input variable name and Assign from values are not identical |
| Get Available Datastore (DXC) | Input Variable | vpassword | password | | Input variable name and Assign from values are not identical |
| Get Available Datastore (DXC) | Input Variable | diskSizeGB | diskSizeGB | \${threshtoldSpaceGB} | Hard-coded values present in use constant field |
| Get Available Datastore (DXC) | Input Variable | propsRootObjType | propsRootObjType | ClusterComputeResour ce | Hard-coded values present in use constant field |
| Get Available Datastore (DXC) | Input Variable | selectedClusterName | cluster | | Input variable name and Assign from values are not identical |
| Get Available Datastore (DXC) | Input Variable | overrideNRAS | | RAS_Win_Path | Hard-coded values present in use constant field |
| Get Available Datastore (DXC) | Input Variable | vport | port | | Input variable name and Assign from values are not identical |
| Get Available Datastore (DXC) | Input Variable | vprotocol | protocol | | Input variable name and Assign from values are not identical |
| Clone Virtual Machine | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Clone Virtual Machine | Input Variable | async | | false | Hard-coded values present in use constant field |
| Clone Virtual Machine | Input Variable | taskTimeOut | | 3600 | Hard-coded values present in use constant field |
| Clone Virtual Machine | Input Variable | vmIdentifierType | | Name | Hard-coded values present in use constant field |
| Clone Virtual Machine | Input Variable | virtualMachine | cloneTemplate | | Input variable name and Assign from values are not identical |

| | | | | | |
|-----------------------|----------------|-------------------|---------------|-----------|--|
| Clone Virtual Machine | Input Variable | vmName | vmHostname | | Input variable name and Assign from values are not identical |
| Clone Virtual Machine | Input Variable | clusterName | cluster | | Input variable name and Assign from values are not identical |
| Clone Virtual Machine | Input Variable | dataStore | datastoreName | | Input variable name and Assign from values are not identical |
| Clone Virtual Machine | Input Variable | markAsTemplate | | false | Hard-coded values present in use constant field |
| Clone Virtual Machine | Input Variable | thinProvision | | true | Hard-coded values present in use constant field |
| Clone Virtual Machine | Input Variable | connectionTimeout | | 30 | Hard-coded values present in use constant field |
| Clone Virtual Machine | Input Variable | socketTimeout | | 30 | Hard-coded values present in use constant field |
| Get Task State | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Task State | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Set Power State | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Set Power State | Input Variable | async | async | false | Hard-coded values present in use constant field |
| Set Power State | Input Variable | taskTimeOut | taskTimeOut | 4800000 | Hard-coded values present in use constant field |
| Set Power State | Input Variable | vmIdentifierType | | VMID | Hard-coded values present in use constant field |
| Set Power State | Input Variable | virtualMachine | vmId | | Input variable name and Assign from values are not identical |
| Set Power State | Input Variable | vmPowerState | vmPowerState | poweredOn | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | closeSession | closeSession | true | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------------|----------------|------------------------|------------------------|--|--|
| Get Virtual Machine | Input Variable | vmIdentifierType | | vmid | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | virtualMachine | vmId | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | getDetailed | | false | Hard-coded values present in use constant field |
| Update Primary NIC Properties | Input Variable | parentComponentId | serverComponentId | | Input variable name and Assign from values are not identical |
| Update Primary NIC Properties | Input Variable | childComponentName | | Primary NIC | Hard-coded values present in use constant field |
| Update Primary NIC Properties | Input Variable | jsonObject | | { "MAC_ADDRESS": "\${netMacAddr}", "VLAN_ID": "\${netPortGroup}" } | Hard-coded values present in use constant field |
| Get properties for Disks | Input Variable | virtualMachine | vmHostname | | Input variable name and Assign from values are not identical |
| Get properties for Disks | Input Variable | childComponentName1 | | Disk 1 | Hard-coded values present in use constant field |
| Get properties for Disks | Input Variable | childComponentName2 | | Disk 2 | Hard-coded values present in use constant field |
| Get properties for Disks | Input Variable | offeringName | platForm | | Input variable name and Assign from values are not identical |
| Set Resources (CPU and Memory) | Input Variable | virtualMachine | vmname | | Input variable name and Assign from values are not identical |
| Set Resources (CPU and Memory) | Input Variable | vmMemorySize | memorySize | | Input variable name and Assign from values are not identical |
| Set Resources (CPU and Memory) | Input Variable | vmCpuCount | cpu | | Input variable name and Assign from values are not identical |
| Wait For Guest | Input Variable | virtualMachine | vmHostname | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed in Clone VM Step | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | | \${run_id} | Hard-coded values present in use constant field |

| | | | | | |
|--------------------|----------------|------------------------|----------|-------------------------|--|
| Error Handling | Input Variable | constantFailureMessage | | Failed in Clone VM Step | Hard-coded values present in use constant field |
| Check Power State | Input Variable | virtualMachine | vmId | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | | Failed in Clone VM Step | Hard-coded values present in use constant field |
| Get Details of NIC | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get Details of NIC | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Details of NIC | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Get Details of NIC | Input Variable | vmIdentifierType | | Name | Hard-coded values present in use constant field |
| Get Details of NIC | Input Variable | virtualMachine | vmname | | Input variable name and Assign from values are not identical |
| Get Details of NIC | Input Variable | deviceNumber | | 1 | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | async | | true | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | virtualMachine | vmname | | Input variable name and Assign from values are not identical |
| Configure NIC | Input Variable | deviceNumber | | 1 | Hard-coded values present in use constant field |

| | | | | | |
|-----------------|----------------|------------------------|--------------|--|--|
| Configure NIC | Input Variable | netPortGroup | vlan | SFT041_VLAN391_INT_VM | Input variable name and Assign from values are not identical |
| Configure NIC | Input Variable | netPortGroup | vlan | SFT041_VLAN391_INT_VM | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | netNicType | | VmxNet3 | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | netWakeOnLan | | true | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | connect | | true | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | connectAtPowerOn | | true | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 120 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | | Failed in Clone VM Step | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 60 | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | sawUrl | sawUrl | \${smaxHostname}/auth/authentication-endpoint/authenticate/login?TENANTID=\${smaxTenantId} | Hard-coded values present in use constant field |
| Get SSO Token | Input Variable | username | smaxUsername | | Input variable name and Assign from values are not identical |
| Get SSO Token | Input Variable | password | smaxPassword | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | json | resultJson | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.Id | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | url | | https://\${smaxHostname}/rest/\${smaxTenantId}/ems/ServiceComponent | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | authType | | Basic | Hard-coded values present in use constant field |

| | | | | | |
|------------------|----------------|---------------------------|--------------|--|--|
| Http Client Get | Input Variable | username | smaxUsername | | Input variable name and Assign from values are not identical |
| Http Client Get | Input Variable | password | smaxPassword | | Input variable name and Assign from values are not identical |
| Http Client Get | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken};TENANTID=\${smaxTenantId} | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParams | | filter=DisplayLabel eq ('\${businessApplication}')&layout;=DisplayLabel | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Http Client Get | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | url | | https://\${smaxHostname}/rest/\${smaxTenantId}/ems/bulk | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | body | | { "relationships": [{ "name": "ServiceComponentContainsDevice", "firstEndpoint": { "ServiceComponent": "\${bussAppEntityId}" }, "secondEndpoint": { "Device": "\${entityId}" } }], "operation": "CREATE" } | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | username | smaxUsername | | Input variable name and Assign from values are not identical |
| Http Client Post | Input Variable | password | smaxPassword | | Input variable name and Assign from values are not identical |
| Http Client Post | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |

| | | | | | |
|------------------|----------------|--------------------------|--|--|---|
| Http Client Post | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | headers | | Cookie:LWSSO_COOKIE_KEY=\${ssoToken};TENANTID=\${smaxTenantId} | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Http Client Post | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Create Entity | Input Variable | sawUrl | | https://\${smaxHostname} | Hard-coded values present in use constant field |
| Create Entity | Input Variable | tenantId | | \${smaxTenantId} | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|----------------------------|----------------------------|---|--|
| Create Entity | Input Variable | inputJSON | inputJSON | { "entity_type":"Device", "properties":{ "SubType":"Server", "H ostName":"\${hostname} ", "GlobalId":"\${globalId}", "OwnedByPerson":"\${re questorId}", "VirtualDevice":"true", " HcMSubscriptionId_c":" \${subscriptionId}", "NetworkType_ ... | Hard-coded values present in use constant field |
| Create Entity | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Create Entity | Input Variable | useCookies | useCookies | true | Hard-coded values present in use constant field |
| Create Entity | Input Variable | keepAlive | keepAlive | true | Hard-coded values present in use constant field |
| Create Entity | Input Variable | headers | headers | Cookie:LWSSO_COOK IE_KEY=\${ssoToken}; TENANTID=\${tenantId} | Hard-coded values present in use constant field |
| Create Entity | Input Variable | requestCharacterSet | requestCharacterSet | ISO-8859-1 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessag e | constantFailureMessag e | Failed to Get information on Business Application / To create relation with entity | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | sourceCode | sourceCode | Configure Server With WSUS | Hard-coded values present in use constant field |
| Get Script Job Result | Input Variable | jobId | jobId | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | jobId | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | timeout | | 600000 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessag e | constantFailureMessag e | Flow failed to Execute Script in SA jobId :\${jobId} | Hard-coded values present in use constant field |

| | | | | | |
|---------------------|----------------|---------------|--------------|-------------------|--|
| Start Server Script | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | scriptToRun | sourceCode | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | args | scriptArgs | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHostIds | serverId | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | scriptTimeout | | 600 | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | agent | serverNames | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | jobID | jobid | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | timeout | | 600000 | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | scriptToRun | sourceCode | WSUS Initial Scan | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | scriptToRun | sourceCode | WSUS Initial Scan | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | args | scriptArgs | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHostIds | serverId | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | scriptTimeout | | 600 | Hard-coded values present in use constant field |

| | | | | | |
|------------------------|----------------|----------------|--------------|------------------------------------|--|
| Get Script Job Result | Input Variable | jobId | jobId | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Loop | Input Variable | count | | 3 | Hard-coded values present in use constant field |
| Loop | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Loop | Input Variable | to | | \${count} | Hard-coded values present in use constant field |
| Loop | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Loop | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 15 | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 45 | Hard-coded values present in use constant field |
| Run Communication Test | Input Variable | attachableName | hostName | | Input variable name and Assign from values are not identical |
| Run Communication Test | Input Variable | attachableType | | SERVER | Hard-coded values present in use constant field |
| Run Communication Test | Input Variable | attachableID | serverId | \${serverId} | Input variable name and Assign from values are not identical |
| Run Communication Test | Input Variable | attachableID | serverId | \${serverId} | Hard-coded values present in use constant field |
| Run Communication Test | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Linux OA Agent Install | Input Variable | policyName | | \${SA Policy/OA Policy Name Linux} | Hard-coded values present in use constant field |
| Linux OA Agent Install | Input Variable | policyID | | \${SA Policy/OA Policy ID Linux} | Hard-coded values present in use constant field |
| Linux OA Agent Install | Input Variable | attachableID | attachableID | \${serverId} | Hard-coded values present in use constant field |
| Linux OA Agent Install | Input Variable | attachableType | | SERVER | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|------------------------|-------------------------|--------------------------------------|--|
| Linux OA Agent Install | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Windows OA Agent Install | Input Variable | host | hostName | | Input variable name and Assign from values are not identical |
| Windows OA Agent Install | Input Variable | policyName | | \${SA Policy/OA Policy Name Windows} | Hard-coded values present in use constant field |
| Windows OA Agent Install | Input Variable | policyID | | \${SA Policy/OA Policy ID Windows} | Hard-coded values present in use constant field |
| Windows OA Agent Install | Input Variable | attachableID | attachableID | \$(serverId) | Hard-coded values present in use constant field |
| Windows OA Agent Install | Input Variable | attachableType | attachableType | SERVER | Hard-coded values present in use constant field |
| Windows OA Agent Install | Input Variable | separator | separator | , | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | agent | hostName | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \$(run_id) | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to find Server in SA | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \$(run_id) | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to Install OA Agent | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \$(run_id) | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to install OA Agent | Hard-coded values present in use constant field |
| Remove OA version11 | Input Variable | host | serverId | | Input variable name and Assign from values are not identical |
| Remove OA version11 | Input Variable | script | Port_check_script_Linux | MFIT OA Remove 2.0 | Input variable name and Assign from values are not identical |

| | | | | | |
|-----------------------------|----------------|-----------------------------|-------------------------|--------------------------------------|--|
| Remove OA version11 | Input Variable | script | Port_check_script_Linux | MFIT OA Remove 2.0 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | fromType | fromType | BusinessApplication | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | toType | toType | host_node | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | relationType | relationType | containment | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | prop | prop | name=Containment | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | cmdbVersion | cmdbVersion | 11 | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Add Relationship | Input Variable | certificateVerifier | | true | Hard-coded values present in use constant field |
| Add Relationship | Input Variable | certificateHostnameVerifier | | true | Hard-coded values present in use constant field |
| Get Provider Details | Input Variable | providerId | ucmdbProviderId | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to add Relation in UCMDB | Hard-coded values present in use constant field |
| Search Business Application | Input Variable | objectType | | business_application | Hard-coded values present in use constant field |
| Search Business Application | Input Variable | conditionAttributes | | name | Hard-coded values present in use constant field |
| Search Business Application | Input Variable | conditionOperators | | == | Hard-coded values present in use constant field |
| Search Business Application | Input Variable | conditionValues | businessApplication | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | objectType | objectType | Node | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | prop | prop | host_iscomplete=true | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------------|----------------|-----------------------------|------------------------|---|--|
| Modify Object Attribute(s) | Input Variable | certificateVerifier | | false | Hard-coded values present in use constant field |
| Modify Object Attribute(s) | Input Variable | certificateHostnameVerifier | | false | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to update Property "host_iscomplete=true" | Hard-coded values present in use constant field |
| update Domain | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| update Domain | Input Variable | objectType | | Node | Hard-coded values present in use constant field |
| update Domain | Input Variable | prop | | domain_name=\${domain} | Hard-coded values present in use constant field |
| update Domain | Input Variable | certificateVerifier | | false | Hard-coded values present in use constant field |
| update Domain | Input Variable | certificateHostnameVerifier | | false | Hard-coded values present in use constant field |
| Sleep 7 min | Input Variable | seconds | | 420 | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | agent | VMname | | Input variable name and Assign from values are not identical |
| Update Server Information Windows | Input Variable | serverID | serverId | | Input variable name and Assign from values are not identical |
| Update Server Information Windows | Input Variable | forceUpdate | | True | Hard-coded values present in use constant field |
| Update Server Information Windows | Input Variable | refetch | | True | Hard-coded values present in use constant field |
| Update Server Information Windows | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Update Server Information Windows | Input Variable | newServerName | | \${VMname}.\${dnsDomain} | Hard-coded values present in use constant field |
| Update Server Information Windows | Input Variable | rebootRequired | | false | Hard-coded values present in use constant field |
| Update Server Information Windows | Input Variable | stage | | LIVE | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------------------|----------------|------------------------|------------------------|---|--|
| Update Server Information Windows | Input Variable | use | | PRODUCTION | Hard-coded values present in use constant field |
| Sleep Loop for 30 min | Input Variable | seconds | | 30 | Hard-coded values present in use constant field |
| Sleep Loop for 30 min | Input Variable | from | from | 1 | Hard-coded values present in use constant field |
| Sleep Loop for 30 min | Input Variable | to | | 30 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to add Customer group In SA | Hard-coded values present in use constant field |
| Update Server Information Linux | Input Variable | serverID | serverId | | Input variable name and Assign from values are not identical |
| Update Server Information Linux | Input Variable | forceUpdate | | True | Hard-coded values present in use constant field |
| Update Server Information Linux | Input Variable | refetch | | True | Hard-coded values present in use constant field |
| Update Server Information Linux | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Update Server Information Linux | Input Variable | rebootRequired | | false | Hard-coded values present in use constant field |
| Update Server Information Linux | Input Variable | stage | | LIVE | Hard-coded values present in use constant field |
| Update Server Information Linux | Input Variable | use | | PRODUCTION | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to add Customer group In SA | Hard-coded values present in use constant field |
| Update Server Properties | Input Variable | host | SAHostname | | Input variable name and Assign from values are not identical |
| Update Server Properties | Input Variable | nameServer | VMname | | Input variable name and Assign from values are not identical |
| Update Server Properties | Input Variable | script | script | MFIT UpdateServerVO.py | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|------------------------|------------------------|-------------------------------------|--|
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to update SA Properties | Hard-coded values present in use constant field |
| Get Supplemental Account | Input Variable | primaryEmail | requestorEmail | | Input variable name and Assign from values are not identical |
| Get Supplemental Account | Input Variable | environment | environmentBuild | | Input variable name and Assign from values are not identical |
| Get Server VO | Input Variable | agent | Host | | Input variable name and Assign from values are not identical |
| Create Project VSM | Input Variable | requestingUser | requestorEmail | | Input variable name and Assign from values are not identical |
| Create Project VSM | Input Variable | approvers | requestorEmail | | Input variable name and Assign from values are not identical |
| Create Project VSM | Input Variable | hidden | | false | Hard-coded values present in use constant field |
| Create User VSM | Input Variable | groupName | groupId | | Input variable name and Assign from values are not identical |
| Create User VSM | Input Variable | requestingUser | requestorEmail | | Input variable name and Assign from values are not identical |
| Create User VSM | Input Variable | primaryUpn | upn | | Input variable name and Assign from values are not identical |
| Create User VSM | Input Variable | expiration | | 2999-01-01 | Hard-coded values present in use constant field |
| Host Registration VSM | Input Variable | systems | Host | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | VSM Registration flow failed | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to get sup account | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------|----------------|------------------------|------------------------|---|--|
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | "Add Admin Users - failed" | Hard-coded values present in use constant field |
| Linux - Add admin User | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Linux - Add admin User | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Linux - Add admin User | Input Variable | sourceCode | sourceCode | /opt/LinuxCOE/bin/csa-post.pl /opt/mount1 /opt/mount2 MFI PROJ-\${projectId} APP \${domain} | Hard-coded values present in use constant field |
| Linux - Add admin User | Input Variable | serverNames | serverId | | Input variable name and Assign from values are not identical |
| Windows Add Admin | Input Variable | script | script | start-script.py | Hard-coded values present in use constant field |
| Windows Add Admin | Input Variable | args | | -t \${hostName} -s MFI-AddProjectWinAdmins -a "\${groupId}" -z 5 | Hard-coded values present in use constant field |
| DB To Check Project | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| DB To Check Project | Input Variable | Command | DB_Details/SQL_COMMAND | SELECT "GROUP_ID" FROM public."VSM_GROUP" WHERE "BUSINESS_APPLICATION" = '\${businessApplication}' AND "NETWORK" = '\${networkType}' AND "PLATFORM" = '\${platform}'; | Hard-coded values present in use constant field |
| DB To Check Project | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| Error Handling | Input Variable | failureMessage | errorMsg | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | DB Query Failed check the quesry/DB Connection | Hard-coded values present in use constant field |
| SQL Command [Get Seq No.] | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| SQL Command [Get Seq No.] | Input Variable | Command | DB_Details/SQL_COMMAND | SELECT nextval('public."VSM_COUNT_S"'); | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------|----------------|--------------------|----------------------------|--|---|
| SQL Command [Get Seq No.] | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| INSERT Project Name in DB | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| INSERT Project Name in DB | Input Variable | Command | DB_Details/SQL_COM MAND | INSERT INTO public."VSM_GROUP"("GROUP_NAME", "BUSINESS_APPLICATION", "NETWORK", "PLATFORM", "GROUP_ID") VALUES ('\${role}_\${projectId}', '\${businessApplication}', '\${networkType}', '\${platform}', '\${role}_\${projectId}'); COMMIT; | Hard-coded values present in use constant field |
| INSERT Project Name in DB | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| INSERT Project Name in DB | Input Variable | groupId | | \${role}_\${projectId} | Hard-coded values present in use constant field |
| Update GroupOwnedType | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| Update GroupOwnedType | Input Variable | Command | DB_Details/SQL_COM MAND | UPDATE CSA_SERVICE_SUBSCR_GROUP_OWNED_TYPE = 1 WHERE UUID = '\${subscriptionId}'; COMMIT; | Hard-coded values present in use constant field |
| Update GroupOwnedType | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |
| Set Group Ownership | Input Variable | DbType | | PostgreSQL | Hard-coded values present in use constant field |
| Set Group Ownership | Input Variable | Command | DB_Details/SQL_COM MAND | INSERT INTO CSA_SERVICE_SUBSCR_GROUP(FK_SERVICE_SUBSCR_ID, OWNER_GROUP, GROUP_ORDER) VALUES('\${subscriptionId}', 'cn=\${groupId},ou=windowsgroups,ou=groups,ou=virtualsm,dc=microfocus,dc=com', 0); COMMIT; | Hard-coded values present in use constant field |
| Set Group Ownership | Input Variable | authenticationType | | sql | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|------------------------|------------------------|--|--|
| Flow Inputs | Input Variable | coreVersion | coreVersion | sas107 | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | script | script | MFIT OA Replace Values in CONF | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | scriptToRun | script | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHosts | host | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | targetHostIds | serverId | | Input variable name and Assign from values are not identical |
| Start Server Script | Input Variable | args | | \${ipaddress} \${hostName} | Hard-coded values present in use constant field |
| Start Server Script | Input Variable | scriptTimeout | | 300 | Hard-coded values present in use constant field |
| Get Script Job Result | Input Variable | jobId | jobid | | Input variable name and Assign from values are not identical |
| Get Script Job Result | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Wait for Job | Input Variable | jobID | jobid | | Input variable name and Assign from values are not identical |
| Wait for Job | Input Variable | timeout | | 600000 | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | agent | vmHost | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to find Server in SA | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to Execute Script in SA jobId :\${jobid} | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|------------------------|------------------------|---|--|
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Candidate Providers | Input Variable | resourceBindingId | RSC_BINDING_ID | | Input variable name and Assign from values are not identical |
| Get Resource Provider Id | Input Variable | xml | candidatePoolXML | | Input variable name and Assign from values are not identical |
| Get Resource Provider Id | Input Variable | xpathQuery | | //candidateProvider/resourceProvider/property/displayName[text() = "Network"]/../values/value[text() = "\${networkType}"]/../../resourceProvider/id/text() | Hard-coded values present in use constant field |
| Get Resource Provider Id | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| Update Valid Providers | Input Variable | resourceBindingXML | | <ResourceBinding> <id>\${RSC_BINDING_ID}</id> <validProvider> <resourceBinding><id>\${RSC_BINDING_ID}</id></resourceBinding> <resourceProvider><id>\${resourceProviderId}</id></resourceProvider> </validProvider> </ResourceBinding> | Hard-coded values present in use constant field |
| Update Valid Providers | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Valid Providers | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Update Valid Providers | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Update Valid Providers | Input Variable | resourceBindingId | RSC_BINDING_ID | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | AD Flow failed to select correct provider ID | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------------|----------------|------------------------|------------------------|--|--|
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | AD Flow failed to select correct provider ID | Hard-coded values present in use constant field |
| Update AD Property | Input Variable | ADproviderId | resourceProviderId | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Update Valid Provider Pool | Input Variable | resourceBindingXml | | <ResourceBinding> <id>\${resourceBindingId}</id> \${resourcePoolXML} </ResourceBinding> | Hard-coded values present in use constant field |
| Update Valid Provider Pool | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Update Valid Provider Pool | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| Update Valid Provider Pool | Input Variable | chunked | chunked | false | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to process Resource Pool Information | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to process Resource Pool Information | Hard-coded values present in use constant field |
| Get Candidate Providers | Input Variable | trustAllRoots | | false | Hard-coded values present in use constant field |
| Get Candidate Providers | Input Variable | x509HostnameVerifier | | strict | Hard-coded values present in use constant field |
| IPAM Network Selection Process | Input Variable | providerId | resourceProviderId | | Input variable name and Assign from values are not identical |
| XPath Query for Subnet | Input Variable | xml | providerXML | | Input variable name and Assign from values are not identical |
| XPath Query for Subnet | Input Variable | xpathQuery | | /ResourceBinding//candidateProvider/candidatePool/displayName[text()='\${element}']/../id/text() | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------|----------------|----------------------|---------------------|--|--|
| XPath Query for Subnet | Input Variable | parsingFeatures | | http://apache.org/xml/features/disallow-doctype-decl true http://xml.org/sax/features/external-general-entities false http://xml.org/sax/features/external-parameter-entities false | Hard-coded values present in use constant field |
| Get VM Threshold DiskSpace | Input Variable | memory | requestedMemory | | Input variable name and Assign from values are not identical |
| Get VM Threshold DiskSpace | Input Variable | childComponentName1 | childComponentName1 | Disk 1 | Hard-coded values present in use constant field |
| Get VM Threshold DiskSpace | Input Variable | childComponentName2 | childComponentName2 | Disk 2 | Hard-coded values present in use constant field |
| Get VM Threshold DiskSpace | Input Variable | bufferSapce | bufferSapce | 50 | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Store Resource Pool Info | Input Variable | resourcePoolID | ss | | Input variable name and Assign from values are not identical |
| Resource Pool Selection | Input Variable | requestedstorage | threshtoldSpaceGB | | Input variable name and Assign from values are not identical |
| Resource Pool Selection | Input Variable | selectedCluster | poolValues | | Input variable name and Assign from values are not identical |
| Update Valid Provider Pool | Input Variable | resourceBindingXml | | <ResourceBinding> <id>\${resourceBindingId}</id> <validProvider> <resourceBinding> <id>\${resourceBindingId}</id> </resourceBinding> <resourceProvider> <id>\${resourceProviderId}</id> </resourceProvider> <validPool> <id>\${selectedClusterpool}</id> </validPool> </validProvider> < ... | Hard-coded values present in use constant field |
| Update Valid Provider Pool | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Valid Provider Pool | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Update Valid Provider Pool | Input Variable | chunked | chunked | false | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------------------|----------------|----------------------|-------------------|---|--|
| Get Cluster Name | Input Variable | xpathQuery | | //ResourceBinding/candidateProvider/candidatePool/id[text()=\${selecte dClusterpool}']/../display Name/text() | Hard-coded values present in use constant field |
| Get Cluster Name | Input Variable | parsingFeatures | | http://apache.org/xml/fe atures/disallow-doctype -decl true http://xml.org/ sax/features/external-g eneral-entities false http ://xml.org/sax/features/e xternal-parameter-entiti es false | Hard-coded values present in use constant field |
| Get Cluster Name | Input Variable | xml | document1 | | Input variable name and Assign from values are not identical |
| Update Component Property - CPU | Input Variable | onlyUpdate | | yes | Hard-coded values present in use constant field |
| Update Component Property - CPU | Input Variable | propertyName | | number_of_cpu | Hard-coded values present in use constant field |
| Update Component Property - CPU | Input Variable | values | requestedCPU | | Input variable name and Assign from values are not identical |
| Update Component Property - CPU | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Update Component Property - CPU | Input Variable | consumerVisible | | true | Hard-coded values present in use constant field |
| Update Component Property - CPU | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Component Property - CPU | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Update Component Property - CPU | Input Variable | componentId | serverComponentId | | Input variable name and Assign from values are not identical |
| Update Component Property - Memory | Input Variable | onlyUpdate | | yes | Hard-coded values present in use constant field |
| Update Component Property - Memory | Input Variable | propertyName | | memory_size | Hard-coded values present in use constant field |
| Update Component Property - Memory | Input Variable | values | memory | | Input variable name and Assign from values are not identical |
| Update Component Property - Memory | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Update Component Property - Memory | Input Variable | consumerVisible | | true | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------------------|----------------|------------------------|------------------------|--|--|
| Update Component Property - Memory | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Component Property - Memory | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Update Component Property - Memory | Input Variable | componentId | serverComponentId | | Input variable name and Assign from values are not identical |
| Update Component Property - Disk Size | Input Variable | onlyUpdate | | yes | Hard-coded values present in use constant field |
| Update Component Property - Disk Size | Input Variable | propertyName | | disk_size | Hard-coded values present in use constant field |
| Update Component Property - Disk Size | Input Variable | values | thresholdSpaceGB | | Input variable name and Assign from values are not identical |
| Update Component Property - Disk Size | Input Variable | separator | | , | Hard-coded values present in use constant field |
| Update Component Property - Disk Size | Input Variable | consumerVisible | | true | Hard-coded values present in use constant field |
| Update Component Property - Disk Size | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Component Property - Disk Size | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Update Component Property - Disk Size | Input Variable | componentId | serverComponentId | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to update compnent propeties CPU/Memory/Dsk Storage | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to process Resource Pool Information | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to process Resource Pool Information | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------------|----------------|------------------------|------------------------|---|--|
| IPAM Get Properties | Input Variable | providerId | ipamProviderId | | Input variable name and Assign from values are not identical |
| IPAM Get Properties | Input Variable | resourcePoolID | ipamResourcePool | | Input variable name and Assign from values are not identical |
| IPAM Reserve Next available IP | Input Variable | url | | \${ipamProtocol}://\${ipamHostname}:\${ipamPort} | Hard-coded values present in use constant field |
| IPAM Reserve Next available IP | Input Variable | username | ipamUsername | | Input variable name and Assign from values are not identical |
| IPAM Reserve Next available IP | Input Variable | password | ipamPassword | | Input variable name and Assign from values are not identical |
| IPAM Reserve Next available IP | Input Variable | network | subnet | | Input variable name and Assign from values are not identical |
| Update Primary NIC Properties | Input Variable | parentComponentId | svcComponentId | | Input variable name and Assign from values are not identical |
| Update Primary NIC Properties | Input Variable | childComponentName | | Primary NIC | Hard-coded values present in use constant field |
| Update Primary NIC Properties | Input Variable | jsonObject | | { "IP_ADDRESS": "\${ipAddress}", "GATEWAY": "\${gatewayIp}", "SUBNETMASK": "\${subnetMask}" } | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | IPAM Flow failed to get IP Address/Add Host record | Hard-coded values present in use constant field |
| IPAM Add Attributes | Input Variable | IpamUrl | ipamHostname | | Input variable name and Assign from values are not identical |
| IPAM Add Attributes | Input Variable | username | ipamUsername | | Input variable name and Assign from values are not identical |
| IPAM Add Attributes | Input Variable | password | ipamPassword | | Input variable name and Assign from values are not identical |
| IPAM Add Attributes | Input Variable | recordInfo | hostRecord | | Input variable name and Assign from values are not identical |
| Date Parser | Input Variable | date | epochTime | | Input variable name and Assign from values are not identical |
| Date Parser | Input Variable | dateFormat | | unix | Hard-coded values present in use constant field |

| | | | | | |
|-------------------|----------------|------------------------|------------------------|--|--|
| Date Parser | Input Variable | outFormat | | yyyyMMdd | Hard-coded values present in use constant field |
| Wait For Lock | Input Variable | timeout | waitForLockTimeout | 600 | Input variable name and Assign from values are not identical |
| Wait For Lock | Input Variable | timeout | waitForLockTimeout | 600 | Hard-coded values present in use constant field |
| Wait For Lock | Input Variable | lockId | dateLockId | | Input variable name and Assign from values are not identical |
| Wait For Lock | Input Variable | seconds | delayBetweenRequests | | Input variable name and Assign from values are not identical |
| Release Lock | Input Variable | lockId | dateLockId | | Input variable name and Assign from values are not identical |
| Release Lock | Input Variable | Lock_Id | | \${lockId} | Hard-coded values present in use constant field |
| Release Lock | Input Variable | lockId | dateLockId | | Input variable name and Assign from values are not identical |
| Release Lock | Input Variable | Lock_Id | | \${lockId} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | IPAM Flow failed to get IP Address/Add Host record | Hard-coded values present in use constant field |
| Release Lock | Input Variable | lockId | dateLockId | | Input variable name and Assign from values are not identical |
| Release Lock | Input Variable | Lock_Id | | \${lockId} | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Hard-coded values present in use constant field |
| LDAP Get Computer | Input Variable | host | adProvider | | Input variable name and Assign from values are not identical |
| LDAP Get Computer | Input Variable | username | adUsername | | Input variable name and Assign from values are not identical |
| LDAP Get Computer | Input Variable | password | adPassword | | Input variable name and Assign from values are not identical |
| LDAP Get Computer | Input Variable | DN | domainDN | \${OU},\${adBaseDN} | Input variable name and Assign from values are not identical |

| | | | | | |
|-------------------------|----------------|---------------|-------------|--------------------------------|--|
| LDAP Get Computer | Input Variable | DN | domainDN | \${OU},\${adBaseDN} | Hard-coded values present in use constant field |
| LDAP Get Computer | Input Variable | filter | | (cn=\${hostname}) | Hard-coded values present in use constant field |
| LDAP Get Computer | Input Variable | propertyNames | | distinguishedName | Hard-coded values present in use constant field |
| LDAP Get Computer | Input Variable | searchScope | | onelevel | Hard-coded values present in use constant field |
| LDAP Add Property Value | Input Variable | host | adProvider | | Input variable name and Assign from values are not identical |
| LDAP Add Property Value | Input Variable | DN | ComputerDN1 | | Input variable name and Assign from values are not identical |
| LDAP Add Property Value | Input Variable | propertyName | | servicePrincipalName | Hard-coded values present in use constant field |
| LDAP Add Property Value | Input Variable | propertyValue | | HOST/\${hostname}.\${adBaseDN} | Hard-coded values present in use constant field |
| LDAP Add Property Value | Input Variable | username | adUsername | | Input variable name and Assign from values are not identical |
| LDAP Add Property Value | Input Variable | password | adPassword | | Input variable name and Assign from values are not identical |
| LDAP Add Property Value | Input Variable | host | adProvider | | Input variable name and Assign from values are not identical |
| LDAP Add Property Value | Input Variable | DN | ComputerDN1 | | Input variable name and Assign from values are not identical |
| LDAP Add Property Value | Input Variable | propertyName | | servicePrincipalName | Hard-coded values present in use constant field |
| LDAP Add Property Value | Input Variable | propertyValue | | HOST/\${hostname} | Hard-coded values present in use constant field |
| LDAP Add Property Value | Input Variable | username | adUsername | | Input variable name and Assign from values are not identical |
| LDAP Add Property Value | Input Variable | password | adPassword | | Input variable name and Assign from values are not identical |
| LDAP Add Property Value | Input Variable | host | adProvider | | Input variable name and Assign from values are not identical |
| LDAP Add Property Value | Input Variable | DN | ComputerDN1 | | Input variable name and Assign from values are not identical |

| | | | | | |
|--------------------------|----------------|------------------------|------------------------|---|--|
| LDAP Add Property Value | Input Variable | propertyName | | servicePrincipalName | Hard-coded values present in use constant field |
| LDAP Add Property Value | Input Variable | propertyValue | | HOST/\${hostname}.\${domainAlt} | Hard-coded values present in use constant field |
| LDAP Add Property Value | Input Variable | username | adUsername | | Input variable name and Assign from values are not identical |
| LDAP Add Property Value | Input Variable | password | adPassword | | Input variable name and Assign from values are not identical |
| Create Computer Account | Input Variable | host | adProvider | | Input variable name and Assign from values are not identical |
| Create Computer Account | Input Variable | username | adUsername | | Input variable name and Assign from values are not identical |
| Create Computer Account | Input Variable | password | adPassword | | Input variable name and Assign from values are not identical |
| Create Computer Account | Input Variable | computerCommonName | hostname | | Input variable name and Assign from values are not identical |
| Create Computer Account | Input Variable | sAMAccountName | | \${hostname}\$ | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | AD Flow failed to Create Computer Account | Hard-coded values present in use constant field |
| Disable Computer Account | Input Variable | host | adProvider | | Input variable name and Assign from values are not identical |
| Disable Computer Account | Input Variable | computerCommonName | hostname | | Input variable name and Assign from values are not identical |
| Disable Computer Account | Input Variable | username | adUsername | | Input variable name and Assign from values are not identical |
| Disable Computer Account | Input Variable | password | adPassword | | Input variable name and Assign from values are not identical |
| Sleep | Input Variable | seconds | | 15 | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 15 | Hard-coded values present in use constant field |
| Loop | Input Variable | count | | 5 | Hard-coded values present in use constant field |

| | | | | | |
|------------------|----------------|------------------|--------------|---|--|
| Loop | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Loop | Input Variable | to | | \${count} | Hard-coded values present in use constant field |
| Loop | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Loop | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | coreHost | CoreHost | | Input variable name and Assign from values are not identical |
| Get Server VO | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | coreVersion | CoreVersion | | Input variable name and Assign from values are not identical |
| Get Server VO | Input Variable | agent | host | | Input variable name and Assign from values are not identical |
| Deactivate Agent | Input Variable | port | | 2222 | Hard-coded values present in use constant field |
| Deactivate Agent | Input Variable | password | corePassword | | Input variable name and Assign from values are not identical |
| Deactivate Agent | Input Variable | command | | /opsw/api/com/opsware/server/ServerService/method/decommissionself:i=\${serverId} | Hard-coded values present in use constant field |
| Deactivate Agent | Input Variable | knownHostsPolicy | | allow | Hard-coded values present in use constant field |
| Deactivate Agent | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Deactivate Agent | Input Variable | pty | | false | Hard-coded values present in use constant field |
| Deactivate Agent | Input Variable | timeout | | 90000 | Hard-coded values present in use constant field |
| Deactivate Agent | Input Variable | connectTimeout | | 10000 | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|------------------|--------------|---|--|
| Deactivate Agent | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Deactivate Agent | Input Variable | useGlobalContext | | false | Hard-coded values present in use constant field |
| Deactivate Agent | Input Variable | host | CoreHost | | Input variable name and Assign from values are not identical |
| Deactivate Agent | Input Variable | username | coreUsername | | Input variable name and Assign from values are not identical |
| Delete Server from SA | Input Variable | port | | 2222 | Hard-coded values present in use constant field |
| Delete Server from SA | Input Variable | password | corePassword | | Input variable name and Assign from values are not identical |
| Delete Server from SA | Input Variable | command | | /opsw/api/com/opsware/server/ServerService/method/removeSelf:i=\${serverId} | Hard-coded values present in use constant field |
| Delete Server from SA | Input Variable | knownHostsPolicy | | allow | Hard-coded values present in use constant field |
| Delete Server from SA | Input Variable | characterSet | | UTF-8 | Hard-coded values present in use constant field |
| Delete Server from SA | Input Variable | pty | | false | Hard-coded values present in use constant field |
| Delete Server from SA | Input Variable | timeout | | 90000 | Hard-coded values present in use constant field |
| Delete Server from SA | Input Variable | connectTimeout | | 10000 | Hard-coded values present in use constant field |
| Delete Server from SA | Input Variable | keepAlive | | 0 | Hard-coded values present in use constant field |
| Delete Server from SA | Input Variable | closeSession | | true | Hard-coded values present in use constant field |
| Delete Server from SA | Input Variable | useGlobalContext | | false | Hard-coded values present in use constant field |
| Delete Server from SA | Input Variable | host | CoreHost | | Input variable name and Assign from values are not identical |
| Delete Server from SA | Input Variable | username | coreUsername | | Input variable name and Assign from values are not identical |

| | | | | | |
|----------------------------|----------------|------------------------|------------------------|--|--|
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to remove Server from SA | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Given Server not found in SA | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | corePort | corePort | 443 | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | coreProtocol | coreProtocol | https | Hard-coded values present in use constant field |
| Get Server VO | Input Variable | agent | hostName | | Input variable name and Assign from values are not identical |
| OA Agent Uninstall Linux | Input Variable | host | serverId | | Input variable name and Assign from values are not identical |
| OA Agent Uninstall Linux | Input Variable | script | | \${SA/OA Agent Uninstall Linux} | Hard-coded values present in use constant field |
| OA Agent Uninstall Windows | Input Variable | host | serverId | | Input variable name and Assign from values are not identical |
| OA Agent Uninstall Windows | Input Variable | script | | \${SA/OA Agent Uninstall Windows} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to Un-Install OA Agent | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to find the server to Un-Install OA Agent | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to Remove SystemElement \${entityId} from SMAX | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Input variable name and Assign from values are not identical |

| | | | | | |
|-------------------------------|----------------|------------------------|------------------------|---|--|
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustKeystore | OO_TRUST_KEYSTORE_PATH | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Resource Provider Details | Input Variable | providerId | providerId | \${RSC_PROVIDER_ID} | Hard-coded values present in use constant field |
| vCenter Unprovision Server | Input Variable | vmID | vmid | | Input variable name and Assign from values are not identical |
| vCenter Unprovision Server | Input Variable | vmDatacenter | dataCenter | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | vmDatacenter | dataCenter | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | virtualMachine | vmName | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | getDetailed | | true | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | connectionTimeout | | 30 | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | socketTimeout | | 30 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Undeply Server-Manually delete server from SA | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |

| | | | | | |
|---|----------------|------------------------|------------------------|--|--|
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Undeply Server- VmName field is empty. Manually check and delete the server from vcenter | Hard-coded values present in use constant field |
| Remove Host Record | Input Variable | hostName | hostname | | Input variable name and Assign from values are not identical |
| Remove Host Record | Input Variable | authType | authType | Basic | Hard-coded values present in use constant field |
| Remove Host Record | Input Variable | trustAllRoots | trustAllRoots | true | Hard-coded values present in use constant field |
| Remove Host Record | Input Variable | x509HostnameVerifier | x509HostnameVerifier | allow_all | Hard-coded values present in use constant field |
| Remove Host Record | Input Variable | url | ipamUrl | | Input variable name and Assign from values are not identical |
| Remove Host Record | Input Variable | username | ipamUsername | | Input variable name and Assign from values are not identical |
| Remove Host Record | Input Variable | password | ipamPassword | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to remove Host record from IPAM | Hard-coded values present in use constant field |
| Get Child Component Properties (Bcakup Nic) | Input Variable | childComponentName | | Backup NIC | Hard-coded values present in use constant field |
| IPAM Get Properties (Backup Nic) | Input Variable | providerId | IPAM providerId | | Input variable name and Assign from values are not identical |
| IPAM Remove Host Record | Input Variable | ipamUrl | ipamUrl | https://\${ipamHost} | Hard-coded values present in use constant field |
| IPAM Remove Host Record | Input Variable | ipamPassword | ipamPasword | | Input variable name and Assign from values are not identical |
| IPAM Remove Host Record | Input Variable | hostname | hostName | | Input variable name and Assign from values are not identical |
| IPAM Remove Host Record | Input Variable | domain | zone | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | overrideNRAS | | RAS_Win_Path | Hard-coded values present in use constant field |

| | | | | | |
|--------------------------|----------------|------------------------|------------------------|--------------------------------|--|
| Delete Computer Account | Input Variable | host | adProvider | | Input variable name and Assign from values are not identical |
| Delete Computer Account | Input Variable | username | adUsername | | Input variable name and Assign from values are not identical |
| Delete Computer Account | Input Variable | password | adPassword | | Input variable name and Assign from values are not identical |
| Delete Computer Account | Input Variable | computerCommonName | hostname | | Input variable name and Assign from values are not identical |
| Delete Computer Account | Input Variable | sAMAccountName | sAMAccountName | \${hostname}\$ | Hard-coded values present in use constant field |
| Disable Computer Account | Input Variable | host | adProvider | | Input variable name and Assign from values are not identical |
| Disable Computer Account | Input Variable | username | adUsername | | Input variable name and Assign from values are not identical |
| Disable Computer Account | Input Variable | password | adPassword | | Input variable name and Assign from values are not identical |
| Disable Computer Account | Input Variable | computerCommonName | hostname | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | AD Flow Failed delete computer | Hard-coded values present in use constant field |
| Get Supplemental Account | Input Variable | primaryEmail | requestorEmail | | Input variable name and Assign from values are not identical |
| Create User VSM | Input Variable | groupName | cloudGroup | | Input variable name and Assign from values are not identical |
| Create User VSM | Input Variable | requestingUser | requestorEmail | | Input variable name and Assign from values are not identical |
| Create User VSM | Input Variable | primaryUpn | upn | | Input variable name and Assign from values are not identical |
| Create User VSM | Input Variable | expiration | | 2999-01-01 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |

| | | | | | |
|---------------------------|----------------|---------------------------|------------------------|---|--|
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Unable to add supplemental user to subscription owned group | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | url | url | \${csaApiUrl}service/subscription/\${subscriptionId} | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | headers | | Accept:application/json | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | contentType | | application/json | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Subscription Details | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| JSON Path | Input Variable | json | subscriptionJSON | | Input variable name and Assign from values are not identical |
| JSON Path | Input Variable | jsonPathQuery | | \$.ext.csa_owner_group[0] | Hard-coded values present in use constant field |
| Get Current Date and Time | Input Variable | localeLang | localeLang | en | Hard-coded values present in use constant field |
| Get Current Date and Time | Input Variable | localeCountry | localeCountry | US | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------|----------------|----------------------|------------------------|---------------------|--|
| Get Current Date and Time | Input Variable | Field_2 | | \${in2} | Hard-coded values present in use constant field |
| Get Current Date and Time | Input Variable | Field_3 | | \${in3} | Hard-coded values present in use constant field |
| Get Current Date and Time | Input Variable | Field_4 | | \${in4} | Hard-coded values present in use constant field |
| Get Current Date and Time | Input Variable | Field_1 | | \${in1} | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustKeystore | OO_TRUST_KEYSTORE_PATH | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Resource Provider Details | Input Variable | providerId | providerId | \${RSC_PROVIDER_ID} | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | async | | false | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | virtualMachine | vmName | | Input variable name and Assign from values are not identical |

| | | | | | |
|-----------------|----------------|--------------------|----------|--|--|
| Delete Snapshot | Input Variable | removeAllSnapshots | | true | Hard-coded values present in use constant field |
| Create Snapshot | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Create Snapshot | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Create Snapshot | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Create Snapshot | Input Variable | async | | false | Hard-coded values present in use constant field |
| Create Snapshot | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Create Snapshot | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Create Snapshot | Input Variable | virtualMachine | vmName | | Input variable name and Assign from values are not identical |
| Create Snapshot | Input Variable | snapshotName | | HCM Snapshot | Hard-coded values present in use constant field |
| Create Snapshot | Input Variable | description | | Snapshot taken by HCM on \${currentDateTime} | Hard-coded values present in use constant field |
| Create Snapshot | Input Variable | snapshotMem | | true | Hard-coded values present in use constant field |
| Create Snapshot | Input Variable | quiesce | | true | Hard-coded values present in use constant field |
| Get Snapshot | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get Snapshot | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Snapshot | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Get Snapshot | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Get Snapshot | Input Variable | virtualMachine | vmName | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------|----------------|------------------------|------------------------|---------------------------|--|
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to create Snapshot | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to create Snapshot | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustKeystore | OO_TRUST_KEYSTORE_PATH | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Resource Provider Details | Input Variable | providerId | providerId | \${RSC_PROVIDER_ID} | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | async | | false | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Delete Snapshot | Input Variable | virtualMachine | vmName | | Input variable name and Assign from values are not identical |
| Delete Snapshot | Input Variable | removeAllSnapshots | | true | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------------|----------------|------------------------|------------------------|--|--|
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Delete Snapshot | Hard-coded values present in use constant field |
| SA Get Properties | Input Variable | providerId | SAProviderId | | Input variable name and Assign from values are not identical |
| IPAM Get Properties (Backup Nic) | Input Variable | providerId | ipamProviderId | | Input variable name and Assign from values are not identical |
| IPAM Reserve Next available IP | Input Variable | url | | https://\${ipamHost}:\${ipamPort} | Hard-coded values present in use constant field |
| IPAM Reserve Next available IP | Input Variable | hostname | VMName | \${VMName}-b | Input variable name and Assign from values are not identical |
| IPAM Reserve Next available IP | Input Variable | hostname | VMName | \${VMName}-b | Hard-coded values present in use constant field |
| IPAM Reserve Next available IP | Input Variable | username | ipamUsername | | Input variable name and Assign from values are not identical |
| IPAM Reserve Next available IP | Input Variable | password | ipamPasword | | Input variable name and Assign from values are not identical |
| IPAM Reserve Next available IP | Input Variable | network | subnet | | Input variable name and Assign from values are not identical |
| Update Backup NIC Properties | Input Variable | parentComponentId | serverComponentId | | Input variable name and Assign from values are not identical |
| Update Backup NIC Properties | Input Variable | childComponentName | | Backup NIC | Hard-coded values present in use constant field |
| Update Backup NIC Properties | Input Variable | jsonObject | | { "IP_ADDRESS": "\${nextIp}", "GATEWAY": "\${gatewayIp}", "SUBNETMASK": "\${subnetMask}", "VLAN_ID": "\${vLan}", "name": "\${hostRecord}", "domain_name": "\${zone}" } | Hard-coded values present in use constant field |
| Get Details of NIC 2 | Input Variable | host | vcenterHost | | Input variable name and Assign from values are not identical |
| Get Details of NIC 2 | Input Variable | user | vcenterUsername | | Input variable name and Assign from values are not identical |

| | | | | | |
|----------------------|----------------|------------------|-----------------|-------|--|
| Get Details of NIC 2 | Input Variable | password | vcenterPassword | | Input variable name and Assign from values are not identical |
| Get Details of NIC 2 | Input Variable | port | vcenterPort | | Input variable name and Assign from values are not identical |
| Get Details of NIC 2 | Input Variable | protocol | vcenterProtocol | | Input variable name and Assign from values are not identical |
| Get Details of NIC 2 | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Get Details of NIC 2 | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Get Details of NIC 2 | Input Variable | virtualMachine | VMName | | Input variable name and Assign from values are not identical |
| Get Details of NIC 2 | Input Variable | vmDatacenter | dataCenter | | Input variable name and Assign from values are not identical |
| Get Details of NIC 2 | Input Variable | deviceNumber | | 2 | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | host | vcenterHost | | Input variable name and Assign from values are not identical |
| Configure NIC | Input Variable | port | vcenterPort | 443 | Input variable name and Assign from values are not identical |
| Configure NIC | Input Variable | port | vcenterPort | 443 | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | protocol | vcenterProtocol | | Input variable name and Assign from values are not identical |
| Configure NIC | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | async | | false | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | vmDatacenter | dataCenter | | Input variable name and Assign from values are not identical |
| Configure NIC | Input Variable | deviceNumber | | 2 | Hard-coded values present in use constant field |

| | | | | | |
|------------------------|----------------|------------------------|------------------------|--|--|
| Configure NIC | Input Variable | netPortGroup | vLan | | Input variable name and Assign from values are not identical |
| Configure NIC | Input Variable | netMacGeneration | | Manual | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | connect | | true | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | connectAtPowerOn | | true | Hard-coded values present in use constant field |
| Configure NIC | Input Variable | user | vcenterUsername | | Input variable name and Assign from values are not identical |
| Configure NIC | Input Variable | password | vcenterPassword | | Input variable name and Assign from values are not identical |
| Configure NIC | Input Variable | virtualMachine | VMName | | Input variable name and Assign from values are not identical |
| Vcenter Get Properties | Input Variable | providerId | vcenterProviderId | | Input variable name and Assign from values are not identical |
| Configure VM Interface | Input Variable | coreHost | SACore | | Input variable name and Assign from values are not identical |
| Configure VM Interface | Input Variable | corePort | SAPort | | Input variable name and Assign from values are not identical |
| Configure VM Interface | Input Variable | coreProtocol | SAProtocol | | Input variable name and Assign from values are not identical |
| Configure VM Interface | Input Variable | coreUsername | SAUsername | | Input variable name and Assign from values are not identical |
| Configure VM Interface | Input Variable | corePassword | SAPassword | | Input variable name and Assign from values are not identical |
| Configure VM Interface | Input Variable | script | script | Add IPAM Backup NIC | Hard-coded values present in use constant field |
| Configure VM Interface | Input Variable | args | args | -t \${VMName} -s "ConfigureBackupInterface_\${platform}" -a "\${nextIp}\${subnetMask}" -z 15 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Flow Failed to add BackUp NIC | Hard-coded values present in use constant field |

| | | | | | |
|---------------------|----------------|------------------------|------------------------|---|--|
| Sleep | Input Variable | seconds | | 90 | Hard-coded values present in use constant field |
| Update DNS Resolver | Input Variable | constantFailureMessage | constantFailureMessage | Flow failed to Update DNS Resolver Configuration | Hard-coded values present in use constant field |
| Update DNS Resolver | Input Variable | sourceCode | | NAMESERVERS=\${PROXY/NAMESERVERS} SEARCH_HOSTS=\${PROXY/SEARCH-HOSTS} configure_dns_name_server(){ IFS="," names=\$(sudo grep nameserver /etc/resolv.conf) for nameserver in \$NAMESERVERS; do nameserver_exists=\$(sudo grep nameserver /etc/resolv.conf grep \$nameserver) if ["\$nameserver_exis ... | Hard-coded values present in use constant field |
| Update DNS Resolver | Input Variable | sourceCodeType | | SH | Hard-coded values present in use constant field |
| Update DNS Resolver | Input Variable | timeout | | 0 | Hard-coded values present in use constant field |
| Update DNS Resolver | Input Variable | sa_core_host | SACore | | Input variable name and Assign from values are not identical |
| Update DNS Resolver | Input Variable | sa_user | SAUsername | | Input variable name and Assign from values are not identical |
| Update DNS Resolver | Input Variable | sa_password | SAPassword | | Input variable name and Assign from values are not identical |
| Update DNS Resolver | Input Variable | saPort | SAPort | | Input variable name and Assign from values are not identical |
| Update DNS Resolver | Input Variable | saVersion | SACoreVersion | | Input variable name and Assign from values are not identical |
| Update DNS Resolver | Input Variable | target_host | VMName | | Input variable name and Assign from values are not identical |
| Flow Inputs | Input Variable | vmIdentifierType | vmIdentifierType | name | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | cpuValue | oldcpu | | Input variable name and Assign from values are not identical |

| | | | | | |
|-----------------|----------------|--------------|--------------|-------|--|
| Set CPU Count | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Set CPU Count | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Set CPU Count | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Set CPU Count | Input Variable | async | | false | Hard-coded values present in use constant field |
| Set CPU Count | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Set CPU Count | Input Variable | vmCpuCount | currentCpu | | Input variable name and Assign from values are not identical |
| Get Power State | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get Power State | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Power State | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Shutdown Guest | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Shutdown Guest | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Shutdown Guest | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Get Power State | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get Power State | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Power State | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 30 | Hard-coded values present in use constant field |
| Set Power State | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Set Power State | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------------|----------------|------------------------|------------------------|---------------------|--|
| Set Power State | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Set Power State | Input Variable | async | | false | Hard-coded values present in use constant field |
| Set Power State | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Set Power State | Input Variable | vmPowerState | | poweredOn | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 60 | Hard-coded values present in use constant field |
| Get Resource Provider Details | Input Variable | providerId | providerID | \${RSC_PROVIDER_ID} | Input variable name and Assign from values are not identical |
| Get Resource Provider Details | Input Variable | providerId | providerID | \${RSC_PROVIDER_ID} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Flex CPU | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Flex CPU | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | resourceType | | CPU | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | usedValue | resultCpu | | Input variable name and Assign from values are not identical |
| Update Resource Pool Utilization | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | port | vcenterPort | | Input variable name and Assign from values are not identical |
| Extend Disk | Input Variable | protocol | vcenterProtocol | | Input variable name and Assign from values are not identical |

| | | | | | |
|----------------------------------|----------------|------------------------|------------------------|-----------------------|--|
| Extend Disk | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | async | | false | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | vmIdentifierType | vmIdentifierType | NAME | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | vmDatacenter | dataCenter | | Input variable name and Assign from values are not identical |
| Extend Disk | Input Variable | deviceNumber | deviceNumber | 2 | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | host | vcenterHost | | Input variable name and Assign from values are not identical |
| Extend Disk | Input Variable | user | vcenterUsername | | Input variable name and Assign from values are not identical |
| Extend Disk | Input Variable | password | vcenterPassword | | Input variable name and Assign from values are not identical |
| Extend Disk | Input Variable | diskSize | currentSize | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Flex Disk 2 | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | resourceType | | STORAGE | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | usedValue | resultDisk | | Input variable name and Assign from values are not identical |
| Update Resource Pool Utilization | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | port | vcenterPort | | Input variable name and Assign from values are not identical |

| | | | | | |
|----------------------------------|----------------|------------------------|------------------------|-----------------------|--|
| Extend Disk | Input Variable | protocol | vcenterProtocol | | Input variable name and Assign from values are not identical |
| Extend Disk | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | async | | false | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | vmIdentifierType | vmIdentifierType | NAME | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | vmDatacenter | dataCenter | | Input variable name and Assign from values are not identical |
| Extend Disk | Input Variable | deviceNumber | deviceNumber | 3 | Hard-coded values present in use constant field |
| Extend Disk | Input Variable | host | vcenterHost | | Input variable name and Assign from values are not identical |
| Extend Disk | Input Variable | user | vcenterUsername | | Input variable name and Assign from values are not identical |
| Extend Disk | Input Variable | password | vcenterPassword | | Input variable name and Assign from values are not identical |
| Extend Disk | Input Variable | diskSize | currentSize | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Flex Disk 3 | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | resourceType | | STORAGE | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | usedValue | resultDisk | | Input variable name and Assign from values are not identical |
| Update Resource Pool Utilization | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Flow Inputs | Input Variable | vmIdentifierType | vmIdentifierType | name | Hard-coded values present in use constant field |

| | | | | | |
|---------------------|----------------|--------------|--------------|-----------------|--|
| Get User Identifier | Input Variable | csaUser | HCM/CSA_USER | \${CSA_OO_USER} | Hard-coded values present in use constant field |
| Get Power State | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get Power State | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Power State | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Shutdown Guest | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Shutdown Guest | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Shutdown Guest | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | async | | false | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Set Memory Size | Input Variable | vmMemorySize | memoryMB | | Input variable name and Assign from values are not identical |
| Set Power State | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Set Power State | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Set Power State | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Set Power State | Input Variable | async | | false | Hard-coded values present in use constant field |
| Set Power State | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------------|----------------|------------------------|------------------------|-----------------------|--|
| Set Power State | Input Variable | vmPowerState | | poweredOn | Hard-coded values present in use constant field |
| Get Power State | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get Power State | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Power State | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 30 | Hard-coded values present in use constant field |
| Get Resource Provider Details | Input Variable | providerId | providerID | \${RSC_PROVIDER_ID} | Input variable name and Assign from values are not identical |
| Get Resource Provider Details | Input Variable | providerId | providerID | \${RSC_PROVIDER_ID} | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | | 60 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Flex Memory | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Flex Memory | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | resourceType | | MEMORY | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | usedValue | resultmemsize | | Input variable name and Assign from values are not identical |
| Update Resource Pool Utilization | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Update Resource Pool Utilization | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |

| | | | | | |
|-------------------|----------------|----------------------------|--|---|---|
| Reverse Lifecycle | Input Variable | url | | \${HCM/HCM-CSA-URL} }rest/lifecycleengine/ex ecute?userIdentier=\${ userIdentifier} | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | contentType | | application/xml | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | body | | <?xml version="1.0" encoding="UTF-8" standalone="yes"?> <Li fecycleExecutionReque st> <reverse>true</reve rse> <serviceCompone ntId>\${SVC_COMPON ENT_ID}</serviceComp onentId> <serviceInstan celd>\${SVC_INSTANC E_ID}</serviceInstancel d> <targetStateName> RESERVED</targetStat eName> </LifecycleExe cutionRequest> | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | connectionsMaxPerRou te | | 2 | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|--------------------------|--|--|---|
| Reverse Lifecycle | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Reverse Lifecycle | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | url | | \${HCM/HCM-CSA-URL}rest/lifecycleengine | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | queryParams | | userIdentifier=\${userIdentity}&serviceInstanceId;=\${SVC_INSTANCE_ID} | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | headers | | Accept:application/xml | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|---------------------------|-----------------------|---|--|
| Get Life Cycle Status | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Count | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Count | Input Variable | to | EPP_HPSA_RETRY | 150 | Input variable name and Assign from values are not identical |
| Count | Input Variable | to | EPP_HPSA_RETRY | 150 | Hard-coded values present in use constant field |
| Count | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Count | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | EPP_UNREACHABLE_SLEEP | 60 | Input variable name and Assign from values are not identical |
| Sleep | Input Variable | seconds | EPP_UNREACHABLE_SLEEP | 60 | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | url | | \${HCM/HCM-CSA-URL}rest/lifecycleengine/execute?userIdentier=\${userIdentier} | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |

| | | | | | |
|------------------|----------------|--------------------------|--|--|---|
| Deploy Lifecycle | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | contentType | | application/xml | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | body | | <?xml version="1.0" encoding="UTF-8" standalone="yes"?> <LifecycleExecutionRequest> <reverse>false</reverse> <serviceComponentId>\${SVC_COMPONENT_ID}</serviceComponentId> <serviceInstanceId>\${SVC_INSTANCE_ID}</serviceInstanceId> <targetStateName>DEPLOYED</targetStateName> </LifecycleExecutionRequest> | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | method | | POST | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Deploy Lifecycle | Input Variable | formParamsAreURLEncoded | | false | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|----------------------|-----------------------|--|--|
| Deploy Lifecycle | Input Variable | requestCharacterSet | | ISO-8859-1 | Hard-coded values present in use constant field |
| Sleep | Input Variable | seconds | EPP_UNREACHABLE_SLEEP | 60 | Input variable name and Assign from values are not identical |
| Sleep | Input Variable | seconds | EPP_UNREACHABLE_SLEEP | 60 | Hard-coded values present in use constant field |
| Count | Input Variable | from | | 1 | Hard-coded values present in use constant field |
| Count | Input Variable | to | | 150 | Hard-coded values present in use constant field |
| Count | Input Variable | incrementBy | | 1 | Hard-coded values present in use constant field |
| Count | Input Variable | reset | | false | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | url | | \$(HCM/HCM-CSA-URL)rest/lifecycleengine | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | authType | | Basic | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | queryParams | | userIdentifier=\${userIdentifier}&serviceInstanceId;=\${SVC_INSTANCE_ID} | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | headers | | Accept:application/xml | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | preemptiveAuth | | true | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | trustAllRoots | | true | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | proxyPort | | 8080 | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | x509HostnameVerifier | | allow_all | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | connectTimeout | | 0 | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | socketTimeout | | 0 | Hard-coded values present in use constant field |

| | | | | | |
|-----------------------|----------------|---------------------------|------------------------|-----------------------|--|
| Get Life Cycle Status | Input Variable | useCookies | | true | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | keepAlive | | true | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | connectionsMaxPerRoute | | 2 | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | connectionsMaxTotal | | 20 | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | followRedirects | | true | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | queryParamsAreURLEncoded | | false | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | queryParamsAreFormEncoded | | true | Hard-coded values present in use constant field |
| Get Life Cycle Status | Input Variable | method | | GET | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Re-Build VM | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustKeystore | OO_TRUST_KEYSTORE_PATH | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Reboot Server | Input Variable | vmPowerState | vmPowerState | poweredOn | Hard-coded values present in use constant field |
| Reboot Server | Input Variable | vmID | vmid | | Input variable name and Assign from values are not identical |

| | | | | | |
|-------------------------------|----------------|------------------------|------------------------|------------------------------|--|
| Get Resource Provider Details | Input Variable | providerId | providerId | \${RSC_PROVIDER_ID} | Hard-coded values present in use constant field |
| Get Power State | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Get Power State | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Get Power State | Input Variable | vmIdentifierType | vmIdentifierType | VMID | Hard-coded values present in use constant field |
| Get Power State | Input Variable | closeSession | closeSession | true | Hard-coded values present in use constant field |
| Get Power State | Input Variable | virtualMachine | vmid | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | virtualMachine | vmName | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | getDetailed | | true | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | connectionTimeout | | 30 | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | socketTimeout | | 30 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to restart the server | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Hard-coded values present in use constant field |

| | | | | | |
|-------------------------------|----------------|------------------------|------------------------|----------------------------|--|
| Get User Identifier | Input Variable | trustKeystore | OO_TRUST_KEYSTORE_PATH | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Resource Provider Details | Input Variable | providerId | providerId | \${RSC_PROVIDER_ID} | Hard-coded values present in use constant field |
| Revert To Snapshot | Input Variable | port | port | 443 | Hard-coded values present in use constant field |
| Revert To Snapshot | Input Variable | protocol | protocol | https | Hard-coded values present in use constant field |
| Revert To Snapshot | Input Variable | closeSession | closeSession | false | Hard-coded values present in use constant field |
| Revert To Snapshot | Input Variable | async | | false | Hard-coded values present in use constant field |
| Revert To Snapshot | Input Variable | taskTimeOut | | 800 | Hard-coded values present in use constant field |
| Revert To Snapshot | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Revert To Snapshot | Input Variable | virtualMachine | vmName | | Input variable name and Assign from values are not identical |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Restore Snapshot | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustKeystore | OO_TRUST_KEYSTORE_PATH | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |

| | | | | | |
|-------------------------------|----------------|------------------------|------------------------|----------------------------|--|
| Get Resource Provider Details | Input Variable | providerId | providerId | \${RSC_PROVIDER_ID} | Hard-coded values present in use constant field |
| vCenter Set Power State VM | Input Variable | vmPowerState | vmPowerState | poweredOn | Hard-coded values present in use constant field |
| vCenter Set Power State VM | Input Variable | vmID | vmid | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | virtualMachine | vmName | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | getDetailed | | true | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | connectionTimeout | | 30 | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | socketTimeout | | 30 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Start the server | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustKeystore | OO_TRUST_KEYSTORE_PATH | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| Get Resource Provider Details | Input Variable | providerId | providerId | \${RSC_PROVIDER_ID} | Hard-coded values present in use constant field |

| | | | | | |
|----------------------------|----------------|------------------------|------------------------|---------------------------|--|
| vCenter Set Power State VM | Input Variable | vmPowerState | vmPowerState | poweredOff | Hard-coded values present in use constant field |
| vCenter Set Power State VM | Input Variable | vmID | vmid | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | virtualMachine | vmName | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | getDetailed | | true | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | connectionTimeout | | 30 | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | socketTimeout | | 30 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Stop the server | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | trustAllRoots | TRUST_ALL_ROOTS | false | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | x509HostnameVerifier | HOSTNAME_VERIFIER | strict | Hard-coded values present in use constant field |
| Get User Identifier | Input Variable | trustKeystore | OO_TRUST_KEYSTORE_PATH | | Input variable name and Assign from values are not identical |
| Get User Identifier | Input Variable | csaUser | CSA_OO_USER | | Input variable name and Assign from values are not identical |
| vCenter Set Power State VM | Input Variable | vmPowerState | vmPowerState | suspended | Hard-coded values present in use constant field |
| vCenter Set Power State VM | Input Variable | vmID | vmid | | Input variable name and Assign from values are not identical |

| | | | | | |
|-------------------------------|----------------|------------------------|------------------------|---------------------------|--|
| Get Resource Provider Details | Input Variable | providerId | providerId | \${RSC_PROVIDER_ID} | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | closeSession | | false | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | vmIdentifierType | | name | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | virtualMachine | vmName | | Input variable name and Assign from values are not identical |
| Get Virtual Machine | Input Variable | getDetailed | | true | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | connectionTimeout | | 30 | Hard-coded values present in use constant field |
| Get Virtual Machine | Input Variable | socketTimeout | | 30 | Hard-coded values present in use constant field |
| Error Handling | Input Variable | oorunId | oorunId | \${run_id} | Hard-coded values present in use constant field |
| Error Handling | Input Variable | constantFailureMessage | constantFailureMessage | Failed to Stop the server | Hard-coded values present in use constant field |

Analysis of System Property Used:

| Property Name | OO Path | Where it is used |
|-----------------|-----------------------|-----------------------------|
| AD-EXT-BASE-DN | AD/AD-EXT-BASE-DN | not used |
| AD-EXT-HOSTNAME | AD/AD-EXT-HOSTNAME | Get Supplemental Account |
| AD-EXT-PASSWORD | AD/AD-EXT-PASSWORD | Get CustomSpec XML |
| AD-EXT-PORT | AD/AD-EXT-PORT | Get Supplemental Account |
| AD-INT-BASE-DN | AD/AD-INT-BASE-DN | not used |
| AD-INT-HOSTNAME | AD/AD-INT-HOSTNAME | Get Supplemental Account |
| AD-INT-PASSWORD | AD/AD-INT-PASSWORD | Get CustomSpec XML |
| AD-INT-PORT | AD/AD-INT-PORT | Get Supplemental Account |
| DB-NAME | DB-CSA/DB-NAME | VSM Registration 2.0 |
| DB-PORT | DB-CSA/DB-PORT | VSM Registration 2.0 |
| DB-SERVER-NAME | DB-CSA/DB-SERVER-NAME | VSM Registration 2.0 |
| DB-NAME | DB-CSAEX/DB-NAME | Get guestOS From DB |
| DB-NAME | DB-CSAEX/DB-NAME | Get VC Cluster and Template |
| DB-NAME | DB-CSAEX/DB-NAME | IPAM Generate Hostname |
| DB-NAME | DB-CSAEX/DB-NAME | Cancel Subscription Service |
| DB-NAME | DB-CSAEX/DB-NAME | Execute Public Action |

| | | |
|-------------------------------------|---|-----------------------------|
| DB-NAME | DB-CSAEX/DB-NAME | Get Subscription Status |
| DB-NAME | DB-CSAEX/DB-NAME | Get VM Threshold DiskSpace |
| DB-NAME | DB-CSAEX/DB-NAME | VSM Registration |
| DB-NAME | DB-CSAEX/DB-NAME | VSM Registration 2.0 |
| DB-PORT | DB-CSAEX/DB-PORT | Get guestOS From DB |
| DB-PORT | DB-CSAEX/DB-PORT | Get VC Cluster and Template |
| DB-PORT | DB-CSAEX/DB-PORT | IPAM Generate Hostname |
| DB-PORT | DB-CSAEX/DB-PORT | Cancel Subscription Service |
| DB-PORT | DB-CSAEX/DB-PORT | Execute Public Action |
| DB-PORT | DB-CSAEX/DB-PORT | Get Subscription Status |
| DB-PORT | DB-CSAEX/DB-PORT | Get VM Threshold DiskSpace |
| DB-PORT | DB-CSAEX/DB-PORT | VSM Registration |
| DB-PORT | DB-CSAEX/DB-PORT | VSM Registration 2.0 |
| DB-SERVER-NAME | DB-CSAEX/DB-SERVER-NAME | Get guestOS From DB |
| DB-SERVER-NAME | DB-CSAEX/DB-SERVER-NAME | Get VC Cluster and Template |
| DB-SERVER-NAME | DB-CSAEX/DB-SERVER-NAME | IPAM Generate Hostname |
| DB-SERVER-NAME | DB-CSAEX/DB-SERVER-NAME | Cancel Subscription Service |
| DB-SERVER-NAME | DB-CSAEX/DB-SERVER-NAME | Execute Public Action |
| DB-SERVER-NAME | DB-CSAEX/DB-SERVER-NAME | Get Subscription Status |
| DB-SERVER-NAME | DB-CSAEX/DB-SERVER-NAME | Get VM Threshold DiskSpace |
| DB-SERVER-NAME | DB-CSAEX/DB-SERVER-NAME | VSM Registration |
| DB-SERVER-NAME | DB-CSAEX/DB-SERVER-NAME | VSM Registration 2.0 |
| HCM-API-URL | HCM/HCM-API-URL | Get Subscription Status |
| HCM-API-URL | HCM/HCM-API-URL | Add Supplemental User |
| HCM-CSA-URL | HCM/HCM-CSA-URL | not used |
| HCM-DELETE-RESOURCES | HCM/HCM-DELETE-RESOURCES | IPAM Remove Host Record |
| HCM-DELETE-RESOURCES | HCM/HCM-DELETE-RESOURCES | Release BackUp NIC IP |
| HCM-DELETE-RESOURCES | HCM/HCM-DELETE-RESOURCES | Windows unjoin AD |
| HCM-DELETE-RESOURCES | HCM/HCM-DELETE-RESOURCES | Deactivate SA Agent |
| HCM-DELETE-RESOURCES | HCM/HCM-DELETE-RESOURCES | OA Agent uninstall |
| HCM-DELETE-RESOURCES | HCM/HCM-DELETE-RESOURCES | Retire SMAX Device |
| HCM-DELETE-RESOURCES | HCM/HCM-DELETE-RESOURCES | Undeploy Compute |
| HCM-IDM-URL | HCM/HCM-IDM-URL | not used |
| HCM-MSSQL-SUBSCRIPTION-OWNER-EMAIL | HCM/HCM-MSSQL-SUBSCRIPTION-OWNER-EMAIL | not used |
| HCM-ORACLE-SUBSCRIPTION-OWNER-EMAIL | HCM/HCM-ORACLE-SUBSCRIPTION-OWNER-EMAIL | not used |
| HCM-REST-URL | HCM/HCM-REST-URL | not used |
| PROVIDER-TENANT-NAME | HCM/PROVIDER-TENANT-NAME | not used |
| TENANT-NAME | HCM/TENANT-NAME | Cancel VM |
| TENANT-NAME | HCM/TENANT-NAME | Create Subscription Service |
| VM-NAME-PREFIX | HCM/VM-NAME-PREFIX | IPAM Generate Hostname |
| NAMESERVERS | PROXY/NAMESERVERS | not used |

| | | |
|----------------------------|----------------------------------|-------------------------------------|
| PROXY-DEV | PROXY/PROXY-DEV | SYNC vCenter Resource Pool Capacity |
| SEARCH-HOSTS | PROXY/SEARCH-HOSTS | not used |
| OA Agent Uninstall Linux | SA/OA Agent Uninstall Linux | not used |
| OA Agent Unisntall Windows | SA/OA Agent Unisntall Windows | not used |
| SCRIPT-TIMEOUT | SA/SCRIPT-TIMEOUT | OA Agent Uninstall Linux |
| SCRIPT-TIMEOUT | SA/SCRIPT-TIMEOUT | Remove OA version11 |
| SCRIPT-TIMEOUT | SA/SCRIPT-TIMEOUT | Update Server Properties |
| SCRIPT-TIMEOUT | SA/SCRIPT-TIMEOUT | OA Agent Uninstall Windows |
| TARGET-HOSTS | SA/TARGET-HOSTS | VSM Registration 2.0 |
| TARGET-HOSTS | SA/TARGET-HOSTS | Enable Backup NIC |
| OA Policy ID Linux | SA Policy/OA Policy ID Linux | not used |
| OA Policy ID Windows | SA Policy/OA Policy ID Windows | not used |
| OA Policy Name Linux | SA Policy/OA Policy Name Linux | not used |
| OA Policy Name Windows | SA Policy/OA Policy Name Windows | not used |
| SMAX-HOSTNAME | SMAX/SMAX-HOSTNAME | not used |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Create Device |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Create SMAX Subscription |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Cancel Subscription Service |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Get Person Details |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Create Subscription Service |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Get SSO Token |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Retire Device |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Get UserId from Email |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Get UserId from Username |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Execute Public Action |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Update Device Comments |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Update SystemElement Comments |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Get Subscription Status |
| SMAX-PROXY-HOST | SMAX/SMAX-PROXY-HOST | Create SMAX Device |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Create Device |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Create SMAX Subscription |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Cancel Subscription Service |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Get Person Details |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Create Subscription Service |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Get SSO Token |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Retire Device |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Get UserId from Email |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Get UserId from Username |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Execute Public Action |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Update Device Comments |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Update SystemElement Comments |
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Get Subscription Status |

| | | |
|-----------------------------|----------------------------------|-------------------------------------|
| SMAX-PROXY-PORT | SMAX/SMAX-PROXY-PORT | Create SMAX Device |
| SMAX-TENANT-ID | SMAX/SMAX-TENANT-ID | not used |
| SMAX-TRUSTALL-ROOTS | SMAX/SMAX-TRUSTALL-ROOTS | Get SSO Token |
| SMAX-X509-HOSTNAME-VERIFIER | SMAX/SMAX-X509-HOSTNAME-VERIFIER | Get SSO Token |
| HOST | VCENTER/HOST | SYNC vCenter Resource Pool Capacity |

Analysis of System Account Used:

| Account Name | OO Path |
|------------------------------|----------------------------------|
| AD-EXT-SERVICE-ACCOUNT | AD/AD-EXT-SERVICE-ACCOUNT |
| CSA-CREDENTIALS | DB/CSA-CREDENTIALS |
| CSAEX-CREDENTIALS | DB/CSAEX-CREDENTIALS |
| HCM-ADMIN-ACCOUNT | HCM/HCM-ADMIN-ACCOUNT |
| HCM-CONSUMER-ACCOUNT | HCM/HCM-CONSUMER-ACCOUNT |
| HCM-IDM-ACCOUNT | HCM/HCM-IDM-ACCOUNT |
| HCM-SERVICE-ACCOUNT-EXTERNAL | HCM/HCM-SERVICE-ACCOUNT-EXTERNAL |
| HCM-SERVICE-ACCOUNT | HCM/HCM-SERVICE-ACCOUNT |
| SMAX-SERVICE-ACCOUNT | SMAX/SMAX-SERVICE-ACCOUNT |
| VCENTER-SERVICE-ACCOUNT | vCenter/VCENTER-SERVICE-ACCOUNT |