On the Validity of Metamorphic Relations for Knowledge-Conflict Testing of Retrieval-Augmented Generation Systems

Aditi Saxena, Suvidh Jain, and Aryan Garg

***Abstract*—Retrieval-augmented generation (RAG) systems answer questions using documents that they look up. These documents change over time, so it is hard to know what the correct answer should be after a change. Metamorphic testing deals with this problem by comparing the answers to two related inputs, instead of checking each answer against a fixed answer key. A framework presented at ASE 2026 uses this idea. Its counterfactual-noise (CN) operator adds a passage that contradicts a fact, and it expects the answer to change. This operator produces the highest violation rates in that framework. However, if two values conflict and nothing says which one is current, there is no single correct answer. In this paper, we ask whether such tests can tell faults apart from correct behaviour. We define four validity criteria (decidability, value alignment, placement invariance and provenance). We check the released code of the framework against them, and we re-analyse the outputs released by its authors in a pre-registered study. The code marks a CN test as passed whenever the answer changes, and it never compares the answer with the injected value. In the released outputs, at least 77.4% (460/594) of the reported CN violations are answers that match the ground truth of the dataset. In addition, 26.0% (694/2,671) of the CN mutants are refusals by the model that was asked to write them. We then propose MR-Provenance-Swap. It gives both conflicting values a date and swaps only the dates, so that the expected answer follows from the input. We tested it on 392 questions built from real Wikipedia edits and on synthetic counterfactuals, with three open models. For the two smaller models, the published test reports violation rates of 8–35%, while our test finds date-insensitive or inverted answers in 36–51% of the cases, mostly on different questions ($|\varphi| \leq 0.16$). The largest model lists both values or abstains in 84–86% of the dated conflicts. Our pre-registered hypothesis that the two tests disagree for all three models was not supported. Our results suggest that tests with conflicting facts need a signal of which value is current, such as a date, and an oracle that checks the answer against the injected value.**

***Index Terms*—Metamorphic testing, test oracle, retrieval-augmented generation, knowledge conflict, mutation testing, large language models.**

I. Introduction

RETRIEVAL-AUGMENTED generation (RAG) systems answer questions in two steps. First, they look up passages in a collection of documents, called the corpus. Then a language model writes an answer based on these passages. In real systems, the corpus keeps changing. Prices are updated, rules are replaced, and documents are added or removed. This makes testing hard. A test usually compares the answer with a stored correct answer, but that stored answer can become wrong when the documents change. The question of how to know the correct output of a test is known as the test-oracle problem [1].

Metamorphic testing (MT) is a common way to deal with this problem [2]. Instead of checking one answer against a known value, MT runs the system twice: once on an original input (the source test case), and once on a changed input (the follow-up test case). It then checks that the two answers relate in an expected way. This expected relationship is called a metamorphic relation. A case in which it does not hold is called a violation, and it is reported as a fault.

Kim et al. [3] recently used MT to test RAG systems whose documents change. Their framework has 11 ways of changing the input, called mutation operators, and two kinds of metamorphic relations. Over 28,500 changed inputs (mutants), it reports violation rates of 4.9–10.2%. One operator, counterfactual noise (CN), adds a passage that contradicts the fact needed to answer the question. It gives the highest violation rate on every dataset and in both of the framework's settings, up to 27.6% on VQAonBD in pre-chunk mode. The authors also released their code and outputs, which made our analysis possible.

A violation only shows a fault if the relation describes something that a correct system must always do [2]. Tests with conflicting facts can break this rule. Imagine a company report that gives revenue as $2,111, and an added passage that says the figure was $1,600. If nothing shows which value is current, one careful system might keep $2,111, another might switch to $1,600, and a third might mention both. All three answers are reasonable. A test that demands only one of them is therefore not a reliable sign of a fault.

In this paper, we study whether tests with conflicting facts are valid, using the CN test of Kim et al. [3] as a case study. We first read the paper and its released code. We then re-analyse the outputs that the authors released. Finally, we run an experiment with a new test that we propose. Most of our analyses were pre-registered. This means that we wrote down our hypotheses and pass or fail thresholds before we looked at or generated the data. Our contributions are:

- Four validity criteria for tests with conflicting facts: decidability, value alignment, placement invariance and provenance (Section III).
- A check of the ASE 2026 framework against these criteria, with each finding traced to the released code or to the text of the paper (Section V).

The authors are with [PENDING: affiliation to be confirmed].

- A pre-registered analysis of the released outputs, which measures how much these findings change the published results (Section VI).
- MR-Provenance-Swap (MR-PS), a new test whose expected answer can be worked out from the input. We compare it with the published test on real Wikipedia edits and on synthetic counterfactuals, using three open models (Section VII).

The rest of the paper is organised as follows. Section II explains metamorphic testing, conflicting facts in RAG, and the framework we study. Section III defines the validity criteria, and Section IV describes how we designed the study. Sections V–VII present the results, and Section VIII discusses them. Section IX covers threats to validity, Section X related work, and Section XI concludes.

II. Background

A. Metamorphic testing

In MT, a source test case x is changed into a follow-up test case x'. A metamorphic relation (MR) says how the two outputs, $S(x)$ and $S(x')$, should relate. A simple example is a sorting program: if we shuffle the input list, the sorted output must stay the same. MRs are built from necessary properties, which are things that must hold for a correct program [2]. Segura et al. [2] also mention *expected* properties, in their summary of work on machine-learning classifiers. A violation of a necessary property is caused by a fault. A violation of an expected property only shows a difference between what the system does and what the user expects. So, before we report a violation as a fault, we need to know which kind of property the relation describes. When MT is used to evaluate a system, the change made to the input is often called a mutation, and the changed input is called a mutant.

B. RAG systems when documents change

When a document is updated, the index of a RAG system might hold the old version, the new version, or both. It is well known that old information can lead to wrong answers. For example, HoH [4] builds question-answer pairs from the differences between Wikipedia snapshots. It shows that old passages lower answer accuracy, even when the current passage is also retrieved. Ahmed et al. [5] report that old documents can turn a correct answer into a wrong one, and that "dates alone produce only modest adaptation." On what a model should do, Cattan et al. [6] say that, when a conflict is caused by old information, models should "prioritize the up-to-date information … while optionally acknowledging the presence of outdated sources." WikiContradict [7] treats an answer that points out a real contradiction as the desired behaviour. These studies look at how systems behave. In this paper, we look at something different: whether tests can detect this behaviour correctly.

C. The framework we study

The framework of Kim et al. [3] changes the documents in one of two places: before they are split into small pieces called chunks (pre-chunk), or in the passages that the system has already retrieved (post-chunk). By default, it retrieves only the single best chunk ($k = 1$). It uses GPT-5-mini both to answer and to judge answers, and text-embedding-3-small to turn text into vectors for search. It is evaluated on five datasets (RepLiQA, and the T2-RAGBench parts ConvFinQA, FinQA, TAT-DQA and VQAonBD), with 300 starting questions each. A question is kept only if the model gets it wrong without the documents and the unchanged RAG system gets it right. In this way, the answers depend on the documents. The CN operator "prompts a separate LLM to generate a plausible counterfactual statement given the original fact with the user query."

For each mutant, a judge model decides whether the change keeps the meaning of the original (semantics-preserving) or changes it (semantics-altering). For preserving mutants, the test expects the same answer: $y' \approx y$. For altering mutants, the paper states: "We expect $y' \neq y$, specifically where y' aligns with the injected fact." On the four datasets with numeric answers, two answers count as equal if they are within 1% of each other. On RepLiQA, a language model judges whether two answers match. The paper also reports a repair step, in which faults are checked again after a fix has been applied.

III. Validity criteria for tests with conflicting facts

We use the following notation. Let q be a question, C a corpus, and $y = S(q, C)$ the answer of system S. A conflict mutation δ adds a passage d' that gives a different value $v' \neq y$ for the same fact. The follow-up answer is $y' = S(q, C \cup \{d'\})$, and the test $P(y, y', \delta)$ says what y' should be. We propose four criteria that such a test must meet before its violations can be treated as faults.

V1 Decidability. It must be possible to work out the expected answer from the follow-up input alone. Suppose that $C \cup \{d'\}$ contains both y and v', and that nothing shows which one is valid. Then following v', keeping y and reporting both are all reasonable. A test that demands one of them describes, at most, an expected property and not a necessary one. Without such information, the only answer we can demand is that the system points out the conflict or declines to answer.

V2 Value alignment. If a test demands that the answer changes to the new value, it must check that the new answer actually matches v' (or follows from it). Checking only that $y' \neq y$ is not enough. Such a check accepts wrong answers, and it fails every system that kept its original answer.

V3 Placement invariance. If it does not matter where the new passage appears, the result of the test should not depend on its position. LLMs are known to prefer evidence based on where it appears [8–10]. A result that depends on position may therefore reflect how the test was built, and not the system.

V4 Provenance. Provenance is information about where a value comes from or when it was valid. A test that demands an update is valid only if the input marks d' as the current value, for example with a date, a note saying that it replaces the earlier value, or a version number.

V1 and V4 are two sides of the same rule: we can only demand an update when the input shows which value is

current. V2 and V3 are about how to check the answer once the expected answer is clear. The criteria are not only for the framework we study. They apply to any test that adds information which conflicts with the original input.

IV. Study design

A. Research questions

We ask four research questions:

RQ1 Do the conflict tests of the ASE 2026 framework meet the validity criteria?
RQ2 How do the problems we find affect the published results?
RQ3 Does a test with a clear expected answer find faults that the published test misses?
RQ4 When the expected answer is clear, do synthetic counterfactuals give similar results to real updates?

We answer RQ1 by reading the paper and the released code, and RQ2 by re-analysing the released outputs. For RQ3 and RQ4, we run an experiment with a new test and three open models.

B. Type of study and link to the original study

In the terms of the ACM SIGSOFT Empirical Standards [11], our RQ2 analysis is an independent reproduction: we re-analyse the original data, and we add new measures. Our experiment for RQ3 and RQ4 is a conceptual extension, because it uses a different test, different models and different data. The original authors were not involved in our study. [PENDING: State whether the findings were shared with the original authors before submission, and summarise any response.]

C. Pre-registration and statistics

To avoid adjusting our analysis after seeing the results, we wrote down our hypotheses, measures and thresholds before we opened or generated the data. We also saved a fingerprint (hash) of each analysis script. Any analysis that we added later is marked as post hoc. For each proportion, we give a 95% confidence interval (Wilson method), which is the range in which the true value is likely to lie. Questions from the same Wikipedia page are related to each other. To account for this, we estimate differences between the two tests by resampling whole pages (a page-clustered bootstrap with 10,000 resamples). For RQ4, we resample whole questions instead. To measure how often the two tests flag the same cases, we use the φ coefficient, where values near zero mean that the two tests flag unrelated cases. Finally, we use the exact McNemar test for paired changes, and Fisher's exact test to compare two independent proportions.

V. RQ1: Checking the framework against the criteria

A. Method

We read the published paper [3] and its released code in full. The code is in a single commit, `597fd6582b`. We traced each finding to a file and line, or to a passage of the paper. We also checked that the arXiv version 2607.26843v1 is identical to the published version in every passage we quote. To avoid mistakes, a script checks every citation and quotation in this paper against saved copies of the sources. All 29 checks pass.

B. Findings

On the four numeric datasets, the test for altering mutants is written in `step3_mutation_campaign.py`, lines 746–748:

```
else: # semantics-altering mutation
   verdict = "SATISFIED" if not answers_match else "
       VIOLATED"
   # answers_match: mutated answer equals the
       ORIGINAL answer within 1%
```

In other words, the result depends only on whether the new answer differs from the old one. We could not find any place in the code where the answer is compared with the injected value. Table I lists this finding and the others, and shows which criterion each one concerns.

C. Answer to RQ1

The CN test does not meet V1 and V4, because the counterfactual has no provenance and because the paper describes the expected behaviour in more than one way. Its code does not meet V2 on any of the five datasets. The position of the counterfactual is fixed in the post-chunk setting (A5). Whether this changes the results is something we measure in Section VI.

VI. RQ2: Effect on the published results

A. Data and reproduction check

We analysed the outputs released for both settings and all five datasets: the original answers, the mutants, the test results, the ground-truth checks and the repair results. We saved a hash of our analysis script before opening the data. Afterwards, we made one change, knowing only the names of the files and fields. This change added a measure that we had defined but not yet written in code. As a first check, we counted the CN violations ourselves. Our counts match Table 1 of the paper in all ten combinations of dataset and setting.

B. Violations and the ground truth

This analysis was pre-registered. Of the 461 CN violations for altering mutants, 460 are answers that match the ground truth (Wilson 95% CI [0.988, 1.000]). The ground truth is the correct answer stored in the dataset. The same is true for RepLiQA, where the authors' own judge accepts 64 of the 65 answers. Altering mutants account for 461 of the 594 CN violations reported in the paper. So at least 77.4% of the reported CN violations are answers that match the ground truth of the dataset.

The following example comes from a post-chunk CN mutant in FinQA. The question was "What was the percentage change in Aon's HR Solutions revenue from 2009 to 2010, given that the revenue in 2009 was $1267 and in 2010 was $2111?", and the ground truth is 0.666. The added counterfactual said: "An internal memo later claims HR Solutions revenue in 2010

TABLE I
FINDINGS FROM THE CODE AND THE PAPER, AND THE CRITERIA THEY CONCERN (CODE COMMIT `597FD6582B`; LINE NUMBERS REFER TO THE RELEASED FILES).

ID	Crit.	Finding (evidence)
A1	V2	On the numeric datasets, an altering mutant passes (SATISFIED) if and only if the answer differs from the original answer. The injected value is never compared (`step3`, L746–748; ground-truth check L1057–1069).
A1′	V2	The overall evaluation sets `system_good = (is_preserving == (gt_correct == "correct"))`. For altering mutants, an answer that is wrong with respect to the original ground truth therefore counts as good behaviour (L1199).
A2	V1/V2	Questions are kept only if the original answer matches the ground truth (`step2`, L218–221). So every violation of an altering mutant is an answer within ≈2% of the ground truth, and every changed answer passes unless the system declined to answer.
A3	V2	For non-preserving mutants, `fault_repaired = (gt_correct != "correct")`. A CN fault therefore counts as repaired as soon as the answer stops matching the original correct answer (`step4`, L390–395; the extra repair scripts use the same rule).
A4	V1	The paper defines the fault in more than one way: "signalling or resolving the discrepancy" (§3.2.1) and "y' aligns with the injected fact" (§4.5). The §6.1 example treats *ignoring* the counterfactual as a fault, while the §6.3 example treats *adopting* it as a fault that "persisted after repair", even though under A3 that answer counts as repaired. In the released outputs, the §6.3 case (RepLiQA, post-chunk, GPT-5.4) is recorded with `is_repaired = True`, and the §6.1 case is a reported fault whose answer matches the ground truth.
A5	V3	Post-chunk CN puts the counterfactual after the original text (`mutation_operators.py`, L651), and pre-chunk CN puts it at a random position (L602). The paper does not study the effect of position.
A6	V1	The counterfactual is written to "mislead a reader into giving a wrong answer" (L551–556), and it has no date or other provenance.
A8	V2	For altering mutants, the RepLiQA judge sees the *original* context or document (L814, L858) and a one-line description of the change, but not the counterfactual itself.
A9	n/a	If writing the counterfactual fails with an error, the code quietly switches to a simpler built-in method and does not record this (L539–544, L568–574).

was $1,600, not $2,111. On that basis, the change from 2009 would be about a 26% increase …". The system answered 0.666 both before and after the change. This answer fits the numbers given in the question itself. Even so, the published test recorded the case as VIOLATED.

C. Refusals among CN mutants

This analysis was not pre-registered. We report it as a descriptive result that we found afterwards. While checking the quality of the generated counterfactuals, we noticed that many of them were not counterfactuals at all. Of the 2,671 CN mutants, 694 (26.0%) are refusals by the model that was asked to write them, for example "Sorry, I can't help create misleading counterfactuals…". The share ranges from 3.7% (RepLiQA, pre-chunk) to 47.7% (TAT-DQA, post-chunk). It is above one third in the post-chunk setting on four of the five datasets (Fig. 1). To check our method for finding refusals, we read two random samples by hand. All 30 cases it flagged were refusals, and none of 60 cases it did not flag were refusals.

The authors' judge labelled 677 of the 694 refusals as semantics-preserving. As a result, these mutants were tested with the relation for preserving mutants, and they passed in 664 of the 694 cases. Most refusals turn down the request and offer help instead. A keyword search suggests that about a third of them repeat the value given in the document, and a few add an example that is clearly labelled as made up. If we leave refusals out, the published CN violation rates rise by up to 17.2 percentage points (from 22.3% to 39.5% for TAT-DQA in the post-chunk setting).




Fig. 1. Share of CN mutants in the released outputs of the ASE 2026 framework that are refusals by the model that was asked to write them, per dataset and setting (694 of 2,671 overall).

D. Position and value alignment

Both analyses in this subsection were pre-registered. In the pre-chunk setting, the counterfactual is placed at a random position. This gives a natural experiment on position. The violation rate is 0.344 (45/131) when the counterfactual comes before the correct value, and 0.368 (28/76) when it comes after it ($\Delta = -0.025$, Fisher $p = 0.76$). We found no effect of position.

We also expected that many passed tests would be answers that changed, but did not follow the injected value. This was not the case. On simple lookup questions, re-checking the passed tests for value alignment changes the result in only 9.6% of the cases, which is below our pre-set threshold of 10%.

We had also planned two more measures based on exact number matching. They counted passed tests and repairs whose answer matched neither the original value nor the injected one. When we read these cases by hand, we found that most of the answers do follow the counterfactual, but in other units or after some calculation. We therefore consider both measures invalid and draw no conclusions from them. Finally, we found no case of the silent switch to the simpler method (A9) among the pre-chunk CN mutants.

E. Answer to RQ2

In the released outputs, at least three quarters of the reported CN violations are answers that match the ground truth. About one CN mutant in four is a refusal that contains no counterfactual. On the other hand, the position of the counterfactual and the value alignment of passed tests seem to have little effect on the published results.

VII. RQ3 and RQ4: A test with a clear expected answer

A. How MR-Provenance-Swap works

The results so far suggest that the main problem with the CN test is that its expected answer cannot be worked out from the input. To fix this, we propose MR-Provenance-Swap (MR-PS). Let v_o be an original value and v_m a conflicting (mutated) value for the same fact. Each value is shown in its own passage, and each passage starts with a date in the form "(as of YYYY-MM-DD)". Let $t_1 < t_2$ be two dates. In the source test case (condition CORRECT), v_m has the later date t_2 and v_o the earlier date t_1. In the follow-up test case (condition SWAPPED), the two dates are exchanged, and nothing else changes. A system that trusts the most recent information should therefore give v_m in the first case and v_o in the second. In short, when the dates swap, the answer should swap too.

To score the answers, we label the value in each answer automatically as *new*, *old*, *both* or *neither*. For each question, conflict source and passage order, the pair of answers then gets one of four outcomes. It is PASS if the answer follows the later date in both conditions, and INSENSITIVE if it gives the same single value in both. It is INVERTED if it follows the earlier date in both, and ACK if the system points out the conflict or declines to answer in at least one condition. An MR-PS violation is an INSENSITIVE or INVERTED outcome. To make sure that position does not matter, we run each case with both passage orders.

B. Strengths and limitations

Measured against the criteria in Section III, MR-PS has several strengths. Its expected answer follows from the input and needs no answer key (V1, V4). The answer is compared with both possible values (V2). Running both passage orders controls for position (V3). In addition, pointing out the conflict is reported as its own outcome, instead of being counted as a pass or a violation.

MR-PS also has limitations. First, it assumes that the newest value should win. Systems that should follow a different rule (e.g., trusting the most reliable source) would need a different signal and a different expected answer. Second, the dates are written inside the text. So the test checks whether a system uses dates in the text, not whether it uses document metadata. Third, our automatic labelling of values only works for questions with a single value to look up. Fourth, running both passage orders doubles the number of system runs for each conflict. Finally, the test does not apply to conflicts without provenance. For those, V1 says that the only answer we can demand is to point out the conflict or decline.

C. Experimental setup

We built 392 questions on 145 Wikipedia pages from changes in the pages' infoboxes (the summary boxes at the top of an article). For each page, we compared the last version before 2025-10-01 with the version current in October 2026. The pages cover UN member states and samples of companies listed on Nasdaq and the NYSE. Old and new values are extracted automatically, years are not used as values, and no question contains its own answer. For five randomly chosen pages, we checked our stored versions against the live MediaWiki API, and they were byte-identical.

We use two sources of conflict. In REAL, the old value from Wikipedia conflicts with the new one. In CN, the current value conflicts with a counterfactual written by qwen2.5:7b-instruct, which must differ from the current value and must not be a year. Each prompt contains the two conflicting passages and one unrelated passage from the same page, as in post-chunk mutation. We combine the date condition {none, correct, swapped} with the order {mutation last, mutation first}. We also add a control prompt that shows only the new value, to check that each model can answer the question at all (adequacy). This gives 13 prompts per question and model. The systems under test are phi3-mini (3.8B, Q4_0), Qwen2.5-7B-Instruct and Qwen2.5-14B-Instruct (both Q4_K_M). They are compressed open models, which we run on a laptop at temperature 0 with at most 24 output tokens.

To compare MR-PS with the published test, we apply the published test to the prompts without dates and with the mutation last, which matches the post-chunk setting used by ASE. A case is VIOLATED if the answer gives the original value alone. We fixed hypotheses H1–H4 and their thresholds before running the models.

D. Results

All three models passed the adequacy check (0.990 for phi3, 0.806 for Qwen-7B and 0.901 for Qwen-14B, against a pre-set threshold of 0.60). All runs finished, and the hash of the script we ran matches the pre-registered one. Table II compares the two tests. Table III and Fig. 2 show the MR-PS outcomes on real updates.

RQ3: Faults found by the test with a clear expected answer: Our first hypothesis (H1) was that at least one model would show MR-PS violations in at least 10% of the pairs. This is supported. Taking both sources together, the violation rate is 0.511 [0.486, 0.536] for phi3, 0.385 [0.361, 0.409] for Qwen-7B, and 0.011 [0.007, 0.017] for Qwen-14B.

H2 predicted that the two tests would mostly flag different cases ($\varphi < 0.30$) for every model. This is not supported. It holds for phi3 and Qwen-7B ($|\varphi| \leq 0.161$), but for Qwen-14B on real updates $\varphi = 0.323$. This value is based on only six violations under each test (cell counts 2, 4, 4 and 382), so it is not precise. Even so, we report the pre-registered result as it is.

For the two smaller models, the published test reports fewer violations than MR-PS. For example, for Qwen-7B on real updates it reports 8.2% violations, while 41.3% of the date-swap pairs are insensitive or inverted. A breakdown that we

TABLE II
VIOLATION RATES UNDER THE PUBLISHED TEST AND UNDER MR-PS (PRE-REGISTERED WILSON 95% CIS; 392 QUESTIONS ON 145 PAGES; 784 DATE-SWAP PAIRS PER SOURCE), THE DIFFERENCE MR-PS − PUBLISHED WITH A PAGE-CLUSTERED BOOTSTRAP 95% CI (10,000 RESAMPLES), AND THE φ COEFFICIENT BETWEEN THE TWO TESTS ON THE SAME CASES.

Model	Source	Published	MR-PS	Δ [page-boot]	φ
phi3-mini	REAL	0.301 [0.258, 0.348]	0.513 [0.478, 0.548]	+0.21 [0.14, 0.28]	−0.161
	CN	0.347 [0.302, 0.395]	0.509 [0.474, 0.544]	+0.16 [0.10, 0.23]	−0.147
Qwen2.5-7B	REAL	0.082 [0.058, 0.113]	0.413 [0.379, 0.448]	+0.33 [0.29, 0.38]	0.075
	CN	0.089 [0.065, 0.122]	0.356 [0.323, 0.390]	+0.27 [0.22, 0.31]	0.110
Qwen2.5-14B	REAL	0.015 [0.007, 0.033]	0.017 [0.010, 0.028]	+0.00 [−0.01, 0.01]	0.323
	CN	0.010 [0.004, 0.026]	0.005 [0.002, 0.013]	−0.01 [−0.02, 0.01]	−0.009




Fig. 2. Left: violation rates on real updates under the published test and under MR-PS. Right: MR-PS outcomes on real updates (784 date-swap pairs per model).

TABLE III
MR-PS OUTCOMES ON REAL UPDATES (784 PAIRS PER MODEL).

Model	PASS	INSENSITIVE	INVERTED	ACK
phi3-mini	170	387	15	212
Qwen2.5-7B	90	313	11	370
Qwen2.5-14B	97	11	2	674

made afterwards helps to explain this. On questions where the model ignores the dates, it usually picks the mutated value when no dates are shown. The published test counts this as a pass (Qwen-7B: 142/208, with answers listing both values in 42/208; phi3: 138/214). In these cases, a pass tells us which value the model picked, but not whether it knew which value was current.

H3, about how the tests rank the models, was descriptive. Both tests rank the models in the same order (Qwen-14B $<$ Qwen-7B $<$ phi3). Qwen-14B, however, behaves differently from the other two models. With dated conflicts, it lists both values or declines in 86% of the real-update pairs (674/784) and in 84% of the CN pairs (659/784). It gives the later-dated value alone in only 12–15% of them. Neither test counts pointing out the conflict as a violation, so both report low violation rates for this model.

RQ4: Can synthetic counterfactuals replace real updates?: H4 required the difference between synthetic and real conflicts to be smaller than 0.05 ($|\mathrm{PS}(\mathrm{CN}) - \mathrm{PS}(\mathrm{REAL})| < 0.05$), which we checked by resampling whole questions. The difference is within this limit for phi3 (-0.004 [-0.043, $+0.037$]) and Qwen-14B (-0.011 [-0.024, -0.001]), but not for Qwen-7B (-0.057 [-0.087, -0.028]). For Qwen-7B, synthetic counterfactuals lead to slightly fewer faults than real updates. So, with a test that has a clear expected answer, synthetic counterfactuals seem to be a fair stand-in for real updates for two of the three models.

Additional pre-registered analyses: We also pre-registered a question about whether the two tests would rank answering strategies differently. Before running it at full scale, we ran a small pilot with Qwen-7B on 20 questions that were not in the main sample. To continue, a strategy told to use the most recently dated value had to pass at least 15 percentage points more date swaps than a strategy that treats the later passage as a correction. Instead, it passed 5 points fewer (-5 points; 15% against 20%). So we did not run the main experiment, and this question is still open. The pilot also gave an exploratory observation. A prompt that asked for exactly one number cut the answers listing both values from 37.5% to 2.5%, but it also raised date-insensitive answers from 55% to 75%.

The prompt in our main experiment allowed several numbers ("Reply with only the number(s), separated by commas"). This might have encouraged Qwen-14B to list both values. We therefore pre-registered a follow-up, in which we ran Qwen-

14B again on the same 784 real-update pairs, with a prompt that asked for exactly one number. Answers listing both values or declining dropped from 86.0% to 31.5%. In total, 443 pairs moved away from pointing out the conflict, and 16 moved towards it (exact McNemar $p < 10^{-100}$). This shows that the listing behaviour was mostly caused by the prompt. With the new prompt, the model followed the later date in 59.2% of the pairs [55.7, 62.6], and it was date-insensitive or inverted in 9.3%. Our pre-set rule needed at least 60% to say that the model follows dates, so we call the result mixed. The follow-up also explains the H2 result for Qwen-14B: with the original prompt, the model gave very few single-value answers on which the two tests could disagree.

VIII. Discussion

A. What a CN violation means

Our results show that, in the framework we studied, a CN violation almost always means that the system kept the correct answer after a passage written to mislead it was added. Seen this way, the CN violation rate measures how well a system resists the injected claim, but with the sign reversed. It does not measure a failure to take in new knowledge. Ranking systems by their CN violation rates might therefore favour the systems that accept injected claims most easily. This reading only applies to the released code and data, and it does not concern the other operators of the framework.

B. Another way to read the CN test

One could argue that CN is meant to test whether a system takes in the new state of its documents. In that case, an unchanged answer would be a failure to adapt by definition. Four points speak against this reading. First, the framework does not define the fault in one consistent way. The list of fault types refers to "signalling or resolving the discrepancy" (§3.2.1). The judge's rubric treats an answer that "appropriately acknowledges conflicting information" as a success (§5.2.3). The repair example treats adopting the counterfactual as a fault that "persisted after repair" (§6.3). Second, the added passage has no provenance, and it is written to "mislead a reader into giving a wrong answer". So nothing in the input marks it as the new state (V1, V4). Third, even with this reading, the test would still need to check that the answer matches the injected value, and the code does not do this (V2). Fourth, the test is one-sided. A system that always accepts contradicting text would never fail it, while a system that holds back when the evidence conflicts would. We could not find out whether this changes which systems people would choose, because the pilot for that question did not pass its pre-set threshold.

C. What this means for testing RAG systems

Based on our results, we suggest four practices for testing RAG systems with conflicting facts. (i) Conflict mutations should carry provenance, such as a date, and tests should be designed so that the expected answer follows from the input, as in swap-based tests. (ii) Tests should check that the answer matches the injected value, not only that it changed. (iii) Generated mutants should be checked for refusals, and any fallback during generation should be logged. (iv) Pointing out a conflict and declining to answer should be reported as separate outcomes. Qwen-14B shows why the last point matters. Both tests report few violations for this model, but only because it mostly lists both values. This is not what Cattan et al. [6] recommend for old information, and it depended strongly on the prompt.

D. What this means for research

It is already known that language models make little use of dates [4, 5]. Our results add a testing point of view. Without provenance in the mutation, a test cannot tell a failure to update apart from reasonable caution. With provenance and a swap, the expected answer can be checked without an answer key. The RQ4 results also connect to the question of whether mutants behave like real faults, which Just et al. [12] studied for programs. With a test that has a clear expected answer, synthetic counterfactuals were close to real updates for two of the three models. Whether this also holds for other domains, larger models and other kinds of provenance is still an open question.

IX. Threats to validity

a) Construct validity: Construct validity is about whether we measure what we intend to measure. Value alignment is only defined for simple lookup questions. Exact number matching does not recognise answers given in other units or calculated from the value, which is why we declared two measures invalid. To check our automatic labelling of values, we read 90 outputs from an earlier experiment on the same questions by hand. We disagreed with the labels in 3.3% of them, and all of these cases were unit conversions. A formal check is [PENDING: 200 cases, two annotators, Cohen's κ]. We checked our method for finding refusals on samples of flagged and unflagged cases (Section VI).

b) Internal validity: Internal validity is about whether the way we ran the study could have affected the results. To avoid adjusting the analysis to the data, we pre-registered the re-analysis and the MR-PS hypotheses and saved their hashes. The refusal analysis and the breakdown of disagreements between the tests, however, were done afterwards. The prompt in our main experiment allowed several numbers, which made Qwen-14B list both values more often. We tested this in a separate pre-registered follow-up, and we report both results.

c) Conclusion validity: Conclusion validity is about whether our statistics support our conclusions. Our confidence intervals take into account that questions from the same page are related. The φ value for Qwen-14B, however, is based on few violations and is not precise. One pre-registered hypothesis (H2) and one pre-set threshold were not met, and we did not run the experiment that depended on that threshold.

d) External validity: External validity is about whether the results apply to other settings. Our experiment uses three small open models, compressed to 4 bits, and a single domain (Wikipedia infobox values). The results might therefore not

hold for larger models or other domains. We also studied only one framework. Its problems (A1–A8), however, are properties of its code, and they do not depend on the models in our experiment. Finally, our findings refer to the published paper [3], which we checked is identical to arXiv 2607.26843v1 in all quoted passages, and to code commit `597fd6582b`. Later versions of the code might differ.

X. Related work

a) Metamorphic testing of RAG and LLM systems: Besides Kim et al. [3], MeTMaP [13] uses metamorphic testing to check vector matching in LLM-based generation, and retromorphic testing [14] looks for hallucinations in RAG. The chunk-coverage measure of Kim et al. [15] asks how thoroughly a test suite covers the documents, rather than how to judge answers. Evaluation tools such as Ragas [16] score single answers against documents that do not change.

b) Test oracles and the validity of tests: Barr et al. [1] review the test-oracle problem, Segura et al. [2] review metamorphic testing, and Seca [17] review oracle problems in machine learning. Just et al. [12] studied whether mutants behave like real faults in programs. Our RQ4 asks the same question for mutants that add conflicting facts.

c) Old information and conflicting facts: Besides HoH and the work on stale documents, Temporal Wiki [18] studies models that see several versions of a fact at once, and FRESCO [19] shows that re-ranking models prefer older Wikipedia versions. Re^3 [20] deals with time-related hallucinations in retrieval. Finally, Kortukov et al. [21] report that synthetic conflicts between a document and what a model has learned make update failures look more common than real documents do.

d) Position effects in conflicts: When sources conflict, LLMs prefer evidence based on where it appears [8, 9], and RAG answers change when the order of the retrieved passages changes [10].

XI. Conclusion

In this paper, we asked whether tests with conflicting facts can show real faults in RAG systems. We found that the counterfactual test of the framework we studied does not meet our criteria of decidability, provenance and value alignment. In the framework's released results, at least 77.4% of the reported counterfactual violations are answers that match the ground truth, and 26.0% of the counterfactual mutants are refusals by the model that was asked to write them. We also showed that a test which dates the conflicting values and then swaps the dates has a clear expected answer and needs no answer key. For two of the three models we studied, it found more date-related failures than the published test, mostly on different cases. For the third model, it showed that the model mostly listed both values, and that this depended on the prompt. Future work should look at other kinds of provenance, larger models and other testing frameworks.

Data Availability

The replication package contains the analysis scripts, preregistration logs and results, in particular `oracle_audit/analyze_ase_outputs.py`, `pretests/p15_provenance_swap.py` and `verification_2026-10-13/check_claims.py` (project repository, branch `staleness-oracle-audit`). The outputs of the framework we studied are available from its authors' Figshare archive, and we do not redistribute them. The Wikipedia versions can be downloaded by page identifier and timestamp.

Acknowledgment

[PENDING: Authors to review.] The authors used an AI assistant (Claude, Anthropic) to write and run analysis scripts, check sources and draft text. The authors reviewed and edited all content and take full responsibility for the publication.

References

[1] E. T. Barr, M. Harman, P. McMinn, M. Shahbaz, and S. Yoo, "The oracle problem in software testing: A survey," *IEEE Transactions on Software Engineering*, vol. 41, no. 5, pp. 507–525, 2015.

[2] S. Segura, G. Fraser, A. B. Sanchez, and A. Ruiz-Cortés, "A survey on metamorphic testing," *IEEE Transactions on Software Engineering*, vol. 42, no. 9, pp. 805–824, 2016.

[3] J. Kim, S. Pasini, and P. Tonella, "When knowledge changes: Metamorphic testing of RAG systems with mutations," in *Proceedings of the 41st IEEE/ACM International Conference on Automated Software Engineering (ASE '26)*. ACM, 2026, pp. 3140–3151, also arXiv:2607.26843v1 (identical in all passages quoted here). Artefact: github.com/dbr7/RAG-metamorphic-mutation, commit 597fd6582b.

[4] J. Ouyang, T. Pan, M. Cheng, R. Yan, Y. Luo, J. Lin, and Q. Liu, "HoH: A dynamic benchmark for evaluating the impact of outdated information on retrieval-augmented generation," in *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2025, pp. 6036–6063, ACL Anthology 2025.acl-long.301.

[5] M. S. Ahmed, L. Galke Poech, and R. Röttger, "Stale-document poisoning: When outdated retrieval overrides correct model answers," 2026, arXiv:2609.31342.

[6] A. Cattan, A. Jacovi, O. Ram, J. Herzig, R. Aharoni, S. Goldshtein, E. Ofek, I. Szpektor, and A. Caciularu, "DRAGged into conflicts: Detecting and addressing conflicting sources in search-augmented LLMs," 2025, arXiv:2506.08500.

[7] Y. Hou, A. Pascale, J. Carnerero-Cano, T. Tchrakian, R. Marinescu, E. Daly, I. Padhi, and P. Sattigeri, "WikiContradict: A benchmark for evaluating LLMs on real-world knowledge conflicts from Wikipedia," 2024, arXiv:2406.13805; NeurIPS 2024 Datasets and Benchmarks Track.

[8] A. Naphade, "Rational synthesizers or heuristic followers? analyzing LLMs in RAG-based question-answering," 2026, arXiv:2601.06189.
[9] X. Yang, Z. Liu, R. Li, and Y. Lei, "Large language models in resolving contextual knowledge conflicts," 2026, arXiv:2609.03148; to appear at EMNLP 2026.
[10] Q. Zhang, H. Zhang, L. Pang, H. Zheng, and Z. Zheng, "Stable-RAG: Mitigating retrieval-permutation-induced hallucinations in retrieval-augmented generation," 2026, arXiv:2601.02993; to appear at ACL 2026.
[11] P. Ralph *et al.*, "Empirical standards for software engineering research," 2020, arXiv:2010.03525.
[12] R. Just, D. Jalali, L. Inozemtseva, M. D. Ernst, R. Holmes, and G. Fraser, "Are mutants a valid substitute for real faults in software testing?" in *Proceedings of the 22nd ACM SIGSOFT International Symposium on Foundations of Software Engineering (FSE)*, 2014, pp. 654–665.
[13] G. Wang, Y. Li, Y. Liu, G. Deng, T. Li, G. Xu, Y. Liu, H. Wang, and K. Wang, "MeTMaP: Metamorphic testing for detecting false vector matching problems in LLM augmented generation," 2024, arXiv:2402.14480.
[14] B. Yu, Y. Zhang, L. Lin, L. Briand, and E. Muñoz, "Retromorphic testing with hierarchical verification for hallucination detection in RAG," 2026, arXiv:2603.27752.
[15] J. Kim, S. Pasini, and P. Tonella, "Testing retrieval-augmented generation systems with chunk coverage," 2026, arXiv:2607.18155.
[16] S. Es, J. James, L. Espinosa-Anke, and S. Schockaert, "Ragas: Automated evaluation of retrieval augmented generation," 2023, arXiv:2309.15217.
[17] D. Seca, "A review on oracle issues in machine learning," 2021, arXiv:2105.01407.
[18] A. Özer and Ç. Yıldız, "Question answering under temporal conflict: Evaluating and organizing evolving knowledge with LLMs," 2025, arXiv:2506.07270.
[19] S. An, H. Lee, S. Yuan, C.-c. J. Chen, C.-J. Hsieh, V. Mohan, and A. Min, "FRESCO: Benchmarking and optimizing re-rankers for evolving semantic conflict in retrieval-augmented generation," 2026, arXiv:2604.14227.
[20] J. Cao, J. Ouyang, M. Cheng, Z. Zhou, Y. Li, Z. Liu, C. Liu, and S. Wang, "Re^3: Relevance & recency retrieval for mitigating temporal hallucination," in *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2026, pp. 25 735–25 760, ACL Anthology 2026.acl-long.1180.
[21] E. Kortukov, A. Rubinstein, E. Nguyen, and S. J. Oh, "Studying large language model behaviors under context-memory conflicts with real documents," 2024, arXiv:2404.16032.