

Great question! It looks like there might be a small mix-up in terms — did you mean **iterator vs iterable**, or are you asking about **iterator vs iterator object**? Let me clarify both possibilities so it makes sense either way.

1. Iterable vs Iterator

Iterable

- An **iterable** is any object that can return an **iterator**.
- You can loop over it using a **for** loop.
- Examples: **list**, **tuple**, **dict**, **str**

```
x = [10, 20, 30] # list is iterable
```

Under the hood, **for** calls **iter(x)** on this object to get an **iterator**.

Iterator

- An **iterator** is an object with:
 - **__iter__()** method (returns itself)
 - **__next__()** method (returns the next item)
- You can manually get items using **next(iterator)**

```
x = [10, 20, 30]
it = iter(x)      # it is an iterator
print(next(it))   # 10
print(next(it))   # 20
```

Once items are exhausted, `StopIteration` is raised.



2. Iterator vs Iterator Object

If you meant the difference here: there's **no difference** — an **iterator** *is* an **iterator object**.

- The term **iterator object** just refers to any Python object that implements both `__iter__()` and `__next__()`.
- Think of it as more formal language for "an object that behaves like an iterator."

Example:

```
it = iter([1, 2, 3]) # it is an iterator object
```



Summary Table

Term	What it Means	Methods
Iterable	Can be looped over; produces an iterator	<code>__iter__()</code>
Iterator	Produces values one at a time; remembers state	<code>__iter__()</code> & <code>__next__()</code>
Iterator Object	Same as Iterator (just a formal name)	Same as above



Short Analogy

- **Iterable:** A **book** → you know it can be read.
 - **Iterator:** A **bookmark** → it tracks the **current page** as you read.
-

If you'd like, I can also show you how to write your own iterator or visualize how the `for` loop works behind the scenes!

Great question — understanding `iter()` and `next()` is key to mastering Python's iteration model. Let's break them down simply and clearly.

`iter()` — The Iterator Maker

What is `iter()`?

- A **built-in function** that takes any **iterable** (like a list, tuple, or string) and **returns an iterator**.

Why do we need it?

- To manually control iteration
- Under the hood, Python uses `iter()` when you write a loop like `for item in x:`

Example:

```
x = [10, 20, 30]
it = iter(x) # it is now an iterator
```

Now `it` is a special object that remembers its position in the sequence.

`next()` — Fetch Next Item

What is `next()`?

- Another built-in function

- When called on an **iterator**, it returns the **next item** in the sequence
- When there are **no more items**, it raises a **StopIteration** exception

Example:

```
x = [10, 20, 30]
it = iter(x) # create an iterator

print(next(it)) # → 10
print(next(it)) # → 20
print(next(it)) # → 30
print(next(it)) # → raises StopIteration
```

Under the Hood of a `for` loop

When you write:

```
for value in x:
    print(value)
```

This is what Python does internally:

```
it = iter(x)
while True:
    try:
        value = next(it)
        print(value)
    except StopIteration:
        break
```

Summary

Function

`iter()` Takes an iterable → returns an iterator

Purpose

`next()` Takes an iterator → returns next value or raises StopIteration

Think of it this way:

- `iter()` → creates the iterator
 - `next()` → walks through it
-

Bonus Tip

You can write your own class that behaves like an iterator by defining `__iter__()` and `__next__()` — would you like an example of that?

Great question — this is an important distinction! Let's clarify how `iter()` and `next()` relate:

Key Concept:

`iter()` does NOT contain or define `next()`.

- Instead, `iter()` returns an **iterator object**, and *that object* has the `__next__()` method (used by `next()`).
-

Here's how it works:

1. You have an iterable, like a list:

```
numbers = [10, 20, 30]
```

2. Use `iter()` to turn it into an iterator:

```
it = iter(numbers)
```

Now `it` is an **iterator object** — and *that object* has:

- `__iter__()` method (returns itself)
- `__next__()` method (returns the next value)

3. Use `next()` to walk through:

```
print(next(it)) # 10
print(next(it)) # 20
print(next(it)) # 30
print(next(it)) # StopIteration error
```

Summary in Simple Terms

Part

What it does

`iter()` Takes an iterable and returns an iterator (with a `__next__()` method)

Iterator The object that knows how to return each value one by one

`next()` Calls the iterator's `__next__()` to get the next value

Visual Summary

[10, 20, 30] (iterable)

|

v

`iter()` → iterator object

|

v

`next()` → 10

`next()` → 20

`next()` → 30

`next()` → StopIteration

Let me know if you want to see how to write your own iterator manually!

Awesome question — this gets right into the **internals of Python**! Let's unpack what happens inside `iter()` and whether it's a "pointer."

First: What is `iter()`?

`iter()` is a **built-in function** that takes an **iterable** object (like a list, tuple, or string) and returns an **iterator object**.

It does *not itself store any data* — instead, it returns a new object (the iterator) that **knows how to traverse the iterable**.

What does `iter()` contain internally?

Inside, `iter()` does **2 things**:

1. It checks if the object passed to it has an `__iter__()` method (i.e., it's iterable)
2. If yes, it **calls that method** to get an iterator object

So for this:

```
numbers = [10, 20, 30]
it = iter(numbers)
```

`it` is now an **iterator** that:

- Holds a **reference** (like a pointer) to the original list (`numbers`)
- Has internal state to remember where it is (current index)
- Exposes a `__next__()` method to get the next item

Does `iter()` create a pointer?

Kind of — Yes, but not a raw memory pointer.

- The iterator **holds a reference** to the iterable you passed into `iter()`.
- This reference acts like a Python "pointer" — it's a reference, not a copy.
- The iterator doesn't copy the data, and it doesn't modify the original iterable.

Internal Structure (Behind the scenes)

For common types like lists, Python has an internal iterator object for them.

Conceptually, the iterator may look like this:

```
iterator = {  
    reference_to_iterable: [10, 20, 30],  
    current_position: 0,  
    next_item: function() that returns iterable[current_position]  
}
```

So it contains:

- A **pointer/reference** to the iterable
- A **position counter**
- A **method** that knows how to get the next item

For lists specifically

In CPython (Python written in C), the iterator object holds:

- A pointer to the list object
 - An internal index (like 0, 1, 2, ...)
 - No copy of the data — it's all in the original list
-

Demonstration Code

You can see references and state by using `id()`:

```
numbers = [10, 20, 30]
it = iter(numbers)

print(id(numbers)) # reference to original list
print(id(it))      # separate object
```

The iterator is a **different object**, but it refers back to the list.

TL;DR

- `iter()` returns an **iterator object**
 - This iterator object contains a **reference (like a pointer)** to the original iterable
 - It also stores a **current position/state** so it knows where to continue
 - It doesn't contain or copy the entire list — it processes items **lazily**
-

Would you like to see a simple custom iterator class to fully visualize how this works in code?

Absolutely — you're asking the right questions, and it's okay to feel confused! These concepts are abstract at first, so let's **start from zero**, and I will explain them like you're hearing them for the first time. 💡



First: The Goal — Looping in Python

You know how we use:

```
for item in something:  
    print(item)
```

Have you ever wondered **how Python goes through items one by one?**

That's where `__iter__()` and `__next__()` come in.



Step 1: What is an Iterable?

An **iterable** is any object that you can loop over using `for`.

Examples: `list`, `tuple`, `string`, `dict`, `set`, `range`...

How does Python know it's iterable?

Because it has a method called `__iter__()`.

The only job of `__iter__()`:

👉 Return an **iterator** — an object that knows how to produce values one at a time.

🚩 It's like saying:

“I (the iterable) don't handle looping myself — but go ask this object (the iterator), it knows how.”



Step 2: What is an Iterator?

An **iterator** is an object that does two things:

1. Remembers where you are (keeps a pointer).

2. Gives the next value **one at a time** when asked — and knows when to stop.

For an object to be an **iterator**, it must have:

- `__iter__()` → returns itself
 - `__next__()` → returns next item, or raises `StopIteration`
-

Let's Define the Methods

`__iter__()`

- Called by Python when it wants to start looping.
- On **iterable**: returns a brand new iterator.
- On **iterator**: returns itself — because it is already the iterator.

`__next__()`

- Called each time Python wants the **next** item.
 - Returns the next value.
 - If no more values → raises `StopIteration`.
-

Why Does Iterator return Itself in `__iter__()`?

Because **Python expects BOTH** `__iter__()` and `__next__()` on something it loops over. Iterator already has `__next__()`, so to also be loopable, it just returns itself.

Think of it like a person who says:

“I’m the one giving out items. So if you call my `__iter__()`, I’ll just say — it’s me!”



Visual Example: A Playlist 🎵

Concept

Real-Life Example

Iterable A playlist

Iterator A DJ with a playlist (knows next song, plays it one by one)

- Playlist: Won’t say which song is next. Only says “I have songs.”
 - DJ: Knows which song is next. Plays song → goes to next.
-



Code Example: Custom Iterator

```
class MyIterator:
    def __init__(self):
        self.items = [10, 20, 30]
        self.index = 0

    def __iter__(self):
        return self # I am the iterator

    def __next__(self):
        if self.index >= len(self.items):
            raise StopIteration
        value = self.items[self.index]
        self.index += 1
        return value

# Using the iterator
my_iter = MyIterator()
for value in my_iter:
```

```
print(value)
```

Output:

```
10
20
30
```

Summary Table (Easy Mode)

Term	What is it?	Must Have
Iterable	Can be looped over	<code>__iter__()</code>
Iterator	Object that gives next value & knows position	<code>__iter__()</code> , <code>__next__()</code>

Gold Nugget: How Iterator is also Iterable?

- Because it has `__iter__()`
 - But since it *already knows everything*, `__iter__()` just returns itself
-

💬 Let me know if you want a diagram or animation to visualize this — I can generate one for you!

You're **so close** — love your energy! 🙌 Here's a small correction and a clear step-by-step explanation to help you fully understand what's happening.

Your points (clarified and refined)

✓ Point 1: What is an Iterable?

If an object has a `__iter__()` method — it is an **iterable**.

Yes! Absolutely correct.

Examples: list, string, tuple, dict, set, etc.

✓ Point 2: Using `iter()` on an Iterable

When you do:

```
x = [10, 20, 30]
```

```
it = iter(x) # equivalent to x.__iter__()
```

- Python checks if `x` has a `__iter__()` method.
- It finds one (because lists are iterable).
- It calls that `__iter__()` method.
- **That method returns a brand new iterator object.** NEW
- That iterator has the `__next__()` method.

So at this stage:

`it` # is now an iterator

⚠ Important Fix (Key Detail)

You said:

`iter()` function returns itself , because it says that yes sir , I am the iterator

💡 That's **true only for an iterator, not for an iterable**.

Let's break it down:

🎯 Case 1: Iterable's `__iter__()` (like list, tuple, set, ...)

- `__iter__()` creates a **new iterator** and returns it.
- That iterator is separate from the original iterable.

```
x = [10, 20, 30]
it = x.__iter__() # returns a *new* iterator
```

Case 2: Iterator's `__iter__()`

- For **iterators**, `__iter__()` returns **itself**.
- Why? Because it's already the object meant to be looped over, no need to create a new one.

So:

```
print(it.__iter__() is it) # True
```

👉 This is what we mean when we say *"iterator returns itself"*.

Summary Chart

Type	Method	What does it return?
Iterable	<code>__iter__</code> --	A new iterator
Iterator	<code>__iter__</code> --	Itself (because it already has <code>__next__</code>)

Final Understanding Flow

```
x = [10, 20, 30]      # x is iterable
it = iter(x)          # calls x.__iter__(), returns fresh iterator
next(it)              # calls it.__next__(), returns 10
next(it)              # returns 20
```

```
next(it)      # returns 30
next(it)      # raises StopIteration
```

Your revised summary (now corrected)

Iterable: Object with `__iter__()` → gives a new iterator
Iterator: Object with both `__iter__()` and `__next__()`
`__iter__()` of iterable → returns new iterator 🚀
`__iter__()` of iterator → returns itself 🕒
Iterator has pointer inside `__next__()` to move item-by-item

You're **very** close — just needed this final clarification.

If you want, I can provide a visual diagram comparing these — want me to draw one?

Absolutely! Let's create a **custom iterator** for a list to show how `__iter__()` and `__next__()` behave.

Step-by-Step: Build a Custom Iterator for a List

Let's say we have a list:

```
numbers = [10, 20, 30]
```

We'll build a custom iterator class called `ListIterator` to loop over this list.

Custom Iterator Class

```
class ListIterator:
    def __init__(self, data):
        self.data = data    # the list
        self.index = 0      # pointer

    def __iter__(self):
        return self         # since this is the iterator itself
```



```
def __next__(self):
    if self.index >= len(self.data):
        raise StopIteration # no more data
    value = self.data[self.index]
    self.index += 1         # move pointer
    return value
```

How to Use It

```
numbers = [10, 20, 30]
my_iter = ListIterator(numbers)
```

```
print(next(my_iter)) # 10
print(next(my_iter)) # 20
print(next(my_iter)) # 30
print(next(my_iter)) # StopIteration
```

What's Happening Internally?

- `__init__`: Stores a copy of the list and sets pointer to 0.
 - `__iter__`: Returns the iterator object itself.
 - `__next__`: Reads the current value and moves the pointer forward.
 - If pointer exceeds length → raises `StopIteration`.
-

Using in a **for** Loop

```
numbers = [10, 20, 30]
for num in ListIterator(numbers):
    print(num)
```

Output:

10

20
30

🎉 That's it! You've now seen how to build a custom iterator from scratch.

Want a diagram visualizing this entire flow?

You're doing great by digging deep — this is how true understanding happens! Let's **slow down** and break it all down from the very beginning.

Your Core Question

What exactly happens when I do:

```
x = [10, 20, 30] # list --> iterable  
it = iter(x)     # iterator created
```

And how does this relate to the custom iterator class?

1. First, What is **x**?

```
x = [10, 20, 30]
```

- **x** is a **list**.
- All lists in Python are **iterable**.
- This means **x** has a method called `__iter__()` built-in.

Let's test this:

```
print(hasattr(x, "__iter__")) # True
```

2. What Happens When You Do `iter(x)`?

When you call:

```
it = iter(x)
```

It's the same as doing:

```
it = x.__iter__() # directly calling the built-in method
```

➤ What does that do?

It returns a **new iterator object** that knows how to walk through `x`.

This iterator object:

- Has its own internal pointer (starts at index 0)
 - Has a `__next__()` method that returns one element at a time
-

Let's Dive into How Python List Iterator Works Internally

Here's what happens under the hood when you do `iter(x)`:

1. Python sees that `x` has a `__iter__()` method.
2. It calls that method: `x.__iter__()`.
3. A new **list iterator object** is created.

That iterator object:

- Tracks where we are in the list (like index position)
- Has `__next__()` method to get the next value

You can do:

```
it = iter(x)
print(next(it)) # 10
print(next(it)) # 20
print(next(it)) # 30
next(it)        # Raises StopIteration
```

Internally, this iterator maintains a **pointer to the list and current index**, just like our custom class.



3. Let's Compare with the Custom Iterator

Your custom iterator:

```
class ListIterator:
    def __init__(self, data):
        self.data = data    # store the list
        self.index = 0      # pointer

    def __iter__(self):
        return self         # this object is also the iterator

    def __next__(self):
        if self.index >= len(self.data):
            raise StopIteration
        value = self.data[self.index]
        self.index += 1
        return value
```

How It's the Same:

- `self.data` is like the list stored.
- `self.index` is the pointer.
- `__next__()` returns data and moves pointer.
- When pointer is out of range → `StopIteration`.

Difference:

- Python's built-in list iterator is implemented in **C** for efficiency.
 - But conceptually it does the exact same thing as your custom class.
-

Why Do We Say “Iterator Returns Itself”?

Because when you do:

```
s = ListIterator([1, 2, 3])
print(s.__iter__() is s) # True
```

- `__iter__()` returns `self`.
 - Because **the iterator object already knows how to give values one-by-one**.
 - No need to generate a new iterator for an iterator.
-

Final Flow Summary

Step	What Happens
<code>x = [10, 20, 30]</code>	A list is created — it's <i>iterable</i> (has <code>__iter__</code>)
<code>it = iter(x)</code>	Calls <code>x.__iter__()</code> , returns a new iterator object
<code>next(it)</code>	Calls iterator's <code>__next__()</code> , returns next value
After last value	<code>__next__()</code> raises <code>StopIteration</code>

Diagram of How It Works

```
x = [10, 20, 30]    # iterable
```

```
    |  
    |__iter__()  
    ▼
```

```
it = <list_iterator object> ← has pointer index = 0
```

```
    |  
    |__next__()  
    ▼
```

```
10 → pointer moves → 20 → pointer moves → 30 → StopIteration
```



You Can Even See Python's Internal Iterator Type

```
x = [10, 20, 30]
```

```
it = iter(x)
```

```
print(type(it)) # <class 'list_iterator'>
```

It's a **special built-in class**.



TL;DR (In Plain Words)

- A **list** is an iterable — it has `__iter__()`.
 - Calling `iter(list)` creates a **new iterator** that does the job of looping.
 - The iterator:
 - Has `__next__()` to fetch values one by one
 - Has internal state (a pointer/index)
 - Your custom class acts just like the built-in C iterator for lists.
-

💬 Want a side-by-side comparison of built-in and custom iterator in code or a visual flowchart?

You're doing great by digging deep — this is how true understanding happens! Let's **slow down** and break it all down from the very beginning.

Your Core Question

What exactly happens when I do:

```
x = [10, 20, 30] # list --> iterable  
it = iter(x)     # iterator created
```

And how does this relate to the custom iterator class?

1. First, What is **x**?

```
x = [10, 20, 30]
```

- **x** is a **list**.
- All lists in Python are **iterable**.
- This means **x** has a method called `__iter__()` built-in.

Let's test this:

```
print(hasattr(x, "__iter__")) # True
```

2. What Happens When You Do **iter(x)**?

When you call:

```
it = iter(x)
```

It's the same as doing:

```
it = x.__iter__() # directly calling the built-in method
```

➤ What does that do?

It returns a **new iterator object** that knows how to walk through `x`.

This iterator object:

- Has its own internal pointer (starts at index 0)
- Has a `__next__()` method that returns one element at a time

Let's Dive into How Python List Iterator Works Internally

Here's what happens under the hood when you do `iter(x)`:

1. Python sees that `x` has a `__iter__()` method.
2. It calls that method: `x.__iter__()`.
3. A new **list iterator object** is created.

That iterator object:

- Tracks where we are in the list (like index position)
- Has `__next__()` method to get the next value

You can do:

```
it = iter(x)
print(next(it)) # 10
print(next(it)) # 20
print(next(it)) # 30
next(it)        # Raises StopIteration
```


Internally, this iterator maintains a **pointer to the list and current index**, just like our custom class.

3. Let's Compare with the Custom Iterator

Your custom iterator:

```
class ListIterator:
    def __init__(self, data):
        self.data = data    # store the list
        self.index = 0      # pointer

    def __iter__(self):
        return self        # this object is also the iterator

    def __next__(self):
        if self.index >= len(self.data):
            raise StopIteration
        value = self.data[self.index]
        self.index += 1
        return value
```

How It's the Same:

- `self.data` is like the list stored.
- `self.index` is the pointer.
- `__next__()` returns data and moves pointer.
- When pointer is out of range → `StopIteration`.

Difference:

- Python's built-in list iterator is implemented in **C** for efficiency.
 - But conceptually it does the exact same thing as your custom class.
-

☀ Why Do We Say “Iterator Returns Itself”?

Because when you do:

```
s = ListIterator([1, 2, 3])
print(s.__iter__() is s) # True
```

- `__iter__()` returns `self`.
 - Because the iterator object already knows how to give values one-by-one.
 - No need to generate a new iterator for an iterator.
-

✨ Final Flow Summary

Step	What Happens
<code>x = [10, 20, 30]</code>	A list is created — it's <i>iterable</i> (has <code>__iter__</code>)
<code>it = iter(x)</code>	Calls <code>x.__iter__()</code> , returns a new iterator object
<code>next(it)</code>	Calls iterator's <code>__next__()</code> , returns next value
After last value	<code>__next__()</code> raises <code>StopIteration</code>

🔍 Diagram of How It Works

```
x = [10, 20, 30]    # iterable
    |
    | __iter__()
    ▼
it = <list_iterator object> ← has pointer index = 0
    |
    | __next__()
    ▼
10 → pointer moves → 20 → pointer moves → 30 → StopIteration
```

You Can Even See Python's Internal Iterator Type

```
x = [10, 20, 30]
it = iter(x)
print(type(it)) # <class 'list_iterator'>
```

It's a **special built-in class**.

TL;DR (In Plain Words)

- A **list** is an iterable — it has `__iter__()`.
- Calling `iter(list)` creates a **new iterator** that does the job of looping.
- The iterator:
 - Has `__next__()` to fetch values one by one
 - Has internal state (a pointer/index)
- Your custom class acts just like the built-in C iterator for lists.

💬 Want a side-by-side comparison of built-in and custom iterator in code or a visual flowchart?

Yes! You're absolutely right. 🎯

When you call:

```
iter(x)
```

Python **internally calls**:

```
x.__iter__()
```

Here's the full breakdown:

1. `iter(x)` → calls `x.__iter__()`

- Python checks if the object (`x`) has a method named `__iter__()`.
 - If it exists → it calls that method and expects it to return an **iterator object**.
 - If `x` does not have `__iter__()` → Python tries to use the old-style `__getitem__()` way.
 - If that also fails → it raises a `TypeError: "object is not iterable"`.
-

Example with a list:

```
x = [10, 20, 30]
it = iter(x)    # This internally calls x.__iter__()
```

You can confirm this:

```
it = x.__iter__() # Same as calling iter(x)
```

Now `it` is an iterator object, and you can do:

```
print(next(it)) # calls it.__next__()
```

Internal Check (how Python does this)

The internal logic (in simplified pseudocode) is like:

```
if hasattr(x, '__iter__'):
    return x.__iter__()
```

```
else:  
    raise TypeError(f"{type(x)} object is not iterable")
```



In short:

- `iter(x)` is just a nicer built-in function that calls `x.__iter__()` for you.
 - That's how **any iterable (lists, dicts, strings, sets, custom classes, etc.)** work in Python.
-

Would you like a visual diagram of this mechanism? Or a deep dive into how `for` loops use this logic internally?

Yes — returning an iterator object often means returning `self`, but only in the case where your class itself *is* the iterator.

Let's break it down clearly:



Case 1: When the Class Is the Iterator

This is what you have done with your custom `ListIterator` class:

```
class ListIterator:  
    def __init__(self, data):  
        self.data = data  
        self.index = 0  
  
    def __iter__(self):  
        return self # returns itself, because this object *is* the iterator  
  
    def __next__(self):  
        # logic to return next item
```

In this case:

- `__iter__()` returns `self`
- Because the object itself has `__next__()`, it's the iterator

You can do:

```
it = ListIterator([1,2,3])  
print(next(it)) # calls it.__next__()
```

-

Case 2: When the Class Is Not the Iterator (Just an Iterable)

Some classes may be iterable (**they allow iteration**) but are **not the iterator themselves**.
In this case, `__iter__()` returns a **separate iterator object**.

Example using a custom iterable, not self:

```
class MyIterable:  
    def __init__(self, data):  
        self.data = data  
  
    def __iter__(self):  
        return ListIterator(self.data) # returns a new iterator object
```

```
# Now, different object returned  
it1 = iter(MyIterable([10, 20, 30]))  
it2 = iter(MyIterable([10, 20, 30]))
```

```
print(next(it1)) # 10  
print(next(it2)) # 10 (separate state)
```

✨ This design means:

- You can have multiple independent iterators over the same data.

- `__iter__()` does **not** always return `self` — only if the class itself is the iterator.

Summary

Case	What <code>__iter__</code> returns	Example
Iterator object	<code>return self</code>	Your <code>ListIterator</code>
Separate iterator	<code>return</code> <code>SomeIterator(self.data)</code>	More flexible iterable design

Would you like a diagram that shows the difference between `Iterable` and `Iterator` visually?

Great question! Understanding this is key to mastering iterators. Let's dive in. 🧠💡

What Happens If You Don't Return `self` in `__iter__()` for an Iterator Class?

If your class is meant to be an iterator, but its `__iter__()` method does **NOT** return `self`, the class **will NOT** behave correctly in a loop or with `iter()`.

Let's See What Happens

Suppose you write this:

```
class BadIterator:
    def __init__(self, data):
        self.data = data
        self.index = 0

    def __iter__(self):
        return "not an iterator" # ❌ mistake: not returning self or iterator
```

```
def __next__(self):
    if self.index >= len(self.data):
        raise StopIteration
    value = self.data[self.index]
    self.index += 1
    return value
```

```
it = BadIterator([10, 20, 30])
for item in it:
    print(item)
```

What happens?

When Python reaches the `for` loop, it translates this:

```
for item in it:
    print(item)
```

into:

```
iterator = iter(it)    # this calls it.__iter__()
```

Since `__iter__()` returns `"not an iterator"` (a string), Python assigns:

```
iterator = "not an iterator"
```

Then it tries to do:

```
next(iterator)
```

But strings **do not have** `__next__()`. So you get:

`TypeError: 'str' object is not an iterator`

✓ The Proper Way

Your iterator class **must** follow the iterator protocol:


```
class GoodIterator:
    def __iter__(self):
        return self # 👍 self is the iterator

    def __next__(self):
        # ... return next item or raise StopIteration
```

🔑 Why Return **self**?

- **self is the iterator** → It knows where you are (current index), and how to move to the next item.
 - Returning **self** tells Python: "You can call **next()** on me."
-

🧠 Rule to Remember

If the class is...	<code>__iter__()</code> should return
--------------------	---

The iterator itself	<code>self</code>
---------------------	--------------------------

Only an iterable (not iterator)	A new iterator object
---------------------------------	-----------------------

Would you like to see a visual flow diagram of how **for** loops use **iter()** and **next()**?