NOV-DEC 2017

Total No. of Questions—8] [Total No. of Printed Pages—3

Seat No.	

[5252]-569

S.E. (Computer) (Second Semester) EXAMINATION, 2017

MICROPROCESSOR

(2015 PATTERN)

Time : Two Hours **Maximum Marks : 50**

N.B. :— (*i*) Solve Q. **1** *or* Q. **2**; Q. **3** *or* Q. **4**; Q. **5** *or* Q. **6**; Q. **7** *or* Q. 8.

(*ii*) Neat diagrams must be drawn wherever necessary.

(*iii*) Figures to the right indicate full marks.

(*iv*) Assume suitable data, if necessary.

1. (*a*) Explain immediate and register addressing mode with an examples. [2]

(*b*) Explain with example SHL and ROL instructions. [4]

(*c*) Explain in detail the control registers of 80386. [6]

Or

2. (*a*) Explain MSW. [2]

(*b*) Explain paging mechanism. [4]

(*c*) Explain the following instructions, mention flags affected : [6]

(*i*) LIDT

(*ii*) CLD

(*iii*) MOVS.

P.T.O.

3. (*a*) What is CPL and RPL ? [2]

(*b*) Differentiate between memory mapped I/O and I/O mapped I/O. [4]

(*c*) Draw and briefly explain Task State Segment. [6]

Or

4. (*a*) When does a page fault occur ? [2]

(*b*) Explain any *two* I/O privilege instructions. [4]

(*c*) Explain what happens when an interrupt calls a procedure as an interrupt handler. [6]

5. (*a*) What are the contents of various registers of processor 80386 after reset ? [3]

(*b*) How many debug registers are present in 80386 ? List and draw all of them. [4]

(*c*) With neat diagram explain the process of linear adress formation in V86 mode. [6]

Or

6. (*a*) Write short note on "Instruction Address Breakpoint". [3]

(*b*) What all initializations required to start processor in real mode after reset ? [4]

(*c*) With neat diagram explain "Entering and leaving V86 mode". [6]

7. (*a*) Explain HOLD and HLDA signals of 80386DX. [3]

(*b*) List various bus states when address pipelining is used. [4]

(*c*) Draw read cycle with non-pipelined address timing. [6]

Or

8. (*a*) Explain the following signals : [3]

(*i*) NMI

(*ii*) INTR

(*iii*) RESET

(*b*) Draw and explain 80387 register stack. [4]

(*c*) Draw 'write cycle with pipelined address timing'. [6]