

# Spacecraft Propulsion and Design Challenge

## Phobos Orbiter Mission Design: MomenTUM

1<sup>st</sup> Beatriz Mas Sanz

*Chair of Space Propulsion and Mobility  
Technical University of Munich  
Munich, Germany  
ge86san@mytum.de*

2<sup>nd</sup> Marta Pelivan

*Chair of Space Propulsion and Mobility  
Technical University of Munich  
Munich, Germany  
marta.pelivan@tum.de*

3<sup>rd</sup> Julian Schmid

*Chair of Space Propulsion and Mobility  
Technical University of Munich  
Munich, Germany  
juli.schmid@tum.de*

4<sup>th</sup> Sven J. Steinert

*Chair of Space Propulsion and Mobility  
Technical University of Munich  
Munich, Germany  
0000-0003-4424-670X*

**Abstract**—The target of this design challenge is, to develop a propulsion system concept that can provide the sufficient performance to send a spacecraft to Phobos with an Ariane 62 rocket as its launch system. For this, different concepts are compared in a variety of trade-offs. Finally, a system that uses a bipropellant as well as an electric propulsion system is chosen and worked out in detail to prove, that this concept can satisfy the given requirements of the launcher, the mission and the propulsion system itself.

**Index Terms**—Mars, Phobos, quasi-satellite orbit, bipropellant, chemical propulsion, electrical propulsion

### I. INTRODUCTION

The study presented in this report focuses on the preliminary design of the propulsion system for a proposed mission to Phobos, one of the moons of Mars. The primary objective of this mission is to study the origin, together with the physical and chemical composition of Phobos, through the deployment of a surface probe.

The feasibility of the mission will be ensured by designing a propulsion system that can safely and efficiently transport the spacecraft to Phobos, maintain a Quasi-Satellite Orbit (QSO) around the moon for a minimum of two years, and provide sufficient power and propulsion for the surface probe to conduct its scientific experiments. The spacecraft is planned to be launched on a dedicated Ariane 62 rocket from Kourou between 2026-2029, and it will be de-orbited into the Martian atmosphere at the end of its mission.

The report will begin by describing the trajectory to reach Phobos. This will be followed by the presentation of the proposed concept for the propulsion system, along with a detailed explanation of the trade-offs leading to the final concept, its components and how it addresses the challenges of the mission.

Overall, the study performed in this report aims to present a feasible preliminary design that can help ensure the success of the mission.

### II. WORKFLOW

In this section, the workflow design process of the spacecraft and specifically the spacecraft propulsion system is introduced. This is shown in Figure 1. In it, a continuous iteration process is presented to ensure, that an optimized spacecraft configuration can be reached. The main mechanism in this process is a closed loop between the mission analysis software General Mission Analysis Tool (GMAT) and the self-developed MATLAB (The Mathworks, Inc.) scripts `dV_calc.m`, `mass_design.py` and `pressure_temp_sim.m`. Results, such as a propulsion subsystem schematic, technical drawings of the system and different budgets for mass, propellant and delta v can be drawn from this process.

#### A. GMAT

The General Mission Analysis Tool (GMAT) is used to compute the trajectory and simulate the mission in space and time. Hereby the mission was first implemented impulsive, then with finite chemical burns and ultimately with additional finite electric burns in `MomenTUM_finite.script`. As an output of this simulation, a result file `result.txt` is created, holding certain events by their timestamp and fuel level as well as burn-times and key-variables of the mission. This rather long file is shortened to the most important lines by a small script `cleaning.py` into `result_clean.txt`. Additionally the distance to Phobos is outputted by GMAT and plotted by `plot.py`.

#### B. dv Script

The delta v script `dV_calc.m` is a program written in MATLAB. Its function is to take a given spacecraft dry mass, as well as the thrust and ISP of the engine used in the maneuvers, together with the dedicated burn-times from GMAT per maneuver. These values are then transformed into the respective delta v and propellant mass of each maneuver via the Tsiolkovsky rocket equation [1].




Fig. 1. Flowchart of workflow

### C. Mass Budget Script

To compute the launch mass of the spacecraft as well as the solar array size and the engine performance data, a mass budget script `mass_design.py`, written in MATLAB, is used. Here, the delta v's and the pressurant mass are needed as an input, while especially the spacecraft dry mass and engine performance is inserted back into GMAT as an output of this script. In this script, the ESA margin philosophy [2] is respected.

### D. Pressure Script

The amount of pressurant required for the mission is calculated using the MATLAB pressure script `pressure_temp_sim.m`. The required inputs for the tool are the `result_clean.txt` file coming from GMAT transformed to a `.xlsx` file, as well as the pressurant and propellant tank characteristics (volumes and mean operating pressures). The outputs of this script are:

- the total helium mass within the whole system at the beginning of operation, which is fed back to GMAT.
- the amount of helium within both pressurant and propellant tanks throughout the maneuvers.
- the pressure and temperature changes of helium within the pressurant and propellant tanks during the maneuvering time.

### E. Arrangement Analysis Script

The spacecraft's configuration is determined by the arrangement analysis script `arrangement_analysis.m`, written in MATLAB. In this script, the orbital stability criteria for the spacecraft are matched with the spacecrafats geometrical layout and placement of the individual internal parts. This then results in a shape which directly influences the placement of

the reaction control system (RCS). By the correct placement of the RCS thrusters, a combined main-engine placement offset and misalignment can be compensated, resulting in a resilient spacecraft design. A 3D model can then be derived from this configuration and fed back to indicate if the internal parts fit within the restricted volume. The spacecraft's volume, the shifting center of gravity (CoG) and the moments of inertia are an output of this analysis which can then be compared to the requirements of the launch vehicle [3].

## III. MISSION ANALYSIS AND OVERALL SPACECRAFT

### A. Mission Requirements

The mission requirements form the baseline of the design process and are directly given in the design challenge [4].

TABLE I  
MISSION REQUIREMENTS [4]

Mission Requirements	
Req. ID	Statement
MIS.001	The system shall send a satellite to Phobos which will release a surface probe to Phobos ,one of the moons of Mars, to study its origin as well as its physical and chemical composition.
MIS.002	The satellite shall be launched by a dedicated Ariane 62
MIS.003	The total system mass shall not exceed 2600 kg.
MIS.004	The launch date shall lay between 2026 and 2029.
MIS.005	The system shall reach an orbit around Phobos (Quasi-Satellite Orbit (QSO)) for a minimum of 2 years to study Phobos from space and to serve as a relay for the surface probe.
MIS.006	At end of life (EOL) the spacecraft shall be de-orbited into the martian atmosphere (40km altitude at periapsis).

## B. Basic Mission Trajectory

For a transit to Mars, multiple launch windows are possible within the required launch frame of 2026 to 2029 (MIS.004). The most interesting opportunities are the energy minima Type 2 transfers in 2026 [5] where the required characteristic energy (C3) and arrival excess speed are particularly low. In order to offer a safety margin in case of any delays, the second most optimal window, starting at 31.10.2026 was chosen which takes place before the most optimal one at 6.11.2026. So in a case of emergency the launch date can be prospered while still being able to fly the mission with the same hardware.

The trajectory starts by its carrier, an Ariane 62 (MIS.002) and its ejection on its outgoing asymptote. However, the mission launch opportunity requires  $9.144 \text{ km}^2/\text{s}^2$  of C3 where the Ariane 62 can only supply a infinity velocity of  $2.5 \text{ km/s}$  ( $6.25 \text{ km}^2/\text{s}^2$  C3). Therefore the first maneuver is performed to match the required C3, when the spacecraft is leaving the influence of earth. Next, a trajectory correction maneuver (TCM) is performed to target the arrival at Mars precisely. When arriving at Mars, a Mars orbit insertion (MOI) is performed to reduce the spacecraft access velocity to a high elliptical orbital velocity. When crossing Phobos orbital plane, an inclination change is done near to the spacecrafts apoapsis followed by a raise of its periapsis to intersect with Phobos orbit. To match the point in time where Phobos and the spacecraft align, a parking orbit is created where after one round-trip, Phobos is matched with a deceleration burn where now its orbital parameters are similar to achieve a quasi satellite orbit. For the required delta v to perform orbital maintenance, literature values for this case have been used as  $\frac{1.16}{8.23} \text{ m/s}$  delta v per day [6] and the mission duration MIS.005 plus margin. Ultimately as MIS.006 requires, the spacecraft is deorbited into the martian atmosphere through a deceleration burn at its apoapsis. The full set of delta v magnitudes for this impulsive trajectory and its V,N,B vector components are listed in table II corresponding to `MomenTUM_impulsive.script`.

TABLE II  
REQUIRED DELTA V FOR IMPULSIVE MANEUVERS

Maneuver Name	Magn. [m/s]
C Match C3	509.350
C TCM	34.553
C MOI	751.782
C Match INC	13.153
E Raise Peri	35.660
E Parking Insertion	197.507
E Match Phobos	640.000
E Orbital Maintenance	104.950
E EOL	561.664
<b>Total</b>	<b>2848.619</b>

V	N	B
x		
x	x	x
x		
	x	
x		
x		
x		
x	x	x
x		

## C. Propulsion System Trade-off

To analyze which propulsion system combination shall be used for this mission, the following trade-off, depicted in Table III is conducted. The objective is to select the configuration with the minimum launch mass, which is calculated by the mass budget script. The mission delta v used in this comparison originates from a finite chemical implementation of the impulsive trajectory `MomenTUM_biprop_only.script`. The maneuvers Raise Peri to EOL are considered done electrically in a mixed system. In this analysis, if a maneuver is performed with an electric engine, the delta v is doubled because of the high uncertainty in regard to the continuous thrust maneuvers. In this simplified case, only the biprop-electric and the biprop propulsion system fulfil MIS.003 and stay below the 2600 kg capability of the launcher [3]. Since the biprop-electric system has the lowest launch mass and the doubling of the delta V for the electrical maneuvers is assumed conservatively high, the lightest propulsion system is expected to be the combination of a bipropellant and electric propulsion. A more detailed comparison between the bipropellant only and the biprop-electric system can be found in the Appendix A.

TABLE III  
PROPULSION SYSTEM TRADE-OFF

Propulsion System Trade-off					
Propulsion System	Biprop Electric	Biprop	Electric	Monoprop Electric	Monoprop
Total Mission dV [m/s]	4698.2	3277.5	6555.0	4698.2	3277.5
Launch Mass [kg]	2124.4	2128.3	2878.3	3022.8	6949.7

## D. Advanced Mission Trajectory

To apply the selected bipropellant and electric system, the trajectory has to be adapted. For the bipropellant section, the general approach of maneuvers can be kept, since their burn-times are comparably short. Besides the C3 maneuver, which has no time constrains, only the MOI critically spreads over a longer range of space and time as seen in Figure 2.




Fig. 2. Chemical maneuvers: MOI, Match INC, Raise Peri min

After the inclination change and raising the periapsis to a minimum, the maneuvers are carried out by the electric propulsion in a different approach. The first electric section is the circularization of the orbit through a loop of burns by true anomaly which can be seen in figure 3 where yellow sections represent thrust arcs. The over-raise in periapsis comes for the

benefit of drastically reduced flight-time and the over-raising is therefore a compromise of minimal delta v and flight-time.




Fig. 3. Electric maneuver: Circularization

From there on, the electric thruster continuously fires to spiral down and approach Phobos. The very low eccentricity of Phobos is capitalized on here, so that a matching can be achieved from a circular spiral. To match the intersection with Phobos correctly in time, the spiraling is paused (displayed green in Figure 4) before its spiraling achieves a semi major axis of 9378.8 km and therefore a matching orbital period.




Fig. 4. Electric maneuver: Spiral Down Match

The Orbital Maintenance is assumed as in the impulsive section and its corresponding fuel mass is deducted. The EOL maneuver is also a loop of thrust arcs that decelerate the spacecrafts around its apoapsis, marked by true anomaly which can be seen in Figure 5. Hereby the assumption of 10 times the thrust equals to  $\frac{1}{10}$  of the nominal burn-time was made to reduce computation time. This concludes the finite simulation of the selected bipropellant electrical system carried out in the GMAT script `MomenTUM_finite.script`.




Fig. 5. Electric maneuver: EOL

#### E. *deltaV Budget*

As a result of the now fully specified trajectory and its finite simulation, the maneuver delta vs and burn times are given precisely in Table IV below.

TABLE IV  
DELTAV BUDGET

Maneuver Name	Type	[m/s]	[s]
C3	finite	516.868	2155.85
TCM	finite	1.395	5.35
MOI	finite	850.981	2858.31
Match INC	finite	14.550	42.44
Raise Peri min	finite	4.515	13.13
Total Chemical		1388.308	5075.07
Circularize	finite	713.753	10164236.2
Spiral Down Match	finite	831.526	11334710.2
Orbital Maintenance	stochastic	104.950	
EOL	finite, assumption	708.395	9035872.4
Total Electric		2358.624	30534818.8
<b>Total</b>		<b>3746.932</b>	<b>30539893.9</b>

An more in depth overview of the mission is put together in the mission timeline in Table XXVI that marks all states by a timestamp and their associated spacecraft values.

#### F. *Mass Budget*

The mass budget of the final spacecraft is depicted in Table V. It is generated by the mass budget script and lists all subsystems and propellants with their respective masses and margins. These margins are based on the ESA margin philosophy [2]. While most subsystem masses are already fixed for the mission, the STR and PWR subsystem need to be calculated via to following equations [4]. Regarding the STR subsystem, Equation 1 is used, while for the PWR subsystem, Equation 2 shall be applied. In case of the CPROP and EPROP subsystem, commercial parts are chosen to form the subsystems total mass. For the launch adapter, the PLA6 1194 is used which can be found in the user's manual of the

Ariane 62 [3]. In this budget, the dry mass is stated with the integrated Phobos surface probe, which is dropped in a later mission phase. This is because the harness and structural mass has to be sized for the probe as well, which then needs to be included. As a result, the dry mass is not a constant value over the whole mission.

$$m_{STR} = 0.0224 \cdot m_{wet} + 27.823 \quad (1)$$

$$m_{PWR} = 0.0758 \cdot P_{Earth} + 37.741 \quad (2)$$

TABLE V  
MASS BUDGET

SC Mass Budget		
System	Margin	Mass [kg]
AOGNC	40.0	
COM	25.0	
CDH	15.0	
CPROP	126.9	
EPROP	45.4	
INS	50.0	
MEC	55.0	
PWR	398.6	
STR	73.9	
TC	15.0	
Probe	20.0	
Harness	10%	86.6
<b>Dry Mass</b>		<b>951.3</b>
System Margin	20%	
<b>Dry Mass incl. System Margin</b>		<b>1141.6</b>
CPROP Fuel Mass		736.0
CPROP Fuel Margin	2%	15.0
CPROP Pressurant Mass		3.5
CPROP Pressurant Mass Margin	2%	0.1
EPROP Fuel Mass		162.7
EPROP Fuel Mass Margin	2%	3.3
<b>Total Wet Mass</b>		<b>2062.4</b>
Launch Adapter		85.0
<b>Total Launch Mass</b>		<b>2147.4</b>

### G. Spacecraft Baseline

As a result of the mass budget, the spacecraft baseline design can be derived, which is shown in Table VI. In it, the chosen main components of the individual subsystems are displayed together with some key data. While the mass and the propulsion components, together with the heating system, are a direct optimized result of the iteration process between GMAT, the delta v budget, mass budget and pressure drop script, some other components are chosen on the basis of the Ice Giants mission from ESA [7]. The Phobos surface probe as a payload can be traced back to MIS.001 in Table I. Especially the space frame design is chosen to keep the placement of the propulsion system components flexible.

TABLE VI  
SPACECRAFT BASELINE

Spacecraft Baseline Design	
Mass (incl. 20% sys. margin)	Dry mass: 1141.6 kg Chemical propellant mass (excl. margin): 751.3 kg Electrical propellant mass (excl. margin): 166.0 kg Wet mass: 2062.4 kg
Payload	Phobos surface probe Phobos imager
Propulsion	1x main bipropellant thruster (450 N) 12x RCS thruster (12 N) 2x pressurant tank (40 l) 1x bipropellant tank (331 l) 2x bipropellant tank (198 l) 1x electric thruster (0.090 N) 2x noble gas tank (60 l)
AOGNC	1x coarse rate sensor 2x navigation cameras 2x IMUs 2x star trackers 4x reaction wheels (+ RCS thrusters)
Communications	X-band uplink/downlink Ka-band downlink
Power	2x solar array (2m x 7.5m) Power Processing Unit (PPU) + internal batteries
Data Handling	Redundant On-Board Computing (OBC) capability + storage
Structures	Space frame design
Thermal	MLI insulation blankets Heating system within the pressurant tanks

## IV. CHEMICAL PROPULSION SYSTEM

### A. Chemical Propulsion System Requirements

The chemical propulsion system requirements in Table VII are derived from the mission requirements in Table I.

TABLE VII  
PROPULSION SYSTEM REQUIREMENTS

Propulsion System Requirements	
Req. ID	Statement
CPROP.001	The propulsion system shall provide the necessary thrust and delta v, required to perform the foreseen mission manoeuvres.
CPROP.002	The propulsion system shall provide torques to compensate the main engine misalignments and for all other attitude and orbit control maneuvers, including safe-mode operation and reaction wheel off loading, as required by mission planning.
CPROP.003	The subsystem shall have inhibits against critical failures leading to personnel hazard (e.g. while handling the spacecraft)
CPROP.004	The propulsion system shall include single failure tolerant measurement of the propellant pressure.
CPROP.005	The propulsion system shall provide means to isolate potential external leakages and/or failures of thruster flow control valves.
CPROP.006	The propulsion system shall include access points (valves) for filling and draining the propulsion system on ground.
CPROP.007	All components within the propulsion system shall be TRL9.
CPROP.008	As many components as possible within the chemical propulsion system shall be of european origin.

### B. Assumptions

For the chemical propulsion system design the assumptions listed in Table VIII were used for the calculations.

TABLE VIII  
ASSUMPTIONS

Assumptions	
1	The overall ISP for the bipropellant engine is assumed to be an average between the main engine and RCS thrusters weighed by their thrust
2	The power required at Mars was scaled with respect to the power requirement in Earth using the inverse square law.

### C. Chemical System Trade-offs

The initial system trade-offs in Section III-C resulted in the selection of a bipropellant chemical subsystem over monopropellant. The application of this subsystem as part of an upper stage engine with low thrust range ( $< 40$  kN) leads to the selection of a pressure fed cycle [4]. A dual-mode bipropellant system was disregarded since the bipropellant engine is relevant during the initial high-thrust phase of the mission, and the flexibility of switching to low-thrust, high-specific impulse propulsion is already provided by the electric propulsion subsystem.

Two main trade-off's were conducted for the bipropellant chemical subsystem design: the thruster selection process and the tank configuration.

The thruster selection was driven by requirements derived from the mission analysis calculations, which define a required thrust higher than 400 N, and a longest burn time of around 3000 s. The following thrusters were considered: Ariane S400-12, Ariane S400-15, NAMMO LEROS 2b and Aerojet Rocketdyne R-4D-15 HiPAT™. All these options fit the mission analysis requirements regarding thrust range, ISP, and oxidizer to fuel ratio. The Aerojet thruster was dismissed due to its US origin (CPROP.008). With the remaining European thrusters, the driver of the trade-off was the launch mass, which resulted the lower for the selected thruster: Ariane S400-15, as shown in Table IX [8].

TABLE IX  
BIPROPELLANT MAIN THRUSTER TRADE-OFF

Thruster	Launch mass [kg]	Thrust [N]	Burn Time [s]	ISP [s]
Ariane S400-12	1584.494	340 to 440 [420]	3960	318.000
Ariane S400-15	1578.371	342 to 440 [425]	6600	321.000
NAMMO LEROS 2b	1584.663	367 to 456 [420]	6600	319.500

Nominal values in []

The selected propellant combination is Monomethylhydrazine (MMH) and mixed oxides of nitrogen (MON-3). The fuel is defined by the thruster specification. With respect to the oxidizer, the thruster enabled using Nitrogen Tetroxide (NTO), MON-1 or MON-3. MON was selected over NTO due to its lower sensitivity to temperature fluctuations and the higher availability of European tanks with demonstrated

compatibility. MON-3 was chosen over MON-1 because it has a lower vapor pressure, making it easier to handle and safely store before and during the mission.

A further trade-off determined number of propellant tanks required. Figure 6 shows the options considered, whereby the propellant tanks are from Ariane Group and the pressurant tanks from MT Aerospace (CPROP.007 and CPROP.008).




Fig. 6. Bipropellant Tanks Configuration Trade-off

The lightest option is configuration 4, however later stability analysis explained in Section VI-B proved it unsuitable. Therefore, the next lightest and thus selected configuration includes one 331 l MMH tank, two 198 l MON tanks and 2 40 l helium tanks.

The rest of the subsystem is developed around the selected thruster and tank configuration. It will be described in detail in the following sections.

### D. Chemical Propulsion System Architecture

In this chapter the architecture overview of the whole bipropellant subsystem will be given and technical decisions derived from the system requirements will be justified. The Chemical propulsion subsystem was developed to fulfill specific system requirements, stated in Table VII, and assumptions depicted in the Table ?? and it is unique technical solution. The flow chart of the chemical subsystem with all the relevant details is shown in Figure 17 in the Appendix A. From the mission design it is derived that the first five maneuvers are performed using chemical propulsion including MOI which is the most demanding one concerning the overall propulsion subsystem. The main engine S400-15 from ArianeGroup shall provide the necessary thrust for this orbit insertion maneuver, the trajectory correction maneuver and remaining maneuvers while twelve ArianeGroup RCS thrusters S10-26 shall provide the thrust for a 3-axis attitude control once arrived in orbit around Phobos for at least two years. These two off the shelf bipropellant thrusters meet the requirements of this mission

and are chosen also considering economic reasons and heritage of around 40 completed missions for the S400-12 and S400-15 engines. Both selected thrusters are helium pressurized and use monomethyl-hydrazine (MMH) as fuel and mixed oxides of nitrogen MON-3 as oxidizer. From the flow chart it is visible that two 40 liter tanks are used for pressurized helium. To fill the tanks and access the fluid, fill and drain valves are placed after every tank. Helium is leaving the pressurant tanks with 310 bar and goes through a dual mechanical pressure regulator which lowers the pressure to 20 bar. Normally closed pyro valves are placed before and after pressure was regulated to isolate it in case of any leakage. Redundant check valves are ensuring that the flow is going only in the direction of the propellant tanks and safety relief valves are placed in case of any kind of over pressurisation of helium before entering the pressurization tanks. To secure that propellants are not going upstream and mixing with helium, normally closed pyro valves are placed before the propellant tanks. In the feed line of the main engine, pyro ladders are introduced and are chosen due to their redundancy and minimum leakage. Furthermore, the mission is designed in a way that the main engine is passivated in between the second and third maneuver due to long waiting time as well as after fifth (last chemical) maneuver which leads to a possible leakage of propellants. The pyro ladder will isolate main engine during these periods and ensures redundant access to the main engine. Upstream the RCS thrusters latch valve is placed to control the propellant flow for attitude control. The latch valves are used because of their ability to open and close numerous times which is advantageous in the case of attitude control. The S10-26 are dual seat thrusters meaning they have two flow control valves serially connected which allow a more precise attitude control and the shutdown of a thruster in case of a failure or malfunction.

#### E. Chemical Propulsion System Mass Budget

To compute the dry mass of the chemical subsystem, the component selection is iterated throughout the development process to ensure a failure free mission by choosing off the shelf equipment while taking into account heritage from already completed missions. The current baseline consists of the equipment listed in the Table X. One of the assumptions of this mission is to have an all European component design, but at this point of development some of the selected components are outside of Europe and are marked in orange. In future development steps, this should be replaced with European components to fulfill the CPROP.008 requirement and reduce cost. Taking into account the ESA margin philosophy [2], a margin of 20% is applied on pipes and 5% for off the shelf components.

TABLE X  
BIPROPELLANT PART LIST

Description	Type/Manufacturer	Amount	Mass per unit [kg]	Margin	Mass inc. margin
Pipes	Pipes	1	2.540	0.2	3.048
Main Engine	S400-15	1	5.200	0.05	5.460
RCS Thruster	S10-26	12	1.800	0.05	8.190
Helium Tank	PVG Family 40l	2	8.500	0.05	18.700
Fuel Tank	OST 25/0	1	21.000	0.05	22.050
Oxide Tank	OST 25/0	2	21.000	0.05	44.100
Fill Vent Valve	ArianeGroup	3	0.060	0.05	0.315
Latch Valve	ArianeGroup	4	0.545	0.05	2.289
Pyro Isolation Valve	ArianeGroup	16	0.160	0.05	2.688
Safety Relief Valve	Safran	2	0.700	0.05	1.470
Check Valve	Vacco	4	0.020	0.05	0.084
Filter	Vacco	8	1.500	0.05	12.600
Dual Pressure Regulator	Stanford Mu	1	1.130	0.05	1.187
Pressure Transducer	Bradford Space	5	0.230	0.05	1.207
Thermocouples	Collins Aerospace	12	0.350	0.05	4.410
Total					126.948

#### F. Chemical Propellant Budget

TABLE XI  
CHEMICAL PROPELLANT BUDGET

	[kg]	[kg]
Maneuver Name	MMH	MMO
C3	116.714	192.578
TCM	0.290	0.478
MOI	155.285	256.221
Match INC	2.298	3.791
Raise Peri min	0.169	0.280
Total Chemical	274.756	453.348
Margin 1% AOGNC	2.748	4.533
Margin 2%	5.495	9.067
Margin Sum	8.243	13.600
Leftover	8.744	14.427
<b>Total</b>	<b>283.500</b>	<b>467.775</b>

#### G. Helium Fill Level, Pressure and Temperature in Pressurant and Propellant Tanks

The feeding system for the propellant tanks is pressure regulated to enable for consistent and predictable performance and to optimize fuel efficiency, which is important for a long-duration mission. A pressure regulated system requires the pressurant gas to be stored in additional tanks. In the presented bipropellant system, the propellant tanks are pressurized with Helium stored in two 40-liter tanks from MT Aerospace [9].

The options considered as a pressurant gas were helium and nitrogen, which were determined by the selected propellant tanks. Helium is used as a pressurant gas due to the following advantages over nitrogen:

- its lower density, which means it can provide the same pressure at lower mass or volume
- a lower viscosity, useful for precise flow control and better flow over small orifices and valves

- it is non-reactive even at high temperatures and pressures, making it ideal for use in a pressurized system where contamination or chemical reactions can be a concern

However, there are also some disadvantages to using helium over nitrogen. For example, helium is more expensive and less widely available than nitrogen, which can make it less cost-effective. Nonetheless, its low density and thus reduction of the launch mass is the deciding factor in favour of helium.

To guarantee the required operation of the bipropellant chemical thrusters, thereby contributing to requirement CPROP.001, a thorough analysis of the Helium fluidic conditions throughout the bipropellant engine operation is performed. This analysis is based on the assumptions listed on Table XII.

TABLE XII  
ASSUMPTIONS PRESSURANT TANK SIZING

Assumptions	
1	The initial ullage volume in the propellant tanks is filled with Helium before the start of operation.
2	The temperature of Helium in the propellant tanks is calculated as the equilibrium temperature between the Helium in the tank and the incoming Helium from the pressure regulator.
3	The temperature increase of Helium over the pressure regulator due to the Joule-Thomson effect is averaged over the maneuver time with the conditions at the beginning and end of the maneuver.
4	Heat transfer in Helium within the propellant tanks at the liquid-vapour interface and at the tank walls is neglected.
5	The required combustion chamber inlet pressure is 18.5 bars and the pressure drop between the propellant tanks and the thruster is 1.5 bars, leading to a required propellant tank pressure of 20 bars

For the propulsion system design, one of the most relevant parameters is the amount of helium required in the system since it influences the launch mass, both directly as additional wet mass and indirectly as it affects dry mass of the required pressurant tanks. In order to maintain the required engine operation, the pressurization system shall contain enough helium for all foreseen maneuvers and at least an additional ullage mass of 20 %. Table XIII shows the fulfillment of these conditions.

TABLE XIII  
PRESSURANT TANK MARGIN

Initial Helium Mass in Pressurant Tank [kg]	3.266
Total Helium Mass maneuvers [kg]	1.961
Leftover Helium in pressurant tank [kg]	1.305
<b>Pressurant Mass Margin [%]</b>	<b>40.000</b>
Required Pressurant Mass Margin [%]	20.000

Regarding the selection of the pressurant tanks, two suppliers were considered: Northrop Grumman and MT Aerospace. Despite the higher range of volumes offered by the Northrop Grumman [10], it was not selected because of its US origin (CPROP.008). The high-pressure helium tanks offered by MT aerospace have a Mean Operating Pressure (MEOP) of 310 bars, which results in a total volume of helium of 48 liters required for maneuvers. Considering an ullage volume of

20 %, the volume of helium shall be at 57.6 ( $m^3$ ) [4]. Nevertheless, the sizing of the helium tanks is not only dependent on the required volume, but also on the helium pressure and temperature conditions, both in the propellant and in the helium tanks. For this reason, a fluidic simulation was performed with the following objectives:

- guaranteeing safe propellant conditions;
- maintaining the pressure of helium within the pressurant tanks above the 20 bars required in the propellant tanks;
- keeping the helium temperature within the pressurant tank between - 30 and + 60°C as specified by the tank supplier (Table XXV);

The calculated pressure and temperature conditions of helium within the pressurant tanks throughout the maneuvering time are depicted in figures 8 and 7. For this calculation, only the first five maneuvers are considered, since the remaining maneuvers are not performed with the chemical engine. As observed in figure 7, the helium pressure is still above 100 bars after the last chemical maneuver, leaving more than enough margin for the RCS thruster operation. The temperature of helium within the pressurant tank remains between - 20 and + 50°C, as depicted in figure 7 fulfilling the aforementioned tank temperature constraint. In order to keep the temperature in this range, a heater is added to the pressurant tank. This heater is active in between maneuvers, as well as during the biggest maneuvers, which coincide with the biggest pressure and temperature drops in the charts: the first and third maneuver, namely C3 and MOI respectively.




Fig. 7. Helium Pressure in Pressurant Tanks




Fig. 8. Helium Temperature in Pressurant Tanks




Fig. 9. Helium Mass in Tanks

Table XIV displays the exact pressure and temperature values at the beginning and end of each chemical maneuver, as well as the heating power required. The pressurant tank is warmed up to 50 °C before the beginning of operation and between the second and third maneuvers; and to 20 °C before the last two chemical maneuvers. The maximum heater power required is 200 W during the MOI maneuver, which can be easily provided by the power system since at this point of operation, the electric engine is still not in use.

TABLE XIV  
PRESSURANT TANK SIZING

	[m/s]	[kg]	[bar]	[°C]	[W]
Maneuver Name	Delta v	Helium required	Pressure	Temperature	Heater
C3	509.350	0.836	310.000 177.175	50.000 -17.479	50
TCM	34.553	0.002	177.175 176.903	-17.479 -17.635	OFF
Waiting time			223.156	50.000	≤50
MOI	751.782	1.105	223.156 96.268	50.000 -6.683	200
Waiting time			105.854	20.000	≤50
Match INC	13.153	0.017	105.854 103.498	20.000 17.369	OFF
Rais Peri min	35.660	0.001	103.498 103.332	17.369 17.184	OFF
Total Helium Mass maneuvers [kg]	1.961				
Ullage Helium in propellant tanks [kg]	0.259				
Leftover Helium in pressurant tank [kg]	1.305				
Total Helium Mass [kg]	3.525				

As shown in the last four rows of the table, the total amount of helium required in the system is 3.525 kg, accounting for the helium within the pressurant tanks and the initial helium within the propellant tanks filling their ullage volume. The mass distribution of helium within the bipropellant feeding system throughout the maneuvering time is depicted in Figure 9.

With respect to guaranteeing safe propellant operation, the relevant parameter is the helium temperature within the propellant tanks. It is critical to prevent the freezing of the propellants during operation. The freezing temperature of MMH is - 52 °C [11] and -15 °C for MON-3 [12] at a pressure of 20 bars. The upper temperature limit is defined by the boiling temperatures at this pressure condition, which are approximately 87 °C for MMH and 56 °C for MON-3 [13]. Figure 10 shows that the temperature of helium within the propellant tanks stays between 20 and 36 °C throughout operation, within the propellants' safe temperature range.




Fig. 10. Helium Temperature in Propellant Tanks

#### H. Reaction Control System (RCS)

The RCS system is based on the CPROP.002 requirement, shown in Table VII. To design this RCS system, an allowable engine offset and misalignment is needed. In this case, the engine offset can be interpreted as an offset of the center of gravity from the main axis as well. An allowable offset of 60 mm is given for the launch phase as a static unbalance for a three-axis stabilized spacecraft in the launchers user's manual [3]. For the design of this RCS system, a similar offset shall be chosen. In this case, the static offset shall not be traced back to the misplacement of the engine as the only source.

For the engine misalignment, the Ice Giants mission is used as a reference [7]. The resulting allowable combined engine errors are depicted in XV. Because the RCS system is not only needed for the compensation of the main engine moments in the thrust phases, but also for the AOGNC maneuvers, namely the desaturation of the reaction wheels while in the station keeping phase around Phobos, the RCS system shall be placed at the location where it's needed for the longest time duration. This then leads to a positioning in the center of gravity plane at the station keeping phase. For the positioning of the RCS thrusters, the configuration displayed in Figure 11 is selected. This configuration of 12 thrusters each, shows an overall good static and dynamic tracking error as well as a redundancy of two thrusters and is also portrayed as the best out of 14 different configurations [14]. More thrusters would increase the redundancy but also lead to a higher system mass and more complex system because the piping needs to be considered as well. Therefore, this configuration is chosen. In it, each bipropellant RCS-engine has a thrust of 10.25 N for the given pressure of the propellant, which also feeds the main bipropellant engine.

TABLE XV  
ALLOWABLE ENGINE MISALIGNMENT

Allowable combined engine errors	
Maximum offset [mm]	50.0
Maximum misalignment [deg]	1.0




Fig. 11. RCS Thruster Configuration

## V. ELECTRICAL PROPULSION SYSTEM

### A. Electrical Propulsion System Requirements

TABLE XVI  
ELECTRIC PROPULSION SYSTEM REQUIREMENTS

Electric Propulsion System Requirements	
Req. ID	Statement
EPROP.001	The total mass of the electric subsystem shall be as low as possible.
EPROP.002	The additional power demand shall be as low as possible.
EPROP.003	The thruster shall have a burntime of under one year to achieve the required deltaV.
EPROP.004	All parts shall be originated from european manufacturers.
EPROP.005	The thruster shall be capable to perform orbital maintenance
EPROP.006	All components within the electric propulsion system shall be TRL9.

### B. Electrical Propulsion System Trade-off's

The electrical propulsion system is completely build around its key component, its thruster. In the thruster selection its specified thrust, power demand and specific impulse all together ultimately have driven the selection. Following EPROP.001, the lowest total mass is the target value to optimise for. The complete mass of the electrical propulsion system contains not only hardware and fuel mass but also the mass associated to meet the additional power demands. In compliance with EPROP.004 all to us available european electric thrusters have been collected and are evaluated in Table XXVII. To ensure EPROP.005, a minimal thrust of approximately 5 mN is required (discarded marked red). Using the impulsive delta v values by an uncertainty factor of 2, for the sections planned to be performed electrically, burn times can be computed. In order to set a limit in flight time and feature realistic operational times, EPROP.003 was created and applied. This additional requirement narrowed down the options significantly (discarded marked red). As EPROP.003 being an indirect requirement on thrust at roughly 80 mN, EPROP.005 is passively contained. From there, the fuel mass was calculated over delta v and specific impulse as well as the additional solar mass was derived from the linear part of the power mass Equation 4. The minimal sum of which leaded to the selection of the Safran PPS 1350 Hall Effect Thruster, which was additionally refined by trying out all narrowed down options in the mass\_design.m script and comparing its launch masses. Both approaches concluded the same choice.

### C. Electrical Propulsion System Architecture

To complete the system architecture, additional components have been selected suiting the Safran PPS 1350 Thruster. As suggested in the Safran Portfolio [15], the complete propulsion system for the SMART-1 lunar probe was presented as setup for this thruster. Conveniently almost all of the components can be transferred to this mission which lead to the copy of the system architecture of SMART-1 for this mission. Only the xenon tank did not suit the required fuel mass and had to be replaced as shown in Table XVII. This was additionally convenient since the xenon tank was the only part being manufactured outside of Europe and by this change EPROP.004 can remain fulfilled. Since only the subsystem drymass of SMART-1 was reported, the tank mass of the Lincoln Composites xenon Tank was estimated and deducted from the SMART-1 subsystem drymass. The adapted flowchart of the electrical propulsion system and connection of components can be seen in Figure 18 and the hardware in Figure 19.

#### D. Electrical Propulsion System Mass Budget

TABLE XVII  
ELECTRIC PARTLIST

Description	Manufacturer	Qt.	[kg] Mass per Unit	[kg] Marg.	[kg] Total Mass
Hall Effect Thruster PPS 1350	Safran (France)	1			
xenon Flow Controller	Safran (France)	2			
Bang-Bang Pressure Regulation Unit	Safran (France)	1			
xenon Tank 49 liter	Lincoln Comp. (USA)	1	> 5.000		
Power Processing Unit Thruster Switch Unit	ETCA (Belgium)	1			
Pressure Regulation Electronic Card	Atermes (France)	1			
SMART-1 subsys. drymass		1	29.000		
SMART-1 subsys. drymass without Xe tank		1	24.000	0.05	25.200
xenon Tank S-XTA / 120l	MT Aerospace (Germany)	1	16.800	0.20	20.160
<b>Total</b>					<b>45.360</b>

#### E. Power Budget and Solar Panel Sizing

Due to a very high efficiency of the Power Supply Unit (PPU), the total power demand of the electrical system is set equal to the power usage of the Hall Effect Thruster itself. Therefore, the power demand of the electrical system of 1500W is added to the base power usage of 550W which together is converted via the provided power system mass formula directly as seen in Equation 4 below. To transfer power requirements from Mars to Earth, the inverse-square law is used as in Equation 3. The additional power demand of the electric propulsion is consequentially scaling the power mass linearly by a factor of  $0.0758 \cdot 1.524^2$  kg per Watt. The power system mass  $m_{PWR}$  (Equation 4) is including the mass of the solar arrays as well as the power conditioning hardware.

$$P_{\text{Earth}} = P_{\text{Mars}} \cdot 1.524^2 = 2050W \cdot 1.524^2 = 4761.3W \quad (3)$$

$$m_{PWR} = 0.0758 \frac{\text{kg}}{\text{W}} \cdot P_{\text{Earth}} + 37.741\text{kg} = 398.65\text{kg} \quad (4)$$

The surface area of the solar panels is directly derived by the solar constant at Mars  $E_{\text{Mars}}$  and an assumed solar cell efficiency of  $\eta = 0.29$ .

$$A_{\text{Solar}} = \frac{P_{\text{Mars}}}{\eta \cdot E_{\text{Mars}}} = \frac{2050W}{0.29 \cdot \frac{1361}{1.524^2} \frac{\text{W}}{\text{m}^2}} = 12.06\text{m}^2 \quad (5)$$

In order to fit a modular size for the solar panels, the solar array area is rounded up to  $A_{\text{Solar}} = 13\text{m}^2$  into two symmetrical 6.5 m x 1 m sections.

#### F. Electrical Propellant Budget

TABLE XVIII  
ELECTRICAL PROPELLANT BUDGET

Maneuver Name	[kg]
Circularize	51.805
Spiral Down Match	56.065
Orbital Maintenance	6.982
EOL	47.725
Total Electric	162.578
Margin 2%	3.252
Leftover	3.422
<b>Total</b>	<b>166.000</b>

#### G. Technology Needs

Besides all other components being flight proven and align with EPROP.006, the selected xenon Tank from the S-XTA family of MT Aerospace is still under development and is therefore a technological need.

## VI. SPACECRAFT ARCHITECTURE

#### A. Spacecraft Orientation

The orientation of the spacecraft in the quasi-satellite orbit around Phobos in respect to Phobos is chosen in a way, that the instruments always face Phobos, as displayed in Figure 12. To achieve such an orientation in the main axis frame of the spacecraft, a constant rotation around the Z-axis is needed. The rotation speed has to match one orbital period around Mars. In this case, a rotational period of 27576.2 seconds is needed. In this orientation, the AOGNC system shall provide the required torques to counter the induced orbital perturbations. For station-keeping, the electrical engine is used. The RCS thrusters enable reaction wheel desaturation of the AOGNC system by locking the spacecraft in place. While the chemical and electrical thrusters are placed alongside the X-axis of the spacecraft, the solar arrays are located alongside to Y-axis, where they can rotate freely around the axis without changing the spacecrafts attitude. This orientation is chosen to ensure sun-tracking of the solar arrays. As presented in Figure 13, the instrument and communication subsystem are located on the Z-axis to ensure, that the field of view is always in the direction of Phobos and undisturbed by the other parts of the spacecraft. In case of the transmission of data to Earth or the Mars Relay Network via i.e. NASA's Mars Reconnaissance Orbiter (MRO) or the Mars Atmospheric and Volatile EvolutioN (MAVEN) orbiter, the spacecraft can interrupt its constant rotation around the Z-axis to then point itself in the dedicated direction [16]. This capability is also needed for the orbital station-keeping maneuvers to point the X-axis, and therefore the thrust vector, respectively.




Fig. 12. Spacecraft orientation in XY-plane




Fig. 13. Spacecraft orientation in YZ-plane

### B. Spacecraft Stability Analysis

To ensure that a flat spin is not occurring during the mission phase around Phobos where a constant rotational speed is present, the following relation for the moments of inertia in the main axis system, shown in Equation 6, needs to be fulfilled [1].

$$I_z \geq I_y \geq I_x \quad (6)$$

While the components of the spacecraft that account for the dry mass, except the Phobos surface probe, are stationary in respect to the internal spacecraft frame, the propellants are not. Therefore the center of gravity (CoG) shifts over the mission as displayed in Table XIX. Since the CoG is the reference point for the calculation of the moments of inertia, these change as well over the duration of the mission, presented in Table XX. In all instances, the criteria set in Equation 6 is fulfilled. To further validate this stability analysis, the CoG can be

moved away from the X-axis by 60 mm in the Y- and Z-direction, which is the maximum tolerable limit given by the Ariane 6 user's manual for the static unbalance of a three-axis stabilized spacecraft [3]. With this offset, the moments of inertia, displayed in Table XXI result. In this case, the stability criteria is still valid, therefore the chosen configuration is feasible.

TABLE XIX  
CENTER OF GRAVITY

Center of gravity over time					
Point in time	1	2	3	4	5
$CoG_x$ [m]	1.6966	1.7322	1.7324	1.9146	1.9192
$CoG_y$ [m]	0.0000	0.0000	0.0000	0.0000	0.0000
$CoG_z$ [m]	0.0000	0.0000	0.0000	0.0000	0.0000
Point in time	6	7	8	9	10
$CoG_x$ [m]	1.9196	1.8928	1.8613	1.8571	1.8276
$CoG_y$ [m]	0.0000	0.0000	0.0000	0.0000	0.0000
$CoG_z$ [m]	0.0000	0.0000	0.0000	0.0000	0.0000

TABLE XX  
MOMENTS OF INERTIA

Moment of inertia over time					
Point in time	1	2	3	4	5
$I_x$ [ $kgm^2$ ]	3008.1	2885.0	2884.7	2720.8	2718.3
$I_y$ [ $kgm^2$ ]	5626.6	5571.0	5570.8	5496.9	5495.8
$I_z$ [ $kgm^2$ ]	7416.7	7238.0	7237.6	6999.8	6996.1
Point in time	6	7	8	9	10
$I_x$ [ $kgm^2$ ]	2718.1	2718.1	2718.1	2718.1	2718.1
$I_y$ [ $kgm^2$ ]	5495.7	5455.0	5411.0	5405.5	5368.1
$I_z$ [ $kgm^2$ ]	6995.8	6955.2	6911.2	6905.7	6868.3

TABLE XXI  
MOMENTS OF INERTIA WITH AN OFF-CENTER COG BY 60 MM IN Y- AND Z-DIRECTION

Moment of inertia over time					
Point in time	1	2	3	4	5
$I_x$ [ $kgm^2$ ]	2967.7	2860.8	2860.5	2718.3	2716.0
$I_y$ [ $kgm^2$ ]	5631.4	5574.7	5574.6	5499.1	5498.0
$I_z$ [ $kgm^2$ ]	7372.4	7211.0	7210.6	6995.9	6992.6
Point in time	6	7	8	9	10
$I_x$ [ $kgm^2$ ]	2715.9	2715.5	2715.1	2715.1	2714.7
$I_y$ [ $kgm^2$ ]	5497.9	5457.1	5412.9	5407.3	5369.7
$I_z$ [ $kgm^2$ ]	6992.3	6951.5	6907.3	6901.8	6864.2

### C. Spacecraft Launcher Compatibility

In this section it shall be analyzed, if the spacecraft complies with the requirements of the Ariane 62 launch vehicle, depicted in Table XXII. Here, the CoG envelope is a result from the given equations with the inserted spacecraft wet mass, which is presented in Table V for a spacecraft with a wet mass bellow 4 tons. By comparing these values with the spacecrafts characteristics in Table XXIII it can be demonstrated, that the requirements of the launch vehicle are fulfilled, even with a margin of 10 %. Also the moments of inertia in the transverse and rolling directing are within the given boundaries. Consequently, the spacecraft is suited for a launch with the Ariane 62 launch vehicle.

TABLE XXII  
ARIANE 62 LAUNCH VEHICLE REQUIREMENTS [3]

Ariane 62 launch requirements	
Launch weight requirement [kg]	<2600.0
Diameter [m]	<4.600
CoG requirement in X [m]	0.4887 <CoG <2.3663
CoG requirement in Y and Z [m]	CoG <0.060
Spacecraft transverse inertia momentum [ $kgm^2$ ]	<90000
Spacecraft roll inertia momentum [ $kgm^2$ ]	<45000

TABLE XXIII  
SPACECRAFT LAUNCH PARAMETERS

Spacecraft launch parameters	
Launch weight [kg]	2141.4
Launch weight with 10 % margin[kg]	2355.5
Dimensions in X [m]	4.000
Dimensions in Y and Z (without RCS) [m]	2.7058 x 2.7058
Dimensions in Y and Z (with RCS) [m]	2.7058 x 3.8250
CoG in X [m]	1.6966 to 1.9196
CoG in X with 10% margin [m]	1.5269 to 2.1116
CoG in Y and Z [m]	0.000
Spacecraft transverse inertia momentum in Y [ $kgm^2$ ]	3008.1
Spacecraft transverse inertia momentum in Z [ $kgm^2$ ]	5626.6
Spacecraft roll inertia momentum in X [ $kgm^2$ ]	7416.7

To conclude this section, the spacecraft is shown in the chosen fairing, namely the A62 short fairing, in Figure 14 with its solar panels folded. The dimensions of the fairing are taken from the Ariane 6 user's manual [3].




Fig. 14. Spacecraft in the A62 short fairing with undeployed solar arrays

### D. Spacecraft Rendering

The final rendering of the spacecraft together with a rendering of the propulsion system of the spacecraft is visualized in this section. The first rendering shows the spacecraft in its orbital configuration with the solar arrays deployed in Figure 15. The key components that make up the chemical and electrical propulsion system together with the dedicated piping are shown in the second rendering, Figure 16. Special attention is given to the complex orientation of the pipes in 3D so that the amount of bends is equal between the respective MMH pipes from the tank in red and the MON-3 pipes form both tanks in light blue. This ensures a similar pressure drop over the pipes between the fuel tanks and the engine. The helium tanks in purple are located on top of the fuel tanks. In the middle right above the MMH tank is the xenon tank in cyan which feeds into the electrical propulsion system. More information about the placement of the individual parts is given in form of the technical drawings in the Appendix A.




Fig. 15. Spacecraft with deployed solar arrays




Fig. 16. Spacecraft Propulsion System

## VII. SUMMARY AND LESSONS LEARNED

The report aimed to propose a preliminary design for the propulsion system of a spacecraft that will deliver a surface probe to Phobos. The concept presented combines a chemical and electrical engine, with all necessary components selected and displayed in their respective system schematics. The orbit trajectory selected to reach the destination with the proposed concept is also described. Simulations of the pressure and temperature of helium as a pressurant gas were performed and an analysis for the whole spacecraft stability and RCS thruster function was conducted, to ensure feasibility and safe operation.

The concept development process highlighted the complexity of designing a propulsion system for space missions. The main lesson learned by the team was that every component and aspect in the system is interconnected and that each design

decision has a significant impact on the overall system. For example, each small change in the mission trajectory affected the propellant budget which, affects the weight and feasibility of the propulsion system. Similarly, using two propellant tanks instead of one redefined many other aspects such as the launch mass, the pressurant gas calculation or the stability analysis.

The study presented a feasible preliminary design for the propulsion system, but there are still several open points that require further investigation. One such point is the design change of using one helium tank instead of two, which needs to be further analyzed for its feasibility and impact on the overall propulsion system. Furthermore, a more detailed calculation of the pressure drops over components and pipes needs to be conducted to redefine the pressure needed in the propellant tanks. This calculation could potentially affect the performance of the propulsion system. For the presented concept, the inlet pressure for the combustion chamber was taken as its maximum of 18.5 bars. However, its effect on the mixture ratio or efficiency of the engine, which requires further study. In case of the spacecraf's arrangement, the analysis is performed in a simplified manner. For a more detailed analysis, a CAD program can be used to analyze the behaviour of the center of gravity as well as the moments of inertia. Addressing these open points will improve the feasibility and performance of the proposed mission.

## VIII. TEAM SETUP

### A. Beatriz Mas Sanz - Systems Engineer

- 1) Project Plan and Requirements Definition
- 2) Propulsion System Trade-offs
- 3) Pressurant Tank Sizing Script

### B. Marta Pelivan - Propulsion System Architect

- 1) Chemical Equipment Selection
- 2) Chemical Propulsion Architecture

### C. Julian Schmid - Spacecraft System Architect

- 1) MATLAB script mass design
- 2) MATLAB script arrangement analysis
- 3) MATLAB script dV
- 4) 3D Assembly and technical drawings

### D. Sven J. Steinert - Mission Analyst and IT Specialist

- 1) GMAT Trajectory and Evaluation
- 2) 3D Modelling
- 3) Electric Propulsion System

## IX. ACCESS OF DATA

All presented files can be accessed in the Git-Repository.

## X. INDIVIDUAL WORK - BEATRIZ MAS SANZ

### A. Project Plan and Requirements Definition

During the very initial development stages, it was important to align the core objectives of the space propulsion system design and the steps to achieve them.

1) *Requirements Definition:* The mission requirements (Table I) and the main propulsion system requirements (Table VII) were mostly derived from the design challenge and were validated against every iteration performed to develop the system [4]. Some additional requirements were added regarding the origin of the components and their technology readiness level. By using components with TRL9, the risk of failure or incomplete development, is minimized. The preference for European components was set as a requirement for the following reasons:

- Compatibility: By using components from the same region, compatibility issues may be minimized.
- Regulations: Certain components from outside of Europe are subject to export controls or import restrictions.
- Support: using European suppliers, the production team will have easier access to technical support during the system manufacturing and testing process.

Additionally, this project can be a way to showcase European technology and expertise, and to support European industries and jobs.

The main design driver was selected to be the launch mass, not only due to the decisive constraint of 2600 kg set by the Ariane 62 launcher, but also to maximize the benefit of every kilogram sent to space. The overall cost of the propulsion system was not assessed, due to the lack of information found about the components costs. Regarding more detailed subsystem requirements, the ECSS Standard for Propulsion General Requirements was reviewed to select the applicable requirements [17]. Most of these requirements are too detailed for this early stage of conceptual development, but they provided a relevant overview of what aspects needed to be considered: global performance, subsystem sizing, imbalances, contamination and cleanliness or leak tightness, to name a few.

2) *Project Plan:* Once the mission objectives were defined, Figure 21 shows the project plan. The main use of this plan was to have an estimation of how much time was available for each phase, considering the reduced time frame to achieve the final objectives.

### B. Propulsion System Trade-offs

1) *Pairwise Comparison and Utility Analysis:* At the point of development where the type of propulsion system was still unclear, a pairwise comparison and utility analysis was the methodology used to compare the different options in combination with the mass estimation script: `mass_design.py`. Several relevant criteria were defined to evaluate the different options [18]. These criteria include:

- Launch mass (MIS.003)
- Volume propulsion system (MIS.002)
- Power Requirement (MIS.005)

- Industrialization (CPROP.006)
- Technological Risk (CPROP.007)
- Propellant Toxicity (CPROP.003)

The selection and weighing of the criteria was derived from the defined system requirements. Each criterion was assigned a weighing factor using a pairwise comparison. The resulting weights correspond to the design philosophy of the project: launch mass is the most important criterion, followed by industrialization, as depicted in Figure 22. This trade-off was performed between four different propulsion systems: bipropellant only or bipropellant-electric propulsion from European or US suppliers. The American thrusters considered were Aerojet Rocketdyne R-4D-15 HiPAT™ (bipropellant) and NASA's NEXT-C Thruster (electric). For the European options Ariane Group S400-12 apogee engine (bipropellant) and Ariane Group Radio Frequency Ion Thruster RIT 10 EVO were considered. Each concept was evaluated for each criterion and the utility analysis shown in Figure 20 resulted in the overall concept selection of a bipropellant-electric propulsion system from European suppliers.

A validity check was performed on the objectivity of the evaluation method by removing the worst concept or the least important criteria and proving that the winning concept remains the same in both scenarios.

### 2) Chemical System Tank Configuration Trade-off Script:

The objective of the Tank Configuration MATLAB Script was to optimise the number of MMH and MON tanks with regards to the system mass. Given the initial estimations for propellant volumes and the tanks available from both Ariane Group and MT Aerospace, different configurations were considered. The detailed tank selection for each assessed configuration is depicted in section IV-C. The additional helium required to fill the ullage volume in the propellant tank is also calculated and compared to ensure that the mass saved with a bigger tank is not regained as wet mass.

### C. Pressurant Tank Sizing Script

The `pressure_temp_sim.m` script was developed based on the calculations presented by NESC Academy in their online lesson for Bottle Blow-Down analysis [19] and it was adapted to the needs and conditions of this concept development. The script is structured as follows:

1) *Inputs from Mission Analysis:* The inputs necessary for the pressure script calculation come from mission analysis. GMAT provides the propellant mass necessary per maneuver and the maneuver durations. These values are extracted by the script from a `.xlsx` file derived from the GMAT output `result_clean.txt`.

2) *Inputs from System Architecture:* Further inputs required for the calculation come from the tank and propellant selection. Specifically, these inputs entail the volume of the selected propellant and pressurant tanks, their mean operating pressures and the density of the propellants. The freezing and boiling temperatures and vapor pressure of the propellants are not required for the calculations. Nevertheless, they shall

be considered when analyzing the results, to make sure the propellants stays out of the critical conditions.

*3) Definition of initial state of helium in every tank and boundary conditions:* Helium is initially stored within the helium tank at a pressure of 310 bars and it is pre-heated to 50 °C before the first maneuver. The selection of the initial conditions traces back to the tank specification: the initial pressure is the tank's MEOP and the temperature is 10 °C below the maximum allowable tank temperature (Table XXV). Regarding the conditions in the propellant tanks, the pressure is kept constant at 20 bars by the pressure regulator and the initial temperature is set to ambient temperature (20 °C). The assumption of a 20 bar pressure in the propellant tanks, is an estimation calculated by adding the known pressure drops over the selected valves and adding additional 0.25 bars for the piping. However, this assumption is yet to be validated.

*4) Heat Load selection:* The heat flow required during maneuvers to prevent the temperature of helium from falling below 20 °C is set as an input for the calculation. However, it needs to be iterated manually in case this condition is not fulfilled. With respect to heating up in between maneuvers, it is also iterated manually by setting the target temperatures after the waiting times between TCM and MOI maneuvers and between MOI and Match INC. In the final iteration, these temperatures are set to 50 °C and 20 °C respectively.

*5) Iterative calculations for each maneuver and waiting times:* Firstly, an initial approximation of the temperature of helium when reaching the propellant tanks is calculated. This calculation considers the temperature increase of helium over the pressure regulator due to the Joule Thomson effect  $\Delta T_{Maneuver}$  [20] as shown in Equation 7, where  $p_{HePropTank} - p_{HeHeTank}$  is the pressure drop over the pressure regulator and the Joule Thomson coefficient for Helium is  $\mu = -0.06K/bar$  [20]. This approximation assumes that neither pressure nor temperature change within the helium tank during the maneuver.

$$\Delta T_{Maneuver} = \mu \cdot (p_{HePropTank} - p_{HeHeTank}) \quad (7)$$

Secondly, the amount of helium required per maneuver is calculated iteratively. How much helium is required to fill the volume in the propellant tanks left free by the consumed propellants depends on the density of the helium under the conditions in the propellant tank. However, the propellant tank conditions at the end of the maneuver are dependant on the conditions of the pressurant tank at the end of the maneuver, which again depend on the amount of helium required for the maneuver. This co-dependence explains the performed iteration. During this iteration, the temperature of helium within the propellant tanks  $T_{HePrT2}$  is calculated as the equilibrium temperature between the helium that is already in the propellant tank  $m_{HePrT} \cdot T_{HePrT1}$  and the incoming helium from the pressure regulator  $m_{HeMan} \cdot T_{HePR}$ .

$$T_{HePrT2} = \frac{m_{HePropT} \cdot T_{HePrT1} + m_{HeMan} \cdot T_{HePR}}{m_{HePrT} + m_{HeMan}} \quad (8)$$

Using the final equilibrium temperature  $T_{HePropT2}$  the density of helium within the propellant tanks is defined and

finally the required helium mass to fill the required volume each maneuver. The amount of helium required per maneuver defined the helium mass flow which enables the calculation of the helium status within the helium tank at the end of the maneuver. The changes of helium conditions over the maneuvers are neither isothermal nor adiabatic processes, so the first thermodynamic equation is used to calculate the change in the internal energy of the gas [19]. Equation 9 exemplifies the calculation of the internal energy of helium after a maneuver  $U_{He2}$ . It depends on the internal energy before the maneuver  $U_{He1}$ , the maneuver duration  $t_{Man}$ , the heat load applied during the maneuver  $\dot{Q}_{Man}$ , the enthalpy of the helium leaving the tank  $H_{He1}$  and its mass flow  $\dot{m}_{HeMan}$  [19]. Thereafter, the Coolprop database [21] is integrated to the script to calculate the pressure and temperature of helium based on its internal energy and density, hence considering helium a real gas.

$$U_{He2} = U_{He1} + t_{Man} \cdot (\dot{Q}_{Man} - H_{He1} \cdot \dot{m}_{HeMan}) \quad (9)$$

At this point, the pressure and temperature of helium after a maneuver has been calculated, so the initial assumption of constant conditions in the pressurant tank can be corrected. The whole calculation is repeated again averaging the temperature increase over the pressure regulator with the initial and final pressure in the helium tank. Table XXIV represents the results for intermediate calculations of the helium temperatures at different stages.

TABLE XXIV  
HELIUM TEMPERATURE

Maneuver Name	[°C] Temperature in Helium Tank	[°C] Joule-Thomson Avg. Temperature Increase	[°C] Avg. Temperature reaching Propellant Tank
C3	50.000 -17.676	13.407	29.569
TCM	-17.676 -17.869	9.404	-8.369
MOI	50.000 -14.791	7.866	25.470
Match INC	20.000 16.387	4.111	22.304
Raise Peri min	16.387 16.004	4.020	20.215

Consequently new values for the required helium per maneuver and condition changes are obtained, that lead to the final results per maneuver. Two waiting times are also considered in the script, where the conditions of helium in the pressurant tank change due to the temperature increase induced by the electric heater in the tank.

*6) Results Display:* One of the most important results of this script are the amount of helium required in total, since it directly influences the launch mass; and the amount of helium required for the maneuvers, since it defines the size of the pressurant tanks. Furthermore, the filling level, pressure and temperature changes of helium within the pressurant tank throughout the maneuvering time are displayed. These demonstrate there is enough helium for all maneuvers and enough remaining helium to operate the RCS thrusters, and its pressure and temperature conditions fulfil the objectives described in Section IV-G.

## REFERENCES

- [1] U. Walter, *Astronautics: The Physics of Space Flight*. Springer eBook Collection, Cham: Springer International Publishing, 3rd ed. 2018 ed., 2018.
- [2] European Space Agency, “Margin philosophy for science assessment studies.” 2011. Available at [https://sci.esa.int/documents/34375/36249/1567260131067-Margin\\_philosophy\\_for\\_science\\_assessment\\_studies\\_1.3.pdf](https://sci.esa.int/documents/34375/36249/1567260131067-Margin_philosophy_for_science_assessment_studies_1.3.pdf) Issue 1 Revision 3.
- [3] ArianeSpace, “ARIANE 6 USER’S MANUAL,” 2016. Available at [https://www.arianespace.com/wp-content/uploads/2021/03/Mua-6\\_Issue-2\\_Revision-0\\_March-2021.pdf](https://www.arianespace.com/wp-content/uploads/2021/03/Mua-6_Issue-2_Revision-0_March-2021.pdf) Issue 2 Revision 0.
- [4] C. Manfletti and S. Heizmann, “Spacecraft Propulsion and Design Challenge.” 2022. Available at <https://www.moodle.tum.de/course/view.php?id=80904>.
- [5] Laura M. Burke, Robert D. Falck, and Melissa L. McGuire, “Interplanetary mission design handbook: Earth-to-mars mission opportunities 2026 to 2045 - nasa technical reports server (ntrs),” 2010. Available at <https://ntrs.nasa.gov/citations/20100037210>.
- [6] H. Chen, E. Canalias, D. Hestroffer, and X. Hou, “Effective stability of quasi-satellite orbits in the spatial problem for phobos exploration,” *Journal of Guidance, Control, and Dynamics*, vol. 43, pp. 2309–2320, Dec. 2020.
- [7] European Space Agency, “CDF Study Report Ice Giants: A Mission to the Ice Giants – Neptune and Uranus,” 2019. Available at [https://sci.esa.int/documents/34923/36148/1567260384517-Ice\\_Giants\\_CDF\\_study\\_report.pdf](https://sci.esa.int/documents/34923/36148/1567260384517-Ice_Giants_CDF_study_report.pdf).
- [8] ArianeGroup, “10N, 200N, 400N CHEMICAL BI-PROPELLANT THRUSTER FAMILY: CHEMICAL BI-PROPELLANT THRUSTER FAMILY.” Available at [https://satcatalog.s3.amazonaws.com/components/1007/SatCatalog\\_-\\_ArianeGroup\\_-\\_S400-15\\_Biprop\\_Thruster\\_-\\_Datasheet.pdf?lastmod=20210710070603](https://satcatalog.s3.amazonaws.com/components/1007/SatCatalog_-_ArianeGroup_-_S400-15_Biprop_Thruster_-_Datasheet.pdf?lastmod=20210710070603).
- [9] M. Aerospace, “Mt-tankkatalog.pdf.” <https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf>, 2023. (Accessed on 03/28/2023).
- [10] “Pressurant tanks data sheets - sorted by volume - northrop grumman.” <https://www.northropgrumman.com/space/pressurant-tanks-data-sheets-sorted-by-volume/>. (Accessed on 03/30/2023).
- [11] M. Wade, “Mon/mmh.” <http://www.astronautix.com/m/monmmh.html>, 1997. (Accessed on 03/30/2023).
- [12] A. Crawls, “Basics of space flight: Rocket propellants.” <https://web.archive.org/web/20130521134626/http://www.braeunig.us/space/propel.htm>, 2004. (Accessed on 03/30/2023).
- [13] H. W. Huu P. Trinh, Christopher Burnside, “Assessment of mon-25/mmh propellant system for deep-space engines.” <https://ntrs.nasa.gov/api/citations/20190033304/downloads/20190033304.pdf>, 2019. (Accessed on 03/30/2023).
- [14] M. Pasand, A. Hassani, and M. Ghorbani, “A study of spacecraft reaction thruster configurations for attitude control system,” *IEEE Aerospace and Electronic Systems Magazine*, vol. 32, no. 7, pp. 22–39, 2017. Available at [10.1109/MAES.2017.160104](https://doi.org/10.1109/MAES.2017.160104).
- [15] Safran, “Spacecraft propulsion subsystems.” Available at <https://www.safran-group.com/sites/default/files/2022-11/Safran%20Spacecraft%20Propulsion%20-%20Brochure%20-%20Portfolio.pdf>.
- [16] National Aeronautics and Space Administration, “The Mars Relay Network Connects Us to NASA’s Martian Explorers,” 2021-02-16 00:00:00 UTC. Available at <https://mars.nasa.gov/news/8861/the-mars-relay-network-connects-us-to-nasas-martian-explorers/>.
- [17] E. C. for Space Standardization, “Ecss-e-st-35c rev.1 – propulsion general requirements (6 march 2009) — european cooperation for space standardization.” <https://ecss.nl/standard/ecss-e-st-35c-rev-1-propulsion-general-requirements/>, 2009. (Accessed on 03/31/2023).
- [18] I. Oz and Yilmaz, “Design tradeoffs in full electric, hybrid and full chemical propulsion communication satellite,” *Sakarya University Journal of Computer and Information Sciences*, vol. 2, pp. 124–133, 12 2019.
- [19] R. Wear, “Bottle blow-down analysis — nesc academy online.” <https://nescacademy.nasa.gov/video/2a5828243b7649ad8283d34e391e76741d>, 2021. (Accessed on 03/31/2023).
- [20] D. T. Mage, “Joule—thomson effect on gaseous helium,” *The Journal of Chemical Physics*, vol. 42, pp. 2977–2977, Apr. 1965.
- [21] C. Team, “Welcome to coolprop — coolprop 6.4.3 documentation.” <http://www.coolprop.org/>, 2010. (Accessed on 03/31/2023).
- [22] C. Koppel, F. Marchandise, D. Estublier, and L. Jolivet, “The smart-1 electric propulsion subsystem in flight experience,” in *40th AIAA/ASME/SAE/ASEE Joint Propulsion Conference and Exhibit*, American Institute of Aeronautics and Astronautics, June 2004.

APPENDIX A  
ADDITIONAL RESOURCES

TABLE XXV  
PRESSURANT TANK [9]

Supplier	MT Aerospace
MEOP	310 bar
Total Volume	40-75 l
Temperature Range	-30/ +60 °C
Tank Dry Mass	8.5 – 14.4 kg
Tank Diameter	432 mm
Tank Length	467 - 728 mm
Material	Ti-6Al-4V (Shell) Ti-3Al-2.5V (Tube) Epoxy-based CFRP / T800 (Overwrap)




Fig. 17. Flowchart for Chemical Bipropellant Subsystem




Fig. 18. Flowchart for Electrical Propulsion System as Adaption from SMART-1 [22]




Fig. 19. Electric Propulsion Hardware adapted from SMART-1 [22]

TABLE XXVI  
MISSION TIMELINE

<b>Timestamp</b>		<b>Maneuver Name</b>	<b>Drymass</b>	[kg]	[kg]	[kg]	[kg]	[kg]	[kg]
31 Oct 2026 12:00:00		Ariane 62 Mounted	1226.589	3.525	283.500	467.775	166.000	2147.390	
31 Oct 2026 12:00:37		Ariane 62 Eject	1141.589	3.525	283.500	467.775	166.000	2062.390	
03 Nov 2026 12:00:37	Begin	C3	1141.589	3.525	283.500	467.775	166.000	2062.390	
03 Nov 2026 12:36:32	End	C3	1141.589	3.525	166.786	275.197	166.000	1753.097	
21 Nov 2026 12:36:32	Begin	TCM	1141.589	3.525	166.786	275.197	166.000	1753.097	
21 Nov 2026 12:36:38	End	TCM	1141.589	3.525	166.496	274.719	166.000	1752.330	
17 Aug 2027 04:48:54	Begin	MOI	1141.589	3.525	166.496	274.719	166.000	1752.330	
17 Aug 2027 05:36:32	End	MOI	1141.589	3.525	11.752	19.392	166.000	1342.258	
28 Aug 2027 18:17:43	Begin	Match INC	1141.589	3.525	11.752	19.392	166.000	1342.258	
28 Aug 2027 18:18:25	End	Match INC	1141.589	3.525	9.455	15.600	166.000	1336.169	
29 Aug 2027 17:36:46	Begin	Raise Peri min	1141.589	3.525	9.455	15.600	166.000	1336.169	
29 Aug 2027 17:36:59	End	Raise Peri min	1141.589	3.525	8.744	14.427	166.000	1334.285	
22 Sep 2027 10:44:25	Begin	Circularize	1141.589	3.525	8.744	14.427	166.000	1334.285	
26 Aug 2029 16:26:15	End	Circularize	1141.589	3.525	8.744	14.427	114.195	1282.480	
27 Aug 2029 07:10:20	Begin	Spiral Down Match	1141.589	3.525	8.744	14.427	114.195	1282.480	
01 Jan 2030 14:43:40	Begin	Wait Match	1141.589	3.525	8.744	14.427	58.129	1226.414	
03 Jan 2030 00:29:49	End	Wait Match	1141.589	3.525	8.744	14.427	58.129	1226.414	
06 Jan 2030 21:28:19	End	Spiral Down Match	1141.589	3.525	8.744	14.427	56.458	1224.744	
06 Jan 2030 21:34:01		Arrived - Probe drop	1121.589	3.525	8.744	14.427	56.458	1204.744	
		Orbital Maintenance	1121.589	3.525	8.744	14.427	49.477	1197.762	
06 Jan 2032 21:34:01	Begin	EOL	1121.589	3.525	8.744	14.427	49.477	1197.762	
20 Apr 2032 12:31:53	End	EOL	1121.589	3.525	8.744	14.427	3.422	1151.708	

TABLE XXVII  
ELECTRIC THRUSTER SELECTION

Manufacturer	Name	Power [W]	Thrust [mN]	Isp [s]	Burntime [years]	Fuel Mass [kg]	Solar Mass [kg]	Sum Mass [kg]	Launch Mass [kg]
Morpheus Space	NanoFEEP	0.2	0.001	3000	83443.5960	89.45	0.04	89.64	
		3	0.02	8500	4314.1692	32.64	0.53	33.33	
Morpheus Space	MultiFEEP	0.4	0.001	7000	85944.8386	39.48	0.07	39.85	
		1090	12.5	7000	6.8756	39.48	191.90	258.98	
Rafael	R-200	140	4	800	18.1724	292.19	24.65	316.84	
		350	14	1300	5.5770	193.14	61.62	254.76	
Rafael	R-800	500	23	1300	3.3947	193.14	88.03	281.16	
		1000	53	1550	1.5011	165.05	176.05	341.11	
Safran	PPS X00	200	15	1300	5.2052	193.14	35.21	228.35	
		1000	75	1650	1.0671	155.97	176.05	342.03	
Safran	PPS 1350-G	1500	90	1800	0.8961	144.08	264.08	437.16	1993.5841
		2500	140	1800	0.5761	144.08	440.13	613.21	2487.5044
Safran	PPS 1350-E	2500	100	1600	0.7980	160.39	440.13	600.51	2547.0515
		5000	300	1900	0.2700	137.11	880.26	1017.36	3685.1358
Safran	PPS 5000	2500	150	1730	0.5358	149.40	440.13	615.53	2529.7035
		5000	300	2000	0.2711	130.78	880.26	1043.03	3683.8819
ArianeGroup	RIT uX	50	0.5	3000	166.8872	89.45	8.80	98.25	
ArianeGroup	RIT 10 EVO	145	5	1900	16.2017	137.11	25.53	162.64	
		435	15	3000	5.5629	89.45	76.58	166.03	
		760	25	3200	3.3485	84.13	133.80	217.92	
ArianeGroup	RIT 2X	2000	70	3400	1.1993	79.40	352.10	431.50	2053.9215
		2500	88	3500	0.9552	77.23	440.13	517.36	2273.0878
		4000	151	3300	0.5552	81.70	704.21	785.90	2964.5545
		4500	171	3500	0.4916	77.23	792.23	869.46	3172.3386
		4800	198	2450	0.4166	108.27	845.05	953.32	3446.0344
		5300	215	2750	0.3863	97.12	933.07	1030.19	3625.6223

TABLE XXVIII  
TANK DATABASE

Titanium Tanks (Monoprop / Biprop)				
Volume [l]	Ideal mass [kg]	Real mass [kg]	Margin-factor	Tank Source
304	8.9643	17.5	1.95	<a href="https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#198">https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#198</a>
218	6.4284	11	1.71	<a href="https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#199">https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#199</a>
235	6.9297	16	2.31	<a href="https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#200">https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#200</a>
282	8.3156	21	2.53	<a href="https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#201">https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#201</a>
331	8.6514	22.7	2.62	<a href="https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#202">https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#202</a>
700	18.2959	36	1.97	<a href="https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#203">https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#203</a>
1108	28.9598	49	1.69	<a href="https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#204">https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#204</a>
769	18.0379	31.7	1.76	<a href="https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#205">https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#205</a>
1207	31.5474	52.5	1.66	<a href="https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#206">https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#206</a>
1309	34.2134	57	1.67	<a href="https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#207">https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#207</a>
1450	37.8987	61	1.61	<a href="https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#208">https://www.space-propulsion.com/spacecraft-propulsion/bipropellant-tanks/index.html#208</a>
165	4.4232	10.8	2.44	<a href="https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf">https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf</a>
			1.993	
CFRP-Titanium Tanks (Xenon)				
Volume [l]	Ideal mass [kg]	Real mass [kg]	Margin-factor	Tank Source
60	4.1329	11.7	2.83	<a href="https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf">https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf</a>
40	2.7553	6.3	2.29	<a href="https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf">https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf</a>
120	8.2658	14.8	1.79	<a href="https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf">https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf</a>
600	41.3288	68	1.65	<a href="https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf">https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf</a>
900	61.9932	85	1.37	<a href="https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf">https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf</a>
			1.985	
CFRP-Titanium Tanks (Helium, Nitrogen)				
Volume [l]	Ideal mass [kg]	Real mass [kg]	Margin-factor	Tank Source
40	4.5675	8.5	1.86	<a href="https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf">https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf</a>
75	8.5641	14.4	1.68	<a href="https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf">https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf</a>
120	13.7026	23.5	1.72	<a href="https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf">https://www.mt-aerospace.de/files/mta/tankkatalog/MT-Tankkatalog.pdf</a>
			1.752	

		Biprop only (US)		Biprop only (EU)		Biprop-Elec (US)		Biprop-Elec (EU)	
		Weighting		Evaluation		Value		Evaluation	
than	More imp		%		Evaluation		Value		Evaluation
Propulsion System Wet Mass	2	2	2	2	10	33,33%	0,0000	-	4,5960
Volume propulsion system	0	2	0	1	0	3	10,00%	2,1256	0,21
Power Requirement	0	0	0	1	1	2	6,67%	10,0000	0,67
Industrialization	0	2	2	2	8	26,67%	0,0000	-	10,0000
Technological risk	0	1	1	0	2	4	13,33%	10,0000	1,33
Propellant Toxicity	0	2	1	0	0	3	10,00%	0,0000	-
<b>Prüfsumme</b>		<b>100,00%</b>		<b>Summe</b>		<b>2,21</b>		<b>6,49</b>	
		<b>Summe</b>		<b>5,83</b>		<b>6,69</b>			

Bewertungszahl von 0 - 10  
 Bewertungszahl 0 entspricht Alternative erfüllt das Kriterium nicht  
 Bewertungszahl 10 entspricht Alternative erfüllt das Kriterium vollständig

Fig. 20. Criteria Definition



Fig. 21. MomentUM Project Plan

Criterion	Background	Bipropellant (Aerojet)	Biprop Electric (Aerojet and Next_C)	Bipropellant (Ariane)	Biprop Electric (Ariane)
Propulsion system dry mass [kg]	m_PROP in MATLAB	745,4764	0,0000	160,4047	8,9347
Launch mass [kg]	m_prop in MATLAB + dry mass	2,100,5286	0,0000	1,082,4001	10,0000
Volume propulsion system [m3]	V_tot in MATLAB (Tank volumes * 3)	3,4240	2,1256	2,2573	3,8127
Power Requirement [W]	1,277,4168	10,0000	2,763,8654	1,5789	1,277,4168
Industrialization	US	0,0000	US	0,0000	EU
Technological risk	9	10,0000	9	10,0000	9
Toxicity of propellants	Hydrazine more toxic than MMH	0,0000	Hydra/NTO and Xe	0,0000	MMH/NTO
				5,0000	MMH/NTO and Xe
				5,0000	5,0000

Fig. 22. Criteria Definition




Fig. 23. Point-Mass Arrangement in the XY-plane









Fig. 24. Section of the Point-Mass Arrangement in the YZ-plane

# MomenTUM

Position	Part
①	ArianeGroup S400-15 bipropellant engine
②	ArianeGroup OST 25/0 331L tank
③	ArianeGroup OST 25/0 198L tank
④	MT Aerospace PVG Family 40L tank
⑤	MT Aerospace S-XTA 120L tank
⑥	ETCA PPU, Safran BPRU, Safran XFC, EREAMS FU, Atermes PRE Card
⑦	Safran PPS 1350-G electric thruster
⑧	ArianeGroup S10-26 RCS thruster cluster
⑨	ArianeGroup S10-26 RCS thruster
⑩	Solar array (6.5 m x 1 m)
⑪	Spacecraft hull
⑫	RCS cluster connection



SIEMENS

THIS DRAWING HAS BEEN PRODUCED USING AN EXAMPLE  
TEMPLATE PROVIDED BY SIEMENS PLM SOFTWARE

MomenTUM

FIRST ISSUED	31.03.2023	TITLE	
DRAWN BY	Julian Schmid		
CHECKED BY	Julian Schmid		
APPROVED BY	MomenTUM	SIZE DRG NO.	
		A1 MomenTUM_3_tanks_Xenon_dwg1	A
SCALE 1:20		SHEET REV	
			M

ALL DIMENSIONS IN mm

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16

A1

SHEET 1 OF 2

