

BootyPrint CSS Variables Guide

This guide explains how to customize BootyPrint using CSS custom properties (CSS variables). BootyPrint allows you to override its default styling without modifying the SCSS source files.

How to Use CSS Variables with BootyPrint

Simply define your custom CSS variables in the `:root` selector in your HTML file or in a separate CSS file. These will override the default SCSS variables used by BootyPrint.

```
:root {
  --primary: #3f51b5;
  --secondary: #2196f3;
  --font-size-base: 14px;
  --page-size: A5 landscape;
}
```

Available CSS Variables

Below is a list of CSS variables you can customize:

Colors

CSS Variable	Default Value	Description
--white	#fff	White color
--black	#000	Black color
--gray-100 to --gray-900	Various	Gray scale colors
--blue	#0d6efd	Blue color
--indigo	#6610f2	Indigo color
--purple	#6f42c1	Purple color
--pink	#d63384	Pink color
--red	#dc3545	Red color
--orange	#fd7e14	Orange color
--yellow	#ffc107	Yellow color
--green	#198754	Green color
--teal	#20c997	Teal color
--cyan	#0dcaf0	Cyan color
--primary	--blue	Primary theme color
--secondary	--gray-600	Secondary theme color
--success	--green	Success theme color
--info	--cyan	Info theme color
--warning	--yellow	Warning theme color
--danger	--red	Danger theme color
--light	--gray-100	Light theme color
--dark	--gray-900	Dark theme color

Typography

CSS Variable	Default Value	Description
--font-family-sans-serif	system-ui, -apple-system, ...	Sans-serif font family
--font-family-serif	system-ui, -apple-system, ...	Serif font family
--font-family-monospace	SFMono-Regular, Menlo, ...	Monospace font family
--font-family-base	--font-family-serif	Base font family
--font-family-headings	--font-family-sans-serif	Headings font family
--font-size-base	11pt	Base font size
--font-weight-normal	400	Normal font weight
--font-weight-bold	700	Bold font weight
--line-height-base	1.5	Base line height

Page Settings

CSS Variable	Default Value	Description
--page-size	210mm 297mm (A4)	Page size
--page-margin	3mm 3mm 3mm 2mm	Page margins

Other Settings

CSS Variable	Default Value	Description
--grid-columns	12	Number of grid columns
--grid-gutter-width	1.5rem	Grid gutter width
--border-radius	0.25rem	Default border radius
--border-radius-sm	0.2rem	Small border radius
--border-radius-lg	0.3rem	Large border radius

Example

Here's an example of customizing BootyPrint using CSS variables:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Customized BootyPrint Example</title>
  <link rel="stylesheet" href="path/to/bootyprint.css">
  <style>
    :root {
      --primary: #3f51b5;
      --secondary: #2196f3;
      --font-size-base: 14px;
      --page-size: A5 landscape;
      --font-family-base: 'Georgia', serif;
      --border-radius: 0.5rem;
    }
  </style>
</head>
<body>
```

```

    <!-- Your content here -->
</body>
</html>
```

This setup will override the default primary and secondary colors, change the base font size to 14px, set the page size to A5 landscape, use Georgia as the base font, and make border radiuses larger.