Line-based text data: text/html (3 lines)

```
No.
       Time
                      Source
                                            Destination
                                                                  Protocol Length Info
                                                                                 GET /wireshark-labs/INTRO-wireshark-file1.html HTTP/1.1
   1398 74.100060
                      192.168.1.104
                                            128.119.245.12
                                                                  HTTP
                                                                          454
Frame 1398: 454 bytes on wire (3632 bits), 454 bytes captured (3632 bits) on interface \Device\NPF_{5FEC5DA6-61D4-48D9-B6B5-3D96A10D21FC},
Ethernet II, Src: LiteonTe_33:ec:ad (10:63:c8:33:ec:ad), Dst: Tp-LinkT_ef:ad:24 (a0:f3:c1:ef:ad:24)
Internet Protocol Version 4, Src: 192.168.1.104, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 64135, Dst Port: 80, Seq: 1, Ack: 1, Len: 400
Hypertext Transfer Protocol
    GET /wireshark-labs/INTRO-wireshark-file1.html HTTP/1.1\r\n
    Host: gaia.cs.umass.edu\r\n
    Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8\r\n
    Accept-Language: uk-UA,uk;q=0.8,en-US;q=0.5,en;q=0.3\r\n
    Accept-Encoding: gzip, deflate\r\n
    Connection: keep-alive\r\n
    Upgrade-Insecure-Requests: 1\r\n
    \r\n
    [Full request URI: http://gaia.cs.umass.edu/wireshark-labs/INTRO-wireshark-file1.html]
    [HTTP request 1/1]
    [Response in frame: 1402]
No.
       Time
                      Source
                                            Destination
                                                                  Protocol Length Info
   1402 74.224995
                      128.119.245.12
                                            192.168.1.104
                                                                  HTTP
                                                                          491
                                                                                 HTTP/1.1 200 OK (text/html)
Frame 1402: 491 bytes on wire (3928 bits), 491 bytes captured (3928 bits) on interface \Device\NFF_{5FEC5DA6-61D4-48D9-B6B5-3D96A10D21FC},
id 0
Ethernet II, Src: Tp-LinkT_ef:ad:24 (a0:f3:c1:ef:ad:24), Dst: LiteonTe_33:ec:ad (10:63:c8:33:ec:ad) Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.1.104
Transmission Control Protocol, Src Port: 80, Dst Port: 64135, Seq: 1, Ack: 401, Len: 437
Hypertext Transfer Protocol
    HTTP/1.1 200 OK\r\n
    Date: Thu, 11 Jun 2020 17:43:10 GMT\r\n
    Server: Apache/2.4.6 (CentOS) OpenSSL/1.0.2k-fips PHP/7.4.6 mod_perl/2.0.11 Perl/v5.16.3\r\n
    Last-Modified: Thu, 11 Jun 2020 05:59:04 GMT\r
    ETag: "51-5a7c8a866ad4d"\r\n
    Accept-Ranges: bytes\r\n
    Content-Length: 81\r\n
    Keep-Alive: timeout=5, max=100\r\n
    Connection: Keep-Alive\r\n
    Content-Type: text/html; charset=UTF-8\r\n
    \r\n
    [HTTP response 1/1]
    [Time since request: 0.124935000 seconds]
    [Request in frame: 1398]
    [Request URI: http://gaia.cs.umass.edu/wireshark-labs/INTRO-wireshark-file1.html]
    File Data: 81 bytes
```