Fundamentals of Programming I

Chapter 2 - Basic Programming Constructors

Rervision Quiz: Multiple-Choice Questions

36 Questions in Three Levels

All | Easy | Medium | Hard

Score: 0 / 36 · answered 0

1. Who created C++? Easy

A. Dennis Ritchie

B. Bjarne Stroustrup

C. James Gosling

D. Ken Thompson

2. Which file extension is used for C++ source files? Easy

A. .exe

B. .java

C. .obj

D. .cpp

3. Which statement prints text on the screen? Easy

A. cout << "Hi";

B. echo "Hi";

C. cin >> "Hi";

D. print "Hi";

4. Every executable C++ statement ends with... Easy

A. a semicolon ;

B. a period .

C. a colon :

D. a comma ,

5. Which symbol starts a single-line comment? Easy

A. /*
B. #
C. //
D. <!--

6. Which header is needed for cin and cout? Easy

A. iomanip
B. cstring
C. cmath
D. iostream

7. Which is a valid variable name? Easy

A. total_marks
B. total-marks
C. total marks
D. 2total

8. Which type stores whole numbers? Easy

A. double
B. int
C. char
D. bool

9. Which type stores only true or false? Easy

A. float
B. char
C. int
D. bool

10. What does return 0; at the end of main mean? Easy

A. A comment follows
B. The loop ended
C. The program ended normally
D. The program had an error

11. Which operator gives the remainder of a division? Easy

A. #
B. %

C. *

D. /

12. Which keyword creates a constant? Easy

A. fixed

B. constant

C. let

D. const

13. Which phase combines object code with library code to make the executable? Medium

A. Preprocessing

B. Linking

C. Editing

D. Loading

14. What does cout << 7 / 2; print? Medium

A. 4

B. 3.0

C. 3

D. 3.5

15. What is 7 % 3? Medium

A. 2

B. 3

C. 0

D. 1

16. int a = 5; cout << a++; prints... Medium

A. 4

B. 7

C. 6

D. 5

17. int a = 5; cout << ++a; prints... Medium

A. 6

B. 4

C. 7

D. 5

18. After int x = 10; x -= 4; x *= 2; x is... Medium

A. 16

B. 6

C. 20

D. 12

19. What happens in int i = 5.5; ? Medium

A. i becomes 6

B. It will not compile

C. i becomes 5.5

D. i becomes 5 (the fraction is dropped)

20. Which line replaces the word PI with 3.14 before compilation? Medium

A. PI == 3.14;

B. int PI = 3.14;

C. #define PI 3.14

D. const PI = 3.14;

21. A variable declared inside a block { } can be used... Medium

A. nowhere

B. anywhere in the file

C. only in other functions

D. only inside that block

22. What is the difference between = and == ? Medium

A. == joins two strings

B. They are the same

C. = compares, == assigns

D. = assigns a value, == compares two values

23. What is the value of (5 > 3) && (2 > 4) ? Medium

A. 5

B. true (1)

C. 4

D. false (0)

24. On a typical 32-bit compiler, sizeof(int) is... Medium

A. 1 byte

B. 2 bytes

C. 4 bytes

D. 8 bytes

25. int x = 5, y = 5; cout << ++x << y--; prints... Hard

A. 66

B. 65

C. 55

D. 64

26. int a = 2, b = 3; cout << a + b * 2 - 1; prints... Hard

A. 7

B. 9

C. 5

D. 3

27. cout << (double)(5 / 2); prints... Hard

A. 3

B. 2.0 and then an error

C. 2.5

D. 2

28. double avg = (1 + 2) / 2; What is avg? Hard

A. 1

B. 0

C. 1.5

D. 2

29. unsigned short n = 65535; n = n + 1; What is n? Hard

A. 0

B. -1

C. an error message

D. 65536

30. What is 12 & 10 (bitwise AND)? Hard

A. 22

B. 8

C. 14

D. 2

31. What is 1 << 3 ? Hard

A. 6

B. 4

C. 8

D. 3

32. enum Color { RED = 100, BLUE, GREEN = 500, WHITE }; What is WHITE? Hard

A. 501

B. 3

C. 500

D. 101

33. char c = 'a'; c += 2; cout << c; prints... Hard

A. 99

B. a2

C. 2

D. c

34. int x = 1; { int x = 2; } cout << x; prints... Hard

A. nothing (an error)

B. 1

C. 3

D. 2

35. In a == b + c * d , which operation runs first? Hard

A. c * d

B. They all run together

C. b + c

D. a == b

36. int a = 7; int b = a > 5 ? a * 2 : a / 2; b is... Hard

A. 7

B. 5

C. 3

D. 14