

AQUAPROOF

WATERPROOF PRIMER

RELIABLE WATERPROOFING COMPOUND
FOR CONSTRUCTION

Aquaproof is a reliable waterproofing compound that provides effective protection against water ingress in construction projects. Its advanced formulation ensures strong bonding, excellent coverage, and long-lasting performance even in demanding conditions.



EFFECTIVE
PROTECTION



EASY
APPLICATION



COST-
EFFECTIVE



VERSATILE
USE



EFFECTIVE PROTECTION

Provides effective
barrier against water
ingress and dampness.



EASY APPLICATION

Easy to apply with
brush, roller
or spray.



COST- EFFECTIVE

Affordable solution
without compromising
on performance.



VERSATILE USE

Suitable for a wide
range of surfaces
and applications.

1. WHY CHOOSE AQUAPROOF?



Effective Protection

Forms a strong waterproof barrier that prevents water penetration.



Easy Application

Smooth application with brush, roller, or spray for hassle-free use.



Cost-effective

High performance at economical value for all projects.



Versatile Use

Works on a variety of surfaces for diverse construction needs.

2. IDEAL FOR



Basements

Protects basements from seepage and moisture.



Bathrooms

Ideal for walls and floors in bathrooms and wet areas.



Wet Areas

Perfect for kitchens, utility areas, and other wet zones.



Foundation Walls

Prevents water ingress in foundation and retaining walls.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

Type	Acrylic Waterproofing Compound
Appearance	Smooth, Viscous Liquid
Colour	Milky White
Solid Content	55 ± 2%
pH Value	8.0 – 9.5
Specific Gravity	1.00 – 1.10
Drying Time (Touch Dry)	1 – 2 hrs
Drying Time (Recoatable)	4 – 6 hrs
Coverage	1.2 – 1.5 sq.ft./kg/coat*
Application Temperature	5°C to 45°C
Packaging	1kg, 4kg, 10kg, 20kg

*Coverage may vary depending on surface porosity and application.

PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Water Penetration	Nil
Tensile Strength	> 1.0 MPa
Elongation at Break	> 120%
Adhesion to Concrete	> 1.0 MPa
Crack Bridging Ability	Up to 1 mm
Water Resistance	Excellent
Temperature Resistance	-10°C to 60°C

4. SURFACE PREPARATION & APPLICATION GUIDE

1. SURFACE PREPARATION



- Surface must be clean, dry and free from dust, loose particles, oil, and grease.
- Remove laitance, paint, or any weak material.
- Repair cracks and level uneven surfaces.

2. PRIMING



- Apply a suitable primer if required for highly porous surfaces.
- Allow primer to dry completely.

3. APPLICATION



- Stir Aquaproof well before use.
- Apply 2 – 3 coats using brush, roller or spray.
- Ensure uniform coverage and maintain recommended coverage rate.

4. RECOATING



- Apply the next coat after 4 – 6 hours.
- Ensure perpendicular direction application for best results.

5. CURING



- Allow the surface to cure for at least 7 days.
- Keep away from water during the curing period.

5. SAFETY FEATURES & PRECAUTIONS



Refer to SDS for complete safety information.



Keep out of reach of children.



Wear protective gloves and goggles during application.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Dispose of empty containers as per local regulations.

STORAGE



- Store in a cool, dry place.
- Keep container tightly closed when not in use.
- Protect from direct sunlight and extreme heat.
- Shelf life: 12 months from date of manufacture.

RECOMMENDED FOR

- Basements
- Bathrooms
- Wet Areas
- Foundation Walls

TIPS FOR BEST RESULTS

- Apply in recommended thickness for optimal performance.
- Do not apply on wet surfaces.
- Ensure proper curing for maximum waterproofing.
- Inspect surface regularly for long-term protection.

SCAN TO KNOW MORE



EFFECTIVE PROTECTION



EASY APPLICATION



COST-EFFECTIVE



VERSATILE USE

RELIABLE PROTECTION. BUILT TO LAST.