

AQUARIS SUPRA

PREMIUM WATERPROOFING SOLUTION

Aquaris Supra is a premium waterproofing solution formulated with advanced technology to provide superior protection against water ingress, UV rays, and weathering. Ideal for a wide range of exposed surfaces, it ensures long-lasting performance and peace of mind.

- 

SUPERIOR WATERPROOFING
- 

ELASTIC PROPERTIES
- 

UV RESISTANT
- 

LONG-LASTING



- 

SUPERIOR WATERPROOFING
Provides excellent protection against water leakage.
- 

ELASTIC PROPERTIES
Bridges tiny cracks and withstands surface movement.
- 

UV RESISTANT
Resists harmful UV rays and prevents degradation.
- 

LONG-LASTING
Delivers durable protection for many years.

1. WHY CHOOSE AQUARIS SUPRA?

- 

Superior Waterproofing
Creates a seamless barrier against water penetration and dampness.
- 

Elastic Properties
High flexibility allows it to expand and contract with the surface.
- 

UV Resistant
Protects surfaces from UV radiation and harsh weather conditions.
- 

Long-lasting
Engineered for extended durability and reliable performance.

2. IDEAL FOR

- 

Roofs
Flat roofs, sloped roofs and metal roofs.
- 

Terraces
Open terraces and podiums exposed to rain and sun.
- 

Balconies
Protects balconies and verandahs from seepage.
- 

Water Tanks
Ideal for underground and overhead water tanks.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

- Type : Acrylic Waterproofing Coating
- Appearance : Smooth, Viscous Liquid
- Colour : White
- Finish : Matt
- Solid Content : 60 ± 2%
- Elongation at Break : > 150%
- Crack Bridging Ability : Up to 2 mm
- UV Resistance : Excellent
- Water Resistance : Excellent
- Coverage : 1.2 – 1.5 sq.ft./kg/coat*
- No. of Coats : 2 – 3 Coats
- Drying Time (Touch Dry) : 2 – 4 hrs
- Drying Time (Recoat) : 4 – 6 hrs
- Full Cure : 7 Days
- Packaging : 1kg, 4kg, 10kg, 20kg

*Coverage may vary depending on surface porosity and application.

PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Waterproofing	Excellent
Tensile Strength	> 1.5 MPa
Elongation	> 150%
UV Resistance	Excellent
Adhesion to Concrete	> 1.0 MPa
Water Permeability	Nil
Temperature Resistance	-10°C to 60°C
pH Value	7.5 – 8.5

4. SURFACE PREPARATION & APPLICATION GUIDE

- 

1. SURFACE PREPARATION

 - Surface must be clean, dry and free from dust, loose particles, oil and grease.
 - Repair cracks and honeycombs using suitable repair mortar.
 - Allow the surface to cure completely.
- 

2. PRIMING

 - Apply Colorsome Acrylic Waterproofing Primer for better adhesion and performance.
 - Allow primer to dry completely.
- 

3. APPLICATION

 - Stir Aquaris Supra well before use.
 - Apply 2 – 3 coats using a brush, roller or spray.
 - Ensure uniform coverage and maintain recommended coverage rate.
- 

4. RECOATING

 - Apply the next coat after 4 – 6 hours.
 - Ensure perpendicular direction application for best results.
- 

5. CURING

 - Allow the surface to cure for at least 7 days.
 - Keep away from heavy water loading during curing period.

5. SAFETY FEATURES & PRECAUTIONS

- 

Refer to SDS for complete safety information.
- 

Keep out of reach of children.
- 

Wear protective gloves and goggles during application.
- 

In case of contact with eyes, rinse immediately with plenty of water.
- 

If swallowed, seek medical advice immediately.
- 

Ensure adequate ventilation during application and drying.
- 

Dispose of empty containers as per local regulations.

STORAGE

- 
- Store in a cool, dry place.
 - Keep container tightly closed when not in use.
 - Protect from direct sunlight and extreme heat.
 - Shelf life: 12 months from date of manufacture.

RECOMMENDED FOR

- ✓ Roofs
- ✓ Terraces
- ✓ Balconies
- ✓ Water Tanks

TIPS FOR BEST RESULTS

- ★ Do not apply during rain or when rain is expected.
- ★ Maintain coverage and coat thickness for optimum performance.
- ★ Regular inspection is recommended.

