

# AquaShield Emulsion

A water-based exterior wall finish with silicon additives suitable for dry to moderately humid climates.



WATER BASED



LEAD FREE\*  
GUARANTEE



NO ADDED LEAD,  
MERCURY OR  
ARSENIC OR  
CHROMIUM

\*All COLORSOME® products contain no added Lead, Mercury, Arsenic or Chromium.

## 1. AREAS OF APPLICATION



NORMAL  
MASONRY SURFACE



NEW MASONRY  
SURFACE



EXTERIOR WALLS  
(DRY TO MODERATELY  
HUMID CONDITIONS)



RECOATING  
(CEMENT PAINT  
ALTERNATE)

Ideal for a variety of exterior surfaces providing long-lasting protection and enhanced appearance.

## 2. FEATURES AND BENEFITS

- ✓ Formulated with silicon additives
  - ✓ Better anti-algal protection than cement paint
  - ✓ Advanced UV protection
  - ✓ Withstands harsh humidity and heat
- ✓ Excellent film integrity
  - ✓ Lower moisture absorption
  - ✓ Comprehensive 4-year performance warranty

## 3. PRODUCT DETAILS

### PHYSICAL PARAMETERS

- Acrylic Co-Polymer Emulsion
- Sheen: Rich Matt to Eggshell
- Packaging: 20 L
- Shelf life: 2 years
- Coverage: 1 - 2 kg per sq. m in two coats for 1mm DFT

| PARAMETER                       | TEST STANDARD USED                    | TYPICAL VALUES                       |
|---------------------------------|---------------------------------------|--------------------------------------|
| Finish                          | Visual                                | Smooth, Matt, Soft Sheen, Rich Sheen |
| Coverage (2 coats)              | On normal masonry by brushing         | 50 - 60 sq.ft./ltr**                 |
| Recoat Period (30°C, 50-60% RH) | Manufacturer Test                     | 4 - 6 HRS                            |
| Stability of thinned paint      | Manufacturer Test                     | To be used within 24 hours           |
| Shelf Life                      | In original tightly closed containers | 5 years                              |
| Pack Sizes Available            | Manufacturer Standard                 | 1 L, 4 L, 10 L, 20 L                 |

\*\*Actual coverage may vary due to application method, surface roughness, and porosity.

## 4. APPLICATION METHOD



### SURFACE PREPARATION

- New masonry must cure completely (28 days). Clean surface of loose particles, algae, dust, and grease.
- Use generic Wall Primer if chalkiness is present.
- Fill cracks (up to 3mm) with Crack Seal and other dents with standard Wall Putty.



### PRIMING

- For new or dry surfaces, apply one coat of generic Exterior Wall Primer.
- For damp-prone exterior surfaces, apply specific waterproofing coating.
- Horizontal surfaces like ledges should be painted first.



### TOPCOAT APPLICATION

- Dilute AquaShield Emulsion with 75% water (by volume). Stir well and strain.
- Apply 2-3 coats by brush, roller, or spray.
- Maintain 4-6 hours recoat period, consume thinned paint within 24 hours.

## 5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for detailed measures.



Store in a cool, dry place.



Keep out of reach of children and away from eatables.



Wear eye protection during application.



Avoid dust inhalation during sanding and preparation.



Wash skin with soap and plenty of water.



Do not pour leftover paint down the drain or in water courses.



No added Lead, Mercury or Arsenic or Chromium compounds.

### POST PAINTING CARE



- Maintain the surface regular intervals.
- Clean all algal and fungal growth with a water jet or generic biocide.

### STORAGE PRECAUTIONS



Store in a cool and dry place at ambient temperatures.



### RECOMMENDED FOR



- ✓ All interior masonry
- ✓ Concrete
- ✓ Plaster surfaces

### HOW TO USE

- 1 Clean the surface and remove dust and loose particles.
- 2 Apply 2 coats of Epoxy Primer evenly.
- 3 Let it dry for 4-6 hours before applying top coat.



RICH  
FINISH



EASY  
CLEAN



DURABLE  
PROTECTION



LOW  
VOC