

ARA WEATHER COAT

Advanced Exterior Protection
Engineered for Every Climate



EXTREME
WEATHER
PROTECTION



SUPERIOR
WATER
REPELLENCY



UV & FADE
RESISTANT

AREAS OF APPLICATION



Exterior Walls



Commercial
Buildings



Infrastructure
& Concrete



Industrial
Surfaces

FEATURES & BENEFITS

- ✓ Weather Resistant
- ✓ Durable Long-Lasting Finish
- ✓ Water Repellent
- ✓ Fade & UV Protection
- ✓ Excellent Adhesion
- ✓ Anti-Algal & Anti-Fungal
- ✓ Crack & Peeling Resistant
- ✓ Easy to Apply

PRODUCT DETAILS

- **Resin Type:**
Acrylic Copolymer Emulsion
- **Pigment:**
High Performance Pigments & Functional Additives

Parameter	Test Standard Used	Typical Values
Finish	Visual	Smooth Matt
Drying Time (Surface Dry)	ASTM D 1640	30 mins (Surface Dry), Recoat: 4 - 6 hrs.
Dilution	By Volume	Max. 40% with clean water
Coverage	Theoretical	10-12 sq. m/L/coat*
Sheen Level	ASTM D 523	5°-7° at 60° viewing angle
Shelf Life	-	24 months from date of manufacture in original sealed container

*Actual coverage may vary depending on surface condition and application method.

APPLICATION METHOD



SURFACE PREPARATION

Ensure the surface is clean, dry, and free from dust, grease, and loose material. Remove any existing paint or algae. Fill cracks and imperfections with a suitable wall putty. Allow the surface to dry completely.



PRIMING

Apply one coat of a suitable Water Based Exterior Primer and allow it to dry completely (4-6 hours).



APPLICATION

Stir the contents well before use. Apply two coats of Ara Weather Coat with a brush, roller, or spray. Dilute as recommended. Maintain an interval of 4-6 hours between coats.

SAFETY FEATURES & PRECAUTIONS



Ensure good ventilation during application and drying.



Keep out of reach of children.



In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



If swallowed, seek medical advice immediately and show this container or label.



Do not empty into drains or watercourses.



Dispose of contents/container in accordance with local regulations.



Wear suitable protective clothing, gloves, and eye/face protection.



Do not apply in direct sunlight or extreme humidity.



The product is lead-free and non-toxic under normal conditions.



STORAGE PRECAUTIONS

Store in a cool, dry place, away from direct sunlight and extreme temperatures. Keep container tightly closed when not in use.

RECOMMENDED FOR

- ✓ Residential Buildings
- ✓ Commercial Complexes
- ✓ Infrastructure Projects
- ✓ Industrial Installations



WEATHER
RESISTANT



DURABLE
FINISH



WATER
REPELLENT



UV & FADE
PROTECTION



LONG-LASTING
PERFORMANCE