

ARMORCOAT TEX

REFINED TEXTURE • LASTING PROTECTION

Armorcoat Tex provides a refined, protective finish that hides surface imperfections for beautiful, durable exterior walls.

- 

HIDES SURFACE UNDULATIONS
- 

CONCEALS FINE CRACKS
- 

PROVIDES STRUCTURAL PROTECTION
- 

ENSURES EXCELLENT ADHESION



- 

HIDES SURFACE UNDULATIONS
- 

CONCEALS FINE CRACKS
- 

PROVIDES STRUCTURAL PROTECTION
- 

ENSURES EXCELLENT ADHESION

2. AREAS OF APPLICATION



Exterior Walls



Variety of
Exterior Surfaces

FEATURES AND BENEFITS

- ✓ **HIDES SURFACE UNDULATIONS**
Effectively masks surface undulations and unevenness for a smooth and uniform appearance.
- ✓ **CONCEALS FINE CRACKS**
Shields fine cracks and hairline fissures, enhancing the beauty of exterior surfaces.
- ✓ **PROVIDES STRUCTURAL PROTECTION**
Delivers strong protection against harsh weather, moisture, and daily wear, ensuring long-term durability.
- ✓ **ENSURES EXCELLENT ADHESION**
Superior bonding strength for topcoats, resulting in a flawless and long-lasting finish.

3. PRODUCT DETAILS

DESCRIPTION:

Armorcoat Tex is a high-performance exterior texture coating designed to provide a refined, protective finish for exterior walls.

It effectively masks fine cracks and surface undulations while delivering robust structural protection against harsh environmental conditions.

Its superior formulation ensures excellent adhesion for subsequent coats, allowing you to achieve a lasting, professional finish in a variety of shades.

TECHNICAL SPECIFICATIONS:

PARAMETER	DETAILS
Finish	Refined texture
Application	Exterior walls; Variety of exterior surfaces
Binder	Acrylic modified resin
Filler	Specialized mineral fillers
Properties	Crack concealing, Weather resistant, UV resistant, Water repellent, Strong adhesion, Durable & long-lasting
Topcoat Compatibility	Compatible with a wide range of exterior topcoat paints
Packaging	As per available pack sizes
Coverage	Varies with texture and surface – approx. 1.2 to 1.5 kg/m ² (Actual coverage may vary)

4. APPLICATION METHOD

- 1  **PREPARE SURFACE**
Ensure the exterior surface is clean, dry, and free from any loose debris or contaminants.
- 2  **APPLY TEXTURE**
Apply Armorcoat Tex uniformly across the surface to build the desired refined texture and coverage.
- 3  **FINISH**
Allow the texture to dry thoroughly before applying your chosen topcoat for long-lasting protection.

5. SAFETY FEATURES & PRECAUTIONS

-  Kindly refer to the MEDS for Waterproof Primer which gives detailed information about safety measures while handling the material.

 Store the container with the lid tightly closed in an upright position, in a cool, dry place.
-  Keep out of reach of children and away from eatables.

 May be harmful if swallowed. In case of ingestion seek immediate medical attention.

 Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
-  Do not pour leftover material down the drain or in water courses.

 In the event of spills, contain spillage using sand or earth.

 No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS

- 

Store in a cool and dry place at ambient temperatures.

RECOMMENDED FOR

- 
- ✓ Residential buildings
 - ✓ Commercial complexes
 - ✓ Renovation projects
 - ✓ New construction

HOW TO USE

- 1 Clean the surface and remove dust and loose particles.
- 2 Apply Armorcoat Tex evenly.
- 3 Allow to dry and cure.
- 4 Apply topcoat as per requirement.

