

Armorcoat

ADVANCED PROTECTIVE COATING

Lifetime Waterproofing.
Total Peace of Mind.

Armorcoat is a premium liquid-applied coating engineered to withstand extreme weather vagaries with ease. It forms a seamless, exceptionally durable composite barrier that secures your property for a lifetime.



LIQUID-APPLIED
SEAMLESS
APPLICATION



EXTREMELY
DURABLE
MONOLITHIC
FILM



SUPERIOR
WEATHER
RESISTANCE



LIFETIME
PERFORMANCE
GUARANTEE

WHERE IT PERFORMS BEST



RESIDENTIAL & COMMERCIAL TERRACES

Ideal for flat roofs and open terrace areas exposed to all weather conditions.

FEATURES & BENEFITS



LIQUID-APPLIED SEAMLESS APPLICATION

Forms a continuous, joint-free membrane that prevents water leakage effectively.



EXTREMELY DURABLE MONOLITHIC FILM

Creates a tough, elastic film that adapts to surface movements without cracking.



SUPERIOR WEATHER RESISTANCE

Engineered to withstand harsh sun, rain, and temperature variations.



LIFETIME PERFORMANCE GUARANTEE

Backed by a lifetime performance guarantee for lasting protection and reliability.

PRODUCT DETAILS

DESCRIPTION

A premium liquid-applied waterproofing coating that forms a seamless, monolithic membrane for terraces. Engineered for maximum durability and long-term protection against water ingress.

PHYSICAL PROPERTIES

- **Appearance:** Viscous liquid
- **Color:** Grey
- **Packaging:** 20 L
- **Application:** Terraces
- **Drying Time:** Touch dry in 4 – 6 hours*

TECHNICAL SPECIFICATIONS

PARAMETER	DETAILS
Application	Terraces
Type	Liquid applied waterproofing coating
Drying Time	Touch dry in 4 – 6 hours*
Curing Time	7 days for full cure
Coverage	1 – 1.5 kg per sq. m. per coat**
No. of Coats	2 coats recommended
Finish	Seamless monolithic film
Shelf Life	12 months from date of manufacture in original sealed container
Storage	Store in a cool, dry place. Protect from direct sunlight and frost.

*Under standard application conditions.

**Coverage may vary depending on surface porosity and application method.

APPLICATION METHOD

1



PREPARE SURFACE

Ensure the terrace surface is clean, dry, and free from dust, debris, or loose material.

2



APPLY COATING

Apply the liquid Armorcoat evenly across the surface to ensure a consistent, monolithic film thickness.

3



CURE FULLY

Allow the coating to dry completely as directed to develop its full protective and waterproofing properties.

SAFETY FEATURES & PRECAUTIONS



Read the product label and technical data sheet before use.



Wear appropriate gloves and protective clothing during application.



Keep out of reach of children and away from food and feed.



Avoid contact with eyes. In case of contact, rinse thoroughly with water and seek medical advice.



Do not pour leftover material down the drain or in water courses.



In case of spills, contain spillage using sand or earth.

STORAGE PRECAUTIONS



Store in a cool, dry place at ambiecal temperatures. Keep the container tightly closed when not in use.

RECOMMENDED FOR



Ideal for all types of residential and commercial terraces requiring long-term waterproofing protection.

HOW TO USE

- 1 Clean the surface and remove dust, debris, and loose material.
- 2 Apply the coating evenly to achieve the required thickness.
- 3 Allow to dry fully before subjecting to foot traffic or water exposure.



HIGH
PERFORMANCE
FORMULA



ULTRA
DURABLE



EASY
APPLICATION



LIFETIME
PERFORMANCE
GUARANTEE