

ArmorShield

ULTIMATE EXTERIOR PROTECTION & BEAUTY

Stronger Shield. Lasting Beauty.
All-Weather Confidence.

ArmorShield is a high-performance exterior texture protection coat engineered for superior film integrity and low moisture absorption. It safeguards your exterior surfaces year-round, enhances the final topcoat finish, and is backed by a 10-year performance warranty for long-term peace of mind.



YEAR-ROUND
WEATHER
RESISTANCE



SUPERIOR
FILM INTEGRITY



LOW MOISTURE
ABSORPTION



10-YEAR
PERFORMANCE
WARRANTY

1. AREAS OF APPLICATION



RESIDENTIAL EXTERIORS
Villas, bungalows & housing societies




APARTMENT BUILDINGS
High-rise & multi-storey residential complexes



COMMERCIAL SPACES
Offices, retail outlets & showrooms




BOUNDARY WALLS
Compound walls & perimeter protection



TEXTURED SURFACES
Allura Concordia, Reserva & other textures



CONCRETE SURFACES
RCC, plaster, concrete & cement surfaces



EXTERIOR FACADES
Designer facades & architectural surfaces



EXTERNAL WALLS
External walls exposed to harsh conditions



Ideal for Allura Concordia Surfaces, Reserva Textures, Meraki Finishes & other exterior texture and masonry surfaces.

2. FEATURES AND BENEFITS



YEAR-ROUND
WEATHER
RESISTANCE

Provides reliable protection against rain, sun, wind, and extreme weather conditions.



SUPERIOR
FILM INTEGRITY

Ensures a tough, durable protective layer that maintains its performance over time.



LOW MOISTURE
ABSORPTION

Minimizes moisture ingress to keep walls dry, strong, and long-lasting.



10-YEAR
PERFORMANCE
WARRANTY

Backed by a 10-year warranty for assured durability and peace of mind.

3. PRODUCT DETAILS

COMPOSITION

High-quality protective emulsion formulated with advanced additives for enhanced performance and durability.

PHYSICAL PROPERTIES

- **Finish:** Aesthetic finishing
- **Packaging:** 20 L
- **Shelf Life:** 2 years
- **Application:** Allura Concordia; Reserva; Meraki
- **Drying Time:** Touch dry in 4 – 6 hours*

*Under standard application conditions.

TECHNICAL SPECIFICATIONS

PARAMETER	DETAILS
Application	Exterior surfaces
Binder Type	Acrylic Copolymer Emulsion
Drying Time	Touch dry in 4 – 6 hours*
Recoating Time	After 24 hours
Theoretical Coverage	12 – 14 sq m per L per coat**
No. of Coats	1 – 2 coats recommended
Finish	Aesthetic finishing
Shelf Life	2 years from date of manufacture in original sealed container
Storage	Store in a cool, dry place. Protect from direct sunlight and frost.

**Coverage may vary depending on surface texture, porosity and application method.

4. APPLICATION METHOD

1



PREPARE SURFACE

Ensure the application surface is clean, dry, and free from loose particles or contaminants.

2



APPLY ARMORSHIELD

Apply the protective coat evenly to the surface using appropriate professional application tools.

3



FINALIZE FINISH

Allow the coat to dry completely before applying your chosen aesthetic topcoat finish.

5. SAFETY FEATURES & PRECAUTIONS



Read the product label and technical data sheet before use.



Wear appropriate gloves and protective clothing during application.



Keep out of reach of children and away from food and feed.



Avoid contact with eyes. In case of contact, rinse thoroughly with water and seek medical advice.



Do not pour leftover material down the drain or in water courses.



In case of spills, contain spillage using sand or earth.

6. STORAGE PRECAUTIONS



Store in a cool, dry place at ambient temperatures. Keep the container tightly closed when not in use.

7. RECOMMENDED FOR



- ✓ Allura Concordia Surfaces
- ✓ Reserva Textures
- ✓ Meraki Finishes

8. HOW TO USE

- 1 Clean the surface and remove dust, grease, and loose particles.
- 2 Apply a base coat if required.
- 3 Apply ArmorShield as per recommended method and allow to dry before topcoating.



YEAR-ROUND
WEATHER RESISTANCE



SUPERIOR
FILM INTEGRITY



LOW MOISTURE
ABSORPTION



10-YEAR
WARRANTY