

ARMORTEX

PREMIUM ULTRA-DURABLE FINISH

ArmorTex delivers a bold, modern textured finish that protects and beautifies your exterior walls.



- VERSATILE TROWEL PATTERN CAPABILITY
- CONCEALS CRACKS & IMPERFECTIONS
- REINFORCED STRUCTURAL WALL PROTECTION
- EXCELLENT ADHESION FOR TOPCOATS

- ULTRA PROTECTIVE COATING
- WEATHER RESISTANT
- HIGH-BUILD TEXTURE
- 5-YEAR PROTECTION

2. AREAS OF APPLICATION



Exterior Walls



Various Masonry Surfaces

FEATURES AND BENEFITS

- VERSATILE TROWEL-BASED PATTERNS**
Create a wide range of modern and creative texture patterns to suit any architectural style.
- CONCEALS SURFACE IMPERFECTIONS**
Effectively hides fine cracks, surface undulations and minor defects for a flawless appearance.
- REINFORCED STRUCTURAL PROTECTION**
Engineered for structural durability that protects your walls against harsh weather, dirt and aging.
- EXCELLENT ADHESION FOR TOPCOATS**
Provides a strong bonding surface to ensure long-lasting performance of all subsequent paint coats.

3. PRODUCT DETAILS

DESCRIPTION:

ArmorTex is an exterior texture coating engineered for structural durability.

It effectively conceals fine cracks and surface undulations while providing a versatile foundation for creative trowel-based patterns.

ArmorTex ensures superior adhesion for topcoats, delivering long-lasting beauty and robust protection for your walls.

TECHNICAL SPECIFICATIONS:

PARAMETER	DETAILS
Finish	Aesthetic textured finish with a bold and modern look
Application	Exterior walls; Variety of exterior surfaces
Binder	Acrylic modified resin
Filler	Specialized mineral fillers
Properties	Crack concealing, Weather resistant, UV resistant, Dirt resistant, Strong adhesion, Durable & long-lasting
Topcoat Compatibility	Compatible with a wide range of exterior topcoat paints
Packaging	As per available pack sizes
Coverage	Varies with texture and surface – approx. 1.2 to 1.5 kg/m ² (Actual coverage may vary)

4. APPLICATION METHOD

1



PREPARE SURFACE

Ensure the exterior wall is clean, dry, and free from loose particles or contaminants.

2



APPLY TEXTURE

Use a trowel to apply the ArmorTex coating, shaping it into your desired pattern.

3



FINISH AND DRY

Allow the texture to dry completely according to ambient conditions before applying your chosen topcoat shades.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MEDS for Waterproof Primer which gives detailed information about safety measures while handling the material.



Store the container with the lid tightly closed in an upright position, in a cool, dry place.



Keep out of reach of children and away from eatables.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover material down the drain or in water courses.



In the event of spills, contain spillage using sand or earth.



No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS



Store in a cool and dry place at ambient temperatures.

RECOMMENDED FOR



- Residential buildings
- Commercial complexes
- Renovation projects
- New construction

HOW TO USE

- Clean the surface and remove dust and loose particles.
- Apply ArmorTex using a trowel.
- Allow to dry and cure.
- Apply topcoat as per requirement.

SCAN TO KNOW MORE

