

AXIS

WEATHER COAT

PREMIUM PROTECTIVE COATING

Precision-engineered protective coating for extreme environmental conditions.



WATER BASED
Low odor & quick drying



LEAD FREE*
GUARANTEE
No added Lead, Mercury, Arsenic or Chromium.



UV
RESISTANT

Engineered for superior protection against harsh weather, UV rays, and environmental wear.

1. AREAS OF APPLICATION



Industrial
Equipment



Marine
Vessels



Outdoor
Structures



Pipeline
Protection

Ideal for protecting surfaces exposed to extreme weather, UV radiation, moisture, and chemical environments.

2. FEATURES AND BENEFITS



WEATHER PROOF

Shields surfaces from rain, humidity, and harsh weather conditions.



CHEMICAL RESISTANT

Resists a wide range of chemicals and industrial fumes.



UV RESISTANT

Protects against UV degradation and prevents color fading.



HIGH DURABILITY

Long-lasting performance with excellent adhesion and toughness.



WATER REPELLENT

Forms a protective barrier that repels water and prevents seepage.



LONG-LASTING BEAUTY

Retains gloss and color for years, reducing maintenance.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS

- Parameter | Type: Acrylic Emulsion
- Solvent: Water
- Finish: Premium Matt
- Odor: Low
- Lead, Mercury, Arsenic & Chromium Free
- Shelf Life: 24 months
- Packaging: 1 L, 4 L, 10 L, 20 L

PHYSICAL PARAMETERS

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Viscosity	ASTM D 562	95 – 105 KU
Gloss (at 60°)	ASTM D 523	3 – 7 units
Specific Gravity	ASTM D 1475	1.30 ± 0.05
Solid Content	ASTM D 2369	48% – 52%
Drying Time (Touch Dry)	ASTM D 1640	30 – 45 minutes
Drying Time (Hard Dry)	ASTM D 1640	4 – 6 hours
Recoat Time	ASTM D 1640	4 – 6 hours
Washability	Internal Method	> 50,000 cycles

* Results may vary depending on surface type, porosity, application method and environmental conditions.

4. APPLICATION METHOD



SURFACE PREPARATION

- Ensure the surface is clean, dry, and free from dust, dirt, grease, oil, loose paint, or other contaminants.
- Remove all loose, peeling, or flaking paint and treat cracks with suitable putty.
- New masonry surfaces must be cured for at least 28 days.
- Allow the surface to dry completely before painting.



PRIMING

- Apply 1–2 coats of suitable primer (Acrylic Wall Primer / Exterior Primer) at the recommended coverage of 80–100 sq. ft. per liter.
- Dilute primer as per instructions, if required.
- Allow the primer to dry for 2–3 hours before applying the finish coat.



APPLICATION

- Stir Axis Weather Coat thoroughly before use.
- Dilute as per instructions (typically 20–30% with clean water).
- Apply 2–3 coats by brush, roller, or spray.
- Maintain recommended coverage and allow 4–6 hours drying time between coats at 27°C and 65% RH.
- Final cure is achieved after 7 days.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for complete safety information.



Keep out of reach of children.



Wear protective gloves, eye protection & mask.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Do not dispose of leftover paint in drains or water courses.



STORAGE PRECAUTIONS

- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight and frost.
- Shelf Life: 24 months from date of manufacture.



RECOMMENDED FOR

- Industrial Structures
- Marine Vessels
- Outdoor Metal & Concrete Surfaces
- Pipeline & Tank Protection
- Bridges & Infrastructure

HOW TO USE

- Clean the surface and remove dust, grease, and loose material.
- Apply 1 coat of primer and allow it to dry.
- Apply 2–3 coats of Axis Weather Coat with proper interval.
- Let it dry for 4–6 hours before applying next coat.

SCAN TO KNOW MORE



WEATHER PROOF



CHEMICAL RESISTANT



UV RESISTANT



LONG-LASTING DURABILITY



PREMIUM PROTECTION