

BONDFIX DRY

HIGH-PERFORMANCE DRY FIXATIVE MORTAR

Achieve a perfectly smooth finish effortlessly with Bondfix Dry, the ultimate self-curing wall solution.

A free-flowing, single-pack powder that ensures superior adhesion and a durable, professional-grade finish—without the need for water curing.

- 

TROWEL-BASED APPLICATION
- 

HIGH-STRENGTH BOND
- 

QUICK-DRY FORMULA
- 

GYPSUM-ENHANCED STRENGTH



- 

EXCELLENT SURFACE ADHESION
- 

SELF-CURING TECHNOLOGY
- 

EASY APPLICATION
- 

SMOOTH & DURABLE FINISH

2. AREAS OF APPLICATION

- 

Old and New Plastered Walls
- 

Concrete Blocks and RCC Surfaces
- 

Mivan Structures
- 

ACC Cement Brick Walls

FEATURES AND BENEFITS

- 

CONVENIENT SINGLE-PACK POWDER
Easy to handle and store with a free-flowing formulation.
- 

EXCELLENT SURFACE ADHESION
Ensures a strong bond with a wide range of substrates.
- 

SELF-CURING TECHNOLOGY
Eliminates the need for water curing, saving time and labor.
- 

EASY APPLICATION PROCESS
Smooth application for a flawless, professional-grade finish.

3. PRODUCT DETAILS

DESCRIPTION:

Bondfix Dry is a free-flowing, single-pack powder designed for superior adhesion across a wide variety of surfaces.

Its advanced self-curing technology eliminates the need for water curing, saving you time and ensuring a smooth, durable finish.

TECHNICAL SPECIFICATIONS:

PARAMETER	DETAILS
Finish	Smooth
Application	Old plastered walls; New plastered walls; Concrete blocks; Mivan structures; RCC surfaces; ACC cement brick walls
Binder	Specialized polymer & gypsum-based binder
Filler	High-quality graded mineral fillers
Properties	High-adhesion, Self-curing, Shrinkage compensated, Crack resistant, Long-lasting performance
Recommended Thickness	1 – 3 mm per coat
Pack Sizes	1 Kg • 2 Kg • 5 Kg • 10 Kg
Coverage	Approx. 1.2 to 1.5 kg/m ² per mm thickness (Actual coverage may vary depending on surface texture and condition)

4. APPLICATION METHOD

- 

1 PREPARE SURFACE
Ensure the application surface is clean, sound, and free from loose debris or contaminants.
- 

2 MIX PRODUCT
Add the free-flowing powder to water according to the recommended ratio until a consistent paste is achieved.
- 

3 APPLY FINISH
Apply the mixture evenly across the surface to achieve a smooth, professional-grade finish without the need for water curing.

5. SAFETY FEATURES & PRECAUTIONS

- 

Kindly refer to the MSDS for Bondfix Dry for detailed information about safety measures while handling the material.
- 

Store the container with the lid tightly closed, in an upright position, in a cool, dry place.
- 

Keep out of reach of children and away from eatables.
- 

May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- 

Wear eye protection during application. In case of contact plenty of water and seek medical advice.
- 

Do not pour leftover material down the drain or in water courses.
- 

In the event of spills, contain spillage using sand or earth.
- 

No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS

- 

Store in a cool and dry place at ambient temperatures.

RECOMMENDED FOR

- 
 - Residential buildings
 - Commercial complexes
 - Renovation projects
 - New construction

HOW TO USE

- Clean the surface and remove dust and loose particles.
- Mix Bondfix Dry as per ratio.
- Apply evenly to the surface.
- Allow to dry and achieve a smooth finish.

