

UNDERCOATS

BONDFIX EXT

Bondfix Ext is a high-performance, water-based primer for exterior surfaces.



WATER
BASED



NO ADDED
LEAD



SAFE &
ENVIRONMENT
FRIENDLY

1. AREAS OF APPLICATION



EXTERIOR
PLASTERS



EXTERIOR
CEILINGS



ASBESTOS
SHEETS



PREVIOUSLY
PAINTED SURFACES

Ideal for a wide range of exterior surfaces for long-lasting performance.

2. FEATURES AND BENEFITS

- ✓ Best in class capacity and whiteness
- ✓ Improves appearance of top coat
- ✓ Prevent peeling off of top coat
- ✓ Can be applied on cured fresh plaster
- ✓ Excellent adhesion to top coat emulsions
- ✓ Does not chalk
- ✓ Water-based formulation
- ✓ No added heavy metals

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Acrylic Dispersion Emulsion

PHYSICAL PARAMETERS:

- Shelf Life: 5 years
- Stability of thinned paint: Use within 24 hours

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Coverage (sq.m/Ltr)	ASTM D Xxxx	10-12 (on smooth masonry)
Drying Time to Recoat	IS 101/1987 Part 1	4-5 hours (at 25C and 50% RH)
Flash Point	IS 101/1987 Part 1, Sec 6	NA
Pack Sizes	IS Xxxx	1L 4L 10L 20L
Colour	Visual	White

4. APPLICATION METHOD



SURFACE PREPARATION

- New surfaces must be allowed to cure completely for 28 days.
- Ensure surface is free from all dirt, loose plaster, powdery residue, oil, or grease.
- For fungus, algae, or moss, remove by vigorous wire brushing and cleaning with water. An anti-algal/fungal treatment may be used.
- Fill cracks upto 3mm with specialized crack sealant.
- Fill holes and dents with appropriate acrylic putty or a cement/sand mix.



APPLICATION PROCESS

STEP 1: Sand the surface with emery paper 180 and wipe clean.

STEP 2: One coat of high-opacity primer is recommended using brush or roller, thinned with 100% water by volume.

STEP 3: Apply the top coat emulsion coat over the cured Bondfix Ext primer. Application of primer without top coats is not recommended in coastal areas for extended periods.

5. SAFETY FEATURES & PRECAUTIONS



Store in a cool, dry place in an upright position and keep container tightly closed.



Keep out of reach of children and away from food, drink.



Wear eye protection during application.



Use a suitable nose pad during sanding.



Do not breathe vapour or spray.



Wash skin with soap and water.



Do not pour down drain or in water courses.

RECOMMENDED FOR

- ✓ New Construction
- ✓ Renovation
- ✓ Before Top Coat Application



DRYING INFORMATION



Recoat Period
4-5 hrs



Surface Dry
30 min

STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures.



SUPERIOR
BOND STRENGTH



WATER-BASED
FORMULA



HIGH
ADHESION



EXTERIOR
USE



PROFESSIONAL GRADE
FOR LASTING RESULTS