

TILE ADHESIVE

BONDFIX

Advanced Universal Tile Adhesive

Cement-based polymer modified adhesive for interior floor and wall tiling.



**WATER
RESISTANT**



**TRAFFICABLE
(24H)**

1. AREAS OF APPLICATION



Interior
Floors



Interior
Walls



Cement
Screed



Concrete
Slabs



Interior
Plaster

Ideal for interior floors, interior walls, cement screed, concrete slabs, interior plaster and other cement-based substrates.

2. FEATURES AND BENEFITS

- ✓ Meets standard requirement (IS 15477:2019 Type 1T, ISO 13007-1:2014 C1T)
- ✓ Single component, easy-to-use mixture
- ✓ Excellent Adhesion and Slip Resistance
- ✓ Long Pot Life for larger mixed quantities
- ✓ Water Resistant with low water absorption
- ✓ Minimizes shrinkage cracks
- ✓ Less labor and time intensive
- ✓ No pre-soaking of tiles required

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Polyurethane Dispersion

PHYSICAL PARAMETERS:

- Always mix powder in water
- Surface should be sound and SSD
- Apply on substrate and tiles
- Porcelain Tiles
- Vitrified Tiles

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Physical Appearance	Visual	Free Flowing Powder
Available Packs	Internal	20 kgs, 30 kgs
Colour	Visual	Grey
Shelf Life	Internal	1 Year from manufacture
Min Bed Thickness	Internal	23-25% (water)
Coverage	Internal	2 - 2.5 sq.ft / kg (3 mm bed)*
Tensile Adhesion (RT)	ISO 13007-1	1.85 (mix)
Tensile Adhesion (Water)	ISO 13007-1	2-3 hours
Tensile Adhesion (Weat Age)	ISO 13007-1	10 minutes
Tensile Adhesion (Freeze Thaw)	ISO 13007-1	5-10 minutes

4. APPLICATION METHOD



SURFACE PREPARATION

Ensure surfaces are clean, free from dust and contamination. Surfaces should be sound and in SSD (Saturated Surface Dry) condition.



MIXING

Mix BONDFIX powder into water until lump-free mortar consistency is achieved. Approx 7-8 liters potable water is required per 30 kg bag. Use a mechanical mixer and remeasurements.



APPLICATION

Apply adhesive on floor or wall at 3-6 mm thickness with 6 mm notch trowel. Do not spread in more than 1 sq m at a time. Also apply to back of wall tiles and comb. Fix tiles firmly, sliding, and gentle mallet hammer for better bond. Leave adequate joints using spacers. Clean joints and tiles with damp cloth. Leave untouched for 24 hours. Fill joints with Epoxy or Cement Based Grout for best results.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for detailed information on safety measures.



Store bag tightly closed in a cool, dry place.



Keep out of reach of children and away from eatables.



Wear eye protection during application.



May be harmful if swallowed. Seek immediate medical attention if ingested.



Wear a suitable inhalation protection.

PACKAGING SIZES



RECOMMENDED USAGE

- ✓ Interior Floors
- ✓ Interior Walls
- ✓ Ceramic Tiles
- ✓ Porcelain Tiles
- ✓ Vitrified Tiles

USAGE GUIDELINES

- ✓ Always mix powder in water
- ✓ Surface should be sound and SSD
- ✓ Apply on substrate and tiles

DON'TS

- ✓ Don't fix on exterior walls
- ✓ Don't fix over smooth surfaces (concrete / cement terrazzo)
- ✓ Don't fix directly on damp surfaces

