

BONDLOCK PRIMER

Ensure a lasting, professional finish with Bondlock Primer, the ultimate foundation for all your metal projects.



STRONG ADHESION



CORROSION PROTECTION



RUST INHIBITOR

2. AREAS OF APPLICATION



General Metal Surfaces



Industrial Metal Structures



Residential Metal Fixtures



Metal Railings & Frames

FEATURES AND BENEFITS



SUPERIOR METAL ADHESION

Forms a strong bond with metal surfaces for long-lasting results.



CORROSION PROTECTION

Protects metal against rust and environmental damage.



DURABLE BASE COAT

Creates a tough and resilient base for extended surface protection.



EXCELLENT TOPCOAT COMPATIBILITY

Works seamlessly with a wide range of topcoats and finishes.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Alkyd Based Primer

PHYSICAL PARAMETERS:

- Colour and appearance: Grey / Red Oxide (Smooth)
- Packaging: 20 L
- Shelf life: 2 years
- Coverage: 10 – 12 sq m/ L per coat at 25 microns DFT

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Finish	Visual	Smooth Matt
Colour	Visual	Grey / Red Oxide
Solids by Volume	ASTM D 2697	35 – 40%
Specific Gravity	ASTM D 1475	1.20 – 1.40
Touch Dry	ASTM D 1640	30 – 60 mins
Hard Dry	ASTM D 1640	6 – 8 hours
Recoating Interval	–	6 – 8 hours
Application	–	Metal surfaces
Coverage	ISO 11890-1	10 – 12 sq m/ L per coat

4. APPLICATION METHOD



SURFACE PREPARATION

Ensure the metal surface is clean, dry, and free from rust, oil, grease, loose paint and contaminants.
Use wire brushing / sanding if required.



APPLICATION

Stir the primer thoroughly before use.
Apply by brush, roller or spray.
Apply 1 even coat for best results.
Allow to dry for recommended time before applying topcoat.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MEDS for Waterproof Primer which gives detailed information safety measures while handling the paint, which is available on request.



Store the container with the lid tightly closed in an upright position, in a cool, dry place.



Keep out of reach of children and away from eatables.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during application.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover paint down the drain or in water courses.



In the event of spills, contain spillage using sand or earth.



No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures.

RECOMMENDED FOR




- ✓ Industrial Projects
- ✓ Fabrication Units
- ✓ Steel Structures
- ✓ Pre-Painting Applications

HOW TO USE

- 1 Prepare Surface**
Clean the metal surface thoroughly to remove any rust, grease, or loose debris.
- 2 Apply Primer**
Apply an even coat of Bondlock Primer using a brush, roller, or sprayer for optimal coverage.
- 3 Dry and Finish**
Allow the primer to dry completely according to ambient conditions before applying your selected topcoat.

SCAN TO KNOW MORE




STRONG ADHESION



CORROSION PROTECTION



RUST INHIBITOR



DURABLE BASE COAT



EXCELLENT TOPCOAT COMPATIBILITY