

BONDSEAL PRO

PREMIUM MULTI-SURFACE PRIMER & SEALER

STRONG FOUNDATION.
LASTING BEAUTY.

Bondseal Pro combines premium priming and sealing for a superior, long-lasting wall finish.

Engineered for excellence, this dual-action formula provides superior adhesion while actively resisting alkali and primary efflorescence. It creates a robust foundation that protects your walls and ensures a durable, professional-quality finish.

- 

WEATHER RESISTANT
Protects against harsh weather conditions.
- 

HIGH ADHESION
Superior bonding for all surfaces.
- 

NON-TOXIC
Safe for you and the environment.
- 

FAST-DRYING
Dries quickly for faster project completion.



- 

LEAD FREE
No added Lead, Mercury, Arsenic or Chromium.
- AVAILABLE PACK SIZES



1L



4L



10L

1. WHY CHOOSE BONDSEAL PRO?

- 

Dual Primer-Sealer Performance
Acts as both a high-performance primer and sealer for a strong, unified base.
- 

Superior Surface Adhesion
Enhances bonding of topcoats, ensuring a long-lasting and flawless finish.
- 

Alkali-Resistant Formula
Protects walls from alkali attack, preventing chalking and paint failure.
- 

Prevents Primary Efflorescence
Minimizes salt deposits and efflorescence for cleaner, healthier walls.

2. IDEAL FOR



Interior & Exterior Walls
Ideal for both interior and exterior surfaces including plaster, cement render, concrete and masonry walls.



3. PRODUCT DETAILS

TECHNICAL INFORMATION	
PARAMETER	DETAILS
Finish	Matt
Base	Acrylic water-based
Colour	White (opaque)
Coverage	10 – 12 m ² /L per coat*
Drying Time (Touch Dry)	30 – 60 minutes
Recoat Time	4 – 6 hours
Shelf Life	2 years
Pack Sizes	1 L, 4 L, 10 L

*Coverage may vary depending on surface texture, porosity and application method.

4. HOW TO APPLY

- 

1 PREPARE SURFACE
Ensure the wall surface is clean, dry, and free from dust or loose particles.

>
- 

2 APPLY BONDSEAL PRO
Apply an even coat using a brush, roller, or sprayer, allowing it to dry according to standard recoat times.

>
- 

3 FINISH
Once fully cured, the sealed surface is ready for your chosen topcoat to achieve a lasting finish.

5. SAFETY FEATURES & PRECAUTIONS

- 

Use in well-ventilated areas.
- 

Wear protective gloves.
- 

Wear eye protection.
- 

Keep out of reach of children.
- 

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Refer to MSDS for Bondseal Pro for complete safety information.

STORAGE PRECAUTIONS

- 
- Store in a cool, dry place.
 - Keep container tightly closed when not in use.
 - Protect from direct sunlight and extreme temperatures.
 - Shelf life: 12 months from date of manufacture.

RECOMMENDED FOR

- ✓ Interior Walls
- ✓ Exterior Walls
- ✓ Residential Buildings
- ✓ Commercial Buildings
- ✓ Industrial Structures

