

UNDERCOATS

Bondtex Exterior Wall Primer

A water-based undercoat suitable for all exterior surfaces before emulsion application.



WATER
BASED



NO ADDED
LEAD



NO ADDED LEAD/
MERCURY/
CHROMIUM



WATER
BASED



NO ADDED
LEAD/
MERCURY/
CHROMIUM

1. AREAS OF APPLICATION



EXTERIOR
PLASTER



EXTERIOR
CEILING



ASBESTOS
SHEETS



CONCRETE



EXISTING
PAINTED
SURFACES

Ideal for a wide range of exterior surfaces for long-lasting performance.

2. FEATURES AND BENEFITS

- ✓ Excellent opacity & whiteness
- ✓ Does not chalk
- ✓ Improves top coat appearance
- ✓ Excellent top coat adhesion
- ✓ Prevents top coat peeling
- ✓ Apply to adequately cured fresh plaster

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

- Stability of thinned paint:
Use within 24 hours

PHYSICAL PARAMETERS:

- Shelf life: 3 years

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Drying time	Surface dry: 30 min / Recoat: 4–5 hours	
Sheen levels	GH at 35 deg	15–35
Flash point	IS101/1987 Part 1, Sec 6	NA
Thinner	–	Water
Dilution % (Brush/Roller)	–	100%

4. APPLICATION METHOD



SURFACE PREPARATION

- 28-day curing for new masonry in 28 days
- Remove dirt/algae with wire brushing and removed with wire brushing/water cleaning
- Used standard crack seal and putty for holes, cracks or cracks



PRIMING

1. Sand with Emery Paper 180 and wipe clean
2. (Optional) Apply standard wall putty
3. Apply Exterior Wall Primer at 100% water dilution with Brush/Roller
4. Recoat after 4–5 hours



APPLICATION

- Apply an emulsion top coat over the Exterior Wall Primer
- Stir and strain well before use.
- Do not apply when ambient temp is <10°C or drops within 4 hrs

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for
detailed
information



Store tightly
closed in a cool,
dry place



Keep out of
reach of children
and food



Wear eye
protection during
application



Wash skin
with soap and
plenty of water



Do not breathe
vapour or spray



Do not pour paint
down drains



No added
Lead, Mercury
or Chromium
compounds

STORAGE PRECAUTIONS



Store at cool
temperatures
away from
direct sunlight.



RECOMMENDED FOR

- ✓ Exterior Walls
- ✓ Ceilings
- ✓ Concrete

HOW TO USE

- 1 Clean surface.
- 2 Sand surface.
- 3 Apply 1 coat primer.



SUPERIOR
STRENGTH



HIGH MOISTURE
RESISTANCE



PROFESSIONAL
FINISH



EXTERIOR
USE