

BONDWELL PRIMER

PROFESSIONAL EXTERIOR GRADE HIGH-ADHESION FORMULA

Bondwell Primer creates the perfect foundation for a flawless, long-lasting exterior paint finish.



1. PERFECT FOR



EXTERIOR MASONRY
WALLS

2. FEATURES AND BENEFITS



FLAWLESS SURFACE PREPARATION

Ensures a smooth and uniform base for an impeccable finish.



SUPERIOR SURFACE ADHESION

Delivers exceptional bonding strength for long-lasting performance.



IDEAL LEVEL OF WHITENESS

Provides the perfect whiteness to enhance the vibrancy of your topcoat.



ENHANCED TOPCOAT FINISH

Acts as the ideal base to improve topcoat coverage and durability.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Acrylic Copolymer Based Primer

PHYSICAL PARAMETERS:

- Colour and appearance: White (Smooth)
- Packaging: 20 L
- Shelf life: 2 years
- Coverage: 10 – 12 sq m/L per coat at 25 microns DFT

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Finish	Visual	Smooth Matt
Colour	Visual	White
Solids by Volume	ASTM D 2697	35 – 40%
Specific Gravity	ASTM D 1475	1.25 – 1.40
Touch Dry	ASTM D 1640	30 – 60 mins
Hard Dry	ASTM D 1640	6 – 8 hours
Recoating Interval	–	4 – 6 hours
Application	–	Exterior walls
Coverage	ISO 11890-1	10 – 12 sq m/L per coat

4. APPLICATION METHOD



SURFACE PREPARATION

Ensure the exterior wall is clean, dry, and free from dust, grease, or loose debris.



APPLICATION

Stir the product well and apply an even coat using a brush, roller, or spray equipment. Apply uniformly for best results.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MSDS for Waterproof Primer which gives detailed information safety measures while handling the paint, which is available on request.



Store the container with the lid tightly closed in an upright position, in a cool, dry place.



Keep out of reach of children and away from eatables.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover paint down the drain or in water courses.



In the event of spills, contain spillage using sand or earth.



No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures.

RECOMMENDED FOR



Ideal for exterior masonry walls and other cementitious surfaces before topcoat application.

HOW TO USE

- 1 Prepare Surface**
Ensure the exterior wall is clean, dry, and free from dust, grease, or loose debris.
- 2 Apply Primer**
Stir the product well and apply an even coat using a brush, roller, or spray equipment.
- 3 Finish**
Allow the surface to dry completely according to standard environmental conditions before applying your topcoat.

SCAN TO KNOW MORE



WATERPROOF



UV RESISTANT



FAST DRYING



SUPERIOR
ADHESION



ENHANCED
TOPCOAT FINISH