

BUILDWELL READY-MIX PLASTER

Instant Plastering. Stronger Construction.

Buildwell Ready-Mix Plaster is a factory-mixed plaster that ensures consistent quality, excellent workability, and superior bonding—reducing on-site labor and material waste.



CONSISTENT
QUALITY



TIME
SAVING



REDUCED
WASTE



SUPERIOR
BONDING





LEAD FREE
No added Lead,
Mercury, Arsenic
or Chromium.



HIGH STRENGTH
Provides strong
adhesion and
durable finish.



EASY TO USE
Just add water
and mix.

AVAILABLE PACK SIZES



5 Kg



10 Kg



30 Kg

1. WHY CHOOSE BUILDWELL?



Consistent Quality
Factory-mixed for uniform quality and reliable performance.



Time Saving
Eliminates on-site sand & cement proportioning and reduces labor.



Reduced Waste
Accurate formulation minimizes material waste at the site.



Superior Bonding
Enhanced adhesion ensures strong and long-lasting plaster.

2. IDEAL FOR



Interior Walls
Smooth and even finish for internal surfaces.



Exterior Walls
Resistant to weather and environmental conditions.



Ceilings
Ideal for plastering ceilings and overhead surfaces.



Renovation Projects
Perfect for repair, patching and refurbishment work.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS

- Type : Dry Mix Plaster
- Base : Cement Based
- Appearance : Grey Powder
- Max. Grain Size : 1.18 mm
- Water Requirement : 28 – 32%
- pH : 10 – 11
- Shelf Life : 12 months
- Packaging : 5 Kg, 10 Kg, 30 Kg

* Results may vary depending on site conditions.

TYPICAL PERFORMANCE PROPERTIES

Property	Typical Value
Compressive Strength (28 days)	≥ 7.5 N/mm ²
Flexural Strength (28 days)	≥ 2.0 N/mm ²
Bond Strength	≥ 0.5 N/mm ²
Water Retention	≥ 85%
Workability	Excellent
Pot Life	2 – 3 hours
Coverage	12 – 14 m ² /25 mm (thickness)

4. APPLICATION GUIDE



SURFACE PREPARATION

- Ensure the surface is clean, free from dust, oil, grease and loose particles.
- Remove any flaky paint, weak plaster or laitance.
- Repair cracks and uneven areas.
- Dampen the surface with clean water before application.



MIXING

- Add 5.5 – 6.0 litres of clean water for every 25 Kg bag (approx.).
- Mix thoroughly for 3 – 5 minutes until a uniform, lump-free paste is obtained.
- Allow the mixture to rest for 3 minutes and remix before use.



APPLICATION

- Apply plaster using a trowel or plastering machine.
- Spread evenly to the required thickness (10 – 20 mm per coat).
- Level the surface and allow it to set properly.
- For thickness above 20 mm, apply in two coats.



CURING

- No curing required for first 24 hours in normal weather.
- After 24 hours, lightly cure the surface 1 – 2 times a day for 2 – 3 days.
- In extreme weather, continue curing for up to 5 – 7 days.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for complete safety information.



Keep out of reach of children.



Wear protective gloves and mask during handling.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Dispose of empty packaging in accordance with local regulations.

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from moisture and direct sunlight.
- Shelf life: 12 months from date of manufacture.

RECOMMENDED FOR

- Interior & Exterior Plastering
- New Construction
- Renovation & Repair
- Brick, Block & Concrete Surfaces
- Residential & Commercial Projects

HOW TO USE

- Clean the surface and dampen it.
- Mix Buildwell Ready-Mix Plaster with water as per the ratio.
- Apply the plaster and level evenly.
- Allow to set and cure for best strength and finish.

