

WATERPROOFING
CRACKSEAL EXT

Advanced Textured Exterior Crack Filler

High-performance, textured, water-based crack filler for exterior plaster and rough surfaces.



-  **WATER BASED**
-  **LEAD FREE* GUARANTEE**
-  **ALL WEATHER PROTECTION**

* All COLORSOME® products contain no added Lead, Mercury, Arsenic or Chromium

1. AREAS OF APPLICATION



Exterior Plaster



Rough Surfaces



Interior Floor & Exterior Floor



Cement-based Screed

Ideal for exterior plaster surfaces, rough walls, textured finishes and other cement based substrates.

2. FEATURES & BENEFITS

- ✓ Meets specifications of IS 15477:2019 Type 1T and ISO 13007-1:2014 C2TE.
- ✓ Grainy structure for rough surfaces
- ✓ Accommodates minor crack movements
- ✓ Prevents crack reappearance
- ✓ Paintable with water-based and synthetic paints
- ✓ Fills cracks up to 10 mm
- ✓ Easy to apply and clean
- ✓ Non-corrosive towards metals
- ✓ Excellent durability and weather resistance
- ✓ Long pot life & extended open time simplifies installation.
- ✓ Slip resistant for horizontal and vertical application.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Acrylic Base

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Density	ISO	1.91 g/ml
Skin Formation	ISO	7 minutes
Elongation @ break	ISO	65%
Sag, vertical	ISO	< 2 mm
Joint Movement	ASTM	7.5%
Shore A Hardness	ASTM	28 Shore A
Colour	Visual	White
Shelf Life	Visual	12 months
Coverage	-	55 running ft/kg for a 5x5 mm crack
Available Packs	-	1 kg, 25 kg

4. APPLICATION METHOD



SURFACE PREPARATION

- Open and widen crack to form a 'V' shaped groove.
- Clean thoroughly, ensuring no dust or loose particles.
- Surface must be dry and free from oil, grease and contamination.



PRIMING

- Apply a self-priming coat (1:1 dilution with water) of the filler over crack edges.
- Allow to dry 1–2 hours.



APPLICATION

- Apply first coat undiluted.
- Use spatula or putty knife, pressing firmly for full contact and leveling the surface.
- Allow to dry minimum 6 hours.
- Apply second undiluted coat perpendicularly. Spread at least 3 cm on either side.
- Apply in consecutive perpendicular layers to avoid air pockets.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MSDS for detailed information.



Store bag tightly closed in a cool, dry place.



Keep out of reach of children and away from eatables.



Wear eye protection during application. Wear suitable nose pad to avoid dust.



In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- ✓ Meant for plaster cracks; do not apply on structural or joint cracks.
- ✓ Do not apply for cracks wider than 10 mm.
- ✓ Do not apply on wet surfaces.
- ✓ Wear suitable PPE as per site conditions and preparation.
- ✓ Non-flammable.
- ✓ No added Lead, Mercury or Chromium compounds.

STORAGE PRECAUTIONS



Store at a cool and dry place in original sealed container.

HOW TO USE

- 1 Clean and widen to 'V' shaped groove
- 2 Apply 1:1 priming coat and let dry
- 3 Press firmly and level first undiluted coat
- 4 Spread up to 3cm either side of crack
- 5 Apply second undiluted coat perpendicularly

RECOMMENDED FOR



- ✓ Exterior Plaster
- ✓ Rough Surfaces
- ✓ Stone & Heavy Tile Areas
- ✓ Concrete Substrates

