

CRUX COARSE FINISH WALL PUTTY

RUGGED STRENGTH. TEXTURED PERFECTION.

CRUX Coarse Finish Wall Putty is designed for surface leveling and creating textured finishes on both interior and exterior walls.



EXCELLENT
COVERAGE



SURFACE
LEVELING



TEXTURED
FINISH



DURABLE
PERFORMANCE



LEAD FREE
No added Lead,
Mercury, Arsenic
or Chromium.



**EXCELLENT
COVERAGE**
Provides superior
coverage with
less material.



**TEXTURED
FINISH**
Ideal for creating
beautiful textured
wall surfaces.



DURABLE
Long-lasting
finish with strong
adhesion.

AVAILABLE PACK SIZES



1. WHY CHOOSE CRUX COARSE FINISH?



Excellent Coverage
Covers more area with less material
for cost-effective application.



Surface Leveling
Effectively levels uneven surfaces
and fills minor imperfections.



Textured Finish
Creates decorative textured surfaces
with a rugged look.



Durable & Strong
High strength and adhesion for
long-lasting protection.

2. IDEAL FOR



Exterior Walls
Resistant to weather
and environmental
conditions.



Textured Finishes
Ideal for decorative and
architectural textures.



Repair Work
Suitable for patching
and repairing uneven
wall surfaces.



Surface Preparation
Provides a strong, even
base for paints and
coatings.

Perfect solution for both new construction
and renovation projects.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS

- Type : Cement Based Putty
- Base : White Cement & Polymer
- Appearance : Grey / Off-White Powder
- pH : 10 – 11
- Shelf Life : 12 months
- Packaging : Available in 1 Kg, 2 Kg, 5 Kg, 10 Kg & 25 Kg

TYPICAL PERFORMANCE PROPERTIES

Property	Typical Value
Color	Grey
Bulk Density	1.00 – 1.20 g/cc
Water Demand	30 – 36%
Coverage	0.9 – 1.2 m ² /kg (for 2 coats)
Drying Time	2 – 3 hours
Recoating Time	4 – 6 hours
Compressive Strength	≥ 3.0 N/mm ²
Bond Strength	≥ 1.0 N/mm ²

* Results may vary depending on surface condition and application.

4. APPLICATION GUIDE



SURFACE PREPARATION

- Ensure the surface is clean, dry and free from dust, oil, grease or loose particles.
- Remove any loose paint, weak plaster or laitance.
- Repair cracks and uneven areas.
- Dampen the surface with clean water before application.



PREPARATION OF PUTTY

- Mix 1 part of CRUX Coarse Finish Wall Putty with 2 parts of clean water (approx.).
- Stir gradually to form a smooth, lump-free paste.
- Allow the mixture to rest for 5–10 minutes and remix before use.



APPLICATION

- Apply using a putty knife or trowel.
- Spread and level the putty evenly.
- For textured effects, create the desired texture using suitable tools.
- Allow to dry for 4–6 hours.
- Sand if required and clean the surface.
- Apply primer and paint for best results.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for
complete safety
information.



Keep out of
reach of
children.



Wear protective
gloves, mask
and goggles
during handling.



In case of contact
with eyes, rinse
immediately with
plenty of water.



If swallowed,
seek medical
advice
immediately.



Ensure adequate
ventilation during
application and
drying.



Dispose of empty
packaging in
accordance with
local regulations.

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from moisture and extreme weather.
- Shelf life: 12 months from date of manufacture.

RECOMMENDED FOR

- ✓ Exterior & Interior Walls
- ✓ Textured Finishes
- ✓ Repair & Patch Work
- ✓ Surface Preparation
- ✓ New Construction & Renovation

HOW TO USE

- 1 Clean the surface and remove dust, loose particles and contaminants.
- 2 Apply prepared putty in thin coats.
- 3 Level the surface and create texture as required.
- 4 Allow to dry completely before applying primer and paint.



EXCELLENT
COVERAGE



SURFACE
LEVELING



TEXTURED
FINISH



DURABLE
PERFORMANCE



PREMIUM
QUALITY