

DampShield

ADVANCED INTERIOR WATERPROOFING MEMBRANE

PREMIUM FINISH

Protect your interior walls from dampness and extend the life of your topcoat.



3-YEAR
WATERPROOFING
WARRANTY*



SUPERIOR
ADHESIVE
STRENGTH



INCREASES TOP COAT
COVERAGE UP TO
15%*

*Terms & conditions apply.

1. AREAS OF APPLICATION



Interior Walls

2. FEATURES AND BENEFITS



PREVENTS SURFACE DAMPNESS

Acts as a powerful barrier to stop dampness from appearing on walls.



3-YEAR WATERPROOFING WARRANTY*

Assured protection and peace of mind for years to come.



SUPERIOR ADHESIVE STRENGTH

Ensures excellent bonding for a strong and lasting base.



ENHANCED TOPCOAT COVERAGE

Increases top coat coverage by up to 15%* for better results and cost efficiency.

*Under standard application conditions.

3. PRODUCT DETAILS

CHEMICAL COMPOSITION

Acrylic Copolymer Emulsion

PHYSICAL PROPERTIES

- Colour: White
- Finish: Premium Matte
- Packaging: 20 L
- Shelf Life: 2 years
- Coverage: Increases top coat coverage up to 15%*

*Under standard application conditions.

TECHNICAL SPECIFICATIONS

PARAMETER	DETAILS
Application	Interior walls
Dilution	Ready to use (Dilute with water up to 5% if required)
Drying Time	Surface dry in 30 – 60 minutes*
Recoat Time	4 – 6 hours
Coverage	Increases top coat coverage up to 15%*
Theoretical Coverage	10 – 12 sq m/L per coat
No. of Coats	1 coat of DampShield followed by topcoat
Shelf Life	2 years from date of manufacture in original sealed container
Storage	Store in a cool, dry place. Protect from direct sunlight and frost.

* May vary depending on surface condition, temperature and humidity.

4. APPLICATION METHOD

1



PREPARE SURFACE

Ensure the interior wall surface is clean, dry, and free from loose particles or dust.

2



APPLY PRIMER

Apply DampShield evenly across the wall to create a moisture-resistant protective barrier.

3



FINISH

Allow the primer to dry completely before applying your chosen topcoat for a smooth, durable finish.

5. SAFETY FEATURES & PRECAUTIONS



Read the product label and technical data sheet before use.



Wear appropriate gloves and protective clothing during application.



Keep out of reach of children and away from food & feed.



Avoid contact with eyes. In case of contact, rinse thoroughly with water and seek medical advice.



Do not pour leftover product down the drain or in water courses.



In case of spills, contain spillage using sand or earth.

6. STORAGE PRECAUTIONS



Store in a cool, dry place at ambient temperatures. Keep the container tightly closed when not in use.

7. RECOMMENDED FOR



- ✓ Interior Wall Surfaces
- ✓ Residential Spaces
- ✓ Commercial Spaces
- ✓ Renovation Projects

8. HOW TO USE

- 1 Clean the surface and remove dust and loose particles.
- 2 Apply DampShield evenly.
- 3 Let it dry for 4–6 hours before applying topcoat.



100% WATERPROOF
Prevents Water Infiltration



FLEXIBLE MEMBRANE
Bridges Hairline Cracks



STRONG ADHESION
Excellent Bonding to Surfaces



UV & WEATHER RESISTANT
Long-Lasting Performance

*Terms & conditions apply. For details, please refer to our warranty document.