

DECOPRIME

ACRYLIC PRIMER

HIGH-PERFORMANCE PRIMER
FOR PREMIUM FINISHES

Decoprime is a high-performance primer that ensures premium decorative finishes with enhanced durability and adhesion. It seals surfaces, improves paint performance, and provides the perfect base for beautiful, long-lasting results.



PREMIUM FINISH
Provides an ideal base for superior, smooth and elegant finishes.



ENHANCED ADHESION
Strong bonding with surfaces for better paint grip and long life.



SEALS SURFACES
Seals porous surfaces and prevents absorption of top coat.



QUICK DRYING
Dries quickly to save time and speed up your painting process.



AVAILABLE
PACK SIZES



1. WHY CHOOSE DECOPRIME?



Premium Finish
Creates a smooth, even base that enhances the beauty of top coats.



Enhanced Adhesion
Improves bonding of paint film with various surfaces.



Seals Surfaces
Seals and stabilizes surfaces by reducing porosity and absorption.



Quick Drying
Shorter drying time allows for faster recoating and project completion.

2. IDEAL FOR



Premium Interiors
Ideal for high-end interior walls and ceilings.



Decorative Projects
Perfect for textured and decorative finishes.



High-end Finishes
Ensures excellent surface appearance and durability.



Architectural Work
Suitable for residential and commercial architectural applications.

3. PRODUCT DETAILS

TECHNICAL INFORMATION

- Type : Acrylic Primer
- Appearance : Smooth, Viscous Liquid
- Colour : White
- Solid Content : $45 \pm 2\%$
- pH : 8.0 – 9.0
- Specific Gravity : 1.20 – 1.40
- Drying Time (Touch Dry) : 30 – 60 mins*
- Drying Time (Hard Dry) : 3 – 4 hours*
- Recoating Time : 4 – 6 hours*
- Coverage : 10 – 12 sq.ft./kg/coat*
- Application Temperature : 10°C to 40°C
- Thinning : Clean Water (up to 10%)
- Packaging : 1Kg, 4Kg, 10Kg, 20Kg

* Results may vary depending on surface condition and application method.

PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Adhesion Strength	≥ 1.5 MPa
Hiding Power	Excellent
Alkali Resistance	Excellent
Water Resistance	Good
Stain Blocking	Good
Durability	Excellent
Flash Point	Non-Flammable

4. APPLICATION GUIDE



1. SURFACE PREPARATION

- Surface must be clean, dry and free from dust, oil, grease or loose particles.
- Remove flaking paint, chalk or laitance.
- Repair cracks and level uneven areas.



2. PRIMER APPLICATION

- Stir Decoprime well before use.
- Apply one coat evenly using brush, roller or spray.
- Ensure uniform coverage.



3. RECOATING

- Allow to dry for 4 – 6 hours.
- Apply the top coat of your choice for best results.



4. TOP COAT APPLICATION

- Apply 2 coats of quality top coat.
- Follow recommended interval between coats.



5. CURING

- Allow the surface to cure for at least 7 days.
- Avoid heavy cleaning during the curing period.

5. SAFETY FEATURES & PRECAUTIONS



Refer to SDS for complete safety information.



Keep out of reach of children.



Wear protective gloves and goggles during application.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Dispose of empty containers as per local regulations.

STORAGE



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight and extreme heat.
- Shelf life: 12 months from date of manufacture.

RECOMMENDED FOR

- ✓ Premium Interiors
- ✓ Decorative Projects
- ✓ High-end Finishes
- ✓ Architectural Work

TIPS FOR BEST RESULTS

- ★ Use a quality top coat for enhanced results.
- ★ Ensure surface is completely dry before primer application.
- ★ Do not paint in direct sunlight or on hot surfaces.
- ★ Stir well and do not over-thin the primer.



PREMIUM FINISH



ENHANCED ADHESION



SEALS SURFACES



QUICK DRYING